


SPECIFIED

SOLUTIONS
Commercial Floors & Walls

Tradd Street
Engineered



TS1028



TS5014




TS1007

US Units

Style Number	AR707
Construction	4.72" Wide Engineered Planks (4-mm Wear Layer)
Species	White Oak
Nominal Overall Thickness	1/2"
Finish	UV Aluminum Oxide
Gloss Level	7%
Surface Texture	Wirebrushed
Edge Description	Micro Bevel
End Description	Micro Bevel
Profile	Tongue And Groove
Installation Methods	Nail, Staple, Glue, Floating
Installation Grade	Above, On, Below
Variation	High
GREENGUARD® Certified	Yes
Radiant Heat Approved	Yes
Warranty	Lifetime Structural Warranty
All measurements are nominal.	Cartons may include random lengths.

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking - but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



SRW15
Flush Reducer



SROW5
*Overlap Reducer




SSW15
Flush Stairnose



SSOW5
*Overlap Stairnose



SCW15
Threshold / Carpet Reducer



TMW78
T-Molding



QTR96
Quarter Round