

SAFE BOX

INSTRUCTION MANUAL



LECCY & GENESIS

Thank you for using our smart safe box ,be able to operate the safe box better , please read manual first.

1.Security alerts

Make it installed before using of the safe box.

After installation, we recommend you to modify the Master Code immediately. In addition, don't put mechanical key in the safe.

2.Main features

- 1) Solid, arc-welded heavy-gauge steel construction.
- 2) 18mm solid steel bolt for maximum security and durability.
- 3) Powered by 4 x AA 1.5V. Automatic low battery level alert.
- 4) Digital display screen.
- 5) Inside Carpet.
- 6) Pre-drilled mounting holes on back and bottom.
- 7) 3-6 digit guest code and 6 digit master code.
- 8) 5 minutes freeze system in case of wrong code for 3 times.
- 9) Override mechanical key.

3.Lock the safe

Input any 3-6 digit code, then press "LOCK(#)", "CLOSED" display, the safe is closed.

To press "clear(*)" before inputting digit code, the code is hidden on screen.

4.Open the safe

- 1) open by personal code

Input your 3~6 digit code then "OPENED" display, the safe is opened.

- 2) open by master code

Press "LOCK(#)" twice, "SUPER" display, then input Master code (factory default code is "000000"), "OPENED" display, the safe is opened.

- 3) Open by mechanical key (in case code forgot or failure of electronic system): insert key and turn it clockwise, the door is opened, while "opened" display, then enter new 3~6 digital code, press "LOCK(#)", the door closed, then take out the key.

5.change personal code

Input 3-6 digit new personal code, press "LOCK(#)"

6.Change master code

Make sure the safe is unlocked, and the operation is as follows: Press "CLEAR(*)" twice quickly, "PROG" display, enter the master code (factory default code is "000000"), press "LOCK(#)", "CODE" display, then input 6 digit new master code, press "LOCK(#)", "DONE" "GOOD" display in sequence, shows it is successful.

7.Battery test

To press "LOCK(#)", If "BATT-H" display, means the battery energy is enough. If "BATT-L" display, means the battery energy is low, please replace ASAP!

Attention:

- 1) Press "CLEAR(*)" to erase when code is wrong.
- 2) If code is wrongly input, "E-CODE" will display, you can re-enter the code after beep sound.
- 3) wrongly input code by 3 times, "HOLD-5" display, the safe will freeze for 5 minutes.
- 4) In case master code is forgotten, please press reset button on the PCB to restore factory default code (000000).