

## Declaration Of Performance

WaterCare Oil Separator 20 l/s with 2,7 m<sup>3</sup> Integrated sludge trap, Class I - 223372120

No.: DoP\_EN\_223372120\_EN858

Valid from: 2023.02.01

Identification	
1. Product	WaterCare Oil Separator 20 l/s with 2,7 m <sup>3</sup> Integrated sludge trap, Class 1
2. Item number	223372120
3. Intended use	Separate oil from wastewater
4. Manufacturer	WaterCare ApS Stejlebjergvej 14 DK - 5610 Assens Denmark Tel: +45 70 25 65 37 Web: www.watercare.dk
5. Authorized representative	-
6. System of assessment and verification / Notified body	System 4 / Danish Technological Institute
7. Harmonized standard / Notified body number	DS/EN 858-1 Body no. 596555/2014
8. Technical Assessment	Not relevant




Item number: 223372120

9. Declared performance		
Essential characteristics	Performance	Harmonized technical specification
Dimensions	Length: 4010 mm. Width: Ø1748 mm Height: 2721 mm (incl. inspection pipe)	-
Weight	< 600 kg	-
Quality	Class I	DS/EN 858-1 pt. 6.3.6 cf. 8.3.3
Nominal size	NS20	DS/EN 858-1 pt. 6.3.6 cf. 8.3.3
Nominal capacity	6,025 m <sup>3</sup>	DS/EN 858-1 pt. 6.5.6
Max. oil storage capacity	4,15 m <sup>3</sup> (100%)*	DS/EN 858-1 pt. 6.5.2
Integrated sludge trap capacity	2,7 m <sup>3</sup>	-
Water tightness	Passed	DS/EN 858-1 pt. 6.3.2
Effectiveness	Passed	DS/EN 858-1 pt. 6.3.1, 6.3.3-6.3.8, 6.5
Load bearing capacity	Passed	DS/EN 858-1 pt. 6.4
Max. installation depth	2 m (see installation instructions)	-
Hydraulic efficiency	0,40 mg/l oil	DS/EN 858-1 pt. 4
Durability	Passed	DS/EN 858-1 pt. 6.2
Material	PE	-
Reaction to fire	NPD	-
10. Conformity	The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.	

Signed for and on behalf of the manufacturer by:

Assens, date 12.07.2023

  
Jonas Groth, Engineer