


DATASHEET



SL20CCTB

110-230V IP65 Twin Head Black 20W Security Floodlight with PIR,Sensor, CCT and Manual Override

www.mlaccessories.co.uk



MLA PART CODE	SL20CCTB
DESCRIPTION	110-230V IP65 Twin Head Black 20W Security Floodlight with PIR,Sensor, CCT and Manual Override
NET WEIGHT (KG)	0.485
FINISH	Black
DIFFUSER	Opal
DIMENSIONS (MM)	Width - 243 Projection - 173 Base Diameter - 107 Base Depth - 63
TILT (DEGREES)	270
ROTATION (DEGREES)	360
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP65
WATTAGE (W)	20
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1810
LUMENS LIGHT SOURCE ONLY (LM)	1810
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	95.3
CIRCUIT WATTAGE (W)	19
CCT	3000/4000/5500K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.092
DISPLACEMENT FACTOR	>0.9
SVM	0.83

PST-LM	0.14
BEAM ANGLE (DEGREES)	75
LIFE SPAN (HRS)	50,000
L70B50 LIFESPAN (HRS)	54,000
DIMMABLE	No
OPERATING TEMPERATURE	-20~40°C
INPUT VOLTAGE	110/230V
CABLE GLAND INCLUDED	Blind grommet
SENSOR TYPE	PIR
SENSOR OVERRIDE	Yes
SENSOR DETECTION ANGLE (DEGREES)	90
OPTIMUM DETECTION RANGE (M)	8
SENSOR DURATION	2s - 10min
SENSOR LUX SETTINGS	10lux-300lux
STANDBY POWER	<0.5W
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270864410

Date Created: 30/05/2023 12:04

