



LED PLC Direct to Mains




Energy saving LED PLC lamp direct to mains no ballast required. Polycarbonate body with pull and twist adjustment ± 45° for directing light to best position. No mercury or hazardous materials. Instant start with no warm-up time.

- 30,000 hour life
- 15,000 switching cycles
- G24 universal cap. Suitable for G24 2-Pin and G24 4-Pin fittings
- 4000K cool white
- Colour rendering index Ra≥80
- Opal white finish
- Not suitable for dimming
- Not suitable for emergency fittings
- Recommended for indoor use only



Product Code	Watts (W)	Volts (V)		Colour Appearance	Colour Temp (K)		Compact s Fluorescent Eauivalent	Beam Angle	Dimensions (mm)		EnergyOrder Rating Qty	
					(14)	()	(W)		Dia	L		
Single Carton												
14916	7	240	G24 Universal	Cool White	4000	800	18	110°	34	148	G	1
14923	10	240	G24 Universal	Cool White	4000	1100	26	110°	34	171	G	1

Important Information: Crompton Lamps LED PLC direct to mains lamps should be wired directly to mains. DO NOT use a ballast, Warranty excludes damage that may be caused from wiring into a ballast. The luminaire to which it is installed may need re-wiring. Ballast must be bypassed by a qualified person.



Crompton Lamps Limited registered in England and Wales No. 05590551 Registered office and correspondence address: Unit 2, Marrtree Business Park, Bowling Back Lane, Bradford BD4 8QE

Tel: +44 (0)1274 657 088 Fax: +44 (0)1274 657 087 Email: sales@cromptonlamps.com Web: www.cromptonlamps.com