



CABLE REEL HANDLING CATALOG



WHEREVER THE JOB TAKES YOU,
COUNT ON JAMESON™





JLIFT

ONE PERSON. NO TRAILER.

REMOTE CONTROL

With the push of a button, one person can easily load and go in minutes. Corded J-Lift control is included; with optional wireless remote control available separately.

DUAL ACTING HYDRAULICS

Dual action and dual load-holding hydraulic pump and cylinders raise and lower with equal force, which is extremely convenient in cold climates and with lighter spools. This also allows faster stopping with a fully loaded reel for safer operation. **Exceptional RAISE, LOWER & STOP Capabilities!**

POWDER COATED

For long life performance and corrosion resistance.

LIGHT KIT

Connect to truck's 4-pin trailer output for brake lights and turn signals.

Specifications

Part Number	MTK-40
Dimensions	45" x 28" x 30"
Total Weight	293 Lbs.
Weight - Wiring	18 Lbs.
Power Source	12-Volt DC
Finish	Powder Coat
Hydraulic Pump	Dual Action with Corded Remote Control
Hydraulic Hoses	1/4" SAE, 5800 PSI
Cylinders	3000 PSI

Operating Specifications

Maximum Reel Capacity	40" Wide x 48" Diameter Maximum
Maximum Lifting Capacity	1,000 Lbs.*
Hitch Required	Minimum Class IV Hitch
Hitch Recommended	Pintle Plate / Class V Hitch
Wiring Included	20', 4 AWG Harness With Jumper Clamps & Ring Terminal Options

* Minimum Class IV hitch required. Reel weight plus 293 lbs. must not exceed vehicle tongue weight.



PORTABLE REEL BUCK

The all-new Jameson® Portable Reel Buck is a quick and easy way to set up strand and cable reels up to 54" diameter. The reel buck is designed to be easily moved about the job site using the handles on the frame and the spool as a wheel. The durable steel tube frame has a weight capacity of 850 lbs. and can withstand the toughest job sites. The reel buck is collapsible for quick load and unloading and is adjustable for different reel widths and heights.

- Load Capacity: 850 lbs.
- Accommodates Reel widths up to 54" inch diameter
- Designed to work with Arbor Spindle up to 2"
- Heavy-duty adjustable steel frame
- Easy setup and breakdown for transportation

Can ship "small pack" via UPS, FedEx or DHL



Part Number	Description
RB-54	Portable Reel Buck

SPOOL DIAMETER CAPACITY

Max Ø 54" (137 cm)



Max Ø 46" (116 cm)



Max Ø 34" (86 cm)





WHEREVER THE JOB TAKES YOU,
COUNT ON JAMESON™



JAMESONTOOLS.COM

800.346.1956