

WHEREVER THE JOB TAKES YOU, COUNT ON JAMESON™





TREE CARE TOOLS | OVERHEAD CABLE TOOLS | TOOL STORAGE & ORGANIZATION | CABLE REEL HANDLING DUCT RODDERS | DUCT HUNTER | TRACEABLE RODDERS & LOCATING | FIBER BLOWING EQUIPMENT FISH TAPES/FISH RODS | WIRING/SPLICING | INSULATED HAND TOOLS | LIGHTING

since 1956

CONTENTS

TREE CARE TOOLS Fiberglass Poles - Standard Ferrule Pole Pruners Saw Blade Pole Saw Heads Fiberglass Poles - CompositLock** Ferrule Tree Trimming/Line Clearance Kits Tree care Accessories Line Throwing Supplies Hand Saws	4 - 41
OVERHEAD CABLE TOOLS Corner Block/Brackets Stringing Blocks Measuring Poles Aerial Sheaves	42 - 45
TOOL STORAGE & ORGANIZATION Boom Mount Tool Holders Canvas Tool Bags Bucket Mount Tool Holders	46 - 51
CABLE REEL HANDLING J-Lift* Reel Buck	52 - 53
DUCT RODDERS Easy Buddy® - 1/4 in. Duct Rodders Good Buddy® - 3/8 in. Duct Rodders Big Buddy® & Mega Buddy® - 1/2 in. Duct Rodders	54 - 59
TRACEABLE RODDERS & LOCATING Duct Hunter™ Traceable Rodders Live Tracer™ for Gas Mains Live Traver™ Rodders for Gas & Water Service Lines Directional Entry Tools Electrofusion Insertion Tapping Tees	60 - 79
FISH TAPES & FISH RODS Fiberglass Fish Tapes Fish Tape Accessories Glow Fish Rods Fish Rod Accessories Coated Fish Rods	80 - 93
WIRING/SPLICING TOOLS Scissors & Shears Knives Tool Pouches Installers Kit Fiber Optic Stripper Blade Sharpener Cable Cutting & Bending	94 - 104
INSULATED HAND TOOLS Tool Kits Accessories Pliers Cable Cutters Wire Strippers Wrenches Sockets & Drivers Nut Drivers Screwdrivers Hex Keys Knives & Saws	105 - 120
LIGHTING Work/Task Light Equipment Lights Hazardous Location Lights Wide Area/High Bay Expeditionary Lights Shelter Lights PAXLight® Medical Light	121 - 149

Notice

The information in this catalog is effective January 2023 and supersedes all previous catalogs. Since product improvement is a continual process at Jameson, specifications are subject to change without notice.







LEADER IN FIBERGLASS POLES

THE ORIGINAL AND STILL THE BEST





THE ORIGINAL FIBERGLASS POLE INTRODUCED IN 1956

Jameson introduced the first fiberglass lay-up sticks in 1956 to meet the needs of telecommunication linemen.

The strength and durability of fiberglass proved indispensable when lifting leak detection equipment overhead and soon replaced wooden poles as the industry standard.

Today, Jameson poles are available in a variety of configurations with tools and accessories to serve telecommunication linemen, professional arborists and landscapers.

By consistently providing the highest quality fiberglass poles, Jameson remains the professional's choice for line clearance and tree care.





	Poles Models				
	JE SERIES	FG SERIES	BL SERIES	LS SERIES	DOUBLE LOCK™ TELESCOPING
Typical Application	Line Clearance & Aerial Construction	Professional Tree Care & Aerial Construction	Professional Tree Care The Ergonomic Choice for Prolonged Use	Landscapers & Homeowners	Landscapers & Homeowners
Key Features	Foam Core Protects Against Moisture And Debris	Highest Strength. Industry Standard For Over 50 Years. Most Versatile.	Highly Durable Enamel Coating Lightest Weight	Light Duty Landscaping	Telescopes To Save Space
Dielectric Testing	Individually Tested To 100 kV Per Foot For 5 Minutes	Batch Tested To 100 kV Per Foot For 5 Minutes	Batch Tested To 100 kV Per Foot For 5 Minutes	Not Tested	Not Tested
Wall Thickness	0.110"	0.125"	0.075"	0.100"	Standard
Color	High Visibility Safety Yellow	Jameson Yellow	High Gloss Blue	Green	Yellow

PUTTING IT TOGETHER Customize Poles & Accessories PRUNER ADAPTER **EXTENSION** POLE **TOOL HEAD** (PRUNER) SAW HEAD POLE With male ferrule ADAPTER and permanently mounted saw head for attaching saw blade MALE **FERRULE FEMALE EXTENSION POLE FERRULE** With male & female FEMALE ferrules for additional **FERRULE** length POLE BASE POLE With rubber end cap and female ferrule provides BASE POLE solid foundation ADAPTER & FERRULE SYSTEM **POLE CONFIGURATIONS** Makes it easy to change from pruner head to pole saw head or Base Pole - Jameson recommends pole lengths of 4' to 12'. An exterior starting with Base Pole leaf spring locking button on ferrule Extension Pole provides additional offers a strong connection, whether

length, extending workable height.

Saw Head Pole is for use with Saw

- Choose your tool head (pruner, pole saw or accessory)
- Attach tool head to pole's female ferrule with adapter
- For additional length, attach extension pole(s)

For highest performance and safety, Jameson recommends using a Base Pole when using one pole or starting with a Base Pole when working with multiple poles.

attaching poles or tool heads.

This versatility saves time and

money in the field.

Use saw blade with Saw Head Pole or use Pole Saw Head (page 11) with Extension Pole.

SAW HEAD POLE SET UP

SAW BLADE

SAW HEAD

SAW BLADE

SAW HEAD POLE

Jameson recommends using Saw Head Poles with Base Poles

Blade.



JE FOAM CORE POLES

Preferred For Aerial Construction & Line Clearance

Jameson's original foam core pole is the highest quality fiberglass pole available.

- Foam core prevents debris and moisture build up inside pole and adds extra hoop strength and rigidity
- Polymer protective surface veil prevents fiber blooming at surface due to abrasion or ultra-violet light
- · High visibility safety yellow color
- Meets requirements of OSHA Subpart R 1910.269(j)(1)(i): Individually tested to 100KV per foot for five minutes

Not A "Hot Stick" - Not For Use On Energized Lines

Pole Length	1'	4'	6'	8'	10'	12'
Base	JE-1F	JE-4F	JE-6F	JE-8F	JE-10F	JE-12F
Extension	N/A	JE-4	JE-6	JE-8	JE-10	JE-12
Saw Head	N/A	JE-4SFP	JE-6SFP	JE-8SFP	JE-10SFP	JE-12SFP
Pole Kit	N/A	JE-6/3	One 3' Exten	sion Pole & Th	ree 6' Extensio	n Poles
Pole Kit	N/A	JE-6/4	Four 6' Exten	sion Poles		





FG HOLLOW CORE POLES

Preferred For Tree Trimming and Aerial Construction

Jameson's strongest and most popular pole is lighter than the JE series, offering greater control and exceptional bending strength.

 Polymer protective surface veil prevents fiber blooming at surface due to abrasion or ultra-violet light

Batch tested to 100KV per foot for five minutes.

Not A "Hot Stick" - Not For Use On Energized Lines

Pole Length	1'	4'	6'	8'	10'	12'
Base	FG-1F	FG-4F	FG-6F	FG-8F	FG-10F	FG-12F
Extension	N/A	FG-4	FG-6	FG-8	FG-10	FG-12
Saw Head	N/A	FG-4SFP	FG-6SFP	FG-8SFP	FG-10SFP	FG-12SFP
Pole Kit	N/A	FG-6/3F	One 3' Extens 6' Extension F		6' Base Pole, Tv	vo





BL HOLLOW CORE POLES

The Lightweight Option For Tree Trimming

Jameson's highest strength-to-weight ratio pole is lightweight and easy to control, making it ideal for tree trimming.

- Lighter weight results in less fatigue during extended work periods and easier handling
- Durable, high gloss enamel coating for long life, easy cleaning and fiber bloom prevention

Batch tested to 100KV per foot for five minutes

Not A "Hot Stick" - Not For Use On Energized Lines

Pole Length	4'	6'	8'	10'	12'
Base	BL-4F	BL-6F	BL-8F	BL-10F	BL-12F
Extension	BL-4	BL-6	BL-8	BL-10	BL-12
Saw Head	BL-4SFP	BL-6SFP	BL-8SFP	BL-10SFP	BL-12SFP





LS HOLLOW CORE POLES

The Choice for Landscapers

Economical pole for landscapers and homeowners.

- Lightweight, versatile.
- Polymer protective surface veil prevents fiber blooming at surface due to abrasion or ultra-violet light

Not A "Hot Stick" - Not For Use On Energized Lines

Pole Length	4'	6'	8'	10'	12'
Base	LS-4F	LS-6F	LS-8F	LS-10F	LS-12F
Extension	LS-4	LS-6	LS-8	LS-10	LS-12
Saw Head	LS-4SFP	LS-6SFP	LS-8SFP	LS-10SFP	LS-12SFP



DOUBLE LOCK™ TELESCOPING POLES

Saves Space - Adjustable Height

Telescoping Poles are constructed from lightweight fiberglass and offer a space-saving design. The Double Lock system keeps the telescoping pole from collapsing and gives you a secure connection, no matter what the length.

- Double locks (internal lock and external cap) ensure poles will not collapse. Count on a secure connection at any length for maximum versatility and safety.
- · Preferred choice for arborist, home owners and landscapers.
- Lightweight, durable fiberglass will not crimp under high stress like aluminum poles.
- · Compact for easier climbing and storage.

Not A "Hot Stick" - Not For Use On Energized Lines

For safety, Jameson does not recommend attaching additional poles or Tru Shot to Telescoping Poles.



TELESCOPING POLE

Blank End

Part Number	Description
TP-6	4 - 6' Length
TP-12	6 - 12' Length
TP-14	7 - 14' Length



TELESCOPING POLE
With Female Ferrule

Part Number Description

TP-6F 4' - 6' Length

TP-05 4- 0' Length

TP-8F 4' - 8' Length
TP-12F 6 - 12' Length
TP-14F 7 - 14' Length

Ferrule allows the use of Pruner or Pole Saw with the same pole







TELESCOPING POLEWith Permanent Mount Pruner

Part Number	Description
TP-12-14	6 - 12' Length
TP-14-14	7 - 14' Length
Fixed Mount JA-14S Pruner & Rope	



TELESCOPING POLE
With Permanent Mount Pole Saw

Part Number	Description	
TP-12-S	6 - 12' Length	
TP-14-S	7 - 14' Length	
Fixed Mount Pole Saw with SB-13TE 13" Tri-Cut		



TELESCOPING POLE

With Permanent Mount Pole Saw

Part Number	Description
TP-12PKG	6-12' Length Double Lock™ Telescoping Pole Kit
Kit Includes JA-14 Saw Head, and 1	1 Pruner, Adapter, Rope, PS-3FP Pole 3" Tri-Cut Blade

JA SIDE-CUT PRUNERS

For Professional Arborists

This fixed pulley pruner was manufactured with forged steel components for strength, designed for the professional arborist. These heavy duty pruners have a 1-1/4 in. cut capacity with side cut action. The pulley feature reduces the pulling force needed to make the cut. The pruner also features an enhanced spring for smoother cutting action and a raised hook edge to reduce blade drag. Features a removable upper spring pin and blade bolt for easy blade replacement and sharpening.

- Forged steel components for added strength
- Enhanced spring for smoother cutting action
- Raised hook edge reduces blade drag



FIXED PULLEY PRUNER

Part Number	Description
JA-14	Fixed Pulley Pruner, 1.25" cutting capacity



SWIVEL PULLEY PRUNER

Part Number	Description
JA-14S	Swivel Pulley Pruner, Swivel versatility in pull direction and more leverage with less pressure on pulley arm. 1.25" cutting capacity



DOUBLE PULLEY PRUNER

Part Number	Description
JA-14DP	Double Pulley Pruner provides additional leverage and significant reduction in required pulling force. 1.25" cutting capacity. Adapter included.



Part Number	Description
PH-14-PKG	JA-14 Pruner, Adapter & Rope



Part Number	Description
P-14-A	JA-14 Pruner & Adapter



Part Number	Description
PH-14S-PKG	JA-14S Pruner, Adapter & Rope



Part Number	Description
P-14-AS	JA-14S Pruner & Adapter



Part Number	Description	
JA-14DP-PKG	JA-14DP Pruner, Adapter & Rope	



Part Number	Description
PHA-14	Adapts JA-14, JA-14S or JA-34



Pá	art Number	Description
PR-	-20	Pruner Rope with Handle 5/16" X 20'



Part Number	Description
32-18	Leather Guard for JA Pruners



Part Number	Description
PRI-7.5	7.5" Insulator
PRI-12	12" Insulator

Pruner Rope Insulator attaches to rope to break electrical current if rope contacts energized lines above insulator. Fiberglass tested to 100KV per foot for 5 minutes.

JA-34 BIG MOUTH SIDE-CUT PRUNERS

For Professional Arborists

The Jameson Big Mouth Pruner has a 1.75" cutting capacity for larger limbs.

sharpening.



Part Number	Description
JA-34	Fixed Pulley Big Mouth Pruner
175" cutting can	acity pruper



Part Number	Description
JA-34DP	Double Pulley Big Mouth Pruner
Big Mouth Pruner with double pulley for additional leverage and significant reduction in required pulling force 175" cutting capacity. Adapter included	



Part Number	Description
P-34-A	JA-34 Pruner &Adapter





Part Number	Description
PH-34-PKG	IA-34 Pruner Adapter & Rone



Part Number	Description
IA-34DP-PKG	JA-34DP Pruner, Adapter & Rope

PH CENTER-CUT PRUNERS

The Standard with Telecommunication Companies

Jameson PH pruners have been the standard with telecommunication companies for 20+ years to trim foliage around aerial lines or drops. The steel pruners feature a chain pulley and center cut blade.



Part Number	Description
PH-11	Pruner with 1" Center Cut
"Bell B Pruner". Uses SB-1T or SB-2 Saw Blade	



	Part Number	Description
	P-11-A	PH-11 Pruner with Adapter
PH-11 Pruner with adapter to snap into pole's fe		adapter to snap into pole's ferrule



Control Control	
t Number	Description
4-11	Adapter
ots PH-11 Pru	iner to Pole's Ferrule



SAW BLADESFor Pole Saws & Handsaws

Jameson's line of conventional 16" saw blades have long been an industry standard with telecommunication companies for line clearance.

Expanding our product line to meet the demands of professional arborists, Jameson introduced Barracuda $^{\text{\tiny{M}}}$ Tri-Cut Saw Blades.

Hard-chrome plated with impulse hardened teeth, tri-cut blades provide a quicker, cleaner cut with less wear on the blade than traditional blades.









Part Number	Description
SB-16TE	16" Tri-Cut Saw Blade



Part Number	Description
SB-13TE-GUL	13" Barracuda™ Gullet Tri-Cut Blade
Gullets allow chips & debris to exit cut.	







Part Number	Description
SB-13TE-H	13" Barracuda™ Tri-Cut Saw Blade with Hook
Hook prevents si pulls small branc	lipping off or pulling out of cut; hes or vines.



Part Number	Description	
SB-16TE-W	16" Barracuda™ Tri-Cut Mammoth Blade	
Wider, thicker blade is more rigid than typical 16" blades. Does not fit hand saw.		



Part Number	Description
SB-16TE-DH**	16" Barracuda™ Tri-Cut Double Hook Blade

Sharpened upper hook prevents pulling out of cut and quickly removes suckers or vines. Sharpened lower hook scores bark below cut to prevent ripping damage to branch collar. Fits Jameson Pole Saw Heads. Does not fit hand saw handle.



Part Number	Description
SB-1C	16" Single Edge Chrome Blade
Fits PS-3 Pole Saw Head & PH-11 Pruner	



Part Number	Description
SB-1T	13" Single Edge Teflon Coated Blade
Fits PH-11 Pruner	



Part Number	Description
SB-2	16" Single Edge Teflon Coated Blade
Eite DC 2 Dolo 9	Saw Hoad & BH 11 Brupor



Part Number	Description
SB-5U	SB-2 Blade with SB-UC Universal Adapter
Fits UA-1 Adapter	r to snap into pole ferrule



Part Number	Description
SB-UC	Universal Adapter
Attaches Saw Bla	ade To UA-1 Adapter



Part Number	Description
UA-1	Adapter
Snaps into pole's directly to pole	ferrule to attach saw blade



^{**}Items Are Provided In Clamshell-Ready Packaging

POLE SAWS

Corrosion Resistant, Lightweight Aluminum

The Pole Saw Head snaps into Jameson pole ferrules and fits Jameson saw blades.

- \cdot Low profile design maneuvers easily in dense foliage.
- \cdot Convenient hook pulls loose limbs and branches free.

Not For Use On Or Near Live Wires



Part Number	Description
PS-3	Saw Head

Offset Blade Mount; Carriage Bolt Saw Head snaps into pole. Fits SB-2 Saw Blade



Part Number	Description
PS-3FP	Saw Head
Contor Plada N	Acust: Mounting Din

Center Blade Mount; Mounting Pin Mounting Pin for easy blade replacement without tools. Snaps into pole.



Part Number	Description
PS-3FPK	13" Pole Saw Kit With Scabbard
PS-3FPS1 Kit & Le	Pather Scabbard



Part Number	Description
PS-3FPS1	13" Tri-Cut Pole Saw Kit
PS-3FP Saw Hea	d & SB-13TE 13" Saw Blade



Part Number	Description
PS-3FPS2	16" Tri-Cut Pole Saw Kit
PS-3FP Saw Hea	d & SB-16TE 16" Saw Blade



Part Number	Description	
PS-2K	Pole Saw Kit & Scabbard	
PS-3SB Kit & Lea	ther Scabbard	



	Part Number	Description
	PS-3SB	Pole Saw Kit
	PS-3 Saw Head & SB-2 Saw Blade	



Part Number	Description		
PS-3FPK-16DH-B Double Hook Pole Saw Kit			
PS-3FPK-16DH Kit & Rubber Belting Scabbard			



Part Number	Description
PS-3FPK-16DH-L	Double Hook Pole Saw Kit
DS 3EDK 16DH Kit & Loathor Scabbard	



	Part Number	Description			
ĺ	PS-3FPK-16DH	Double Hook Pole Saw Kit			
	PS-3FP Saw Hea	ad & SB-16TE-DH Double Hook			



Part Number	Description
SBB-3DH	Rubber Belting Scabbard for Double Hook Blade



Part Number	Description
SBL-3DH	Leather Scabbard for Double Hook Blade



Part Number	Description		
SBL-2	Leather Scabbard for 13" & 16" Blades		



Part Number	Description			
SBC-2	Canvas Scabbard for 13" & 16" Blades			

TREE CARE TOOLS - COMPOSITLOCK™ POLES





TREE CARE TOOLS

COMPOSITLOCK™ FIRERGI ASS POLES







 $\mathsf{COMPOSITLOCK}^{\mathsf{m}}$ Poles maintain insulating properties across pole sections for line-clearance tree work PLUS offer more secure pole connection for telecommunication, line clearance, arborist and landscape professionals.

INCREASED SAFETY WHEN WORKING AROUND ENERGIZED LINES

Responding in part to the TCIA EHAP® Program and NRECA Commitment to Zero Contacts initiative, Jameson's CompositLock $^{\text{\tiny M}}$ Fiberglass Poles seek to reduce the potential for conductivity.

STRONG, SECURE CONNECTIONS BETWEEN POLE SECTIONS

Over-sized thread profile provides strong, secure connections, eliminating loose fit or "slop" required with traditional aluminum ferrules. The result is less binding, easy cleaning, and improved rigidity the entire working length of the pole.

SMOOTH FERRULE PROFILE

Sunken rivets and threaded attachment result in a smooth profile that moves easily in foliage without snagging

Not A "Hot Stick" - Not For Use On Energized Lines

TREE CARE TOOLS - COMPOSITLOCK™ POLES



JEC FOAM CORE COMPOSITLOCK™ POLE

Preferred for Aerial Construction & Line Clearance

The highest quality fiberglass pole available.

- Foam core prevents debris and moisture build up inside pole and adds extra hoop strength and rigidity
- Polymer protective surface veil prevents fiber blooming at surface due to abrasion or ultra-violet light
- · High visibility safety yellow color
- Meets requirements of OSHA Standard 1910.269(j)(1)(i):
 Individually tested to 100KV per foot for five minutes

Pole Length	4'	6'	8'	10'	12'
Base	JEC-4F	JEC-6F	JEC-8F	JEC-10F	JEC-12F
Extension	JEC-4	JEC-6	JEC-8	JEC-10	JEC-12
Saw Head	JEC-4SFP	JEC-6SFP	JEC-8SFP	JEC-10SFP	JEC-12SFP




FGC HOLLOW CORE COMPOSITLOCK™ POLE

Preferred for Tree Trimming & Aerial Construction

Our strongest and most popular pole is lighter than foam core poles, offering greater control and exceptional bend strength. Batch tested per ASTM F711. ††

- Polymer protective surface veil prevents fiber blooming at surface due to abrasion or ultra-violet light
- Batch tested to 100KV per foot for five minutes.

Pole Length	4'	6'	8'	10'	12'
Base	FGC-4F	FGC-6F	FGC-8F	FGC-10F	FGC-12F
Extension	FGC-4	FGC-6	FGC-8	FGC-10	FGC-12
Saw Head	FGC-4SFP	FGC-6SFP	FGC-8SFP	FGC-10SFP	FGC-12SFP



BLC HOLLOW CORE COMPOSITLOCK™ POLE

The Lightweight Option for Tree Trimming

The highest strength-to-weight ratio pole is lightweight and easy to control, making it ideal for tree trimming. BL poles are batch tested per ASTM F711.⁺⁺

- Durable enamel coating prevents fiber blooming at surface due to abrasion or ultra-violet light
- Batch tested to 100KV per foot for five minutes.

Pole Length	4'	6'	8'	10'	12'
Base	BLC-4F	BLC-6F	BLC-8F	BLC-10F	BLC-12F
Extension	BLC-4	BLC-6	BLC-8	BLC-10	BLC-12
Saw Head	BLC-4SFP	BLC-6SFP	BLC-8SFP	BLC-10SFP	BLC-12SFP



ASE POLE

Rubber end cap and male ferrule to attach poles or tools. Provides solid foundation. Jameson recommends starting with Base Pole.

Male and female ferrules to attach additional poles or

tools. Provides additional length (workable height).

SAW HEAD POLE

Female ferrule and permanently mounted saw head for attaching saw blade.

TREE CARE TOOLS - COMPOSITLOCK™ POLE HEAD TOOLS



Part Number	Description		
PHC-14-PKG	1.25" Side-Cut Single Fixed Pulley Pruner & Rope		

Heavy duty pruner with enhanced spring for smooth cutting action.



Part Number	Description
JAC-14DP-PKG	1.25" Side Cut Double Pulley Pruner & Rope



Part Number	Description	
JAC-34DP-PKG	1.75" Side-Cut Double Pulley Pruner & Rope	
Double pulley for pulling force.	additional leverage & less	



Part Number	Description	
PHC-34-PKG	1.75" Side Cut Single Pulley Pruner & Rope	



Part Number	Description	
PHC-11-PKG	1" Center Cut Pruner Rope & Saw Blade	
Chain pulley pruner. Accommodates SB-2 saw bla		



Part Number	Description	
PHC-12-PKG	1.5" Center Cut Pruner & Rope	
Chain pulley pruner. DOES NOT accept saw blade.		

TREE CARE TOOLS - COMPOSITLOCK™ POLE HEAD TOOLS



	Part Number	Description	
	PSC-3FP	Pole Saw Head	
Center blade mount. Mounting pin for e		9.	



Part Number	Description
PSC-3FPS1	Saw Head & 13" Tri-Cut Blade
PSC-3FPS2	Saw Head & 16" Tri-Cut Blade



Part Number	Description	
PSC-3SB	Pole Saw Kit	
Saw Head & 16" SB-2 Blade		



Part Number	Description
PSC-3FPK-16DH	Pole Saw Kit
Saw Head & Double Hook Blade	



Part Number	Description
PSC-3FPK-16DH-B	Pole Saw Kit
Saw Head, Double H Belting Scabbard	Hook Blade Rubber



Part Number	Description	
WRC-1	Limb Raiser	
Pull or lift branch	nes.	

TREE CARE TOOLS - COMPOSITLOCK™ POLE HEAD TOOLS



Part Number	Description
CL-ADAPTER	Composite Lock Adapter
Easily converts upper end of CompositeLock pole to aluminum female ferrule. 1.75" x 16.5"	







TREE TRIMMING KITS

COMBINATIONS OF POLES AND TOOLS



A variety of combinations make it easy to find the best fit for your tree trimming job.

Adapters allow user to switch from pruner head or pole saw quickly and easily without tools, using the same pole.

Kits are available with pole adapters or permanently mounted (fixed) tool heads.

JE SERIES - ALUMINIUM FERRULES



			4.9		
Part Number	JE-6F	JE-6	PH-14-PKG	JA-34DP	PH-11
Kit Description	6' JE Base Pole	6' JE Extension Pole	JA-14 Purner with Pole Adapter and Pruner Rope	Double Pulley Big Mouth Pruner with Adapter and Pruner Rope	PH-11 Pruner, Adapter & Rope
JE-11K*	√	√ _{x2}			✓
JE-14K*	√	√ _{x2}	✓		
JE-6PKG-2	✓	✓	✓		
JE-6PKG-7	√	✓		✓	
JE-6PKG-8*	√	√ _{x2}		✓	

^{*}Comes with two 6' JE Extension Poles

- Preferred for Aerial Construction and Line Clearance Fiberglass Pole Kits
- High visibility safety yellow color



	4.5				
PS-3FPS2	PS-3FPS1	SB-1T	HS-13TE-O	WR-1	SBC-2
Pole Saw Head, 16" Tri-Cut Blade (SB-16TE)	Pole Saw Head, 13" Tri-Cut Blade (SB-13TE)	Single-Edge Teflon Coated Blade, 16 in.	13" Tri-Cut Hand Saw	Limb & Wire Raiser	Canvas Scabbard
		✓			✓
	✓		✓	✓	
✓					
✓			✓	✓	

TREE CARE TOOLS - LINE CLEARANCE KITS

JE SERIES - ALUMINIUM FERRULES



	1000		1,000		
Part Number	JE-6	JE-6F	JA-14	PH-34-PKG	PS-3FP
Kit Description	6' JE Extension Pole	6' JE Base Pole	JA-14 Purner with Pruner Rope	JA-34 Purner with Pruner Rope	Saw Head Casting with Quick-Change Adapter
JE-18LCKIT-14	✓ _{x2}	✓	✓		✓
JE-18LCKIT-34DP	✓ _{x2}	✓		✓	✓

JE SERIES - COMPOSITLOCK™



Part Number	JEC-6F	JEC-6	PHC-14-PKG	JAC-34DP-PKG	PSC-3FPS2
Kit Description	6' JEC Base Pole	6' JEC Extension Pole	1.25" Side-Cut Single Fixed Pulley Pruner & Rope	1.75" Side-Cut Double Pulley Pruner & Rope	Saw Head & 16" Tri-Cut Blade
JEC-18LCKIT-14	✓	√ _{x2}	✓		✓
JEC-18LCKIT-34DP	✓	✓ x2	✓	✓	✓

TREE CARE TOOLS - LINE CLEARANCE KITS



SB-16TE	SBL-2	PRI-7.5	B-6V
Pole Saw Head, 16" Tri-Cut Blade	Leather Scabbard for 13" & 16" Blades	7.5" Fiberglass Rope Insulator	Pole & Pruner Storage Bag
✓	✓	✓	✓
✓	✓	✓	✓



PRI-7.5	SBL-2	B-6V
7.5" Fiberglass Rope Insulator	Leather Scabbard for 13" & 16" Blades	Pole & Pruner Storage Bag
✓	✓	✓
✓	✓	✓

FG SERIES - ALUMINIUM FERRULES



				4.9			
Part Number	FG-6F	FG-6	FG-3	JA-14	JA-14DP-PKG	JA-34DP	
Kit Description	6' FG Base Pole	6' FG Extension Pole	3' FG Extension Pole	JA-14 Purner with Pruner Rope	JA-14DP Pruner, Adapter Rope	Double Pulley Big Mouth Pruner with Adapter and Pruner Rope	
FG-6PKG-1	✓	✓		✓			
FG-6PKG-2	✓	✓		✓			
FG-6PKG-3	✓	✓			✓		
FG-6PKG-7	✓	✓				✓	
FG-11K	✓	✓ _{x2}					
FG-12K	✓	✓ _{x2}					
FG-14K*	✓	✓ x2		✓			
FG-6-3W	✓	✓ x2	✓				

FG SERIES - COMPOSITLOCK™



Part Number	FGC-6F	FGC-6	PHC-14-PKG	JAC-34DP-PKG	PSC-3FPS2
Kit Description	6' FGC Base Pole	6' FGC Extension Pole	1.25" Side-Cut Single Fixed Pulley Pruner & Rope	1.75" Side-Cut Double Pulley Pruner & Rope	Saw Head & 16" Tri-Cut Blade
FGC-6PKG-1	✓	✓	✓		✓
FGC-6PKG-7	✓	✓		✓	✓



	400	10.00		-			
PH-11	PH-12	PS-3FPS1	PS-3FPS2	SB-1T	HS-13TE-O	WR-1	SBC-2
PH-11 Pruner, Adapter & Rope	PH-12 Pruner, Adapter and Rope	Pole Saw Head, 13" Tri-Cut Blade (SB-13TE)	Pole Saw Head, 16" Tri-Cut Blade (SB-16TE)	Single-Edge Teflon Coated Blade, 16 in.	13" Tri-Cut Hand Saw	Limb & Wire Raiser	Canvas Scabbard
		✓					
		✓			✓	✓	
			✓				
✓				✓			✓
	✓						
						1	

BL SERIES - ALUMINIUM FERRULES



Part Number	BL-8F	BL-6F	BL-8	BL-6
Kit Description	8' BL Base Pole	6' BL Base Pole	8' BL Extension Pole	6' BL Extension Pole
BL-8PKG-1	✓		✓ _{x2}	
BL-8PKG-5	✓		✓ _{x2}	
BL-6PKG-1		✓		✓ _{x2}
BL-6PKG-5		✓		✓ _{x2}
BL-6PKG-7		✓		✓

BL SERIES - COMPOSITLOCK™



Part Number	BLC-6F	BLC-6F	PHC-14-PKG	JAC-34DP-PKG	PSC-3FPS2
Kit Description	6' BLC Base Pole	6' BLC Extension Pole	1.25" Side-Cut Single Fixed Pulley Pruner & Rope	1.75" Side-Cut Double Pulley Pruner & Rope	Saw Head & 16" Tri-Cut Blade
BLC-6PKG-1	✓	✓ _{x2}	✓		✓
BLC-6PKG-7	✓	✓	✓	✓	✓









	40	4/4/		
JA-14	JA-34DP	PS-3FPS2	PS-3FP	
JA-14 Purner with Pruner Rope	Double Pulley Big Mouth Pruner with Adapter and Pruner Rope	Pole Saw Head, 16" Tri-Cut Blade (SB-16TE)	Pole Saw Head	
✓		✓		
	✓		✓	
✓		✓		
	✓		✓	
	✓	✓		

LS SERIES - LANDSCAPERS HOLLOW CORE FIBERGLASS POLE KITS



			-			
Part Number	LS-6F	LS-8F	LS-6	LS-6SFP	JA-14	PH-14S-PKG
Kit Description	6' LS Base Pole with Female Ferrule	8' LS Base Pole with Female Ferrule	6' LS Extension Pole	6' LS Sawhead Pole with PS-3FP Head	JA-14 Purner Permanently Mounted on 6' Pole with Male Ferrule on Bottom Pruner Rope	JA-14 Pruner, Adapter Rope
LS-6PKG-1	✓				✓	
LS-6PKG-2	✓			✓	✓	
LS-6PKG-3	✓		✓			✓
LS-6PKG-4	✓		✓		✓	
LS-6PKG-5	✓		✓			
LS-6PKG-6	✓		✓	✓		
LS-6PKG-7*	✓		✓ _{x2}			
LS-6PKG-8*	✓		✓ _{x2}			
LS-8PKG-1		✓				✓

^{*}Comes with two 6' LS Extension Poles

⁻ Economical poles for lanscapers and homeowners.

⁻ Lightweight and versatile.



JA-14DP-PKG	PH-11	PH-12	PS-3FPS1	SB-16TE	PS-3FP
JA-14DP Pruner, Adapter Rope	PH-11 Pruner, Adapter & Rope	PH-12 Pruner, Adapter and Rope	Pole Saw Head, 13" Tri-Cut Blade (SB-13TE)	Pole Saw Head, 16" Tri-Cut Blade	Pole Saw Head
					✓
✓			✓		
				✓	
	✓				
		✓			
			✓		

TREE CARE TOOLS - ACCESSORIES



BIG SHOT™ LINE LAUNCHERThe Standard with Telecommunication Companies

Launches throw bag and line over tree limbs, delivering line up to 150'. $\,$

For safety and effectiveness, we recommend using with two 4' Jameson poles or one 4' and one 6' pole, always starting with a Base Pole. Not for use with

Telescoping Poles.

Part Number	Description
BS-1	Big Shot Head (No Poles)
BS-1RP	Big Shot Replacement Pouch & Tubing



Part Number	Description
FG-BS-KIT1	Big Shot Kit with Poles
Big Shot Head, 4' FG Base Pole & 4' FG Extension Pole	



Part Number	Description
FG-BS-KIT2	Big Shot Kit with Poles, Throw Line and Throw Bags
Big Shot Head, 4' FG Base Pole & 4' FG Extension Pole, Throw Line (Dyneema® 1.75 mm x 180 ft., Orange), and Throw Bags (10-oz. and 12-oz.)	

TREE CARE TOOLS - ACCESSORIES



Part Number	Description	Color	Strength
TL-DY-175180	Dyneema® 1.75 mm x 180 ft., Order Qty. 12	Orange	450 lbs.
TL-DY-1751000	Dyneema® 1.75 mm x 1000 ft.	Orange	450 lbs.
TL-DY-175180	Dyneema® 2.2 mm x 180 ft., Order Qty. 12	Orange	650 lbs.
TL-DY-221000	Dyneema® 2.2 mm x 1000 ft.	Orange	650 lbs.



Part Number	Description	Color	Strength
TL-PD-25180	Poly/Dyneema® 2.5 mm x 180 ft., Order Qty. 12	Green/White	450 lbs.
TL-PD-251000	Poly/Dyneema® 2.5 mm x 1000 ft.	Green/White	450 lbs.



Part Number	Description	Color	Strength
TL-PE-18200	Polyethylene 1/8 in x 200 ft., Order Qty. 12	Orange/Yellow	250 lbs.
TL-PE-181000	Polyethylene 1/8 in x 1000 ft.	Orange/Yellow	250 lbs.



Part Number	Description	Color	Strength
TL-PE-532200	Polyethylene 5/32 in x 200 ft., Order Qty. 10	Red/Yellow	650 lbs.
TL-PE-5321000	Polyethylene 5/32 in x 1000 ft.	Red/Yellow	650 lbs.

Throw Line Provided In Display-Ready Packaging



Part Number	Description	Color
TB-16	16-oz. Throw Bag ,Order Qty. 12	Orange/ Black
TB-14	14-oz. Throw Bag Order, Qty. 12	Green/Black
TB-12	12-oz. Throw Bag Order, Qty. 12	Yellow/Black
TB-10	10-oz. Throw Bag Order Qty. 12	Red/Black



TREE CARE TOOLS - ACCESSORIES



Part Number	Description
B-6V	6' Pole Storage Bag
B-8V	8' Pole Storage Bag
Heavy duty vinyl bag carries poles and protects them during transport or storage. Features four 6' pole pockets, outside pruner head pocket and carrying straps.	



Part Number	Description	
Part Number	Description	
PPA-1 Pike Pole Adapter		
Adapter snaps into female ferrule of Jameson extension or base pole Allows you to convert the FG or JE Pole into a tool for plumbing up and		

testing utility poles.



IHA-2	Inductive Clamp Adapter
	to female ferrule of Jameson extension use with inductive clamp. 1/4"-20 male

Part Number



Part Number	Description
TPA-1	ACME Universal Thread Adapter
TPA-1-R*	ACME Universal Thread Adapter - Retail



Part Number	Description
WR-1	Limb & Wire Raiser
WR-1-R*	Limb & Wire Raiser - Retail



Part Number	Description
WIPE-KIT12	Fiberglass Tool Cleaner Wipes (12pcs)
WIPE-KIT144	Fiberglass Tool Cleaner Wipes (144pcs)





*Items Ending In "-R" Are Provided In Display-Ready Packaging

TREE CARE TOOLS - HAND SAWS





Tri-Cut Edge for Quick, Clean Cut

Featuring Barracuda™ impulse hardened tri-cut teeth, Jameson hand saws provide an efficient and clean cut. Available with wooden or ergonomic handle with index finger stop for safety and opening for lanyard line. Handles feature two bolts for easy blade replacement.







Part Number	Description
HS-13TE-OS	13" Hand Saw with Leather Scabbard



Part Number	Description
HS-13TE-OB	13" Hand Saw with Rubber Belting Scabbard







Part Number	Description
HS-16TE-OS	16" Hand Saw with Leather Scabbard



Part Number	Description
HS-16TE-OB	16" Hand Saw with Rubber Belting Scabbard







Part Number	Description
HS-16SB	16" Rubber Belting Scabbard



Part Number	Description
HS-13TE-WH	13" Tri-Cut Hand Saw Wood Handle



Part Number	Description
HS-16SL	16" Leather Scabbard



Part Number	Description
HS-13TE-HO	13" Tri-Cut Hook Blade Hand Saw
Hook prevents sl small branches o	lipping off or pulling out of cut; pull r vines.



Part Number	Description
HS-13TE-WH	13" Tri-Cut Hand Saw Wood Handle



Part Number	Description	
HS-16TE-WH	16" Tri-Cut Hand Saw Wood Handle	



Part Number	Description
HS-13TE-GUL-O	13" Tri-Cut Gullet Edge Hand Saw
Gullets allow chir	as and debris to exit cut



Part Number	Description
HS-16TE-GUL-O	16" Tri-Cut Gullet Edge Hand Saw
Gullets allow chips and debris to exit cut.	



Part Number	Description
HS-H-O	Handle Only



Part Number	Description
HS-WHS	Wood Handle Only



Part Number	Description
HS-13TE-LPS	13" Hand Saw With Hard Plastic Scabbard



Part Number	Description
LS-36-2	Leg Straps (2) For Scabbard. Black Nylon With Velcro Closure, 1.5" x 36"



Part Number	Description
HS-11TE-SO	11" Tri-Cut Straight Blade Hand Saw Ergonomic Grip Handle



Part Number	Description
HS-11TE-SW	11" Tri-Cut Straight Blade Hand Saw Wood Handle



Part Number	Description
HS-11TE-SOL	Ergonomic Grip 11" Hand Saw With Leather Scabbard



Part Number	Description
HS-11TE-SWL	Wood Handle 11" Hand Saw With Leather Scabbard



Part Number	Description
HS-11TE-SOB	Ergonomic Grip 11" Hand Saw With Belting Scabbard



Part Number	Description
HS-11TE-SWB	Wood Handle 11" Hand Saw With Belting Scabbard



Part Number	Description
HS-11SL	Leather Scabbard



Part Number	Description
HS-11SB	Rubber Belting Scabbard



Part Number	Description
SB-11TE-S	11" Straight Tri-Cut Blade
Fits Jameson Ha	nd Saw Handle



Part Number	Description
SB-8TE-FPKG	8" Folding Saw with Nylon Sheath



Part Number	Description
SB-8TE-F	Folding Saw Only



Part Number	Description
SB-8TE-FS	Sheath Only for Folding Saw



Part Number	Description		
HL-BP200	Hand Lopper		







MAKING CABLE INSTALLATION EASIER







Jameson developed cable placement tools for fiber optic and coaxial cable installation and maintenance with the guidance from professional linemen. Working from the ground or in the air, our tools make cable construction easier and safer.

CORNER BLOCKS

Corner blocks evenly distribute pressure on coax or fiber cable when pulling around corners. Steel side plates with straight base act as a strut for increased strength. 60 degree model offers more versatility than standard 45 degree blocks. Steel side plates can be replaced in the field. 17" bend radius. Maximum cable diameter 1" Nylon axle bushings provide easier swivel and longer axle life. Adjustable keeper arm holds cable in place as it is pulled through block. Aluminum rollers reduce friction, preventing potential heat build up and damage to synthetic rollers.

POLE MOUNT BRACKETS

Designed to save vertical space on crowded joint occupied poles, brackets are ideal for mounting corner blocks. Nylon strap and ratchet make brackets easy to use and bracket is contoured to fit pole for maximum stability. Ratchet strap will not damage existing cables and weighs less than chain straps. Can be adjusted to work from right or left hand side for convenient operation.







3" ROLLERS FOR 1.5" CABLE



CORNER BLOCKS

Single Row	
Part Number	Description
80-591	90 Degree, Single Nylon Rollers
80-161	60 Degree, Single Nylon Rollers
80-591A	90 Degree, Single Aluminum Rollers
80-161-A	90 Degree, Single Aluminum Rollers

Dual Row	Dual Row		
80-592	90 Degree, Dual Nylon Rollers		
80-162	60 Degree, Dual Nylon Rollers		

Quad Row	Quad Row		
80-594	90 Degree, Dual Nylon Rollers		
80-164	60 Degree, Dual Nylon Rollers		

3" Rubber	3" Rubber Roller	
80-691	Corner Block with 3" Rubber Rollers;	
00 001	Maximum cable diameter 1.5"	

70-101



70-102



70-104



POLE MOUNT BRACKETS

Designed to save vertical space on crowded joint occupied poles, brackets are ideal for mounting corner blocks. Nylon strap and ratchet make brackets easy to use and bracket is contoured to fit pole for maximum stability. Ratchet strap will not damage existing cables and weighs less than chain straps. Can be adjusted to work from right or left hand side for convenient operation.

Single Row	
Part Number	Description
70-101	Use With Single Row Corner Block
70-102	Use With Dual Row Corner Block
70-104	Use With Quad Row Corner Block



EASY RIDER™

Jameson overlash blocks are economical and lightweight, yet the high strength steel frame maintains cable alignment.

Easily snaps over a strand and cable package up to 2.25" diameter. This provides convenient stacking when pushed by lasher.

Features a high, rounded bonnet to prevent block kicking under lasher. Stacks evenly. Non-binding roller axle allows rollers to "ride easily" and rotate smoothly.

Maximum cable diameter .75"

Part Number	Description	
90-400A	Facus Dielos Warsish Alamaina na Dallas	
90-400A-R	Easy Rider™ with Aluminum Roller	
90-400	Face Distance with Made a Dellan	
90-400-R	Easy Rider® with Nylon Roller	
90-413	Easy Rider™ - XL Stringing Block with Nylon Roller	
90-421	Easy Rider™ - DBL String Block with two Nylon Rollers	





VERSA™ BLOCKS

 $\mbox{Versa}^{\mbox{\tiny M}} \mbox{ Blocks offer the versatility of stringing cable at midspan on new and existing overlash construction.}$

Offers easy cable placement from aerial buckets or the ground when used with Jameson lay-up sticks and wire raising tool.

Low profile frame reduces cable damage as it passes through block and wide keeper arm accommodates large cable bundles when used as overlash block.

Part Number	Description
90-100	Easy Rider™ with Aluminum Roller. For up to 1.5" cables
90-100A	Versa" Block with Aluminum Roller. For up to 2.5" diameter cable or bundles and winch lines.



TELESCOPING MEASURING POLES

Fiberglass poles offer fast, accurate one-person measuring of height clearances and horizontal distances.

All measuring poles include carry bag and removable aluminum hook accessory. Ideal for overhead telecommunication lines, railroad, CATV, bridges and structures.

All measuring poles include carrying bag and removable hook

NOTE: Poles are not certified as hot sticks and should not be used in the performance of live line work.

Part Number	Retracted Length	Description	
TP-125M	52"	25' Round Telescoping Measuring Pole, 5-Lb, English & Metric	
TP-136M	59"	36' Round Telescoping Measuring Pole, 7-Lb, English & Metric	
TP-125N	58"	25' Oval Telescoping Measuring Pole, 5-Lb, English Measure Only. Oval for easy grip.	
TP-25HK		Aluminum Replacement Hook for Measuring Pole	

*Items Ending In "-R" Are Provided In Display-Ready Packaging

Oval Measuring Pole

SHV-24 SHV-8

AERIAL BUDDY® FIBER OPTIC SHEAVEProtects ADSS & Other Jacketed Fiber During Installation

- Spring loaded cable guard (patented) eliminates delays caused by cable and pull tape derailing. 2" Opening allows pulling grips to pass through easily.
- Lightweight, reinforced polymer weighs significantly less than aluminum and steel models. Reduces installation fatigue, one-man set up.
- Easy latching mechanism for single-handed operation.
- High strength, impact resistant unit is more durable than aluminum.
- Chemical, UV, corrosion resistant construction for longer life.
- Electrically insulated* for safety.
- Lift hoist swivels 360° and rotates 180° for unrestricted mounting and maneuverability.
- * 100 KV/Ft Dielectric Withstand Stainless Steel Fasteners
- Cable and Pull Tape Stay On Wheel
- · Levels Itself, Strapping Optional
- Lightweight

24" Model Weighs 40% Less Than Lightest Aluminum Model

Specifications	
24" Aerial Sheave	
Weight	14 lbs. (6.35 kgs)
Maximum Load Rate	1,600 lbs.

24" Aerial Sheave Parts	
Part Number	Description
S24-FLR	Full Leg Replacement with Hardware
324-CC	Cable Capture Kit (Locking Nut, Cable Capture, Spring, Guide Rod
324-LL	Lower Leg and Latch Arm
324-WR	Wheel Assembly (Wheel, Axle, Bearings, Screws, Washers

Specifications		
8" Aerial Sheave		
Weight	8 lbs. (3.63 kgs)	
Maximum Load Rate	1,600 lbs.	

8" Aerial Sheave Parts		
Part Number	Description	
S08-FLR	Full Leg Replacement with Hardware	
S08-CC	Cable Capture Kit (Locking Nut, Cable Capture, Spring, Guide Rod	
S08-LL	Lower Leg and Latch Arm	
S08-WR	Wheel Assembly (Wheel, Axle, Bearings, Screws, Washers	
8" and 24" Aerial Sheave Parts		
SHV-HRR	Hoist Ring Kit	
SHV-LR	Latch Kit	
SHV-ULA	Upper Leg Assembly Kit	

Part Number	Description
SHV-24-KIT	24" Fiber Install Sheave With SHV-HK Slip Hook. For Set Up, Take Down, Turns
SHV-24	24" Fiber Install Sheave. For Set Up, Take Down, Turns
SHV-8-KIT	8" Fiber Install Sheave With SHV-HK Slip Hook. For Straight Pulls
SHV-8	8" Fiber Install Sheave. For Straight Pulls
SHV-HK	Slip Hook Accessory. Sold Separately
SHV-SS	Safety Shackle Accessory. Sold Separately





SHV-SS







TOOL STORAGE BUCKET & BOOM TOOL HOLDERS CANVAS TOOL BAGS

Jameson heavy duty bucket mount tool holders offer safe, convenient storage for bucket truck tools. Water repellent and UV resistant, holders withstand extreme weather conditions.

Adjustable clamp bracket allows tool holder to fit any size bucket, with or without liner, and mounts inside or outside bucket.

SAFE, CONVENIENT STORAGE WHEREVER THE JOB TAKES YOU







Part Number	Description
24-01	Polymer Hook with standard end, fits up to 2" bucket lips
24-01-R	Polymer Hook with standard end, fits up to 2" bucket lips Retail



Part Number	Description
24-11	Polymer Hook with standard end, fits up to 3" bucket lips
24-11-R	Polymer Hook with standard end, fits up to 3" bucket lips Retail



Part Number	Description
24-50	Polymer Hook with tapered end, fits up to 3" bucket lips
24-50-R	Polymer Hook with tapered end, fits



Part Number	Description
24-40	Canvas Tool Bag
15 Inside Pockets, 2 Grommets For Hooks 15" X 7" X 10"	



Part Number	Description
24-40S	Bag & Two S Hooks
15 Inside Pockets 15" X 7" X 10"	s, 2 Grommets For Hooks



Part Number	Description	
24-41	Canvas Tool Bag	
15 Outside Pockets, Rope with Swivel Hook, Reinforced Hard Plastic Base, 2 Grommets for S. Hooks 15" X 7" X 10"		



Part Number	Description
24-41S	Bag & Two S Hooks

15 Outside Pockets, Rope with Swivel Hook, Reinforced Hard Plastic Base, 2 Grommets for S Hooks 15" X 7" X 10"



Part Number	Description
24-42	Canvas Tool Bag
13 Outside Pockets, Web Handles, 2 Grommets for S Hooks 15" X 7" x 10"	



Part Number	Description
24-42S	Bag & Two S Hooks
13 Outside Pockets, Web Handles, 2 Grommets for S Hooks 15" X 7" x 10"	



Part Number	Description
24-19	Chainsaw Scabbard With Handsaw Holder

Handsaw holders on both sides for left-hand/righthand convenience. Constructed of durable HDPE to protect against blade wear and extreme weather. Supports Z133-2017: 5.2.13 Compliance



Part Number	Description
24-14L	Chainsaw Scabbard With Removable Liner
Fits standard and hydraulic pistol grip chainsaws. Features a replaceable liner that protects scabbard from chainsaw heat and blade. Adjustable clamp bracket.	
24-14LIN	Replacement Liner for 24-14L



Part Number	Description
24-14A	Chainsaw Scabbard
Fits standard and hydraulic pistol grip chainsaws. Adjustable clamp bracket	



Part Number	Description
24-18L	Fiberglass Chainsaw Scabbard With Removable Liner

Features high gloss gel coat finish to prevent fiberglass blooms and splinters. Fits standard and hydraulic pistol grip chainsaws.
Adjustable clamp bracket.

24-18LIN Replacement Liner for 24-18L



Part Number	Description
24-23	Long Reach Chainsaw Holder
chainsaws and g	oval handled long reach as powered pole pruners

trucks. Fixed mount. 18" x 13"



Part Number	Description
24-12A	Impact Tool Holder
One-piece construction with adjustable clamp bracket. Accommodates most wrenches & drills.	



Part Number	Description
24-12AH	Impact Tool Holder With Scabbard

Expanded opening accommodates the most common wrenches and drills. Features two spare drill bit holders and adjustable clamp bracket.



Part Number	Description
24-25	Tool Tray

Leather tool pouches and drop-in loops. Fixed bucket mount. 22.5" x 18"



Part Number	Description
24-17	Tool Tray
Removable dividers and fixed bucket mounts. 23" x 14" x 8"	



Part Number	Description
24-15D	Double Pocket Tool Holder
Inner pocket: 6.25" x 2.25" x 17" Outer pocket: 5.25" x 12.5" x 15" Thick pock (footing the standard to 8 about the standard the standar	

- Thick neck/back for rigidity & strength
 Tapered pocket edges for increased strength
 Long back or a variety of tools
 Drain holes
 Ribbed inside pocket base for increased strength when tools are dropped in pockets



Part Number	Description
24-02	Circular Saw Holder
Includes strap, ratchet & handle unit 12" x 9"	
24-02B	Replacement Saw Box with Strap & Ratchet



Part Number	Description
24-04	Hydraulic Pruner Holder
Includes strap, ratchet & handle unit 12" X 13"	
24-04B	Replacement Pruner Box with Strap & Ratchet



Part Number	Description
24-03B	Long Reach Chainsaw Holder
Fits most long reach chain saws. Includes straps, ratchets and handle unit. 32" X 5"	
24-03F	Fits Fairmont Style Chainsaw



Part Number	Description
24-03GUARD	Boom Guard
Mount on boom in front of tool holder to protect boom when inserting tool into holder. Includes straps, ratchets & handle unit. 32" X 5"	



Part Number	Description
24-14A	Chainsaw Scabbard
Fits standard and hydraulic pistol grip chainsaws. Adjustable clamp bracket	



Part Number	Description
24-04R	Replacement Handle Unit Handle, Strap & Ratchet
24-08R	Handle Holder Only
24-09R	Strap With Ratchet



Handle Unit Included With All Boom Mount Tool Holders
Ratchet strap fastens handle holder securely into a fixed position on boom. Rubberized coating prevents tool handle from sliding out of upper holder box. Fits round & square booms.

CABLE REEL HANDLING



Specifications			
Part Number	MTK-40		
Dimensions	45" x 28" x 30"		
Total Weight	293 Lbs.		
Weight - Wiring	18 Lbs.		
Power Source	12-Volt DC		
Finish	Powder Coat		
Hydraulic Pump	Dual Action with Corded Remote Control		
Hydraulic Hoses	1/4" SAE, 5800 PSI		
Cylinders	3000 PSI		

Operating Specifications	
Maximum Reel Capacity	40" Wide x 48" Diameter Maximum
Maximum Lifting Capacity	1,000 Lbs.*
Hitch Required	Minimum Class IV Hitch
Hitch Recommended	Pintle Plate / Class V Hitch
Wiring Included 20', 4 AWG Harness With Jumper Clamps & Rit Terminal Options	
* Minimum Class IV hitch required. Reel weight plus 293 lbs. must not exceed vehicle tongue weight.	





<u>JLIFT</u>

ONE PERSON. NO TRAILER.

REMOTE CONTROL

With the push of a button, one person can easily load and go in minutes. Corded J-Lift control is included; with optional wireless remote control available separately.

DUAL ACTING HYDRAULICS

Dual action and dual load-holding hydraulic pump and cylinders raise and lower with equal force, which is extremely convenient in cold climates and with lighter spools. This also allows faster stopping with a fully loaded reel for safer operation. Exceptional RAISE, LOWER & STOP Capabilities!

POWDER COATED

For long life performance and corrosion resistance.

LIGHT KIT

Connect to truck's 4-pin trailer output for brake lights and turn signals.





CABLE REEL HANDLING

PORTABLE REEL BUCK

The all-new Jameson® Portable Reel Buck is a quick and easy way to set up strand and cable reels up to 54" diameter. The reel buck is designed to be easily moved about the job site using the handles on the frame and the spool as a wheel. The durable steel tube frame has a weight capacity of 850 lbs. and can withstand the toughest job sites. The reel buck is collapsible for quick load and unloading and is adjustable for different reel widths and heights.

- · Load Capacity: 850 lbs.
- Accommodates Reel widths up to 54" inch diameter
- Designed to work with Arbor Spindle up to 2"
- Heavy-duty adjustable steel frame
- Easy setup and breakdown for transportation

Can ship "small pack" via UPS, FedEx or DHL















Part Number	Description
RB-54	Portable Reel Buck

SPOOL DIAMETER CAPACITY









FIBERGLASS RODDERS

UNDERGROUND CABLE INSTALLATION AND MAINTENANCE





Since 1980, Jameson's Buddy® System of fiberglass rodders and fish tapes has evolved to become the most comprehensive in the industry. The round, flexible rod slides easily over wires in occupied conduit, offering exceptional bending strength for maneuvering tight turns. Whether installing short run electrical wire or running long distance copper or fiber optic cable, Jameson has a Buddy® to handle the job for you.

- Non-conductive fiberglass rod core
- High visibility orange polymer rod jacket protects against abrasion and reduce friction
- Round, flexible rod slides easily over wires in occupied conduit
- Exceptional bending strength
- Rod marked in 5' increments (1m metric marked available)
- Accessories attach to rod for greater versatility and easier fishing

BUDDY® RODDERS OVERVIEW













	-					
	Easy Buddy®	Good Buddy®	Good Buddy® III	Good Buddy® II	Big Buddy®	Mega Buddy®
Features	Flexible rod handles tight turns & medium length runs. Taller handle and wide wheel base for easy transport.	Detach or fold frame for entry into confined areas. Reel can be set-up vertically or horizontally.	Same diameter and lengths as Good Buddy, but with fixed frame and wide wheel base for easy transport.	Larger frame and reel for longer rod capacity. All terrain wheels optional.	Stiffest rod for long runs in larger conduit. All terrain wheels optional.	Longest length available for large conduit. All terrain wheels standard.
Rod Diameter	1/4" (6.3mm)		3/8" (9.5mm)		1/2" (12	.7mm)
Lengths Available	300'-500' (91.4-152m)	300'- (91.4–1:		400'-1,000'* (121.9-182.9m)	400'–1,000' (121.9–304.8m)	1,500' (457.2m)
Recommended Conduit	1-2" (27–53mm)		2-4" (53–103mm)		4" or Large	r (103mm)
Min. Bend Radius	4" (101.6mm)		7" (177.8mm)		10" (25	4mm)
Pull Strength	400 lbs. (181kg)		1,000 lbs. (452.5kg)		1,000 lbs.	(452.5kg)
Accessory Kit	Included 6-14-AK		Included 9-25-AK		Included	11-38-RK
Dimensions	36.25" x 24.0" x 13" (92.1 x 61 x 33 cm)	29.0" x 29.0" x 27.0" (73.7 x 73.7 x 68.6 cm)	34.0" x 26.5" x 15.5" (86.4 x 67.3 x 39.4 cm)	40.0" x 32.0" x 18.0" (106 x 81.3 x 45.7 cm)	48" x 44 (121.9 x 111.8	
Weights	28 - 35 lbs. (12.7 - 15.9 kg)	55 - 62 lbs. (24.9 - 28.1 kg)	55 - 62 lbs. (24.9 - 28.1 kg)	71 - 137 lbs. (32.2 - 62.1 kg)	120 - 204 lbs. (54.4 - 92.5 kg)	278 lbs. (126.1 kg)
End Ferrule	5/16"–18 Male		3/8"-16 Male		3/8"–16	5 Male

^{*1,000-}ft model is built on Big Buddy frame

[•] All rodders include pulling eye and accessory/repair kit

^{• 400&#}x27; -1,000' Good Buddy II, 400'-1,000' Big Buddy and 1,500' Mega Buddy, ships by Motor Freight



EASY BUDDY®

1/4" Diameter Rod - Lightweight Rodder For 1-2" Conduit

- Drag brake and safety feed eye to control payout
- Bend Radius: 4"
- 400-lb. pull/tensile strength
- Male end ferrule: #5/16"-18 thread pitch
- · Accessory Kit included
- Dimensions: 36.25"H x 24"L x 13"W (92.1 x 61 x 33 cm)

Size	Part Number	Display Packaging	Replacement Reel
300' x 1/4"	6-14-300M	6-14-300M-R	6-300RRM
400' x 1/4"	6-14-400M	6-14-400M-R	6-400RRM
500' x 1/4"	6-14-500M	6-14-500M-R	6-500RRM
600' x1/4"	6-14-600M	6-14-600M-R	6-600RRM



GOOD BUDDY®

3/8" Diameter Rod - Designed to be used in conduit 2-4" in diameter

- 7" Bending Radius
- 1000-lb Pull/Tensile Strength
- Male end ferrule: #3/8"-16 thread pitch
- · Includes End Ferrule and Pulling Eye
- Accessory Kit, End Ferrule and Pulling Eye Included
- Dimensions: 29"H x 29"L x 27"W (Folds to 10" Width) (73.7 x 73.7 x 68.6 cm)

Size	Part Number	Replacement Reel
300' x 3/8"	9-25-300M	9-300RRM
400' x 3/8"	9-25-400M	9-400RRM



GOOD BUDDY III®

3/8" Diameter Rod - Smaller Frame For Maximum Portability

- 300' and 400' lengths
- Wheels and frame handle for transport
- Smaller frame size than GB or GB II
- Friction brake and safety roller feed
- Operates vertically or horizontally
- 1000-lb pull/tensile strength
- Dimensions: 34"H x 26.5"L x 15.5"W (86.4 x 67.3 x 39.4 cm)

Size	Part Number	Replacement Reel
300' x 3/8"	9A-25-300M	9-300RRM
400' x 3/8"	9A-25-400M	9-400RRM

Rod is marked in 5' increments. Add 'MM' to part number for metric measure (1m increments)
TO ORDER METRIC MARKED ROD, ADD AN ADDITIONAL "M" TO PART NUMBER WHEN ORDERING. (EXAMPLE, 6-14-300M WOULD BE 6-14-300MM
* Items Ending In "-R" Are Provided In Display-Ready Packaging



GOOD BUDDY® II

3/8" Diameter Rod - Increased Length For Longer Runs

- 400', 500' and 600' lengths
- Oversized wheels support weight of longer rod
- Frame handle and wheels for transport
- Friction brake and safety roller feed
- Operates vertically or horizontally
- 1000-lb pull/tensile strength
- Dimensions: 40"H x 32"L x 18"W (106 x 81.3 x 45.7 cm)

Size	Part Number	Replacement Reel
400' x 3/8"	11A-25-400M	11A-400RRM
500' x 3/8"	11A-25-500M	11A-500RRM
600' x 3/8"	11A-25-600M	11A-600RRM

Built on Big Buddy frame		
1000' x 3/8"	11-25-1000M	11-25-1000RRM
To order 3/8" Good Buddy II with All-Terrain Wheels, add		
AWK to part number. Example: 11A-25-400M-AWK		



BIG BUDDY®

1/2" Diameter Rod - For Conduit 4" Or Larger

- Drag brake and safety feed eye to control pay out.
- 10" Bending Radius
- 1,000-lb Pull/Tensile Strength
- Male end ferrule: 3/8"-16 thread pitch
- Includes End Ferrule and Pulling Eye
- · Accessory Kit included
- Dimensions: 48"H x 44"L x 21"W (121.9 x 111.8 x 53.3 cm)

Size	Part Number	Replacement Reel
400' x 1/2"	11-38-400M	11-400RRM
500' x 1/2"	11-38-500M	11-500RRM
600' x 1/2"	11-38-600M	11-600RRM
800' x 1/2"	11-38-800M	11-800RRM
1,000' x 1/2"	11-38-1000M	11-1000RRM
To order 1/2" Big Buddy with All-Terrain Wheels, add AWK part number. Example: 11A-38-400M-AWK		



MEGA BUDDY®


1/2" Diameter Rod - For Conduit 4" Or Larger

- 1500 ft. of 1/2-inch diameter fiberglass rod marked every 5 ft. (Metric every 1m)
- Ideal for 4" or larger conduit
- 10" Bend Radius
- 1,000-lb Pull/Tensile Strength
- Drag brake and safety feed eye to control pay out
- Accessory Kit Included: Splice Ferrule, Pulling Eye, End Ferrule, Adhesive, and Emery Cloth
- Dimensions: 48"H x 44"L x 21"W (121.9 x 111.8 x 53.3 cm)
- · Weight: 260 lbs.

Size	Part Number	Replacement Reel
1,500' x 1/2"	11-38-1500M	11-1500RRM

Rod is marked in 5' increments. Add 'MM' to part number for metric measure (1m increments)

ACCESSORIES



Accessories	Description	Easy Buddy	Good Buddy II Good Buddy II Good Buddy III	Big Buddy Mega Buddy
	Canvas Pouch - Pulling Eye, Splice Ferrule, End Ferrule, Adhesive and Emery Cloth	6-14-AK or 6-14-AK-R		
Accessory Kit	Canvas Pouch - Swivel Pulling Eye, Splice Ferrule, End Ferrule, Adhesive and Emery Cloth		9-25-AK or 9-25-AK-R	
	Canvas Pouch - Splice Ferrule (2), End Ferrule, Adhesive, and Emery Cloth			11-38-RK or 11-38-RK-R
Repair Adhesive	Adhesive, Applicator, Emery Cloth		9-167	
Fixed Pulling Eye	Attach pull line or pulling grip to rod	6-160		
Swivel Pulling Eye	Attach pull line or pulling grip to rod	6-139	9-139	11-139
Shackle Fitting	Use with Pulling Eye 11-139 for larger pulling loop		11-142	11-142
Roller Guide	Guide rod through bends, sweeps & misalignments	6-141	9-141 or 9-141-R	11-141 or 11-141-R
Flexible Spring Leader	Guide rod through bends, sweeps & misalignments	6-162		
Flexible Leader w/Lg. Tip	Guide rod through bends, sweeps, & misalignments			
Flexible Leader w/Eyelet	Guide rod through bends, sweeps, & misalignments			
Flexible Fiberglass Stinger Tip	Guide rod through bends, sweeps, & misalignments		9-25-12ST (12" Tip) 9-25-24ST (24" Tip)	11-25-6ST (6' Tip 11-25-8ST (8' Tip
Swivel Coupling	Connect two rods for added length; provides rotation when pulling line, rope, or wire	6-143	9-143	11-143
Rod Grapples	Connect two rodders from opposite directions	6-148	9-148	11-148
Splice Repair Kit	Splice Ferrule, Adhesive, and Emery Cloth	6-140 or 6-140-R	9-140 or 9-140-R	11-140 or 11-140-F
End Ferrule Repair Kit	End Ferrule, Adhesive, and Emery Cloth	6-146 or 6-146-R	9-146 or 9-146-R	11-146 or 11-146-F
All-Terrain Wheel Kit	Replacement All-Terrain Wheel Kit (2 wheels/axle)		11A-AWK (GB II Only)	11-AWK

^{*} Items Ending In "-R" Are Provided In Display-Ready Packaging



REPLACEMENT ROD ON REEL

Jameson Buddy®, Duct Hunter™ and Live Tracer™ rodders are the most durable in the market, but we know job sites can be extremely tough.

Using our repair kits, customers are often able to splice rod or repair end-fittings to keep their rodders in service.

However, on occasion it may be necessary to replace the entire spool of rod due to more severe damage. Removal, disposal and rod replacement can be a difficult and timeconsuming task. Responding to customer feedback, Jameson introduced EZ-REEL™ pre-loaded replacement reels which help improve speed and safety of replacing damaged rod material.



Easy Buddy®

Part Number	Reel	Size
6-300RRM	Easy Buddy®	1/4" x 300'
6-400RRM	Easy Buddy®	1/4" x 400'
6-500RRM	Easy Buddy®	1/4" x 500'
6-600RRM	Easy Buddy®	1/4" x 600'
9-300RRM	Good Buddy® and Good Buddy® III	3/8" x 300'
9-400RRM	Good Buddy® and Good Buddy® III	3/8" x 400'
11A-400RRM	Good Buddy® II	3/8" x 400'
11A-500RRM	Good Buddy® II	3/8" x 500'
11A-600RRM	Good Buddy® II	3/8" x 600'
11-400RRM	Big Buddy®	1/2" x 400'
11-500RRM	Big Buddy®	1/2" x 500'
11-600RRM	Big Buddy®	1/2" x 600'
11-800RRM	Big Buddy®	1/2" x 800'
11-1000RRM	Big Buddy®	1/2" x 1000'
11-1500RRM	Mega Buddy®	1/2" x 1500'

Rod is marked in 5' increments.



See Page 113 for Full List Of Adapters To Use Sonde With Jameson Buddy Rodders

SONDE & ADAPTERS

A sonde is a battery-powered locating beacon used to pinpoint rod end. Its signal is detected by a receiver.

Using an adapter, the sonde is attached to the rod ferrule to locate in underground pipes or conduit.

Can be used with Duct Hunter $^{\scriptscriptstyle{\text{IM}}}$ Traceable Rodders or Buddy $^{\scriptscriptstyle{\text{R}}}$ Rodders.







TRACEABLE RODDERS

LOCATE UNDERGROUND CONDUIT OR PIPE





The Duct Hunter $^{\mathbb{M}}$ is a continuous fiberglass duct rodder with a copper wire embedded in the rod core. Connecting a signal transmitter to the rod energizes the wire, allowing the user to trace the continuous path of the pipe with a receiver.

Works with any non-conductive pipe, such as PE, PVC, concrete, clay or tile. One person can do the job with minimal or no excavation.

- Trace to depths up to 10'
- Trace sewer laterals to confirm no cross bore has occurred
- Trace ductile iron, plastic, tile or concrete pipe
- Attach sonde, roller guide or pulling eye to rod's end ferrule
- · Works with any locator set
- · Accessory kit included
- Sonde adapters available
- Great bending strength
- All rodders include pulling eye or roller guide and repair kit
- All rodders (1/4" and larger) marked in 5' increments (1m metric marked available)

DUCT HUNTER™ **OVERVIEW**











	1/8" Diameter Mini Duct Hunter™	3/16" Diameter Mini Duct Hunter™	1/4" Diameter Duct Hunter™	5/16" Diameter Duct Hunter™	5/16" Diameter Duct Hunter™	7/16" Diameter Duct Hunter™	
Applications	Trace Fiber Optic Micro-DuctTrace Sewer Laterals & Septic		• Trace To Depths U	Trace To Depths Up To 10'			
			Trace Sewer Laterals To Confirm No Cross Bore Has Occurred				
	Lines; Fiberglass \	Lines; Fiberglass Will Not Rust		Plastic, Tile Or Concret	e Pipe		
Features	Ultra-portable Trace fiber-optic microducts 8mm ID and larger Ultra-portable Short straight runs in pipe to 4" diameter		Tall handle & wide wheel base for easy transport Trace longer sewer laterals	Stiffer rod with roller guide moves through corrugated and tile systems	Large frame carries longer lengths All-terrain wheels available	Stiffest rod for largest pipes & longest runs All-terrain wheels available	
Lengths Available	100' - (30.5 -	· 300' 91.4m)	300' - 600' (91.4 - 183m)	300' - 400' (91.4 - 122m)	500' - 800' (152 - 244m) 1200' (366m)	300' - 1000' (91.4 - 305m)	
Recommended Conduit	1/2" - 1" (15 - 25mm)	3/4" - 1-1/2" (20 - 40mm)	1" - 2" (25 - 50mm)	2" - 4" (50 - 100mm)		4" or larger (100mm)	
Min. Bend Radius	1.75" (4.5 cm)	2.5" (6.4 cm)	4" (10.2 cm)	6" (1	6" (15 cm)		
Pull Strength	150 Lbs.	300 Lbs.	400 Lbs.	500 Lbs.		800 Lbs.	
Accessory Kit	Included	(15-18-AK)	Included (16-14-AK)	Included	(12-516-AK)	Included (13-716-AK)	
Dimensions	22" × 17" × 7" (55.9 × 43.2 × 17.8 cm)		36.25" x 24.0"x 13" (92.1 x 61 x 33 cm)	34.0" x 26.5" x 15.5" (86.4 x 67.3 x 39.4 cm)	40.0" x 32.0" x 18.0" (106 x 81.3 x 45.7 cm)	48" x 44" x 21" (121.9 x 111.8 x 53.3 cm)	
Weights	11.1 - 15.0 lbs. (5.0 - 6.8 kg)	11.6 - 15.5 lbs. (5.3 - 7.0 kg)	28.0 - 39.0 lbs. (12.7 - 17.7 kg)	46.7 - 51.7 lbs. (21.2 - 23.5 kg)	65.0 - 105.0 (29.5 - 47.6 kg)	97.0 - 167.0 lbs. (44.0 - 75.8 kg)	
End Ferrule	1/4" - 20				3/8" - 16		

 $^{^*}$ 1,000-ft model is built on Big Buddy frame

[•] All rodders include pulling eye and accessory/repair kit

^{• 500&#}x27; - 800' 5/16" Diameter Duct Hunter and 300' - 1000' 7/16" Duct Hunter, ships by Motor Freight



MINI DUCT HUNTER™ - 1/8" DIAMETER ROD

For Tracing Small Conduit or Pipes

- Trace sewer laterals (up to 4 inches in diameter) to avoid cross bores
- Locate fiber optic cable in plastic pipe without tracer wire
- Bend Radius: 1.75"
- Locate fiber optic micro-duct during fiber-to-the-home applications
- Fiberglass will not rust during plumbing applications
- · Accessory Kit included
- Dimensions: 22" x 17" x 7" (55.9 x 43.2 x 17.8 cm)

Size	Part Number	Replacement Reel
100' x 1/8"	15-18-100	15-18-100RR
150' x 1/8"	15-18-150	15-18-150RR
200' x 1/8"	15-18-200	15-18-200RR
250' x 1/8"	15-18-250	15-18-250RR
300' x 1/8"	15-18-300	15-18-300RR



MINI DUCT HUNTER™ - 3/16" DIAMETER ROD

For Tracing Small Conduit or Pipes

- Trace sewer laterals (up to 4 inches in diameter) to avoid cross bores
- Locate fiber optic cable in plastic pipe without tracer wire
- Bend Radius: 2.5"
- Locate fiber optic micro-duct during fiber-to-the-home applications
- Fiberglass will not rust during plumbing applications
- Accessory Kit included
- Dimensions: 22" x 17" x 7" (55.9 x 43.2 x 17.8 cm)

Size	Part Number	Replacement Reel	
100' x 3/16"	15-316-100	15-100RR	
150' x 3/16"	15-316-150	15-150RR	
200' x 3/16"	15-316-200	15-200RR	
250' x 3/16"	15-316-250	15-250RR	
300' x 3/16"	15-316-300	15-300RR	



DUCT HUNTER™ - 1/4" DIAMETER ROD

For Tracing Small Conduit or Pipes

- Bend Radius: 4"
- Locate sewer laterals to confirm no cross bore has occurred
- Locate ductile iron, plastic, tile or concrete pipe
- For use in conduit with an inside diameter between 1 and 2 inches
- Marked every 5 ft. (Metric every 1m)
- Dimensions: 36.25" x 24" x 13" (92.1 x 61 x 33 cm)

Size	Part Number	Replacement Reel
300' x 1/4"	16-14-300M	16-300RRM
400' x 1/4"	16-14-400M	16-400RRM
500' x 1/4"	16-14-500M	16-500RRM
600' x 1/4"	16-14-600M	16-600RRM




DUCT HUNTER™ - 5/16" DIAMETER ROD

Increased Length For Longer Runs

- For use in conduit with an inside diameter between 2 and 4 inches
- Locate sewer laterals to confirm no cross bore has occurred
- Bend Radius: 6"
- · Locate ductile iron, plastic, tile or concrete pipe
- Traceable fiberglass rod marked every 5 feet
- Dimensions: 34" x 26" x 16" (86.4 x 67.3 x 39.4 cm)

Size	Part Number	Replacement Reel
300' x 5/16"	12-516-300M	12-300RRM
400' x 5/16"	12-516-400M	12-400RRM



DUCT HUNTER™ - 5/16" DIAMETER ROD

Rigid Frame and Wheel Construction For Maximum Portability

- Locate sewer laterals to confirm no cross bore has occurred
- Bend Radius: 6"
- Locate ductile iron, plastic, tile or concrete pipe
- Traceable fiberglass rod marked every 5 feet
- Dimensions: 40" x 32" x 18" (101.6 x 81.3 x 45.7 cm)

Size	Part Number	Replacement Reel
500' x 5/16"	12A-516-500M	12A-500RRM
600' x 5/16"	12A-516-600M	12A-600RRM
700' x 5/16"	12A-516-700M	12A-700RRM
800' x 5/16"	12A-516-800M	12A-800RRM
1200' x 5/16"	12A-516-1200M	12A-1200RRM
	Duct Hunter with All-Te umber. Example: 12A-51	



DUCT HUNTER™ - 7/16" DIAMETER ROD

Rigid Frame and Wheel Construction For Maximum Portability

- Drag brake and safety feed eye to control pay out.
- 9" Bending Radius
- 800lb Pull/Tensile Strength
- Traceable fiberglass rod marked every 5 feet
- For use in conduit with an inside diameter 4 inches or larger
- Male end ferrule: 3/8"-16 thread pitch
- Includes End Ferrule and Pulling Eye
- · Accessory Kit included
- Dimensions: 48"H x 44"L x 21"W (121.9 x 111.8 x 53.3 cm)

	Size	Part Number	Replacement Reel	
	400' x 7/16"	13-716-400M	13-400RRM	
	500' x 7/16"	13-716-500M	13-500RRM	
	600' x 7/16"	13-716-600M 13-716-800M	13-600RRM 13-800RRM	
	800' x 7/16"			
	1000' x 7/16"	13-716-1000M	13-1000RRM	
To order 7/16" Duct Hunter with All-Terrain Wheels, add				

TO ORDER METRIC MARKED ROD, ADD AN ADDITIONAL "M" TO PART NUMBER WHEN ORDERING. (EXAMPLE, 16-14-300M WOULD BE 16-14-300MM)

ACCESSORIES

















End Ferrule

Splice

Swivel Eye

Pulling Eye

Roller Guide

Guide Roller Guide

er Guide with Ba pring Leader Sprin

Ball-Nose Spring Leader

Flexible Leader with Ball

All-Terrain Wheel











1/8"	&	3/16"	Mini	Duct	Hunter	
Accessory Kit						

1/4" Duct Hunter Accessory Kit

5/16 & 7/16" Duct Hunter Accessory Kit

Repair Adhesive

Accessories	Description	1/8" Mini Duct Hunter	3/16" Mini Duct Hunter	1/4" Duct Hunter	5/16" Duct Hunter	7/16" Duct Hunter
	Canvas Pouch - Roller Guide, End Ferrule, Splice Ferrule, 2 Adhesive, 2 Emery Cloth, Heat Shrink Tubing & Rod Terminal				12-516-AK or 12-516-AK-R	13-716-AK or 13-716-AK-R
Accessory Kit	Canvas Pouch - Ball-Nose Spring Leader, End Ferrule, Splice Ferrule, 2 Adhesive, 2 Emery Cloth, Heat Shrink Tubing & Rod Terminal			16-14-AK or 16-14-AK-R		
	Canvas Pouch - Flexible Leader W/Ball, End Ferrule, Splice Ferrule, Pulling Eye, Adhesive, Emery Cloth & Heat Shrink Tubing	15-18-AK or 15-18-AK-R	15-316-AK or 15-316-AK-R			
End Ferrule Repair Kit	End Ferrule, Adhesive, Emery Cloth & Rod Terminal (1/4" & Larger Rod Only)	15-18-146 or 15-18-146-R	15-146 or 15-146-R	16-146 or 16-146-R	12-146 or 12-146-R	13-146 or 13-146-R
Splice Repair Kit	Splice Ferrule, Adhesive, Emery Cloth, Heat Shrink Tubing & Rod Terminal (1/4" & Larger Rod Only)	15-18-140 or 15-18-140-R	15-140 or 15-140-R	16-140 or 16-140-R	12-140 pr 12-140-R	13-140 or 13-140-R
Repair Adhesive	Adhesive, Applicator, Emery Cloth			9-167		
Roller Guide	Guides rod through bends, sweeps, misalignments & wires; Increases contact with pipe on lead end of rod to improve overall signal strength				9-141 (or 9-141-R
Roller Guide with Spring Leader	Heavy-duty spring & chain attached to swiveling roller guide helps guide rod over cables, rough surfaces & pipe joints					
Dall Nace Caring Loader	Heavy-duty spring & chain with ball nose helps rod move over rough surfaces and pipe joints, 3/8"-16 hole (also fits Buddy rodders with 3/8" & 1/2" rods)			16-169		
Ball-Nose Spring Leader Heavy-duty spring & chain with ball nose helps rod move over rough surfaces and pipe joints, 3/8"-16 hole (also fits Buddy rodders with 3/8" & 1/2" rods)					12	:-163
Flexible Leader With Ball	Flexible leader with steel cable and plastic ball helps rod navigate tight bends and pipe joints	15-	163			
Swivel Eye	Attaches pull line to rod, swivels				9-139	
Pulling Eye	Attaches pull line to rod, fixed	15	-160	16-160		
All Terrain Wheels	Two wheels, spacers, lock collars, axle & hex wrench(fits 12A- and 13- models only)				11A	-AWK

^{*} Items Ending In "-R" Are Provided In Display-Ready Packaging

SONDE & ADAPTERS

A sonde is a battery-powered locating beacon used to pinpoint rod end. Its signal is detected by a receiver.

Using an adapter, the sonde is attached to the rod ferrule to locate in underground pipes or conduit.



Can be used with Duct Hunter[™] Traceable Rodders or Buddy® Rodders.

		Part	Thre	eads			
Ту	/pe	Number	Side A	Side B	Fits Sondes:	Fits Jameson F	Rodders:
	e Spring Adapters	6-169	5/16"-18 female	1/4"-20 male	- Jameson 14-170 - Sondes with 1/4"-20 hole (Subsite)	Easy Buddy®	1/4"
	Auapters	6-169-M10	5/16"-18 female	M10 female	- Sondes with M10 stud (Vivax-MetroTech)	Easy Buddy	1/4
			3/8"-16 female	1/4"-20 male	- Jameson 14-170 - Sondes with 1/4*-20 hole (Subsite)	All Good Buddies Big & Mega Buddy* Duct Hunters*	3/8" 1/2" 5/16 & 7/16"
Double Female	Female & Male	16-168	1/4"-20 female	1/4"-20 male	- Jameson 14-170 - Sondes with 1/4*-20 hole (Subsite)	Mini-Duct Hunters [*] Duct Hunter [*] Live Tracer [*]	1/8" & 3/16" 1/4" 1/4"
		10-170	#12-24 female	1/4"-20 male	- Jameson 14-170 - Sondes with 1/4"-20 hole (Subsite)	Little Buddy*	3/16"
Solid A	dapters	6-170	5/16"-18 female	1/4"-20 male	- Jameson 14-170 - Sondes with 1/4"-20 hole (Subsite)	Easy Buddy [®]	1/4"
	1	9-170	3/8"-16 female	1/4"-20 male	- Jameson 14-170 - Sondes with 1/4*-20 hole (Subsite)	All Good Buddies Big & Mega Buddy	3/8" 1/2"
Double Female	Female & Male	12-170	3/8"-16 female	M10 female	- Sondes with M10 stud (Vivax-MetroTech)	Duct Hunters	5/16" & 7/16"
remaie	Wate	15-165	1/4"-20 female	M5 male	- Sondes with M5 hole (Radio detection S6 micro-Sonde)	Mini-Duct Hunters	1/8" & 3/16"
		15-166	1/4"-20 female	M6 male	- Sondes with M6 hole (Radio detection S9 micro-Sonde)	Duct Hunter Live Tracer	1/4" 1/4"
So	nde	14-170	1/4"-20 female		- Sonde, operates at 512 HZ, AAA battery included, up to 4 hours continuous use. Trace depths up to 20' (plastic pipe) or 10' (cast iron pipe). 3.25" x .83" dia.	Mini-Duct Hunters [*] Duct Hunter [*] Live Tracer	1/8" & 3/16" 1/4" 1/4"
		12-165			- Kit: Sonde 14-170 and adapter 9-169	All Good Buddies* Big & Mega Buddy* Duct Hunters*	3/8" 1/2" 5/16" & 7/16"

EZ-REEL™ REPLACEMENT ROD ON REEL





Duct Hunter™ Live Tracer





Mini Duct Hunter™

Live Tracer™

1/8", 3/16" MINI DUCT HUNTER $^{^{\prime\prime}}$ AND LIVE TRACER $^{^{\prime\prime}}$

Part Number	Replacement Cartridge	Size
15-18-100RR	Mini Duct Hunter	1/8" x 100'
15-18-100RR-GL	Live Tracer with fixed bullet tip	1/8" x 100'
15-18-100RR-GLFT	Live Tracer with fixed flexible tip	1/8" x 100'
15-18-150RR	Mini Duct Hunter	1/8" x 150'
15-18-150RR-GL	Live Tracer with fixed bullet tip	1/8" x 150'
15-18-150RR-GLFT	Live Tracer with fixed flexible tip	1/8" x 150'
15-18-200RR	Mini Duct Hunter	1/8" x 200'
15-18-200RR-GL	Live Tracer with fixed bullet tip	1/8" x 200'
15-18-200RR-GLFT	Live Tracer with fixed flexible tip	1/8" x 200'
15-18-250RR	Mini Duct Hunter	1/8" x 250'
15-18-250RR-GL	Live Tracer with fixed bullet tip	1/8" x 250'
15-18-250RR-GLFT	Live Tracer with fixed flexible tip	1/8" x 250'
15-18-300RR	Mini Duct Hunter	1/8" x 300'
15-18-300RR-GL	Live Tracer with fixed bullet tip	1/8" x 300'
15-18-300RR-GLFT	Live Tracer with fixed flexible tip	1/8" x 300'
15-100RR	Mini Duct Hunter	3/16" x 100'
15-100RR-GL	Live Tracer with fixed bullet tip	3/16" x 100'
15-100RR-GLFT	Live Tracer with fixed flexible tip	3/16" x 100'
15-150RR	Mini Duct Hunter	3/16" x 150'
15-150RR-GL	Live Tracer with fixed bullet tip	3/16" x 150'
15-150RR-GLFT	Live Tracer with fixed flexible tip	3/16" x 150'
15-200RR	Mini Duct Hunter	3/16" x 200'
15-200RR-GL	Live Tracer with fixed bullet tip	3/16" x 200'
15-200RR-GLFT	Live Tracer with fixed flexible tip	3/16" x 200'
15-250RR	Mini Duct Hunter	3/16" x 250'
15-250RR-GL	Live Tracer with fixed bullet tip	3/16" x 250'
15-250RR-GLFT	Live Tracer with fixed flexible tip	3/16" x 250'
15-300RR	Mini Duct Hunter	3/16" x 300'
15-300RR-GL	Live Tracer with fixed bullet tip	3/16" x 300'
15-300RR-GLFT	Live Tracer with fixed flexible tip	3/16" x 300'

1/4", 5/16", 7/16" DUCT HUNTER™AND LIVE TRACER™

Part Number	Replacen	nent Reel	Size
16-300RRM	Duct Hunter"		1/4" x 300'
16-400RRM	Duct Hunter"		1/4" x 400'
16-500RRM	Duct Hunter		1/4" x 500'
16-600RRM	Duct Hunter"	Live Tracer	1/4" x 600'
12-300RRM	Duct Hunter" (26" Dia. Reel)	Live Tracer" (26" Dia. Reel)	5/16" x 300'
12-400RRM	Duct Hunter" (26" Dia. Reel)	Live Tracer" (26" Dia. Reel)	5/16" x 400'
12A-500RRM	Duct Hunter" (32" Dia. Reel)	Live Tracer" (32" Dia. Reel)	5/16" x 500'
12A-600RRM	Duct Hunter" (32" Dia. Reel)	Live Tracer" (32" Dia. Reel)	5/16" x 600'
12A-700RRM	Duct Hunter" (32" Dia. Reel)	Live Tracer" (32" Dia. Reel)	5/16" x 700'
12A-800RRM	Duct Hunter" (32" Dia. Reel)	Live Tracer" (32" Dia. Reel)	5/16" x 800'
12A-1200RRM	Duct Hunter" (32" Dia. Reel)	Live Tracer" (32" Dia. Reel)	5/16" x 1200'
13-400RRM	Duct Hunter"		7/16" x 400'
13-500RRM	Duct Hunter"		7/16" x 500'
13-600RRM	Duct Hunter"		7/16" x 600'
13-800RRM	Duct Hunter"		7/16" x 800'
13-1000RRM	Duct Hunter		7/16" x 1000'





TRACEABLE RODDERS

LOCATE LIVE GAS & WATER LINES





The Live Tracer is a continuous fiberglass duct rodder with a copper wire embedded in the rod core.

Connecting a signal transmitter to the rod energizes the wire, allowing the user to trace the continuous path of the pipe with a receiver.

Incorporating a Stuffing Box, the Live Tracer $^{\text{\tiny M}}$ can trace live gas mains and lines without blow by to 125 PSI.

One person can do the job with minimal or no excavation.

- Trace to depths up to 10'
- · Works with any locator set
- No blow-by while feeding rod into live line up to 125 PSI
- Sonde adapters available
- Accessory kit with Stuffing Box included

No Blow-By While Feeding Rod Into Live Line Up To 125 PSI

Less Disruption To Roads And Landscapes

Minimal Pavement Breakage, Excavation And Restoration

Incorporating a stuffing box (included), the Live Tracer rod can be inserted without blow-by up to 125 psi. A locator and receiver set are used to energize and trace the path, or a camera is used to inspect gas main.

Benefits


- No Blow-By While Feeding Rod Into Live Line Up To 125 Psi
- Less Disruption To Roads And Landscapes
- Minimal Pavement Breakage, Excavation And Restoration
- No Service Interruption

#1 - Choose Preferred Method To Enter Gas Main:

- 1. Electrofusion Insertion Tees For Tracing Only Or
- 2. Directional Entry Tool For Tracing & Camera Inspection

#2 - Choose Live Tracer™ Model And Accessories







ELECTROFUSION INSERTION TEES & ACCESSORIES

Tees provide an angled entry port to launch traceable rod into PE pipe. Tees have integrated cutter to shut off gas flow when reinserted; assists with completion. Tees can be direct buried or entry port can be taken to grade in a valve box for future access.



Part Number	Accessories	Electrofusion Tees & Accessories For Gas Main Tracing
16-2-TEE		2" IPS Electrofusion Insertion Tapping Tee, 1" IPS outlet, 4.7mm terminals
16-2-TEE-BX	Electrofusion Tees	2" Tee, Box of 15
16-4-TEE	Liectioidsion rees	4" IPS Electrofusion Insertion Tapping Tee, 1" IPS outlet, 4.7mm terminals
16-4-TEE-BX		4" Tee, Box of 10
16-6-TEE		6" IPS Electrofusion Insertion Tapping Tee, 1" IPS outlet, 4.7mm terminals
16-6-TEE-BX		6" Tee, Box of 7
16-1HSCR	Hand Scraper	Prepares pipe surfaces for electrofusion
16-1PSCR	Poly Peeler	Poly Peeler; prepare 1" IPS pipe (DR11); second male for 1" IPS tee outlet (DR7)
16-RSCR		2" IPS Rotary Peeler - Prepares gas main surface for electrofusion
16-2-RSCR-BLADES		Replacement blade set
16-1928-4PEEL	Rotary Peeler	4" IPS Rotary Peeler - Prepares gas main surface for electrofusion
16-1930-6PEEL		6" IPS Rotary Peeler - Prepares gas main surface for electrofusion
16-TC		Apply air to perform leak check after fusion prior to tapping. 1/4" male quick-disconnect fitting.
16-TCG	Test Caps	With gauge to monitor for pressure drop. 1/4" male quick-disconnect fitting.
16-CW	Cap Wrench	Cap Wrench for EF Tees
16-HVTAP		High Volume Tap Tool with T-Handle for EF Tees
16-HVTTR	Tap Handles	High Volume Tap Tool w/Ratchet Drive for EF Tees. Required for 45° elbow on outlet. Ratchet handle not included. 1/2" sq. drive socket
16-EFC-1		1" IPS to couple transition fitting & elbow to tee outlet. 4.7 mm terminals.
16-EFC-1-CTS	1" Coupler	1" CTS to couple 1" CTS transition fitting to tee outlet. 4.7 mm terminals. Use with 16-1-PERED & 16-EFC-1 to fit EF Tee outlet
16-B7105	T	1" IPS x 24" PE transition fitting. 1" NPT bronze male thread, DR11. Connect to tee outlet & mount 1" ball valve & Stuffing Box
16-B7110	Transition Fittings	1" CTS x 24" PE transition fitting. 1" NPT bronze male thread, :101" wall. Connect to tee outlet & mount 1" ball valve & Stuffing Box
16-1-PERED	1" Reducer	1" IPS to 1" CTS reducer section, PE
16-1520-1CLAMP	Coupler	For 1" CTS couplers, vise-grip style
16-1525-1CLAMP	Clamps	For 1" CTS couplers, vise-grip style
16-45ELB Elbow		1" IPS 45° Elbow, PE. Use to direct transition fitting vertically to grade.

TRACEABLE RODDERS OVERVIEW







	1/4" Live Tracer™	5/16" Live Tracer™	5/16" Live Tracer™		
Applications	Trace Live Gas Mains				
Features	Stuffing Box Attaches To Jameson Electrofu Rated For 125 PSI With No Blow By. Marked				
Lengths Available	600' (183m)	300' - 400' (91.4 - 122m)	500' - 800' (152 - 244m) 1200' (366m)		
Recommended Conduit	2" - 4" (50 - 100mm)	4" or	larger (100mm)		
Minimum Bend Radius	4" (10.2 cm)	6" (15 cm)			
Pull Strength	400 lbs. (181.0 kg)	500 lbs. (226.2 kg)			
Accessory Kit with Stuffing Box	Included with Live Tracer™ 16-14-SB-KIT	Included with Live Tracer™ 12-516-SB-KIT			
Dimensions	36.25" x 24.0" x 13" (92.1 x 61 x 33 cm)	34.0" x 26.5" x 15.5"			
Weights	28.0 - 39.0 lbs. (12.7 - 17.7 kg)	46.7 - 51.7 lbs. 65.0 - 105.0 (21.2 - 23.5 kg) (29.5 - 47.6 kg)			
Male End Ferrule Thread	1/4" - 20	3/8" - 16			



LIVE TRACER™ - GAS MAINS

1/4" Diameter Rod - Lightweight Portable Traceable Rodder

Live Tracer $^{\text{\tiny{M}}}$ Traceable Rodder with an electrofusion insertion tee is designed to locate live gas mains with no blow by connecting a transmitter to the Live Tracer $^{\text{\tiny{M}}}$ to energize the unit with a specific frequency and radiates a signal to the surface where a receiver detects the frequency.

- No blow-by while feeding rod into live main up to 125 PSI
- Less disruption to roads and landscapes
- Minimal pavement breakage, excavation and restoration
- 600 feet of 1/4-inch diameter traceable fiberglass rod marked every 5 feet
- Stuffing Box and Accessory Kit included
- Dimensions: 36.25" x 24.0" x 13" (92.1 x 61 x 33 cm)

Size	Part Number	Replacement Reel	
600' x 1/4"	16-14-600M-GL	16-600RRM	



LIVE TRACER™ - GAS MAINS

5/16" Diameter Flexible Rod

Live Tracer $^{\text{\tiny M}}$ Traceable Rodder with an electrofusion insertion tee is designed to locate live gas mains with no blow by connecting a transmitter to the Live Tracer $^{\text{\tiny M}}$ to energize the unit with a specific frequency and radiates a signal to the surface where a receiver detects the frequency.

- No blow-by while feeding rod into live main up to 125 PSI
- · Less disruption to roads and landscapes
- Minimal pavement breakage, excavation and restoration
- 600 feet of 1/4-inch diameter traceable fiberglass rod marked every 5 feet
- Stuffing Box and Accessory Kit included
- Dimensions: 34.0" x 26.5" x 15.5" $(86.4 \times 67.3 \times 39.4 \text{ cm})$

Size	Part Number	Replacement Reel	
300' x 5/16"	12-516-300M-GL	12-300RRM	
400' x 5/16"	12-516-400M-GL	12-400RRM	



LIVE TRACER™ - GAS MAINS

5/16" Diameter Flexible Rod

Live Tracer™ Traceable Rodder with an electrofusion insertion tee is designed to locate live gas mains with no blow by connecting a transmitter to the Live Tracer™ to energize the unit with a specific frequency and radiates a signal to the surface where a receiver detects the frequency.

- No blow-by while feeding rod into live main up to 125 PSI
- Less disruption to roads and landscapes
- Minimal pavement breakage, excavation and restoration
- 600 feet of 1/4-inch diameter traceable fiberglass rod marked every 5 feet
- Stuffing Box and Accessory Kit included
- Dimensions: 40.0" x 32.0" x 18.0" (106 x 81.3 x 45.7 cm)

Size	Part Number	Replacement Reel
500' x 5/16"	12A-516-500M-GL	12A-500RRM
600' x 5/16"	12A-516-600M-GL	12A-600RRM
700' x 5/16"	12A-516-700M-GL	12A-700RRM
800' x 5/16"	12A-516-800M-GL	12A-800RRM
1200' x 5/16"	12A-516-1200M-GL	12A-1200RRM

TO ORDER 5/16" LIVE TRACER® WITH ALL-TERRAIN WHEELS, ADD AWK TO PART NUMBER. EXAMPLE: 12A-516-700M-AWK (12A-AND 13-MODELS ONLY) TO ORDER METRIC MARKED ROD, ADD AN ADDITIONAL "M" TO PART NUMBER WHEN ORDERING. (EXAMPLE: 6-14-300M WOULD BE 6-14-300M

ACCESSORIES & REPAIR KITS





Wipes Hex Wrench

All-Terrain Wheel



Accessories & Repair Kits	Description	1/4" Live Tracer	5/16" Live Tracer
Accessory Kit with	Canvas storage bag, stuffing box, 3 spare screws, 10 spare O-rings, lubricating wipes, hex wrench, ball-nose spring leader, spare end ferrule with adhesive, rod terminal, static grounding cable	16-14-SB-KIT	
Stuffing Box	Canvas storage bag, stuffing box, 3 spare screws, 10 spare O-rings, lubricating wipes, hex wrench, ball-nose spring leader, roller guide, spare end ferrule with adhesive, rod terminal, static grounding cable		12-516-SB-KIT
Accessory Kit without Stuffing Box	Accessory Kit for gas main tracer, no stuffing box	16-14-Kit_No SB	
Stuffing Box	Stuffing Box with 6 O-rings, 3 spare screws, 1" NPT pipe nipple	16-SB	12-SB
O-Rings	O-rings for Stuffing Box, 10-Pack	16-170	16-170-516
Spare Screws	Screws for Stuffing Box, 3-Pack	16-172	16-172
Lubricating Wipes	Lubricates rod for easier insertion through stuffing box. Canister of 20 wipes, non-toxic, water-based.	15-WIPE 15-WIPE-B (12 ct. box quantity)	
Hex Wrench	3/16" Ball-nose hex wrench for 1/4" and 5/16" stuffing boxes		16-HW316
End Ferrule Repair Kit	End ferrule, rod terminal, adhesive, emery cloth	16-146	12-146
Repair Adhesive	Adhesive, Applicator, Emery Cloth		9-167
Roller Guides	Roller guide helps guide rod over pipe joints and through bends. WILL NOT launch through EF Tees, for use with Directional Tool only.	16-141	9-141 or 9-141-R
Roller Guide w/Spring Leader	Heavy-duty spring & chain attached to swiveling roller guide helps guide rod over pipe joints & through bends. WILL NOT launch through EF Tees; use with Directional Tool only.		9-171
	Heavy-duty spring and chain with ball nose helps rod move over pipe joints and bends, 1/4"-20 hole. Will launch through EF Tees.	16-169	
Ball-Nose Spring Leader	Heavy-duty spring & chain with ball nose helps rod move over pipe joints and bends, 3/8"-16 hole (also fits Buddy rodders 3/8" & 1/2" rods.) Will launch through EF Tees.		12-163
All Terrain Wheel Kit	Heavy-duty spring and chain with ball nose helps rod move over pipe joints and bends, 1/4"-20 hole. Will launch through EF Tees.		11A-AWK

* Items Ending In "-R" Are Provided In Display-Ready Packaging

DIRECTIONAL ENTRY TOOL

The Jameson Directional Entry Tool enables vertical insertion of tracer rods and cameras into live gas mains, facilitating the difficult first bend at entry.

Patented technology developed by GTI, licensed by Jameson LLC

- Works on live mains with no blow by to 125 PSI
- Works on mains as small as 2"
- Rotates 360° to insert in either direction
- Optimized for use with Jameson 1/4" Live Tracer
- Works with commercially available saddles, valves and tap tools
- Works on PVC, PE, steel and ductile iron mains






Part Number	Description
16-DT-2-C	Directional Entry Tool With Hard Case
16-DT-2-SHOE	Replacement Shoe & Hardware
16-DT-2-REPAIR	Repair Kit: Wheel, 2 Lock Handles, Launch Handle, Launch Collar, 2 Launch Seal, 2 Shaft Collars

	Specifications		
Weight, Tool Only	21.5 lbs.		
Weight In Case	50 lbs.		
Tool Dimensions	40.5 x 11 x 9.5 in.		
Case Dimensions	42 x 13 x 12 in.		
Thread size	2" NPT		
Pressure Rating	125 PSI		

Mfr.	ltem	Part Number	Items For Tracing
Jameson	Α	16-DT-2-C	Directional Entry Tool, 2" NPT
	В	16-14-600-GL	1/4" x 600' Live Tracer rodder for gas mains with stuffing box & accessories
	С	16-SB	Stuffing Box for 1/4" rod (included with 16-14-600-GL)
			Items For Tracing & Camera Inspection
	D	360063170	SurTap Kit: Hot-tap tool, cutter, gasket, knife valve, fitting adapter, spanner wrench, coupon removal tool, completion plug installation tool, storage case
	Е	360062606	Knife valve with 2-7/8" buttress thread adapter for VersaTap fittings (included with SurTap Kit 360063170)
	F	360061520	VersaTap electrofusion fitting, 2" IPS, black, 4.7mm electrodes, with completion plug and external cap
GF Central Plastics		360061521	VersaTap electrofusion fitting, 3" IPS, black, 4.7mm electrodes, with completion plug and external cap
		360061522	VersaTap electrofusion fitting, 4" IPS, black, 4.7mm electrodes, with completion plug and external cap
		360061523	VersaTap electrofusion fitting, 6" IPS, black, 4.7mm electrodes, with completion plug and external cap
		360061524	VersaTap electrofusion fitting, 8" IPS, black, 4.7mm electrodes, with completion plug and external cap
	G	360064094	Quick connect adapter for lower end of Jameson 16-DT-2-C to enable mounting to Knife Valve 360062606
			Items For Camera Inspection
	н	TCL-4201	Stuffing Box with split head for camera insertion, 2" NPT, includes gasket set of your choice
Tellus		CLK 4212	10mm Gasket set for TCL-4201
Underground	J	CLK 4211	8mm Gasket set for TCL-4201
		CLK 4210	7mm Gasket set for TCL-4201
Hathorn Corp	К	110002	Key hole gas camera system, 3/8" x 400 ft, compatible with Jameson 16-DT-2-C, use 10mm gasket set



LIVE TRACER™ FOR GAS & WATER SERVICE LINES

Incorporating a stuffing box (included), the Live Tracer rod can be inserted into line without blow-by up to 125 psi. A locator and receiver set are used to energize and trace path.

- No blow-by while feeding rod into live line up to 125 PSI
- Less disruption to roads and landscapes
- Minimal pavement breakage, excavation and restoration







	1/8" Live Tracer Includes Accessory Kit & Stuffing Box	3/16" Live Tracer Includes Accessory Kit & Stuffing Box	
Applications	For Service Lines 1/2" To 1" and Tight Bends	For Service Lines 3/4" to 1-1/2"	
Features	Trace live gas & water service lines from the meter to the main		
Lengths Available	100' - 300' [30.5 - 91.4m]	100' - 300' [30.5 - 91.4m]	
Recommended Conduit	1/2" - 1" [15 - 25mm]	3/4" - 1-1/2" [20 - 40mm]	
Minimum Bend Radius	1.75" [4.5 cm]	2.5" [6.4 cm]	
Pull Strength	150 lbs. [67.9 kg]	300 lbs. [135.8 kg]	
Accessory Kit with Stuffing Box	Included 15-18-SB-KIT	Included 15-316-SB-KIT	
Dimensions	22" × 17" × 7" [55.9 × 43.2 × 17.8 cm]	22" x 17" x 7" [55.9 x 43.2 x 17.8 cm]	
Weights	11.1 - 15.0 lbs. [5.0 - 6.8 kg]	11.6 - 15.5 lbs. [5.3 - 7.0 kg]	



BULLET TIPGuides Rod From Riser To Service Transition

Size	Live Tracer with Bullet Tip	Replacement Canister
100'x 1/8"	15-18-100-GL	15-18-100RR-GL
150' x 1/8"	15-18-150-GL	15-18-150RR-GL
200' x 1/8"	15-18-200-GL	15-18-200RR-GL
250' x 1/8"	15-18-250-GL	15-18-250RR-GL
300' x 1/8"	15-18-300-GL	15-18-300RR-GL
100' x 3/16"	15-316-100-GL	15-100RR-GL
150' x 3/16"	15-316-150-GL	15-150RR-GL
200' x 3/16"	15-316-200-GL	15-200RR-GL
250' x 3/16"	15-316-250-GL	15-250RR-GL
300' x 3/16"	15-316-300-GL	15-300RR-GL




FLEXIBLE TIP

Navigates Difficult Transitions And Stab Fittings; Guides Rod Through Lyco Fittings In 1/2" Pipe.

Size	Live Tracer with Flexible Tip	Replacement Canister
100' x 1/8"	15-18-100-GLFT	15-18-100RR-GLFT
150' x 1/8"	15-18-150-GLFT	15-18-150RR-GLFT
200' x 1/8"	15-18-200-GLFT	15-18-200RR-GLFT
250' x 1/8"	15-18-250-GLFT	15-18-250RR-GLFT
300' x 1/8"	15-18-300-GLFT	15-18-300RR-GLFT
100' x 3/16"	15-316-100-GLFT	15-100RR-GLFT
150' x 3/16"	15-316-150-GLFT	15-150RR-GLFT
200' x 3/16"	15-316-200-GLFT	15-200RR-GLFT
250' x 3/16"	15-316-250-GLFT	15-250RR-GLFT
300' x 3/16"	15-316-300-GLFT	15-300RR-GLFT

ACCESSORIES & REPAIR KITS





Accessories & Repair Kits	Description		1/8" Live Tracer	3/16" Live Tracer
Accessory Kit with Stuffing Box	Canvas storage bag, Stuffing Box, 3 spare screws, 6 O-rings, lubricating wipes, hex wrench, spare bullet t (3/16" kit only) with adhesive, static grounding cable		15-18-SB-KIT	15-316-SB-KIT
Accessory Kit without Stuffing Box	Canvas storage bag, 3 spare screws, 6 spare O-ring: wipes, hex wrench, spare bullet tip & tapered tip with grounding cable		15-18-KIT_No SB	15-316-KIT_No SB
Lubricating Wipes	Lubricates rod for easier insertion through Stuffing 20 wipes, non-toxic, water-based	Box. Canister of	15-WIPE	15-WIPE E-B (12 ct. box quantity)
Hex Wrench	5/32" Ball-nose hex wrench for 1/8" and 3/16" Stuffin	ng Boxes		15-HW532
Grounding Cables	Grounding clip, gas tracer			15-GC
Stuffing Box	Stuffing Box with 6 O-rings, 3 spare screws, 3/4" NF	T pipe nipple	15-18-SB	15-SB
O-Rings	12-pack of O-rings for Stuffing Box		15-18-170-GW	15-170-GW
Spare Screws	3-pack of screws for Stuffing Box			15-172
Repair Adhesive	Adhesive, applicator, emery cloth			9-167
Replacement Terminal	Contact terminal replacement kit. Includes external terminals, end ferrule, adhesive, emery cloth	and internal	15-18-LUG	15-LUG
Bullet Tip Repair Kit	Bullet tip, adhesive, emery cloth - guides rod from r service transition	iser to	15-18-146-GW	15-146-GW
Tapered Tip Repair Kit	Tapered tip, adhesive, emery cloth - guides rod from service transition	n riser to		15-146-GW-T
Flex Tip Repair Kit	Flex tip, adhesive, emery cloth		15-18-168	15-163GLFT

LOCATE ENERGIZED CONDUCTIVE PATHS WITH RECEIVERS & TRANSMITTER

Compact, lightweight locators for easy one-hand operation. LCD display and easy-to-operate function keys are conveniently located on wand

 $Locate\ energized\ conductive\ paths\ such\ as\ iron,\ steel\ and\ copper\ water\ lines,\ gas\ lines,\ tracer\ wire\ by\ plastic\ pipe,\ telephone/TV\ cables\ and\ Jameson\ Duct\ Hunter^{\tiny{\bowtie}}\ Traceable\ Rodders.$

WAND SIGNAL RECEIVER

- · Ideal for short runs
- 2 active frequencies
- 2 operating modes: Line tracing (82 kHZ) and sonde locating (512 Hz)
- Includes carry case, manual, batteries

	Part Number	Description
	17-100R	Wand Signal Receiver
ľ		



- Depth indication with push of a button. Back-lit LCD display.
- 4 active frequencies: 512 Hz, 8 kHz, 33kHz, 82 kHz
- 2 passive frequencies: 60 Hz power & RF
- · Operating Modes: Peak, null and sonde
- Includes carry bag, manual, batteries, conductive clips

Part Number	Description	
17-300R	Cable & Pipe Precision Locating Receiver Equipped with Rechargeable Battery and a Padded Protective Carrying Case	



DIGITAL TRANSMITTER

Digital transmitter energizes conductive paths and supports Jameson's receivers. Includes low frequencies for direct connect long runs, higher frequencies for tracing Duct

Hunter™ rod in plastic pipes or inductive modes.

Lightweight unit features easy-to-read high contrast LCD screen. Includes carrying bag, manual, batteries, ground spike and wire leads.

Part Number	Description
17-500T	Digital Transmitter with Rechargeable Battery and a Padded Protective Carrying Case
	Personal Property of the Personal Property of
-	

INDUCTIVE COUPLER CLAMP

Use with transmitter to apply signal to cables when direct connection is not possible.

Operational frequency range 8kHz to 82kHz. 15 ft. cord, 1/4"-20 mounting hole

Part Number	Description
17-4HC	Inductive Coupler Clamp



SOIL PROBE LOCATES UNDERGROUND UTILITY BOXES, BURIED CONDUIT AND TREE ROOTS

Soil Probe Locates Underground Utility Boxes, Buried Conduit And Tree Roots

- Solid 1/2" fiberglass rod for increased strength and flexibility
- Solid 1" fiberglass handle with double-coated PVC finger grips
- Reinforced steel tip to penetrate ground


Part Number	Description
SP-48	48" T-Bar Soil Probe
SP-TIP	Replacement Tip with Adhesive











BUDDY FISH TAPE TELECOMMUNICATION & ELECTRICAL WIRING

Since 1980, the Jameson Buddy® System of rodders and fish tapes has evolved to become the most comprehensive in the industry.

Jameson fish tapes feature a round, flexible rod that slides easily over wires in occupied conduit, offering exceptional bending strength for maneuvering tight turns.

- Non-conductive fiberglass rod core with orange polymer jacket
- Smooth, round rod installs easily in empty or occupied conduit
- Round rod bends in all directions, unlike flat steel fish tapes





BUDDY® FISH TAPE OVERVIEW



	Wee B	Buddy®	Flex Buddy [™] Flexible Steel	Flex Buddy [™] Non-Conductive Plastic Tip	Little Buddy®		Microduct Fisher [™]	
Features	Round rod flexes and slides easily Easy-grip canists Smooth, non-bin and return Snap-on accessor	y over wires er ading payout	Polymer Mono- Twist Fish Tape with Flexible Steel Leader Tip	Polymer Mono- Twist Fish Tape with Non-Conductive Plastic Tip	Operates vertically or horizontally. Feed eye and drag brake control payout.		ng eye is permanently mo in microduct as small as	
			Durable single-stra fast low-friction fis High-Flex, Non-Kin Design Large Comfort-Grip Handle designed f quick payout	hing k, Single-Strand c Ergonomic				
Rod Diameter	1/8" (3	.2mm)	1/4" (5.	5mm)	3/16" (4.8mm)		1/8" (3.2 mm)	
Lengths Available	50-150' (15	5.2–45.7m)	100-200'(2	.54-5.08m)	150-300' (45.7–91.4m)		160'/350' (50.3/106.7r	n)
Recom- mended Conduit	Conduit As Sma	ıll As 1/2" (16mm)			3/4"-1-1/2" (21-41mm)		Microduct As Small As 6	mm
Bend Radius	1.5" (3	8.1mm)	<0.5" (1:	2.5mm)	2.5" (63.5mm)		1.5" (38.1mm)	
Pull Strength	200 Lbs.	(90.5kg)	550 lb (250kg)	400 lb (181kg)	300 lbs. (135.7kg)		200 lbs (90.5kg)	
Accessory Kits	Included 8-18-AK	N/A	N/	Ά	Included 10-316-AK		N/A	
Dimensions L x W x H	12.5" x 2.0" (31.8 x 5.1 cm)	22"x17"x2" (55	i.8x43.2x5cm)	22" x 17" x 7" (55.9 x 43.2 x 17.8 cm)	12.5" x 2.0" (31.8 x 5.1 cm)	20" x 17" x 10.3" (50.8 x 43.2 x 26.2 cm)	22" x 17" x 7" (55.9 x 43.2 x 17.8 cm)
Weights	2.3 - 3.0 lbs	.(1.0 - 1.4 kg)	6 - 7.8 lb (2	2.7 - 3.5 kg)	12.6 - 15.5 lbs. (5.7 - 7.0 kg)	2.4 lbs. (1.1 kg)	10 lbs. (4.5 kg)	11 lbs. (5.0 kg)
End Ferrule	#10-32	2 Male	#12-24 Male Metal with 6" steel cable leader	#12-24 Male Plastic	#12-24 Male			

Rod is marked in 5' increments. Add 'MM' to part number for metric measure (1m increments)



WEE BUDDY® - WITHOUT ACCESSORY KIT

1/8" Diameter Rod - Lightweight Portable Fish Tape

Wee Buddy's round rod slides easily over existing wires, especially at bends, with a smooth, non-binding payout and return to canister.

Easy-grip design allows for more efficient pushing and pulling when fishing telecom, voice, data or electrical conduit.

Patented canister features snap-on accessory kit.

- Non-Conductive Fiberglass Rod
- Bend Radius: 1.5"
- 200-lb. pull/tensile strength
- · Available With or Without Accessory Kit
- Dimensions: 12.5" Diameter x 2"

Size	Part Number	In Display Package
50' x 1/8"	8-18-50	8-18-50-R
100' x 1/8"	8-18-100	8-18-100-R
150' x 1/8"	8-18-150	8-18-150-R



WEE BUDDY® - WITH ACCESSORY KIT

1/8" Diameter Rod - Lightweight Portable Fish Tape

Wee Buddy's round rod slides easily over existing wires, especially at bends, with a smooth, non-binding payout and return to canister.

Easy-grip design allows for more efficient pushing and pulling when fishing telecom, voice, data or electrical conduit.

Patented canister features snap-on accessory kit.

- Non-Conductive Fiberglass Rod
- Bend Radius: 1.5"
- 200-lb. pull/tensile strength
- Available With or Without Accessory Kit
- Dimensions: 12.5" Diameter x 2"

Size	Part Number	In Display Package
50' x 1/8"	8-18-50K	8-18-50K-R
100' x 1/8"	8-18-100K	8-18-100K-R
150' x 1/8"	8-18-150K	8-18-150K-R



LITTLE BUDDY®

3/16" Diameter Rod - For Conduit 0.75" - 1.5" Diameter

Lightweight, portable unit typically used for running inside and outside conduit drops as well as home drops from the hand-hole box to a building. Also used for light pole and control wiring or walker ducts.

- Operates vertically or horizontally
- Drag brake and safety feed eye control payout
- Non-Conductive Fiberglass Rod
- 3/16" OD Fiberglass Rod
- 2.5" Bending Radius
- 300-lb Pull/Tensile Strength
- · Accessory Kit included
- Dimensions: 22" x 17" x 7"

Size	Part Number	In Display Package	Replacement Reel
150' x 3/16"	10-316-150	10-316-150-R	10-150RR
200' x 3/16"	10-316-200	10-316-200-R	10-200RR
250' x 3/16"	10-316-250	10-316-250-R	10-250RR
300' x 3/16"	10-316-300	10-316-300-R	10-300RR

^{*} Items Ending In "-R" Are Provided In Display-Ready Packaging Rod is marked in 5' increments. Add 'MM' to part number for metric measure (1m increments)



MICRODUCT FISHER™ HANDHELD

1/8" Diameter Rod - Lightweight canister with easy-grip design

Microduct Fisher features all fiberglass rod construction for safety and easy handling. Smooth, round polymer jacket will not nick or scratch fiber or duct wall.

Low profile pulling eye is permanently mounted on rod to move easily in fiber microducts as small as 6 mm, where traditional fish tapes are too large.

- 3.2 mm OD Fiberglass Rod
- 1.5" Bending Radius

Size	Part Number	In Display Package
165' x 1/8"	8-18-165MDR	8-18-165MDR-R



MICRODUCT FISHER™ II WITH HANDLE

1/8" Diameter Rod - Portable Handheld Canister for Easy Transport

Microduct Fisher II ideal for pulling phone wire, network cable or speaker wire through walls, occupied and empty electrical conduit.

- Non-Conductive Fiberglass Rod
- Bend Radius: 1.5"
- Ideal for occupied and empty conduit measuring as small as 6 mm
- The fish tape is designed with a robust brake for controlling the payout speed
- Accessory Kit included
- Dimensions: 22" Diameter x 7"

Size	Part Number	In Display Package	Replacement Reel
350' x 1/8"	10-18-350MDR	10-18-150-MDR-R	10-350RR-MDR



MICRODUCT FISHER™ II ON STAND

1/8" Diameter Rod - For Conduit Measuring as Small as 6 mm

The Microduct Fisher features all fiberglass rod construction for safety and easy handling. Smooth, round polymer jacket will not nick or scratch fiber or duct wall.

- Drag brake and safety feed eye to control pay out.
- 1.5" Bending Radius
- Overall Weight: 16 lbs.
- The fish tape is designed with a robust brake for controlling the payout speed
- Ideal for occupied and empty conduit measuring as small as 6 mm
- · Accessory Kit included
- Dimensions: 22" x 17" x 7"

Size	Part Number	In Display Package	Replacement Reel
350' x 1/8"	10-18-350MDRS	10-18-350MDRS-R	10-350RR-MDR

^{*} Items Ending In "-R" Are Provided In Display-Ready Packaging Rod is marked in 5' increments. Add 'MM' to part number for metric measure (1m increments)

ACCESSORIES



Accessories	Description	Wee Buddy®	Little Buddy®	Microduct Fisher®
Wee Buddy Accessory Kit	Plastic Case, Flexible Leaders (2), Pulling Eye (2), Splice Ferrule (2), End Ferrule (2), Adhesive and Emery Cloth	8-18-AK		
Little Buddy Accessory Kit	Flexible Leaders (2), Pulling Eye (2), Splice Ferrule, End Ferrule (2), Adhesive and Emery Cloth		10-316-AK or 10-316-AK-R	
Fixed Pulling Eye	Attach pull line or pulling grip to rod	8-160 or 8-160-R	10-160	
Flexible Leader w/Sm. Tip	Guide rod through bends, sweeps, and misalignments	8-163 or 8-163-R		
Flexible Leader w/Lg. Tip	Guide rod through bends, sweeps, and misalignments	8-162 or 8-162-R	10-163	
Flexible Leader w/Eyelet	Guide rod through bends, sweeps, and misalignments		10-162	
Pulling Eye Repair Kit	Pulling Eye, Adhesive, and Emery Cloth			8-146MDR or 8-146MDR-R
Splice Repair Kit	Splice Ferrule, Adhesive, and Emery Cloth	8-140 or 8-140-R	10-140 or 10-140-R	8-140MDR or 8-140MDR-R
End Ferrule Repair Kit	End Ferrule, Adhesive, and Emery Cloth	8-146 or 8-146-R	10-146	
Repair Adhesive	Adhesive and Emery Cloth		10-167	

^{*} Items Ending In "-R" Are Provided In Display-Ready Packaging





EZ-REEL PRE-LOADED REPLACEMENT ROD ON REEL

Jameson Buddy® Conduit Rodders and Fish Tapes are the most durable in the market, but we know job sites can be extremely tough.

Using our repair kits, customers are often able to splice rod or repair end-fittings to keep their rodders in service.

However, on occasion it may be necessary to replace the entire spool of rod due to more severe damage. Removal, disposal and rod replacement can be a difficult and time-consuming task. Responding to customer feedback, Jameson introduced EZ-REEL™ pre-loaded replacement reels which help improve speed and safety of replacing damaged rod material.

Size	Part Number	Reel
1/8" x 350'	10-350RR-MDR	Microduct Fisher II
3/16" x 150'	10-150RR	Little Buddy®
3/16" x 200'	10-200RR	Little Buddy®
3/16" x 250'	10-250RR	Little Buddy®
3/16" x 300'	10-300RR	Little Buddy®

^{*} Items Ending In "-R" Are Provided In Display-Ready Packaging



FLEX BUDDY™ FLEXIBLE STEEL TIP, 100'

Polymer Fish Tape with Flexible Steel Leader Tip

Combines the stiffness to push long runs, with the flexibility to handle multiple 90° bends. Non-conductive polymer material resists kinking for durable long-lasting performance on the job site.

- Polymer Mono-Twist Fish Tape with Flexible Steel Leader Tip
- Durable single-strand spiral design for fast low-friction fishing
- High-Flex, Non-Kink, Single-Strand Design
- Large Comfort-Grip Ergonomic Handle designed for smooth and quick payout

Size	Description
5-316-100FST	100' Polymer Mono-Twist Fish Tape with Flexible Steel Leader Tip



FLEX BUDDY™ NON-CONDUCTIVE PLASTIC TIP, 150' Polymer Fish Tape with Flexible Steel Leader Tip

Combines the stiffness to push long runs, with the flexibility to handle multiple 90° bends. Non-conductive polymer material resists kinking for durable long-lasting performance on the job site.

- Polymer Mono-Twist Fish Tape with Flexible Steel Leader Tip
- Durable single-strand spiral design for fast low-friction fishing
- · High-Flex, Non-Kink, Single-Strand Design
- Large Comfort-Grip Ergonomic Handle designed for smooth and quick payout

Size	Description
5-316-150FST	150' Polymer Mono-Twist Fish Tape with Flexible Steel Leader Tip



FLEX BUDDY™ NON-CONDUCTIVE PLASTIC TIP, 200'

Polymer Fish Tape with Flexible Steel Leader Tip

Combines the stiffness to push long runs, with the flexibility to handle multiple 90° bends. Non-conductive polymer material resists kinking for durable long-lasting performance on the job site.

- Polymer Mono-Twist Fish Tape with Flexible Steel Leader Tip
- Durable single-strand spiral design for fast low-friction fishing
- High-Flex, Non-Kink, Single-Strand Design
- Large Comfort-Grip Ergonomic Handle designed for smooth and quick payout

Size	Description
5-316-200FST	200' Polymer Mono-Twist Fish Tape with Flexible Steel Leader Tip



FLEX BUDDY™ NON-CONDUCTIVE PLASTIC TIP, 100'

Polymer Mono-Twist Fish Tape with Non-Conductive Plastic Tip

Combines the stiffness to push long runs, with the flexibility to handle multiple 90° bends. Non-conductive polymer material resists kinking for durable long-lasting performance on the job site.

- Polymer Mono-Twist Fish Tape with Non-Conductive Plastic Tip
- Durable single-strand spiral design for fast low-friction fishing
- High-Flex, Non-Kink, Single-Strand Design
- Large Comfort-Grip Ergonomic Handle designed for smooth and quick payout

Size	Description
5-316-100NCT	100' Polymer Mono-Twist Fish Tape with Non-Conductive Plastic Tip



FLEX BUDDY™ NON-CONDUCTIVE PLASTIC TIP, 150' Polymer Mono-Twist Fish Tape with Non-Conductive Plastic Tip

Combines the stiffness to push long runs, with the flexibility to handle multiple 90° bends. Non-conductive polymer material resists kinking for durable long-lasting performance on the job site.

- Polymer Mono-Twist Fish Tape with Non-Conductive Plastic Tip
- Durable single-strand spiral design for fast low-friction fishing
- · High-Flex, Non-Kink, Single-Strand Design
- Large Comfort-Grip Ergonomic Handle designed for smooth and quick payout

Size	Description
5-316-150NCT	150' Polymer Mono-Twist Fish Tape with Non-Conductive Plastic Tip



FLEX BUDDY™ NON-CONDUCTIVE PLASTIC TIP, 200'

Polymer Mono-Twist Fish Tape with Non-Conductive Plastic Tip

Combines the stiffness to push long runs, with the flexibility to handle multiple 90° bends. Non-conductive polymer material resists kinking for durable long-lasting performance on the job site.

- Polymer Mono-Twist Fish Tape with Non-Conductive Plastic Tip
- Durable single-strand spiral design for fast low-friction fishing
- High-Flex, Non-Kink, Single-Strand Design
- Large Comfort-Grip Ergonomic Handle designed for smooth and quick payout

Size	Description
5-316-200NCT	200' Polymer Mono-Twist Fish Tape with Non-Conductive Plastic Tip

^{*} Electric shock hazard: Do not use near live circuits. Always wear proper PPE when using this product.



GLOW FISH RODS

NON-CONDUCTIVE FIBERGLASS RODS FOR INSIDE WIRING

Jameson is the original manufacturer of non-conductive fiberglass glow rods. Kits are perfect for running wire through drop ceilings, attics, floors, walls and crawl spaces. It's high strength and flexibility allows you to handle turns easily without breakage. All of our rods feature the same size threaded ferrules for maximum versatility.

CHOOSING A GLOW ROD SIZE FOR YOUR JOB

Flexibility Increases As Rod Diameter Decreases

- 1/4" for long spans requiring greater rigidity
 Minimum Bend Radius: 6" Tensile/Pull Strength: 750 lbs
- 3/16" for short spans or in limited space
 Minimum Bend Radius: 4" Tensile/Pull Strength: 500 lbs
- 5/32" for making tight turns offering extreme flexibility with high strength
 Minimum Bend Radius: 3.5" Tensile/Pull Strength: 300 lbs

Using the same size ferrules (#8-32), different diameter rods can be used together in any combination for ultimate on-the-job customization.









1/4" DIAMETER GLOW RODS, 12'

Part Number	Package Length
7-34T	4'

Three 4' x 1/4" Rods. Includes One Bullet Nose with Eyelet, One Hook



1/4" DIAMETER GLOW RODS, 18'

Part Number	Package Length
7-63T	3'

Six 3' x 1/4" Rods. Includes One Bullet Nose with Eyelet, and One Hook



1/4" DIAMETER GLOW RODS, 24'

Part Number	Package Length
7-36-23T	6'
Three 6' x 1/4" Rods, Two 3' x 1/4" Rods. Includes One	



3/16" DIAMETER GLOW RODS, 10.5'

	· · · · · · · · · · · · · · · · · · ·	
Part Number	Package Length	
7S-718T	18"	
Seven 18" x 3/16" Rods. Includes One Bullet Nose with Eyelet, One Hook		



3/16" DIAMETER GLOW RODS, 15'

Eyelet, One Hook

Part Number	Package Length
7S-35T	5'
Three 5' x 3/16" Rods. Includes One Bullet Nose with	



3/16" DIAMETER GLOW RODS, 20'

Part Number	Package Length
7S-45T	5'
Four 5' x 3/16" Rods. Includes One Bullet Nose with	



5/32" DIAMETER GLOW RODS, 6'

Part Number	Package Length
7SS-6	*
One 6' x 5/32" Rod with Permanently Mounted Bullet Nose with Eyelet On Each End of Rod	

* Single rods shipped with hanging tag, not in clear



5/32" DIAMETER GLOW RODS, 18'

	Part Number	Package Length
	7SS-36T	6'
Three 6' x 5/32" Rods. Includes One Eyelet, One Hook		Rods. Includes One Bullet Nose with



FLEXI-MAGNET

Part Number	Description
7-07A	Flexi-Magnet Kit (Retriever and Ball Chain with Ring)

Bendable retriever features a powerful magnetic tip that grabs chain inside wall to pull wire. Includes 10' length of ball chain with ring to hold in place.



COMBO GLOW ROD KITS, 30'

Part Number	Package Length
7S-65K	6'

Six 3/16" x 5' Rods. Includes One Bullet Nose with Eyelet, One Hook, One Whisk, One Ball Chain Bullet Nose



COMBO GLOW ROD KITS, 34'

Part Number	Package Length
7-8\/K	6'

Two 1/4" x 6' Rods, Two 3/16" x 5' Rods, and One 5/32" x 6' Rod. Includes One 5/32" x 6' Rod with Permanently Mounted Bullet Eye On Each End, One Hook, and One Whisk



COMBO GLOW ROD KITS, 35'

Part Number	Package Length
7-8-IK	6'
	s, Two 1/4" x 2.5' Rods, Four ncludes Two Bullet Nose with Eyelet, Whisk



ACCESSORY - BULLET NOSE WITH EYELET

Part Number	Description
7-00A	Bullet Nose with Eyelet (Attach pull line to rod)



ACCESSORY - HOOK

Part Number	Description
7-01A	Hook (Grasp and retrieve)



ACCESSORY - BULLET NOSE WITH RING

Part Number	Description
7-02A	Bullet Nose with Ring (Pull line or grab with hook)



ACCESSORY - WHISK

Part Number	Description
7-03A	Whisk (Guide rod; avoid obstacles)



ACCESSORY - BALL CHAIN BULLET NOSE

Part Number	Description
7-04A	Ball Chain Bullet Nose (Use with Magnet for retrieval)



ACCESSORY - MAGNET

Part Number	Description
7-05A	Magnet (Retrieve Ball Chain)



ACCESSORY - LUMINESCENT WHISK

Part Number	Description
7-08A	For low-light applications. Accepts all Jameson attachments





ACCESSORY - LED LIGHT TIP

Part Number	Description
7-09A	Omni-directional light illuminates dark spaces



Part Number	Description
7-00A	Bullet Nose with Eyelet (Attach pull line to rod)
7-01A	Hook (Grasp and retrieve)
7-02A	Bullet Nose with Ring (Pull line or grab with hook)
7-03A	Whisk (Guide rod; avoid obstacles)
7-04A	Ball Chain Bullet Nose (Use with Magnet for retrieval)
7-05A	Magnet (Retrieve Ball Chain)












Part Number	Description
7-00A	Bullet Nose with Eyelet (Attach pull line to rod)
7-01A	Hook (Grasp and retrieve)
7-02A	Bullet Nose with Ring (Pull line or grab with hook)
7-04A	Ball Chain Bullet Nose (Use with Magnet for retrieval)
7-05A	Magnet (Retrieve Ball Chain)
7-08A	Luminescent Whisk (For low-light applications. Accepts all Jameson attachments)
7-09A	LED Light Tip (Omni-directional light illuminates dark spaces)



Part Number	Description
7-5B	Fish Rod Rigid Storage Case





NON-CONDUCTIVE FIBERGLASS RODS FOR INSIDE WIRING





Yellow Jacket™ Coated Fish Rods from Jameson are perfect for fishing wire and cable with confidence and ease in any environment. Our tough, durable coated fish rods provide the strength and versatility you need when pulling wire and cable in suspended ceilings, raised floors, attics, crawlspaces, or interior wall cavities.

Splinter Shield™ Protective Coating


Resists abrasion and eliminates painful fiberglass splinters, allowing better control and glove-free use by installers.

Exceptional Bend Strength

Fiberglass reinforced polyester core with protective polypropylene coating provides best-in-class bend strength for use in tight bend applications.

Three Available Rod Diameters

Individual kits and combo kits offer choice of $\,$ Low, Mid, and High-Flex rod performance.





LOW-FLEX COATED FISH ROD KITS, 16'

Part Number	Description
7C-82T	16' Low-Flex Fish Rod Kit

(8) 2' Low-Flex Fish Rods, LED Light Tip (7-09A), Hook Tip (7-01A), and Bullet Tip with Eyelet (7-00A)



LOW-FLEX COATED FISH ROD KITS, 15'

Part Number	Description
7C-37T	15' Low-Flex Fish Rod Kit

(3) 5' Low-Flex Fish Rods, LED Light Tip (7-09A), Hook Tip (7-01A), and Bullet Tip with Eyelet (7-00A)



MID-FLEX COATED FISH ROD KITS, 12'

Part Number	Description
7SC-62T	12' Mid-Flex Fish Rod Kit
(6) 2' Mid-Flex Fish Rods, LED Light Tip (7-09A), Hook Tip (7-01A), and Bullet Tip with Evelet (7-00A)	



MID-FLEX COATED FISH ROD KITS, 15'

Part Number	Description
7SC-35T	12' Mid-Flex Fish Rod Kit
	ish Rods, LED Light Tip (7-09A), Hook Bullet Tip with Eyelet (7-00A)



HIGH-FLEX COATED FISH ROD KITS, 15'

Part Number	Description
7SSC-35T	15' High-Flex Fish Rod Kit
(3) 5' High-Flex Fish Rods, LED Light Tip (7-09A), Hook Tip (7-01A), and Bullet Tip with Eyelet (7-00A)	



MULTI-FLEX COATED FISH ROD KITS, 25'

Part Number	Description
7C-45-15T	25' Multi-Flex Fish Rod Kit
	sh Rods, (1) 5' Mid-Flex Fish Rod, LED , Hook Tip (7-01A), and Bullet Tip A)



MULTI-FLEX COATED FISH ROD KITS, 30'

Part Number	Description
7C-30KT	30' Multi-Flex Fish Rod Kit

(2) 5' Low-Flex Fish Rods, (2) 5' Mid-Flex Fish Rods, (2) 5' High-Flex Fish Rods, LED Light Tip (7-09A), Hook Tip (7-01A), Bullet Tip with Eyelet (7-00A), Whisk Tip (7-08A)



MULTI-FLEX COATED FISH ROD KITS, 60'

Part Number	Description
7C-60KB	60' Multi-Flex Fish Rod Kit

(6) 5' Low-Flex Fish Rods, (3) 5' Mid-Flex Fish Rods, (3) 5' High-Flex Fish Rods, LED Light Tip (7-09A), Hook Tip (7-01A), Bullet Tip with Eyelet (7-00A), Whisk Tip (7-08A), Magnet Tip (7-05A), Ball Chain Tip (7-04A), and Rigid Nylon Carry Case (7-5B)









SCISSORS & KNIVES TELECOMMUNICATION PELECTRICAL WIRING



Jameson remains the leading provider of splicer snips and knives to the telecommunications market.

SPLICER SNIPS

Precision ground for consistent quality, Jameson scissors are ideal for telecommunication, and electrical wiring jobs.

SKINNING KNIVES

Straight blade is molded into an easy-grip polymer handle that remains pliable in subzero temperatures. Blade is 20-25% thicker than comparable models.

LEATHER & PVC TOOL POUCHES

Leather pouches are reinforced with steel rivets for durability. Black PVC pouches will not split or tear with age, remaining flexible even in cold weather.





Part Number	Description
32-21NS	Electrician Scissors
32-21NS-R	Electrician Scissors - Retail



SNIP GRIP® ERGONOMIC HANDLE

Part Number	Description
32-40	Snip Grip® Ergonomic Handle
32-40-R	Snip Grip® Ergonomic Handle - Retail



SNIP GRIP® ELECTRICIAN SCISSORS, 5-1/4 IN.

Part Number	Description
32-41NS	Snip Grip® Electrician Scissors
32-41NS-R	Snip Grip® Electrician Scissors - Retail



CABLE SPLICER KNIFE, WITH ERGONOMIC HANDLE, 6-1/4 IN.

Part Number	Description
32-24E	Cable Splicing Knife with Ergonomic Handle, 6-1/4 in.
32-24E-R	Cable Splicing Knife with Ergonomic Handle, 6-1/4 in Retail



CABLE SPLICER KNIFE, STRAIGHT HANDLE

Part Number	Description
32-24J	Knife with Straight Handle
32-24J-R	Knife with Straight Handle - Retail



SLOTTED LEATHER POUCH

Part Number	Description
32-11	Slotted Leather Pouch
32-11-R	Slotted Leather Pouch - Retail



TUNNEL LOOP LEATHER POUCH

Part Number	Description
32-11T	Tunnel Loop Leather Pouch
32-11T-R	Tunnel Loop Leather Pouch - Retail



SLOTTED LEATHER POUCH FOR SCISSORS

Part Number	Description
32-12	Slotted Leather Pouch for Scissors
32-12-R	Slotted Leather Pouch for Scissors - Retail



SLOTTED LEATHER POUCH FOR KNIFE

Part Number	Description
32-25	Slotted Leather Pouch For Knife
32-25-R	Slotted Leather Pouch For Knife - Retail

^{*} Items Ending In "-R" Are Provided In Display-Ready Packaging



LOOP LEATHER POUCH

Part Number	Description
32-15T	Tunnel Loop Leather Pouch Snip Grip® Scissors, and Splicer Knife



TOOL POUCH ADJUSTABLE BELT

Part Number	Description
32-30	Tool Pouch Adjustable Belt



ELECTRICIAN SCISSORS, 5-1/4 IN.

Part Number	Description
32-12NS	Electrician Splicer Scissors, 5-1/4 in. with Slotted Leather Pouch
Kit Includes: 32-12, 32-21NS	



SLOTTED LEATHER POUCH WITH KNIFE

Part Number	Description
32-24P	Slotted Leather Pouch with Knife
32-24P-R	Slotted Leather Pouch with Knife - Retail
Kit Includes: 32	2-25, 32-24J



CABLE SPLICER'S KIT, TUNNEL LOOP LEATHER POUCH (3-PIECE)

Part Number	Description
32-23NS	Cable Splicer's Kit, Tunnel Loop Leather Pouch (3-Piece)
32-23NS-R	Cable Splicer's Kit, Tunnel Loop Leather Pouch (3-Piece) - Retail
Kit Includes: 32-21NS, 32-11T, 32-24J	



CABLE SPLICER'S KIT, SLOTTED LEATHER POUCH (3-PIECE)

Part Num	ber	Description
32-22NS		Cable Splicer's Kit, Slotted Leather Pouch (3-Piece)
Kit Include	s: 32-2	21NS, 32-11, 32-24J



CABLE SPLICER'S KIT, TUNNEL LOOP LEATHER POUCH (3-PIECE)

Part Number	Description
32-43NS	Cable Splicer's Kit, Tunnel Loop Leather Pouch (3-Piece)
32-43NS-R	Cable Splicer's Kit, Tunnel Loop Leather Pouch (3-Piece) - Retail
Kit Includes: 32	!-41NS, 32-11T, 32-24J



CABLE SPLICER'S KIT, SLOTTED LEATHER POUCH (3-PIECE)

Part Number	Description
32-42NS	Cable Splicer's Kit, Slotted Leather Pouch (3-Piece)
32-42NS-R	Cable Splicer's Kit, Slotted Leather Pouch (3-Piece) - Retail
Kit Includes: 32-41NS, 32-11, 32-24J	



ELECTRICIAN FIBER OPTIC SCISSORS, 5-1/2 IN.

Part Number	Description
32-60	Electrician Fiber Optic Scissors, 5-1/2 in.

^{*} Items Ending In "-R" Are Provided In Display-Ready Packaging



TRI-HOLE FIBER OPTIC STRIPPERS

Part Number	Description
32-FS-375	Tri-Hole Fiber Optic Strippers
32-FS-375-R	Tri-Hole Fiber Optic Strippers - Retail



FIBER STRIPPER & SHEARS KIT (3-PIECE)

Part Number	Description
32-60-375	Fiber Stripper & Shears Kit (3-Piece)
32-60-375-R	Fiber Stripper & Shears Kit (3-Piece) Retail
Kit Includes: 32	-60, 32-14T, 32-FS-375



SCISSORS & KNIFE SHARPENER

Part Number	Description
32-50	Scissors & Knife Sharpener
32-50-R	Scissors & Knife Sharpener - Retail







Part Number	Description
32-70-C	Charcoal Hawkbill Skinning Knife
Packaged In Co	ustom Box For Hanging Display

The Hawkbill skinning knife is ideal for heavy-duty line work. Features a curved, double-edged, ice-tempered blade to easily cut through cable jackets and insulation. The knife has a cushioned, ergonomic handle that features an expanded end to protect from hand slippage. An oversized ring provides added strength and makes it easy to store. Overall measures 10 in. long by 2 in. wide by 3/4 in. tall. Blade measures 3 in.

Hawkbill Skinning Knives Are Provided In Display-Ready Packaging.

^{*} Items Ending In "-R" Are Provided In Display-Ready Packaging

CABLE CUTTER

RATCHETING CABLE CUTTER

Not For Use on ACSR Cable or Steel Wire

The RCC-750 has a ratchet mechanism that has been designed to withstand the stress of 750 MCM copper and aluminum cables (maximum O.D. of 0.866"). The blades have a 100% cutting surface which provides the best possible cutting leverage. A thumb release lever allows the operator to back out of a cut when necessary. A locking mechanism closes the handles for easy storage.

NOTE: DO NOT CUT STEEL

FEATURES

- Rated for 750MCM
- Thumb lever blade release
- Robust ratchet mechanism

FEATURES

- Cuts soft copper, aluminum, and multiple conductor cables
- MAX 400mm² (AWG 750MCM) ø22
- · Weight: 2 lbs.
- NOT FOR USE ON ACSR CABLE OR STEEL WIRE

CUTTING CAPACITIES

• 750 MCM Cu or Al

Part Number	Description
RCC-750	Ratcheting Cable Cutter













6.5"









CABLE BENDING MADE EASY!





Bending large gauge electrical cables is difficult, especially in tight spaces. Bulldog Bender gives you the power and leverage to easily install, bend, &

Bulldog Bender gives you the power and leverage to easily install, bend, & terminate cables in service panels, LB conduit bodies, switch gear, motor controls, wireways, and meter bases.

- \bullet Four tool sizes cover wide range of cable sizes up to 1000 MCM
- Provides power and leverage to easily install, bend, & terminate cables
- High-strength steel construction and durable powder coat finish ensure long tool-life
- \bullet 90° offset dowel orientation allows ease of use in a variety of applications
- Pro Handle with Adapter Bar allows left/right cable bends in tight electrical enclosures
- Knurled and Smooth dowels included for maximum versatility and user preference (Standard Knurled Dowels are factory assembled, with optional Smooth dowels included with each tool.)
- Slim handle allows for easy access into tight spaces
- Work from both ends of the tool handle
- LIFETIME WARRANTY



BULLDOG BENDER PUP (4/0 AWG)

Bending large gauge electrical cables is difficult, especially in tight spaces. Bulldog Bender gives you the power and leverage to easily install, bend, & terminate cables in service panels, LB conduit bodies, switch gear, motor controls, wireways, and meter bases. 14" Standard Handle (Smooth Dowels 1.3 lbs.)

Part Number	Description
40	Bulldog Bender™ Pup (4/0 AWG), 14" Standard Handle



BULLDOG BENDER PUP PRO 2-PIECE SET (4/0 AWG)

Bending large gauge electrical cables is difficult, especially in tight spaces. Bulldog Bender gives you the power and leverage to easily install, bend, & terminate cables in service panels, LB conduit bodies, switch gear, motor controls, wireways, and meter bases. 2-Piece Set: 14" Pro-Handle (Smooth Dowels 1.4 lbs.) w/11" Adapter Bar (Smooth Dowels 1.1 lbs.)

Part	t Number	Description
40-2	2	Bulldog Bender™ Pup (4/0 AWG) 2-pc. Set, 14" Pro-Handle w/11" Adapter Bar



Standard Knurled Dowels are factory assembled, with optional Smooth dowels included with each tool. Bulldog Bender Pup is provided with Smooth Dowels only.



BULLDOG BENDER PUP 3-PIECE SET (4/0 AWG)

Bending large gauge electrical cables is difficult, especially in tight spaces. Bull-dog Bender gives you the power and leverage to easily install, bend, & terminate cables in service panels, LB conduit bodies, switch gear, motor controls, wireways, and meter bases. 3-Piece Set: 14" Standard Handle (Smooth Dowels 1.3 lbs.) & 14" Pro-Handle (Smooth Dowels 1.4 lbs.) w/11" Adapter Bar (Smooth Dowels 1.1 lbs.)

40-3 Bulldog Bender" Pup (4/0 AWG) 3-pc. Set, 14" Std. Handle & 14" Pr Adapter Bar	Pro-Handle w/11"





BULLDOG BENDER ORIGINAL (500 MCM)

Bending large gauge electrical cables is difficult, especially in tight spaces. Bulldog Bender gives you the power and leverage to easily install, bend, & terminate cables in service panels, LB conduit bodies, switch gear, motor controls, wireways, and meter bases. 18" Standard Handle (Knurled Dowels 2.6 lbs.) (Smooth Dowels 2.5 lbs.)

Part Number	Description
500	Bulldog Bender™ Original (500 MCM), 18" Standard Handle



Standard Knurled Dowels are factory assembled, with optional Smooth dowels included with each tool. Bulldog Bender Pup is provided with Smooth Dowels only.




BULLDOG BENDER ORIGINAL PRO 2-PIECE SET (500 MCM)

Bending large gauge electrical cables is difficult, especially in tight spaces. Bulldog Bender gives you the power and leverage to easily install, bend, & terminate cables in service panels, LB conduit bodies, switch gear, motor controls, wireways, and meter bases. 2-Piece Set: 18" Pro-Handle, (Knurled Dowels 2.7 lbs.) (Smooth Dowels 2.63 lbs.) w/15" Adapter Bar (Knurled Dowels 2.2 lbs.) (Smooth Dowels 2.1 lbs.)

Part Number	Description	
500-2	Bulldog Bender™ Original (500 MCM) 2-pc. Set, 18" Pro-Handle, w/15" Adapter Bar	



Standard Knurled Dowels are factory assembled, with optional Smooth dowels included with each tool. Bulldog Bender Pup is provided with Smooth Dowels only.



BULLDOG BENDER PUP 3-PIECE SET (4/0 AWG)

Bending large gauge electrical cables is difficult, especially in tight spaces. Bulldog Bender gives you the power and leverage to easily install, bend, & terminate cables in service panels, LB conduit bodies, switch gear, motor controls, wireways, and meter bases. 3-Piece Set: 18" Standard Handle (Knurled Dowels 2.6 lbs.) (Smooth Dowels 2.5 lbs.) & 18" Pro-Handle (Knurled Dowels 2.7 lbs.) (Smooth Dowels 2.6 lbs.) w/15" Adapter Bar (Knurled Dowels 2.2 lbs.) (Smooth Dowels 2.1 lbs.)

	Part Number	Description
A	500-3	Bulldog Bender™ Original (500 MCM) 3-pc. Set, 18" Std. Handle & 18" Pro-Handle w/15" Adapter Bar



BUL Bend Bend in se mete

BULLDOG BENDER BIG DADDY (750 MCM)

Bending large gauge electrical cables is difficult, especially in tight spaces. Bulldog Bender gives you the power and leverage to easily install, bend, & terminate cables in service panels, LB conduit bodies, switch gear, motor controls, wireways, and meter bases. 22" Standard Handle (Knurled Dowels 3.2 lbs.) (Smooth Dowels 3.1 lbs)

Part Number	Description
750H	Bulldog Bender™ Big Daddy (750 MCM), 22" Standard Handle



Standard Knurled Dowels are factory assembled, with optional Smooth dowels included with each tool. Bulldog Bender Pup is provided with Smooth Dowels only.



BULLDOG BENDER BIG DADDY PRO 2-PIECE SET (750 MCM)

Bending large gauge electrical cables is difficult, especially in tight spaces. Bulldog Bender gives you the power and leverage to easily install, bend, & terminate cables in service panels, LB conduit bodies, switch gear, motor controls, wireways, and meter bases. 2-Piece Set: 18" Pro-Handle (Knurled Dowels 3.4 lbs.) (Smooth Dowels 3.3 lbs.), w/15" Adapter Bar (Knurled Dowels 2.3 lbs.) (Smooth Dowels 2.2 lbs.)

Part Number	Description
750-2	Bulldog Bender™ Big Daddy (750 MCM) 2-pc. Set, 22" Pro-Handle w/15" Adapter Bar



Standard Knurled Dowels are factory assembled, with optional Smooth dowels included with each tool. Bulldog Bender Pup is provided with Smooth Dowels only.



BULLDOG BENDER BIG DADDY 3-PIECE SET (750 MCM)

Bending large gauge electrical cables is difficult, especially in tight spaces. Bulldog Bender gives you the power and leverage to easily install, bend, & terminate cables in service panels, LB conduit bodies, switch gear, motor controls, wireways, and meter bases. 3-Piece Set: 22" Standard Handle (Knurled Dowels 3.2 lbs.) (Smooth Dowels 3.1 lbs.) & 22" Pro-Handle (Knurled Dowels 3.4 lbs.) (Smooth Dowels 3.3 lbs.) (Smooth Dowels 3.3 lbs.) (Smooth Dowels 3.3 lbs.) (Smooth Dowels 2.2 lbs.)

Part Number	Description	
750	Bulldog Bender [™] Big Daddy (750 MCM) 3-pc. Set, 22" Std. Handle & 22" Pro-Handle w/15" Adapter Bar	



BULLD Bending Bender ein service meter ba

BULLDOG BENDER T-1000 (1000 MCM)

Bending large gauge electrical cables is difficult, especially in tight spaces. Bulldog Bender gives you the power and leverage to easily install, bend, & terminate cables in service panels, LB conduit bodies, switch gear, motor controls, wireways, and meter bases. 26" Standard Handle (Knurl Dowels 4.9 lbs.) (Smooth Dowels 4.7 lbs.)

Part Number	Description	
T-1000H	F-1000H Bulldog Bender™ T-1000 (1000 MCM), 26" Standard Handle	



Standard Knurled Dowels are factory assembled, with optional Smooth dowels included with each tool. Bulldog Bender Pup is provided with Smooth Dowels only.



BULLDOG BENDER T-1000 PRO 2-PIECE SET (1000 MCM)

Bending large gauge electrical cables is difficult, especially in tight spaces. Bulldog Bender gives you the power and leverage to easily install, bend, & terminate cables in service panels, LB conduit bodies, switch gear, motor controls, wireways, and meter bases. 2-Piece Set: 26" Pro-Handle (Knurled Dowels 3.4 lbs.) (Smooth Dowels 3.3 lbs.) w/18" Adapter Bar (Knurled Dowels 2.3 lbs.) (Smooth Dowels 2.2 lbs.)

Part Number Description		Description
	T-1000-2	Bulldog Bender™ T-1000 (1000 MCM) 2-pc. Set, 26" Pro-Handle w/18" Adapter Bar



Standard Knurled Dowels are factory assembled, with optional Smooth dowels included with each tool. Bulldog Bender Pup is provided with Smooth Dowels only.



BULLDOG BENDER T-1000 3-PIECE SET (1000 MCM)

Bending large gauge electrical cables is difficult, especially in tight spaces. Bull-dog Bender gives you the power and leverage to easily install, bend, & terminate cables in service panels, LB conduit bodies, switch gear, motor controls, wireways, and meter bases. 3-Piece Set: 26" Standard Handle (Knurl Dowels 3.2 lbs) (Smooth Dowels 3.1 lbs.) & 26" Pro-Handle (Knurl Dowels 3.4 lbs.) (Smooth Dowels 3.3 lbs.) w/18" Adapter Bar (Knurl Dowels 2.3 lbs.) (Smooth Dowels 2.2 lbs.)

Part Number	Description
T-1000	Bulldog Bender™ T-1000 (1000 MCM) 3-pc. Set, 26" Std. Handle & 26" Pro-Handle w/18" Adapter Bar











INSULATED TOOLS

MAXIMUM SAFETY.
MAXIMUM DURABILITY.

Meets The International Standard For Live Line Working IEC 60900:2018 and ASTM F1505





ITL has over half a century's worth of experience manufacturing quality insulated tools to the highest possible standard.

Our extensive range covers everything from spanners, torque tools and screwdrivers. We draw on our wealth of experience and expertise to make sure we supply customers with the longest lasting, hardest wearing and safest insulated tools in the world.

LIFETIME WARRANTY ON TOOL AND INSULATION.

The only manufacturer to insulate its tools with Nylon Thermoplastic. The strength of our insulation means it will never wear out, giving years of use from your tool which saves on cost and improves time effectiveness.

NYLON THERMOPLASTIC INJECTION MOLDING

Increases tool safety and durability. The unique Nylon Thermoplastic injection molding process leads to a stronger, tougher and safer insulated tool than a PVC dipped or sleeved product.

TOOL AND INSULATION BOND AS ONE

Every tool is 100% inspected - tested to 10,000 volts / rated to 1,000 volts and with stands temperature extremes from -40° F to 158° F (-40° C to 70° C)

INSULATED HAND TOOLS



JT-KT-00002

19 PC. Deluxe Utility Tool Kit

15 T C. Delake Othicy Tool Kit	
Part Number	Description
JT-SD-01860	1/8" x 3" Slotted Terminal Screwdriver
JT-SD-01890	3/16" x 6" Slotted Electrician Screwdriver
JT-SD-01920	1/4" x 6" Electricians Screwdriver
JT-SD-02010	No. 1 x 3" Phillips Screwdriver
JT-SD-02020	No. 2 x 4" Phillips Screwdriver
JT-PL-00021	8" Combination Pliers
JT-PL-00051	6-1/4" Long Nose Pliers
JT-PC-00120	8" Cable Cutter
JT-PC-00101	6-1/4" Side Cutting Pliers
JT-PL-00141	10" Pump Piers
JT-CT-01830	Cable Jointers Coring Knife
JT-WA-03000	8" Adjustable Wrench
JT-WS- 00441	1/2" Open-End Wrench
JT-WS-00460	11/16" Open-End Wrench
JT-WS-00470	3/4" Open-End Wrench
JT-WS-00490	1" Open-End Wrench
JT-WB-01135	1/2" Box Wrench
JT-WB-01137	11/16" Box Wrench
JT-WB-01140	3/4" Box Wrench
JT-TC-03200	Tool Case (Orange)



JT-KT-00008

12 PC. General Utility Tool Kit in Case

Part Number	Description
JT-PL-00045	9-1/2" Lineman Pliers
JT-PL-00061	8" Long Nose Pliers
JT-PC-00115	7-1/2" Side-Cutting Pliers
JT-SD-01930	1/4" x 4" Slotted Engineers Screwdriver
JT-SD-01940	5/16" x 6" Slotted Engineers Screwdriver
JT-SD-01970	3/8" x 10" Slotted Engineers Screwdriver
JT-TC-03200	Tool Case
JT-SD-02010	No. 1 x 3" Phillips Screwdriver
JT-SD-02020	No. 2 x 4" Phillips Screwdriver
JT-SD-02030	No. 3 x 6" Phillips Screwdriver
JT-PL-00141	10" Pump Pliers
JT-PC-00125	9" Cable Cutter
JT-CT-01830	Cable Jointers Coring Knife



Insulated Tools Are Provided In Display-Ready Packaging



JT-KT-00004 13 PC. Electrician's Kit

Part Number	Description
JT-PL-00045	9-1/2" Lineman Pliers
JT-PL-00061	8" Long Nose Pliers
JT-PC-00111	7" Side Cutting Pliers
JT-PC-00125	9" Cable Cutter
JT-PL-0 0141	10" Pump Pliers
JT-ND-02305	3/16" Nut Driver
JT-ND-02315	1/4" Nut Driver
JT-SD-01860	3/16" x 4" Slotted Terminal Screwdriver
JT-SD-01870	3/16" x 4" Slotted Terminal Screwdriver
JT-SD-01920	1/4" x 6" Slotted Electricians Screwdriver
JT-SD-02020	No. 2 x 4" Phillips Screwdriver
JT-CT-01830	Cable Jointers Coring Knife
JT-TC-03197	Electrician Tool Pouch
JT-ND-02331	5/16" Nut Driver



JT-KT-00029

29 PC. Maintenance Tool Kit

Part Number	Description	
PLIERS		
JT-PL-00021	8" Combination Pliers	
JT-PL-00061	8" Long-Nose Pliers	
JT-PC-00101	6-1/4" Side Cutting Pliers	
OPEN-END WRENCHES		
JT-WS-00430	3/8" Open-End Wrench	
JT-WS-00440	7/16" Open-End Wrench	
JT-WS-00441	1/2" Open-End Wrench	
JT-WS-00450	9/16" Open-End Wrench	
JT-WS-00455	5/8" Open-End Wrench	
JT-WS-00460	11/16" Open-End Wrench	
JT-WS-00470	3/4" Open-End Wrench	
JT-SR-01750	1/2" Ratchet Wrench	
SCREWDRIVERS		
JT-SD-01860	1/8" x 3" Slotted Terminal Screwdriver	
JT-SD-01875	5/32" x 3" Slotted Electrician Screwdriver	
JT-SD-01890	5/16" x 6" Slotted Engineer Screwdriver	
JT-SD-01940	5/16" x 6" Slotted Engineer Screwdriver	
JT-SD-02010	No. 1 x 3" Phillips Screwdriver	
JT-SD-02020	No. 2 x 4" Phillips Screwdriver	

Part Number	Description			
1/2" DRIVE SOCKETS				
JT-SK-01570	3/8" Socket			
JT-SK-01580	7/16" Socket			
JT-SK-01590	1/2" Socket			
JT-SK-01600	9/16" Socket			
JT-SK-01610	5/8" Socket			
JT-SK-01630	3/4" Socket			
JT-SK-02771	3/16" Hex Key Socket			
JT-SK-02772	1/4" Hex Key Socket			
JT-SK-01760	5" Socket Extension			
JT-SK-01770	10" Socket Extension			
JT-CT-01830	Cable Jointers Coring Knife			
JT-TC-03209	Tool Case			



JT-KT-00007 29 PC. Maintenance Tool Kit - Metric

Part Number	Description
PLIERS	
JT-PL-00021	8" Combination Pliers
JT-PC-00101	6-1/4" Side Cutting Nippers
JT-PL-00061	8" Long Nose Pliers
OPEN-END WRENCHES	
JT-WS-00280	10mm Open-End Wrench
JT-WS-00290	11mm Open-End Wrench
JT-WS-00295	12mm Open-End Wrench
JT-WS-00300	13mm Open-End Wrench
JT-WS-00310	14mm Open-End Wrench
JT-WS-00340	17mm Open-End Wrench
JT-WS-00360	19mm Open-End Wrench
JT-SR-01750	1/2" Ratchet Wrench
SCREWDRIVERS	
JT-SD-01860	1/8" x 3" Terminal Screwdriver
JT-SD-01875	5/32" x 3" Electrician Screwdriver
JT-SD-01890	3/16 " x 6" Slotted Screwdriver
JT-SD-01940	5/16" x 6" Slotted Screwdriver
JT-SD-02010	JT-SD-02010
JT-SD-02020	JT-SD-02020

Part Number	Description		
1/2" DRIVE SOCKETS			
JT-SK-01350	10mm Socket		
JT-SK-01360	11mm Socket		
JT-SK-01370	12mm Socket		
JT-SK-01380	JT-SK-01380		
JT-SK-01390	14mm Socket		
JT-SK-01420	19mm Socket		
JT-SK-01440	17mm Socket		
Hex Sockets			
JT-SK-02763	5mm Hex Key Socket		
JT-SK-02764	6mm Hex Key Socket		
JT-CT-01830	Cable Jointers Coring Knife		
JT-TC-03209	Tool Case		
JT-SK-01760	5" Socket Extension		
JT-SK-01770	10" Socket Extension		
JT-CT-01830	Cable Jointers Coring Knife		
JT-TC-03209	Tool Case		



JT-KT-00001 9 PC. Basic Electrician's Kit

J I O. Dasic Electrician 5 Rit		
Part Number	Description	
JT-PL-00045	9-1/2" Lineman Pliers	
JT-PL-00061	8" Long Nose Pliers	
JT-PC-00111	7" Side Cutting Pliers	
JT-PL-00170	6-1/4" Wire Stripper	
JT-SD-01880	3/16" x 3" Electrician Screwdriver	
JT-SD-01890	3/16" x 6" Electrician Screwdriver	
JT-SD-01920	1/4" x 6" Electrician Screwdriver	
JT-SD-02010	No. 1 x 3" Phillips Screwdriver	
JT-SD-02020	No. 2 x 4" Phillips Screwdriver	



Insulated Tools Are Provided In Display-Ready Packaging



JT-KT-00003

9 PC. Basic Electrician's Robertson Kit

Part Number	Description
JT-PL-00045	9-1/2" Lineman Pliers
JT-PL-00061	8" Long Nose Pliers
JT-PC-00111	7" Side Cutting Pliers
JT-PL-00170	6-1/4" Wire Stripper
JT-SD-01880	3/16" x 3" Electrician Screwdriver
JT-SD-01890	3/16" x 6" Electrician Screwdriver
JT-SD-01920	1/4" x 6" Electrician Screwdriver
JT-SD-02024	No. 1 x 4" Robertson Screwdriver
JT-SD-02025	No. 2 x 4" Robertson Screwdriver



JT-KT-00005

9 PC. General Purpose Tool Kit

Part Number	Description
JT-PL-00021	8" Combination Pliers
JT-PL-00051	6-1/4" Long-Nose Pliers
JT-PC-00120	8" Cable Cutter
JT-WA-03000	8" Adjustable Wrench
JT-TC-03191	12-Pocket Tool Roll
JT-SD-01860	1/8" x 3" Slotted Terminal Screwdriver
JT-SD-01890	3/16" x 6" Slotted Electrician Screwdriver
JT-SD-01920	1/4" x 6" Slotted Electrician Screwdriver
JT-SD-02010	No. 1 x 3" Phillips Screwdriver
JT-SD-02020	No. 2 x 4" Phillips Screwdriver



-		
Part Number	Description	
JT-PL-00011	6-1/4" Combination Pliers	



Part Number	Description
JT-PL-00021	8" Combination Pliers



Part Number	Description
JT-PL-00031	10" Combination Pliers



Part Number	Description
JT-PL-00045	9-1/2" Lineman Pliers



Part Number	Description
JT-PL-00051	8" Long-Nose Pliers









Part Number	Description
JT-PL-00141	10" Pump Pliers



Part Number	Description
JT-PL-00151	12" Pump Pliers



Insulated Tools Are Provided In Display-Ready Packaging



Part Number	Description
JT-PL-00161	16" Pump Pliers



Part Number	Description
JT-PC-00101	6-1/4" Combination Pliers



Part Number	Description
JT-PC-00111	7" Side-Cutting Pliers



Part Number	Description
JT-PC-00115	7-1/2" Side-Cutting Pliers



Part Number	Description
JT-PC-00120	1 AWG Strandard Wires Dia. 4 AWG Solid Wires Dia.
8" Cable Croppers for Aluminium and Copper Cables only	



Part Number	Description
JT-PC-00125	2 AWG Strandard Wires Dia. 1 AWG Solid Wires Dia.
9" Cable Croppers for Aluminium and Copper Cables only	



Part Number	Description
JT-PC-00130	3 AWG Strandard Wires Dia. 0 AWG Solid Wires Dia.

0 AWG Solid Wires Dia.

10" Cable Croppers for Aluminium and Copper Cables only



Part Number	Description
JT-PL-00170	6-1/4" Wire Stripper



Part Number	Description
JT-PL-00174	20-10 AWG Solid 22-12 AWG Stranded



ADJUSTABLE WRENCHES

Part Number	Description
JT-WA-03000	8" Adjustable Wrench
JT-WA-03005	10" Adjustable Wrench
JT-WA-03010	12" Adjustable Wrench
JT-WA-03020	15" Adjustable Wrench



ADJUSTABLE WRENCH

Part Number	Description
JT-WA-03015	12" Adjustable Hammerhead



GENERAL PURPOSE OPEN-END WRENCHES

	Part Number	Description
	JT-WS-00810	3/8" General Purpose
	JT-WS-00830	1/2" General Purpose
	JT-WS-00850	5/8" General Purpose
	JT-WS-00870	3/4" General Purpose



OPEN-END WRENCHES - STANDARD

Part Number	Description
JT-WS-00430	3/8" Open-End
JT-WS-00440	7/16" Open-End
JT-WS-00441	1/2" Open-End
JT-WS-00450	9/16" Open-End
JT-WS-00455	5/8" Open-End
JT-WS-00460	11/16" Open-End
JT-WS-00470	3/4" Open-End
JT-WS-00480	7/8" Open-End
JT-WS-00490	1" Open-End



OPEN-END WRENCHES - METRIC

Part Number	Description
JT-WS-00280	10mm Open-End Wrench
JT-WS-00290	11mm Open-End Wrench
JT-WS-00295	12mm Open-End Wrench
JT-WS-00300	13mm Open-End Wrench
JT-WS-00310	14mm Open-End Wrench
JT-WS-00340	17mm Open-End Wrench
JT-WS-00360	19mm Open-End Wrench
JT-WS-00410	24mm Open-End Wrench



RATCHETING BOX WRENCHES - STANDARD

Part Number	Description
JT-WR-07050	3/8" Ratcheting Box Wrench
JT-WR-07052	1/2" Ratcheting Box Wrench
JT-WR-07053	9/16" Ratcheting Box Wrench
JT-WR-07054	5/8" Ratcheting Box Wrench
JT-WR-07056	3/4" Ratcheting Box Wrench
JT-WR-07058	7/8" Ratcheting Box Wrench
JT-WR-07059	1" Ratcheting Box Wrench



OPEN-END WRENCHES - METRIC

Part Number	Description
JT-WR-07010	10mm Ratcheting Box Wrench
JT-WR-07013	13mm Ratcheting Box Wrench
JT-WR-07017	17mm Ratcheting Box Wrench
JT-WR-07019	19mm Ratcheting Box Wrench



BOX WRENCHES

Part Number	Description
JT-WB-01135	1/2" Box Wrench
JT-WB-01137	11/16" Box Wrench
JT-WB-01140	3/4" Box Wrench



UNIVERSAL HOLDING TOOL

Part Number	Description
JT-WA-03116	Adjustable Universal Holding Tool



Insulated Tools Are Provided In Display-Ready Packaging



JT-KT-00023 12 PC. Deep Socket Set - 1/2" Drive

Part Number	Description
JT-SK-01591	1/2" Deep Socket
JT-SK-01601	9/16" Deep Socket
JT-SK-01611	5/8" Deep Socket
JT-SK-01621	11/16" Deep Socket
JT-SK-01631	3/4" Deep Socket
JT-SK-01641	13/16" Deep Socket
JT-SK-01651	7/8" Deep Socket
JT-SK-01661	15/16" Deep Socket
JT-SK-01671	1" Deep Socket
JT-SR-01750	Ratchet Wrench 1/2" Drive
JT-SK-01760	5" Socket Extension
JT-SK-01770	10" Socket Extension
JT-TC-03223	Tool Case





JT-KT-03105

12 PC. Combination Socket Set - 3/8" Drive

in it of combination cock		
Description		
8mm Socket		
10mm Socket		
13mm Socket		
17mm Socket		
19mm Socket		
20mm Socket		

COCC S/O DIIVE		
Part Number	Description	
JT-SK-01723	3/8" Socket	
JT-SK-01725	1/2" Socket	
JT-SK-01739	3/4" Socket	
JT-SK-01744	7/8" Socket	
JT-SR-01780	Ratchet Wrench 3/8" Drive	
JT-SK-01791	5" Extension Bar	
JT-TC-03215	Tool Case	

JT-KT-03100

12 PC. Combination Socket Set - 1/2" Drive

Part Number	Description
JT-SK-01330	8mm Socket
JT-SK-01350	10mm Socket
JT-SK-01380	13mm Socket
JT-SK-01420	17mm Socket
JT-SK-01440	19mm Socket
JT-SK-01450	20mm Socket

COEL - I/Z DIIVE		
Part Number	Description	
JT-SK-01570	3/8" Socket	
JT-SK-01590	1/2" Socket	
JT-SK-01630	3/4" Socket	
JT-SK-01650	7/8" Socket	
JT-SR-01750	Ratchet Wrench 1/2" Drive	
JT-SK-01760	5" Extension Bar	
JT-TC-03202	Tool Case	



JT-KT-03095 19 PC. Combination Socket Set - 1/2" Drive

Part Number	Description
JT-SK-01330	8mm Socket
JT-SK-01350	10mm Socket
JT-SK-01380	13mm Socket
JT-SK-01420	17mm Socket
JT-SK-01440	19mm Socket
JT-SK-01450	20mm Socket
JT-SK-01470	22mm Socket
JT-SK-01500	25mm Socket
JT-SK-01570	3/8" Socket
JT-SK-01580	7/16" Socket
JT-SK-01590	1/2" Socket
JT-SK-01600	9/16" Socket
JT-SK-01630	3/4" Socket
JT-SK-01650	7/8" Socket
JT-SK-01660	15/16" Socket
JT-SK-01670	1" Socket
JT-SR-01750	Ratchet Wrench - 1/2" Drive
JT-SK-01760	5" Extension Bar
JT-SK-01770	10" Extension Bar
JT-TC-03201	Tool Case



JT-KT-00025 7 PC. Torque Set - 1/2" Drive

7 C. Torque Set - 1/2 Drive		
Part Number	Description	
JT-SK-01571	3/8" Deep Socket	
JT-SK-01581	7/16" Deep Socket	
JT-SK-01591	1/2" Deep Socket	
JT-SK-01611	5/8" Deep Socket	
JT-SK-01631	3/4" Socket	
JT-SK-01671	1" Deep Socket	
JT-ST-01745	Torque Wrench - 1/2" Drive	
JT-TC-04005	Tool Case	



Insulated Tools Are Provided In Display-Ready Packaging



RATCHET WRENCHES

Part Number	Description
JT-SR-01775	Ratchet Wrench 1/4"
JT-SR-01750	Ratchet Wrench 1/2" Drive
JT-SR-01780	Ratchet Wrench 3/8" Drive



TORQUE WRENCHES

Part Number	Description
JT-ST-01745	Torque Wrench 1/2" Drive Torque Range 12 – 60 N-m (metric) 8 – 44 ft-lbs. (standard)
JT-ST-01785	Torque Wrench 3/8" Drive Torque Range 12 – 60 N-m (metric) 8 – 44 ft-lbs. (standard)
JT-ST-01711	Torque Wrench (Short) 3/8" Drive, 5-25 Nm)



SOCKET EXTENSIONS - 1/4" DRIVE

Part Number	Description
JT-SK-01776	2" x 1/4" Drive
JT-SK-01778	6" x 1/4" Drive



SOCKET EXTENSIONS - 1/2" DRIVE

Part Number	Description
JT-SK-01760	5" x 1/2" Drive
JT-SK-01770	10" x 1/2" Drive



SOCKET EXTENSIONS - 3/8" DRIVE

Part Number	Description
JT-SK-01790	3" x 3/8" Drive
JT-SK-01791	5" x 3/8" Drive
JT-SK-01792	10" x 3/8" Drive



SOCKET ADAPTER

Part Number	Description
JT-SK-04401	Socket Adapter 3/8" Female x 1/2" Male



HEX SOCKETS - 1/2" DRIVE (STANDARD)

HEA SOCKETS - 1/2 DRIVE (STANDARD)	
Part Number	Description
JT-SK-02771	Hex Key Socket 3/16" x 1/2" Drive
JT-SK-02772	Hex Key Socket 1/4" x 1/2" Drive
JT-SK-02773	Hex Key Socket 5/16" x 1/2" Drive
JT-SK-02774	Hex Key Socket 3/8" x 1/2" Drive
JT-SK-02775	Hex Key Socket 7/16" x 1/2" Drive
JT-SK-02776	Hex Key Socket 1/2" x 1/2" Drive
JT-SK-02777	Hex Key Socket 9/16" x 1/2" Drive
JT-SK-02778	Hex Key Socket 5/8" x 1/2" Drive
JT-SK-02779	Hex Key Socket 3/4" x 1/2" Drive

HEX SOCKETS - 1/2" DRIVE (METRIC)

Part Number	Description
JT-SK-02763	Hex Key Socket 5mm x 1/2" Drive
JT-SK-02764	Hex Key Socket 6mm x 1/2" Drive

HEX SOCKETS - 3/8" DRIVE (STANDARD)

JT-SK-02753	Hex Key Socket 1/8" x 3/8" Drive
JT-SK-02754	Hex Key Socket 1/4" x 3/8" Drive
JT-SK-02755	Hex Key Socket 5/16" x 3/8" Drive
JT-SK-02756	Hex Key Socket 3/8" x 3/8" Drive
JT-SK-02757	Hex Key Socket 1/2" x 3/8" Drive



SOCKETS - 3/8" DRIVE Standard

Part Number	Description
JT-SK-01723	Socket 3/8" x 3/8" Drive
JT-SK-01724	Socket 7/16" x 3/8" Drive
JT-SK-01725	Socket 1/2" x 3/8" Drive
JT-SK-01726	Socket 9/16" x 3/8" Drive
JT-SK-01727	Socket 5/8" x 3/8" Drive
JT-SK-01731	Socket 11/16" x 3/8" Drive
JT-SK-01739	Socket 3/4" x 3/8" Drive
JT-SK-01743	Socket 13/16" x 3/8" Drive
JT-SK-01744	Socket 7/8" x 3/8" Drive

Metric

JT-SK-01716	Socket 8mm x 3/8" Drive
JT-SK-01718	Socket 10mm x 3/8" Drive
JT-SK-01720	Socket 13mm x 3/8" Drive
JT-SK-01730	Socket 17mm x 3/8" Drive
JT-SK-01740	Socket 19mm x 3/8" Drive
JT-SK-01741	Socket 20mm x 3/8" Drive

SOCKETS - 1/4" DRIVE Metric

Menic		
Socket 4mm x 1/4" Drive		
Socket 5mm x 1/4" Drive		
Socket 6mm x 1/4" Drive		
Socket 7mm x 1/4" Drive		
Socket 8mm x 1/4" Drive		
Socket 9mm x 1/4" Drive		
Socket 10mm x 1/4" Drive		
Socket 11mm x 1/4" Drive		
Socket 12mm x 1/4" Drive		
Socket 13mm x 1/4" Drive		
Socket 14mm x 1/4" Drive		

SOCKETS - 1/2" DRIVE Standard

Part Number	Description
JT-SK-01565	Socket 5/16" x 1/2" Drive
JT-SK-01570	Socket 3/8" x 1/2" Drive
JT-SK-01580	Socket 7/16" x 1/2" Drive
JT-SK-01590	Socket 1/2" x 1/2" Drive
JT-SK-01600	Socket 9/16" x 1/2" Drive
JT-SK-01610	Socket 5/8" x 1/2" Drive
JT-SK-01620	Socket 11/16" x 1/2" Drive
JT-SK-01630	Socket 3/4" x 1/2" Drive
JT-SK-01640	Socket 13/16" x 1/2" Drive
JT-SK-01650	Socket 7/8" x 1/2" Drive
JT-SK-01660	Socket 15/16" x 1/2" Drive
JT-SK-01670	Socket 1" x 1/2" Drive

Standard - Deep Socket

JT-SK-01571	Socket, Deep, 3/8" x 1/2" Drive
JT-SK-01581	Socket Deep, 7/16" x 1/2" Drive
JT-SK-01591	Socket Deep, 1/2" x 1/2" Drive
JT-SK-01601	Socket Deep, 9/16" x 1/2" Drive
JT-SK-01611	Socket Deep, 5/8" x 1/2" Drive
JT-SK-01621	Socket Deep, 11/16" x 1/2" Drive
JT-SK-01631	Socket Deep, 3/4" x 1/2" Drive
JT-SK-01641	Socket Deep, 13/16" x 1/2" Drive
JT-SK-01651	Socket Deep, 7/8" x 1/2" Drive
JT-SK-01661	Socket Deep, 15/16" x 1/2" Drive
JT-SK-01671	Socket Deep, 1" x 1/2" Drive

Metric

Part Number	Description	
JT-SK-01330	Socket 8mm x 1/2" Drive	
JT-SK-01350	Socket 10mm x 1/2" Drive	
JT-SK-01360	Socket 11mm x 1/2" Drive	
JT-SK-01370	Socket 12mm x 1/2" Drive	
JT-SK-01380	Socket 13mm x 1/2" Drive	
JT-SK-01390	Socket 14mm x 1/2" Drive	
JT-SK-01420	Socket 17mm x 1/2" Drive	
JT-SK-01440	Socket 19mm x 1/2" Drive	
JT-SK-01450	Socket 20mm x 1/2" Drive	
JT-SK-01470	Socket 22mm x 1/2" Drive	
JT-SK-01500	Socket 25mm x 1/2" Drive	

Metric - Deep Socket

-	
JT-SK-01381	Socket Deep, 13mm x 1/2" Drive
JT-SK-01385	Socket Deep, 16mm x 1/2" Drive
JT-SK-01421	Socket Deep, 17mm x 1/2" Drive
JT-SK-01425	Socket Deep, 18mm x 1/2" Drive
JT-SK-01495	Socket Deep, 28mm x 1/2" Drive



Insulated Tools Are Provided In Display-Ready Packaging



JT-KT-00010

9 PC. Screwdriver Set

Part Number	Description
JT-SD-01880	3/16" x 3" Slotted Electrician Screwdriver 3/16"
JT-SD-01890	3/16" x 6" Slotted Electrician Screwdriver 3/16"
JT-SD-01910	3/16" x 8" Slotted Electrician Screwdriver 3/16"
JT-SD-02010	No. 1 x 3" Phillips Screwdriver
JT-SD-02020	No. 2 x 4" Phillips Screwdriver
JT-SD-02030	No. 3 x 6" Phillips Screwdriver
JT-SD-01930	1/4" x 4" Slotted Engineer Screwdriver
JT-SD-01940	5/16" x 6" Slotted Engineer Screwdriver
JT-SD-01970	3/8" x 10" Slotted Engineer Screwdriver



JT-KT-02150

4-PC. Screwdriver Set

Part Number	Description	
JT-SD-01860	1/8" x 3" Slotted Terminal Screwdriver	
JT-SD-01880	3/16" x 3" Slotted Electrician Screwdriver	
JT-SD-01890	3/16" x 6" Slotted Electrician Screwdriver	
JT-SD-02020	No. 2 x 4" Phillips Screwdriver	



JT-KT-02150

4-PC. Screwdriver Set

Part Number	Description
JT-SD-01860	1/8" x 3" Slotted Terminal Screwdriver
JT-SD-01880	3/16" x 3" Slotted Electrician Screwdriver
JT-SD-01890	3/16" x 6" Slotted Electrician Screwdriver
JT-SD-02020	No. 2 x 4" Phillips Screwdriver

SLOTTED SCREWDRIVERS

Terminal Screwdriver

Part Number	Description	
JT-SD-01860	1/8" x 3" Slotted Terminal Screwdriver	
JT-SD-01870	1/8" x 4" Slotted Terminal Screwdriver	

Electrician Screwdriver

JT-SD-01875	5/32" x 3" Slotted Electrician Screwdriver
JT-SD-01877	3/16" x 6" x 0.03" Slotted Electrician Screwdriver
JT-SD-01880	3/16" x 3" Slotted Electrician Screwdriver
JT-SD-01890	3/16" x 6" x.0.04" Slotted Electrician Screwdriver
JT-SD-01910	3/16" x 8" Slotted Electrician Screwdriver
JT-SD-01920	1/4" x 6" Slotted Electrician Screwdriver

Low Profile Electrician Screwdriver

JT-SD-01900	3/16" x 6" Slotted Low Profile Electrician Screwdriver	
JT-SD-01950	5/16" x 6" Slotted Low Profile Electrician Screwdriver	

Engineer Screwdriver

JT-SD-01930	1/4" x 4" Slotted Engineer Screwdriver
JT-SD-01940	5/16" x 6" Slotted Engineer Screwdriver
JT-SD-01960	3/8" x 8" Slotted Engineer Screwdriver
JT-SD-01970	3/8" x 10" Slotted Engineer Screwdriver



Low Profile Slotted Screwdriver has smooth design from blade to shaft to avoid "catching."



PHILLIPS SCREWDRIVERS

Part Number	Description	
JT-SD-02005	No. 0 x 3" Phillips Screwdriver	
JT-SD-02010	No. 1 x 3" Phillips Screwdriver	
JT-SD-02020	No. 2 x 4" Phillips Screwdriver	
JT-SD-02030	No. 3 x 6" Phillips Screwdriver	



POZIDRIVE SCREWDRIVERS

Part Number	Description	
JT-SD-01979	No. 0 x 3" Pozidrive Screwdriver	
JT-SD-01980	No. 1 x 5" Pozidrive Screwdriver	
JT-SD-01990	No. 2 x 6" Pozidrive Screwdriver	



Insulated Tools Are Provided In Display-Ready Packaging



JT-KT-02295

7-Piece Nut Driver Set

Part Number	Description
JT-ND-02305	3/16" Nut Driver
JT-ND-02315	1/4" Nut Driver
JT-ND-02331	5/16" Nut Driver
JT-ND-02332	11/32" Nut Driver

Part Number	Description
JT-ND-02333	3/8" Nut Driver
JT-ND-02334	7/16" Nut Driver
JT-ND-02335	1/2" Nut Driver

Nut Drivers - Standard

Nul Drivers - Staridard		
JT-ND-02305	3/16" Nut Driver	
JT-ND-02315	1/4" Nut Driver	
JT-ND-02331	5/16" Nut Driver	
JT-ND-02332	11/32" Nut Driver	
JT-ND-02333	3/8" Nut Driver	
JT-ND-02334	7/16" Nut Driver	
JT-ND-02335	1/2" Nut Driver	
JT-ND-02336	9/16" Nut Driver	
JT-ND-02337	5/8" Nut Driver	

Nut Drivers - Metric

JT-ND-02310	5mm Nut Driver	
JT-ND-02320	6mm Nut Driver	
JT-ND-02250 7mm Nut Driver		
JT-ND-02280	8mm Nut Driver	
JT-ND-02290	10mm Nut Driver	
JT-ND-02341	13mm Nut Driver	



JT-KT-02665 6-Piece T-Handle Hex Key Set - Metric

Part Number	Description	
JT-HK-02670	3mm Hex Key	
JT-HK-02680	4mm Hex Key	
JT-HK-02690	5mm Hex Key	
JT-HK-02700	6mm Hex Key	
JT-HK-02746	8mm Hex Key	
JT-HK-02761	10mm Hex Key	

JT-KT-02667 6-Piece T-Handle Hex Key Set - Standard

	,		
	Part Number	ber Description	
	JT-HK-02710	1/8" Hex Key	
	JT-HK-02680	5/32" Hex Key	
	JT-HK-02730	3/16" Hex Key	
	JT-HK-02740	1/4" Hex Key	
JT-HK-02742 JT-HK-02743		5/16" Hex Key	
		3/8" Hex Key	




T-Handle Hex Key - Standard

JT-HK-02710	1/8" Hex Key"	
JT-HK-02680	5/32" Hex Key	
JT-HK-02730	3/16" Hex Key	
JT-HK-02735	3/16" Hex Key Short	
JT-HK-02740	1/4" Hex Key	
JT-HK-02742	5/16" Hex Key	
JT-HK-02743	3/8" Hex Key	
JT-HK-02745	1/2" Hex Key	

T-Handle Hex Key - Metric

ridiale rick key - Medic				
JT-HK-02670 3mm Hex Key				
JT-HK-02680	4mm Hex Key			
JT-HK-02690	5mm Hex Key			
JT-HK-02700	6mm Hex Key			
JT-HK-02746	8mm Hex Key			
JT-HK-02761	HK-02761 10mm Hex Key			





CABLE KNIFE

Part Number	Description	
JT-CT-01830	Cable Jointers Knife	

HACKSAW

Part Number	Description	
JT-CT-01820	12" Hacksaw	
JT-CT-01821	12" x 24 TPI Hacksaw Blades (10 pack)	
JT-CT-01822	12" x 14 TPI Hacksaw Blades (10 pack)	





MINI HACKSAW

	Part Number	Description
	JT-CT-01810	6" Mini Hacksaw
JT-CT-01812		6" Mini Hacksaw Blades (12 pack)

LONG ARM CUTTERS

Part Number	Description	
JT-PC-00136	26" Long Arm Cable Cutter	





MIRROR

Part Number	Description	
JT-CT-01850	Inspection Mirror	

TREE PRUNER

Part Number	Description
JT-PC-00172	Tree Pruner, 26"



Insulated Tools Are Provided In Display-Ready Packaging













For over 25 years, Jameson continues to provide an extensive lighting solution to meet the diverse application needs of our customers. As a trusted and reliable source, we provide quality lighting products and a customer-friendly resource in the design and execution for lighting applications.

We strive to provide the best in high quality LED work lights that are flicker-free, and doesn't interfere with tone test equipment. This technology provides intense light in small spaces for electrical and telecommunication rooms, manholes, garages, and other application needs.

In early 2000 our team of engineers revolutionized expeditionary lighting by creating stringable shelter lights that are lightweight, energy efficient, portable and offer easy set up. Our lights are actively used for a wide variety of missions in all branches of the US Military and are an integral part of various shelter programs.

Our LED equipment lights are designed to withstand extreme environmental conditions and operational applications found in mining and construction.

LIGHTING - PORTABLE WORK LIGHTS

STUBBY® FLUORESCENT WORK LIGHTS

Compact, High Intensity Lighting For Small Work Spaces

Durability and Performance in Twin Lamp Design

- · Twin tube compact fluorescent lamp
- Flexible hanging hook for mounting convenience
- Shock-absorbing handle and end cap combined with shatter-proof tube shield for rugged durability
- IP44 splash proof enclosure
- Damp Location rated
- Service grade rubber cord for ultimate durability and oil resistance
- Remains flexible in cold temps

Electronic Ballast Technology

- Eliminates cumbersome starter canisters
- · Reduces heat output
- · Flicker free lighting
- Does not interfere with tone test equipment
- · Rapid start

STUBBY® 110 VOLT FLUORESCENT LIGHTS

10 Watts - 15"


Part Number	Rated Lamp Power	Cord Length	Weight (Lbs)
31-1325E	13 Watts	25 ft.	2.7
31-1350E	13 Watts	50 ft.	4.5
31-2425E	24 Watts	25 ft.	3.6
31-2450E	24 Watts	50 ft.	5.3
31-3625E	36 Watts	25 ft.	4.0
31-3650E	36 Watts	50 ft.	5.8
31-5025E	50 Watts	25 ft.	4.2
31-5050E	50 Watts	50 ft.	5.9
Available with 25 ft. or 50 ft. Power Cord. NEMA 1-15 plug			





Two large, flexible hanging hooks on 24, 36 and 50 watt lights. One hanging hook on 13 watt light.

STUBBY® LED WORK LIGHTS Long-Life LED Lighting In A Compact Design



- Compact design for small workspaces
- Flexible hanging hook for convenience
- Shock-absorbing handle and end cap combined with shatterproof tube shield for rugged durability

STUBBY® 120-240 VAC LED LIGHTS

Part Number	Rated Lamp Power	Cord Length	Weight (Lbs)				
31-825-LED	10 Watts	25 ft.	5.0				
31-825-LED-R*	10 Watts	25 ft.	5.5				
31-850-LED	10 Watts	50 ft.	6.0				
Available with 25 ft. or 50 ft. Power Cord							

^{*} Items Ending In "-R" Are Provided In Display-Ready Packaging

LIGHTING - PORTABLE WORK LIGHTS

STUBBY® 8 WATT LED 12 VDC (5-14 VDC Range)

Ideal for emergency applications when power is not available; equipment rooms or basements where water is a concern; utility and supervisor vehicles. 10 ft. coil cord and plug adapter.

· Operates off battery pack or direct 12 Volt power source

Part Number	Rated Lamp Power	Cord Length	Weight (Lbs)	
31-12VDC-LED	12 Volt (Light Only)	10 ft.	6.9	



HANDI-LIGHT® FLUORESCENT WORK LIGHTS

Bright, Durable Workspace Lighting

Convenient Lighting in Single Lamp Design

- Single fluorescent lamp
- Two flexible hanging hooks for convenience
- Shock-absorbing handle and end cap combined with shatter-proof tube shield for rugged durability
- IP44 splash proof enclosure and damp location rated
- Service grade rubber cord for ultimate durability and oil resistance. Remains flexible in cold temperatures.
- 110 Volt

Electronic Ballast Technology

- Eliminates cumbersome starter canisters
- · Reduces heat output
- · Flicker free lighting
- · Does not interfere with tone test equipment
- · Rapid start







15 Watts - 26"





HANDI-LIGHT® 110 VOLT FLUORESCENT LIGHT

Part Number	Rated Lamp Power	Cord Length	Weight (Lbs)							
30-1525E	15 Watts	25 ft.	3.3							
30-1550E	15 Watts	50 ft.	5.1							
30-3025E	30 Watts	25 ft.	4.1							
30-3050E	30 Watts	6.0								
30-4025E	40 Watts	25 ft.	6.6							
30-4050E	40 Watts	50 ft.	8.7							
Available with 25 ft. or 50 ft. Power Cord										

LIGHTING - PORTABLE WORK LIGHTS

HANDI-LIGHT® LED WORK LIGHTS Long-Life LED Lighting

Portable Work Light with LED Durability

- $\bullet\,$ LED technology for longer life and reduced power consumption
- Two flexible hanging hooks for convenience
- Shock-absorbing handle and end cap combined with shatterproof tube shield for rugged durability
- · High color rendering index makes identifying wire colors easier

LED Lamp Specifications

- Raw lumens: 1136 lumens
- Color temp: 5000K
- RoHS compliant
- Lamp rated life: 50,000 hours (L70)
- No glass
- · Mercury free
- 100% recyclable
- Equivalent light output of 17 Watts, T8 fluorescent
- Suitable for damp locations
- CRI of 85

Light Specifications

- Voltage input 120 to 277 VAC
- Amp draw .08A at 120 VAC



9 Watts - 31"

Part Number	Rated Lamp Power	Cord Length	Weight (Lbs)
30-925E-LED	9 Watts	25 ft.	3.3
30-925E-LED-R*	9 Watts	25 ft.	3.5
30-950E-LED	9 Watts	50 ft.	4.8

ACCESSORIES FOR STUBBY® & HANDI-LIGHT®



Part Number	Description					
29-01 12 Volt DC Inverter						
Operates light off vehicle's 12 Volt DC power source 75 - 100 Wattage Rating						



Part Number	Description				
23-15	29 in. Vinyl Carry Bag				
23-30	46 in. Vinyl Carry Bag				
23-40	50 in. Vinyl Carry Bag				
Protects and transports light Available in three lengths					

^{*} Items Ending In "-R" Are Provided In Display-Ready Packaging

LIGHTING - PORTABLE LED WORK LIGHT

LED RECHARGEABLE CLAMP LIGHT

Versatile Clamping/Free-Standing Design


900 lumen portable USB rechargeable work light. Carry it, clamp it, place it anywhere. Ultra-bright wide-angle LED output is perfect for workshop, job site, garage, home, and outdoor recreation use.

- High-performance LED provides 900 lumen wide-angle output
- Lightweight, integrated Li-lon battery and USB charging provides ultimate portability
- Dual-brightness settings provide up to 7-hour long-lasting run-time
- Versatile clamp-light or free-standing work light design
- Non-marring pads clamp to wood framing, pipes, doors, and more.
- Two-axis rotating head swivels for perfect aiming
- Indoor/Outdoor use, rated IP54 rainproof/dustproof
- Durable impact-resistant design, folds flat for compact storage

Part Number	Description
31-W900-BY	900 lm LED wide-angle clamp light with USB Li-lon rechargeable battery



Specifi	cations			
Maximum Power	9 Watts			
Light Source	LED			
Maximum Lumen Output	900			
CRI	80			
ССТ	6500 K			
Beam Angle	Wide			
Charging Input	5V USB			
Run Time	2 hours at 100% (High Mode) 7 hours at 30% (Low Mode)			
Charging Time	4.5 hours			
Charging Cable	3.0 ft. USB to Micro USB			
Housing Material	PC, ABS, PP			
Battery type	3.7 V / 4400 mAh			
Operating/Charging Temp	-10°C - 40°C (14°F - 104°F)			
Dimensions: L x W x D	7.4 x 3.8 x 10.4 in. 189 x 96 x 264 mm			
Weight	1.9 lbs (0.85Kg)			
Electrical Class	Class III			
Ingress Protection	IP54 (dustproof, rainproof)			
Impact Rating	IK07			









LIGHTING - RECHARGEABLE LED HEADLAMP

LED RECHARGEABLE HEADLAMP

Rechargeable LED headlamp is versatile and extremely durable. The 31-HDLP Headlamp has 3 different light modes: Flood Light, Spot Light, and Up-Close Light. It is made of impact-resistant materials, which are dust and water resistant, and strong enough for the toughest conditions. The motion-activated sensor allows you to turn the headlamp on and off with a wave of your hand. The Jameson headlamp is perfect for indoor and outdoor work sites, and emergency situations.

- Lumen Output: 250 / 150 / 120
- 3 Modes: Flood, Spot and Up-Close
- Runtime: Up to 3 hours
- IP65 Dust & Water Resistant Rated
- IK07 Impact Resistant
- · Glow-in-the-Dark Reflector illuminates after use for easy locating
- · LED Blinks to warn user battery is dying
- Detachable: Can be used as a small hand light or stationary light utilizing magnet
- · Comes with 4 hard hat mounting clips



Part Number	Description
31-HDLP	Rechargeable LED Headlamp







3.8V/1600 mAh Li-poly
















MOTION ACTIVE SENSOR











LED EQUIPMENT LIGHTS

TOUGH LIGHTING FOR TOUGH JOBS

Jameson offers a diverse line of lights to meet the unique applications of our customers.

XD EXTREME DUTY LED LIGHTS

Features a rugged design with our highest-shock handling capabilities for extreme environments mining, military, marine or tracked equipment. XD lights carry a five (5) year warranty.

HDI HEAVY DUTY ILLUMINATION LED LIGHTS

Make it easier and safer to work at night with the brightness and durability customers require for utility, agriculture, construction, forestry and off-road applications. HDI lights carry a three (3) year warranty.

JLITE LED LIGHTS

Offers versatile lighting for a variety of applications, including light construction vehicles, utility trucks, forklifts, ATV's, golf carts, boats and more. JLites comes with a one (1) year warranty.

XD EXTREME DUTY LED EQUIPMENT LIGHTS

Rugged Design With Our Highest-Shock Handling Capabilities

Our XD LED Equipment Lights offer the intensity, durability and power needed for heavy equipment in environments with extreme temperatures or high shock and vibration applications.

The XD is preferred for mining, marine or tracked equipment applications.

- 50G HALT testing ensures superior performance under extreme shock and vibration
- Double-bolt XD-Lock™ mounting system isolates housing from mounting bracket for high-frequency vibration dampening
- · Housings are machined billet aluminum for optimal thermal transfer, maximizing LED life and efficacy
- Type II anodized aluminum housing for corrosion protection (Mil-A-8625)
- · Corrosion resistant stainless steel mounting bracket
- IP69K Withstands high-temperature/high-pressure water jets
- Advanced thermal management extends LED life at high temperatures and increases effective lumens at low temperatures.
- Zero warm-up for instant-on, flicker-free lighting
- · Borosilicate glass lens resists scratches and repels dust
- Energy efficient Low power consumption provides more lumens per watt compared to HID's
- · Reverse polarity protection
- Extreme high and low temperature performance
- Extended Five (5) Year Warranty









Part Number	\ \ND9	AD3 AD16 AD32		AD60				
	'							
Specifications								
Effective Lumens @ 25°C	3000	5900	11800	24800				
Number of LEDs	9	16	32	80				
Beam Patterns		dium, Vertical Elliptical, Elliptical, Wide, Trapezoid	Spot, Medium, Wide, Vertical Elliptical, Trapezoid	Spot, Medium, Wide, Horizontal Elliptical, Trapezoid				
Shock/Vibration		50	OG RMS @ 10-10,000 Hz at -40°C (-40°F))				
Ingress Protection			IP69K					
Power	45 Watts	85 Watts	170 Watts	270 Watts				
Current	3.8 A @ 12 VDC 1.9 A @ 24 VDC	7.1 A @ 12 VDC 3.5 A @ 24 VDC	14.1 A @ 12 VDC 7.0 A @ 24 VDC	22.5 A @ 12 VDC 11.3 A @ 24 VDC 2.4 A @ 120 VAC				
Input Voltage		10-32 VDC	18-32 VDC or 90-277 VAC					
Operating Temp	-75°C - 90°C (-103°F - 194°F)							
Color Temp (CCT)			5000K Natural White					
Weight	2.0 lbs (0.9 kg)	3.1 lbs (1.4 kg)	5.3 lbs (2.4 kg)	16.4 lbs (7.4 kg) DC Version 19.5 lbs (8.8 kg) AC Version				
Dimensions	5.0 x 4.5 x 3.6 in.	5.6 x 5.2 x 3.9 in. 9.0 x 4.9 x 3.9 in.		19.5 x 6.3 x 6.3 in.				
LED Life (L70)	50,000 Hours							
Termination	Chassis Mounted Deutsch	Chassis Mounted Deutsch Chassis Mounted Amphenol	Chassis Mounted Deutsch	Wire Leads				

XD EXTREME DUTY LED EQUIPMENT LIGHTS

XD Series Ordering Guide - Use Table To Determine Part Number

EXAMPLE PART NUMBER: XD9D04510NGDS

XD9 with deutsch connector, 45 watts, 10 volts, natural white LEDs, borosilicate glass lens, double trunnion, spot beam pattern (see page 23 for additional information on beam patterns)

XD9	D		045	10		N		G		D		S										
Series	Т	ermination	Power (Watts)	,	Input Voltage	LEI	O Color		Lens	М	ount Style		Beam Pattern									
												S	Spot									
				10	10-32VDC							М	Medium									
VDO	D	Deutsch	45				Natural	Natural Borosilicat	Borosilicate	D	Double	٧	Vertical Elliptical									
XD9	D	Connector	45	45	45			N	N	N	N	N	N	N	N	White	G	Glass	D	Trunnion	н	Horizontal Elliptical
				18	18-32VDC							W	Wide									
												Т	Trapezoid									



v	\mathbf{n}
\sim	כע

XD16	D		085	10		N		G		D		s		
I	1		- 1	I		I		-1		-1		-1		
Series	1	Termination	Power (Watts)		Input Voltage) Color		Lens	M	lount Style		Beam Pattern	
					0 10-32VDC						S	Spot		
	D	Deutsch		10								М	Medium	
VD46		Connector	85					Natural	ıl G	Borosilicate	D	Double	٧	Vertical Elliptical
XD16		Amphenol	85			N	White	G	Glass	D	Trunion	Н	Horizontal Elliptical	
		M Connector		1	18 18-32VDC	18-32VDC							W	Wide
													Т	Trapezoid



XD16

Series Termination Power (Watts) Voltage LED Color Lens Mount Style Beam Pattern Deutsch Connector 170	XD32	D		170	10		N		G		D		s	
XD32 D Deutsch 170 Connector 170 N Natural G Glass D Double Trunnion V Vertical Elliptical	Series	Т	ermination				LED) Color		Lens	M	ount Style		
XD32 D Deutsch 170 N Natural G Borosilicate Glass D Double Trunnion W Medium V Vertical Elliptical				(vvaits)									S	
XD32 D Connector 170 N White G Glass D Trunnion V Elliptical			Doutech		10	10-32VDC		Natural		Porocilicato		Double		
	XD32	D		170	18	18-32VDC	N	VI	G		D		V	



XD32

XD80	С		270	18		N		G		D		s		
Series	1	Termination	Power (Watts)		Input Voltage		LED Color		Lens		Mount Style		Beam Pattern	
	Cable										S	Spot		
		18	18-32VDC							М	Medium			
XD80			N	Natural	G	Borosilicate	D	Double	н	Horizontal				
ADOU	C	Leads	270		90-277VAC	IN	White	G	Glass	D	Trunnion	П	Elliptical	
				AC								W	Wide	
												Т	Trapezoid	




XD80

- ALL Deutsch connector versions include mating half Deutsch connector with lead wires.
 XD16 with Amphenol connector does not include mating connector half.

XD EXTREME DUTY LED EQUIPMENT LIGHTS


Beam Patterns






Spot

Focused for far field viewing; needed for spot-lighting and high-speed driving. Use on haul trucks and other swift-moving vehicles. Effective for high beam headlight applications.






Medium

Intermediate distance and area spread for applications requiring more coverage than Spot, but higher illumination than Wide. Can be used on dozers and wheel loaders.








Horizontal Elliptical

Sharp horizontal cutoff for driving and operating applications requiring greater distance, minimized light pollution and wide-angle illumination. Use on haul trucks and other vehicles to limit distracting oncoming traffic. Effective for low-beam headlight applications.




Vertical Elliptical 23° X 36°



Vertical Elliptical

Sharp vertical cutoff for applications requiring large vertical coverage with limited horizontal light pollution and distraction. Illuminates tall surfaces without wasting light horizontally. Use on loaders to illuminate raised buckets while not distracting haul truck drivers.






Wide Beam

Wide area flood pattern for illuminating large areas. Use on tracked and other slower-moving equipment. Great for general illumination around equipment perimeters, rear and decking.



Trapezoid 25° X 10°



Trapezoid

For applications requiring automotive style headlight distribution to reduce glare from oncoming drivers while offering wide area lighting below horizon. Use on haul trucks and other vehicles commonly used in two-way traffic.

HDI HEAVY DUTY ILLUMINATION LED EQUIPMENT LIGHTS

Making It Brighter, Easier And Safer To Work At Night

HDI LED equipment lights offer the brightness and durability required for the toughest jobs in utility, agriculture, construction, forestry, military and off-road applications.

- Energy-efficient, long-life LEDs (rated 50,000 hours)
- $\bullet \ \ \text{IP68 / IP69K} \text{dust-tight / water-tight, plus with stands high-temperature/high-pressure water jets} \\$
- · High shock and vibration resistance
- Reverse-voltage protection prevents damage to circuitry
- Rugged die-cast aluminum housing with black e-coat
- Wide operating temperature range
- Automotive optical grade, hard-coated polycarbonate lens
- Versatile hybrid (spot-wide) beam pattern
- Three (3) year warranty











Part Number	HDI-1810-HY	HDI-1812-P-HY	HDI-136-HY-H	HDI-1800-HY	HDI-1812-3000-HY	HDI-1813-HY	
			Specifications				
Effective Lumens	1260	1380	1400	2500	3000	5000	
Number of LEDs	6	6	6	10	6	22	
Beam Pattern	m Pattern Hybrid (Spot/Wide Beam)						
EMC Rated	EN 1330	9: 2010			EN 13309: 2010		
Shock/Vibration	5G RMS @	10-500 Hz			5G RMS @ 10-500 Hz		
Ingress Protection	IP68 an	d IP69K	IP67		IP68 and IP69K		
Power	14 Watts	14 Watts	12 Watts	22 Watts	33 Watts	50 Watts	
Current	1.2 A @ 12 VDC 0.6 A @ 24 VDC	1.2 A @ 12 VDC 0.18 A @ 76 VDC	1.0 A @ 12 VDC 0.5 A @ 24 VDC	1.8 A @ 12 VDC 0.9 A @ 24 VDC	2.75 A @ 12 VDC 1.38 A @ 24 VDC	4.2 A @ 12 VDC 2.2 A @ 24 VDC	
Voltage	12-24 VDC	12-76 VDC	12-24 VDC	12-24 VDC	12-24 VDC	12-24 VDC	
Operating Temp			-40°C - 6	0°C (-40°F - 140°F)			
Color Temp (CCT)			5700	K Day White			
Weight	1.3 lbs (0.6 kg)	1.6 lbs (0.7 kg)	0.7 lbs (0.3 kg)	2.2 lbs (1.0 kg)	1.6 lbs (0.7 kg)	5.7 lbs (2.6 kg)	
Dimensions	3.5 x 3.5 x 2.8 in.	3.9 x 3.9 x 2.5 in.	4.8 x 4.8 x 1.3 in.	4.6 x 4.6 x 2.6 in.	3.9 x 3.9 x 2.5 in.	6.0 x 5.5 x 3.0 ir	
Mounting Hardware	Stainless Steel C-Bracket	Stainless Steel U-Bracket	Stainless Steel U-Bracket	Stainless Steel C-Bracket	Stainless Steel U-Bracket	Stainless Steel U-Bracket	
Attachment Points	2			4			
Termination	6 in. Wire Leads	Deutsch Connector	6 in. Wire Leads	6 in. Wire Leads	Deutsch Connector	Deutsch Connector	

JLITE LED EQUIPMENT LIGHTS

Versatile Lighting For A Variety Of Applications

Durable housings, sealed construction and easy-mount brackets make Jameson JLite ideal for a wide variety of general-purpose lighting applications: Construction vehicles, utility trucks, forklifts, ATV's, golf carts, boats and more!

- IP65 Protected against dust, dirt and low-pressure water jets
- Durable powder-coated die-cast aluminum housing
- · Corrosion resistant stainless steel mounting bracket
- Impact resistant polycarbonate lens

- · Various beam patterns
- 30,000 hours rated life
- CE and RoHS certifications
- One (1) year warranty













Part Number	JL33C5W	JL11800-FL	JL16C28W	JL13C48W	JL13C65W	JL9C90S	JL9C90W	
----------------	---------	------------	----------	----------	----------	---------	---------	--

			Specifi	cations				
Effective Lumens	500	1800	2520	2700	5460	67	50	
Number of LEDs	33	8	16	13	13	9		
Beam Patterns	Wide	Flood	Wide	Wide	Wide	Spot	Wide	
Ingress Protection	IP65							
Power	5 Watts	18 Watts	28 Watts 30 Watts 65 Watts 90 Watts				Vatts	
Current	0.4 A @ 12 VDC 0.2 A @ 24 VDC	1.4 A @ 12 VDC 0.7 A @ 24 VDC	2.3 A @ 12 VDC					
Voltage	10-30 VDC	12-24 VDC	10-30 VDC					
Operating Temp	-20°C - 50°C (-4°F - 122°F)							
Color Temp (CCT)	6000K Cool White							
Weight	0.2 lbs (0.1 kg)	1.4 lbs (0.6 kg)	0.7 lbs (0.3 kg)	1.1 lbs (0.5 kg)	2.7 lbs (1.2 kg)	6.4 lbs (2.9 kg)		
Dimensions	3.7 x 3.0 x .91 in.	5.6 x 4.0 x 2.3 in.	5.5 x 4.3 x 1.9 in.	5.7 x 4.9 x 2.8 in.	6.5 x 5.6 x 3.7 in.	6.3 x 5.3	3 x 4.7 in.	
Termination	6 in. Wire Lead with Deutsch Connector (Mating Connector Included)							

WIRING HARNESSES SOLD SEPARATELY

Part Number	Description
JLWH-DT1	14 ft. Wiring Harness With On/Off Switch & One Deutsch Connector, Battery Ring Terminals
JLWH-DT2	14 ft. Wiring Harness With On/Off Switch & Two Deutsch Connectors, Battery Ring Terminals





LIGHTING - BACK UP ALARMS

BACK UP ALARMS

Protection For All Work Environments Day or Night

Back Up Alarms provide essential notification alerting the presence of nearby work vehicles. Vehicles equipped with Back-Up Alarms help reduce liability and create a safer work environment around the clock.

Applications include:

- Service/Fleet Vehicles
- Utility Trucks
- Delivery Trucks
- Tractor-Trailers

- Construction Vehicles
- Fork-Lifts
- Heavy Equipment

BACK-UP ALARM

Part Number	BA-151008			
Lumens	N/A			
Operating Voltage	12-24 VDC			
Temperature Range	-30°C - 55°C (-22°F - 131°F)			
Ingress Protection	IP68 / IP69K			
SAE/DOT Noise Compliant	SAE J994			
Weight	0.5 lbs (0.2 kg)			
Dimensions	3.3 x 2.7 x 1.6 in.			
Housing	Glass Filled Nylon			
Mounting	Horizontal or Vertical			
Lens	N/A			
Connection	Terminal Studs			
SAE/DOT Noise Compliant: Meets SAE J994				



BA-151008

- Loud 97dB audible alarm
- Reverse polarity voltage protection
- · Corrosion-resistant design for heavy-duty applications
- Epoxy encapsulated protected against dust, water and vibration

LED STROBE BACK-UP ALARM

Part Number	BA-152051			
Lumens	200			
Operating Voltage	12-24 VDC			
Temperature Range	-40°C - 85°C (-40°F - 185°F)			
Ingress Protection	IP68 / IP69K			
SAE/DOT Noise Compliant	SAE J994			
Weight	0.4 lbs (0.2 kg)			
Dimensions	3.2 x 4.0 x 1.7 in.			
Housing	ABS Plastic			
Mounting	Horizontal or Vertical			
Lens	Optical Grade Acrylic			
Connection	Wire Leads			
SAE/DOT Noise Compliant: Meets SAE J994				



BA-152051

- Loud 97dB audible alarm
- Bright 200 lumen flashing amber LEDs
- High-visibility wrap-around lens for >180° field-of-view
- Multi-function operation, including Night-Silent for use in sound sensitive areas
- · Corrosion-resistant design for heavy-duty applications
- Epoxy encapsulated protected against dust, water and vibration

LIGHTING - MARKER LIGHTS

ML MARKER LIGHTS

High Visibility Brake Lights & Tail Lights For Extreme Environments

Our ML Marker Lights penetrate thick layers of dust or mud buildup, fog, snow and rain to provide high visibility of heavy

Featuring the same robust protection and reliable circuits as the XD lights, ML Marker Lights are fully encapsulated for waterproofing and feature a hardened borosilicate lens.

- Type III Anodized Chassis for corrosion resistance
- Fully Encapsulated PCB prevents ingress of dust and water
- Low Power Consumption
- Thermal Management prolongs life and boosts output
- · Reverse Polarity
- Wide Voltage Input Range
- Dimmable feature allows use as turn signal or brake light






ML24-R-SM

RED LEDS

Part Number	ML24-R-SM
LED Options	DOT Red
Max Power	8-20 Watts
Operating Voltage	10-32 VDC
Raw Lumens	1,340
Effective Lumens	1,206
Current @28VDC	<700mA
Ingress Protection	IP69K
Lifetime (hrs)	50,000
Weight	1.2 lbs










AMBER LEDS

Part Number	ML24-A-SM
LED Options	DOT Amber
Max Power	8-20 Watts
Operating Voltage	10-32 VDC
Raw Lumens	1,340
Effective Lumens	1,206
Current @28VDC	<700mA
Ingress Protection	IP69K
Lifetime (hrs)	50,000
Weight	1.2 lbs







LIGHTING - WIDE AREA / HIGH BAY LIGHTS

VEGA™ PORTABLE RECHARGEBLE LED LIGHT

High Intensity Lighting

Designed for tough conditions, and offering rugged construction and high performance, the LED floodlight was designed to go wherever the job takes you. Lightweight and battery-powered with an integrated carrying handle for maximum portability.

Features:

- 21 High-Performance LEDs
- IP65 Waterjet Resistant
- 8-Hour Battery Life*
- · Shock and Vibration Resistant
- Integrated Battery Meter
- · Dimming Capability
- Switch For Instant Maximum Optical Output
- Charger Included
- Diffuse Lens Changes Spot Optic To Flood (Optional)
- 5-Year Limited Warranty

Applications:

- · Construction Sites
- · Roadside Service
- Rail yards
- · Emergency Repairs
- Expeditionary/FOBs
- Disaster Cleanup
- First Responders
- Security
- Recreation
- Fire & Rescue



Part Number	Description
31-PBL21-S	LED Spotlight, 20° Beam Angle
31-PBL21-W	LED Wide Angle, 76° Beam Angle
31-PBL-TRI	10 ft. Tripod & Mounting Plate (Light Sold Separately)
31-DLW	Diffuse Lens, 76° Beam Angle
31-PBL-MAG1	Magnetic Base (Light Sold Separately)

Specifications		
Lumens	16,670	
*Run Time	*8 Hours At 80% Output	
Battery Type	Rechargeable Lithium Ion	
Operating/Storage Temp	-20°C - 60°C (-4°F - 140°F)	
Charging Temp	5°C - 45°C (41°F - 113°F)	
Dimensions	13.3 x 12.7 x 6.8 in. 337.8 x 322.6 x 172.7 mm	
Weight	19 lbs	





Diffuse Lens (optional)







LIGHTING - WIDE AREA / HIGH BAY LIGHTS

WIDE AREA LIGHTS

Wide Area Light On Adjustable Tripod

Our Tripod Light offers intense, adjustable lighting. The 3 light heads have 360° tilt and rotation to provide lighting for a variety of applications. The adjustable tripod folds to a compact 59" height for convenient storage.

Light Head Features:

- Energy-efficient, long-life LEDs (rated 50,000 hours)
- $\bullet \ \mathsf{IP68} \ \mathsf{/} \ \mathsf{IP69K} \mathsf{dust\text{-}tight} \ \mathsf{/} \ \mathsf{water\text{-}tight}, \ \mathsf{plus} \ \mathsf{withstands} \ \mathsf{high\text{-}temperature/high\text{-}pressure} \ \mathsf{water} \ \mathsf{jets}$
- High shock and vibration resistance
- Reverse-voltage protection prevents damage to circuitry
- Rugged die-cast aluminum housing with black e-coat
- Wide operating temperature range
- Automotive optical grade, hard-coated polycarbonate lens
- Versatile hybrid (spot-wide) beam pattern

Part Number	Description
31-WA-1812-3000-TR	Wide Area LED Light with Tripod

Specifications - Lights		
Power	100 Watts	
Input Voltage	90-264 VAC	
Effective Lumens	9,000	
Weight Per Light Head	1.6 lbs each	
Operating Temperature	-40°C - 60°C (-40°F - 140°F)	
Input Cable	1 (Power In)	
Output Cables	3 (One Per Light)	
Individual Light Head Dimensions	3.9 x 3.9 x 2.5 in. (99.0 x 99.0 x 63.5 mm)	
Input Cable Length	50 ft.	
Plug	NEMA 5-15	

Specifications - Tripod		
Height	5 ft 10 ft. (Collapsed-Extended)	
Base Wide	13.0 - 58.0 in. (Collapsed-Extended	
Material	Aluminum, Powder Coated	
Bar Mount	Quick Release Pin - Removable for Storage	
Folded Dimensions	59.0 x 13.0 x 13.0 in. 1498.6 x 330.2 x 330.2 mm	
Tripod Light Without Case	34.0 lbs	
Light and Case Weight	82.0 lbs	
Transport Case	66.5 x 22.0 x 12.5 in. 1689.1 x 558.8 x 317.5 mm	



LIGHTING - WIDE AREA / HIGH BAY LIGHTS

HIGH BAY LIGHTS Large Area Lighting For Temporary Structures

- Aircraft & Vehicle Maintenance Shelters
- Large & Medium Area Maintenance Shelters
- Morale, Welfare & Recreation Shelters
- · Billeting & Dining Halls
- · Vehicle Wash Bays
- Clear Span Structures
- Inflatable Beam Shelters
- Outdoor Low Mast & Security

Features:

- High Efficiency, Long-Lasting LED Light Sources
- Instant Start (No Warm-Up Period)
- Surface Temperature Remains Safe For Handling
- LEDs Provide Efficient Directional Light That Require No Reflectors Like Metal Halide Lights
- Rugged, Durable Construction Withstands Repeated Installations And Take-Downs
- Sealed Components Survive High-Moisture Environments And Extreme Temperature Conditions
- No Maintenance, Surge Protected
- Simple Installation Mounts To Framework Or Suspended By Hanging Cable
- Safety Cable Prevents Accidental Drops During Installation
- Pivot Bracket For Convenient Aiming/Leveling
- UL Recognized Components

Part Number	Description
31-HB4	LED High Bay Light, 4 Module
31-HB6	LED High Bay Light, 6 Module
31-HB-SC	Safety Cable For High Bay Light
31-HB-HC	Hanging Cable For High Bay Light

Specifications	31-HB4	31-HB6
Power	200 Watts	300 Watts
Input Voltage	90-30	5 VAC
Actual Lumens	33,000	49,500
Beam Angle	9	0°
CRI	>	75
Color Temperature	480	00 K
Number of LEDs	112	168
LED Rated Life (L70)	50,000) hours
Dimensions	14.0 x 12.0 x 7.0 in.	20.7 x 12.0 x 7.0 in.
Weight	13.5 lbs	18.5 lbs
Ingress Protection	IP	67
Cable	14/3 SOOW, 6 ft. or custo	om lengths
Connector	NEMA 5-15 standard	iest)











EXPEDITIONARY SHELTER LIGHTS

Extreme Durability, Performance, and Reliability

Our string lights have revolutionized shelter lighting for expeditionary use and have rapidly grown to include electromagnetic interference (EMI) hardened lights to protect troops from detection, and protect electronic equipment from interference. To meet the military's commitment for "green" equipment, we developed LED lighting systems that provide lower power consumption and longer product life. Our lights are actively used for a wide variety of missions in all branches of the US Military and are an integral part of various shelter programs.

Safety and reliability are paramount in military environment. Our lights demonstrate this during all test phases and more importantly, in the battlefield where it counts. We continue to develop new generations of lighting using the latest technology to bring customers the highest performing and most durable lighting in the industry. The development of expeditionary lighting takes into consideration the need for fast deployment, easy transport and extreme ruggedness.

We also offer PaxLight LED Medical Lights with a compact, lightweight design with rugged engineering and precision lighting required for field hospitals.

FLUORESCENT EXPEDITIONARY LIGHTS


Fluorescent Stringable Shelter Light

For use in Field Hospitals, Command Centers, Force Provider, BEAR Base

- Will Not Compromise Peripheral Electronics. EMI (electromagnetic interference) hardened lights.
- · Will Not Compromise Peripheral Electronics, Communication Equipment, Computers or Medical Equipment.
- · Will Not Trip GFCI when Connecting Over 30 Lights, Exceeding Military Specification Of 12-Light Connectivity.
- Electronic Ballast Is More Efficient, Lighter Weight Than Magnetic Ballast Lights
- Compliant with MIL-STD-461, RE102 (Army Ground Limits) and CE102
- Black out filter greatly reduces visible signature
- · Compliant with MIL-PRF-44259
- Shatterproof, Protective Tube Shield Protects Lamp
- Interoperable With Jameson LED String Lights
- Lightweight For Easy One-Man Set Up
- · Independent Pass-Through Power
- · Low Amp Draw
- · Low Heat Signature
- Multi-Volt
- Twin Lamp Design
- · Individual On-Off Switch
- Durable, Compact Design







Part Number	NSN	Description
31-502SK-IP	6230-01-485-6375	Individual EMI Hardened String Light, Black Out Filter, 2 Hanging Straps, Multi-Volt
31-502SK	6230-01-465-8931	Kit: Two EMI Hardened String Lights, Black Out Filters, 4 Hanging Straps, Multi-Volt
31-502BHS	6230-01-525-0794	Kit: Two EMI Hardened String Lights Black Out Filters, 4 Hanging Straps, Multi-Volt, Vinyl Carry Bag 23-30-B
31-MC-502S	6230-01-519-0393	Kit: Four EMI Hardened Lights, 2 Replacement Lamp Kits, 4 Universal Hanging Straps, Transport Case 31-MC
31-4B-502SK		Kit: Four EMI Hardened Lights, 4 Hanging Straps, Canvas Carry Bag 23-30-4L
31-502SK-IP-C		Individual EMI Hardened String Light, Black Out Filter, 2 Hanging Straps, Multi-Volt, CSA Certification
31-1-50	6230-01-506-9387	Replacement Lamp Kit

Specifications For EMI Light		
Power	36 Watts	
Input Voltage	120-230 VAC 50-60 Hz	
Illumination (Unfiltered)	148.5 fc @ 18 in.	
Illumination (Blackout)	21.4 fc @ 35 in.	
Dimensions (without cord)	35.6 in.	
Dimensions (with cord)	117.0 in.	
Weight	4.5 lbs	
Ballast Type	Electronic	

LED EXPEDITIONARY LIGHTS

LED Integrated Shelter Lights

Our latest EMI Protected LED Expeditionary Shelter Lights are lighter and more compact than previous models. Integrated shelter lights are set up one time and remain in shelter during storage and transport. The ISL mounts close to the liner for maximum headroom with multiple options for attachment.





LED ISL Compared To Previous LED Model

- \bullet 70% Smaller And 13% Lighter than 31-400B LED String Light
- 37% More Efficient than 31-400B LED String Light
- Compared To Other Integrated Lighting Solutions 40% Fewer Lights Required

Environmental / Performance

- MIL-STD-461, RE102 & CE102 compliant (Navy Mobile & Army limits)
- Operating temperature -40°C 49°C (-40°F 102°F)
- Storage temperature -51°C 71°C (-60°F 160°F)
- High humidity operation
- High altitude operation 1500 4700m
- High vibration transport (air and land)
- Functional Shock, 20G
- LED Technology For Long Life & Low Power Consumption
- Instant Start, Flicker-Free Lighting
- Dimming & Blackout Modes
- Connect Up To 36 Lights; GFCI Compatible
- Lights Operate Independently Or Simultaneously by Master Switch
- IP67 Waterproof Housing





LED INTEGRATED SHELTER LIGHTS

- Finned Body Maximizes Cooling And Electronics Life
- Diffuse Lens Prevents Distracting Hot Spots
- Safe Surface Temperature
- · Coated Aluminum Housing Prevents Corrosion
- Independent Pass Through Power
- Backlit Push Button Control On Light & Master Switch
- Master Switch To Control Entire Light String Available Separately
- Superior High & Low Temperature Performance
- Generator Power Compatible
- Uses Standard Nema 5-15 Plug/Conn (No Special Adapters Needed)







Part Number	Descriptions	
31-ISL-B	Integrated Shelter Light Blue Blackout	
31-ISL-R	Integrated Shelter Light Red Blackout	

Part Number	Integrated Shelter Light Switch
31-ISL-SWITCH	Master Switch

IS	L Light Fixture Specifications
Input Voltage	100-240 VAC, 50-60 Hz
Actual Lumens	1320 (100% White)
Power	15 Watts
Power Factor	>.90
LED Rated Life (L70)	50,000 Hours
Operating Modes	100% White, 50% White, Tactical (Blue), Off
Ingress Protection	IP67 Housing (Water Tight Plugs Optional)
ССТ	4900K (White Modes)
CRI	85+ (White Modes)
Weight	4.1 lbs
Dimensions (Without Cords)	7.8 x 5.0 x 3.0 in. 198.1 x 127.0 x 76.2 mm
Dimensions (With Cords)	120.0 x 5.0 x 3.0 in. 3048 x 127.0 x 76.2 mm
Cables	14/3 SJOOW, NEMA 5-15 Plug/Conn

Master Switch Specifications		
Input Voltage	100-240 VAC, 50-60 Hz	
Power	2 Watts	
Power Factor	.60	
Control Buttons	100% White/50% White Toggle, Tactical (Blue/Red), Off	
Ingress Protection	IP67 Housing (Water Tight Plugs Optional)	
Weight	4.9 lbs	
Dimensions (Without Cords)	9.0 x 6.0 x 2.5 in. 228.6 x 152.4 x 63.5 mm	
Dimensions (With Cords)	120.0 x 6.0 x 2.5 in. 3048.0 x 152.4 x 63.5 mm	
Cables	14/3 SJOOW, NEMA 5-15 Plug/Conn	

LED GENERAL PURPOSE STRINGABLE LIGHTS

LED Stringable Low Power Lights

General Purpose Lighting For Billeting, Temporary Shelters, Emergency, and Diaster Relief.

- Lightweight, Compact Design
- Hanging Straps For Easy Mounting
- Connect Lights To Form A Versatile String
- Single Full Power White Mode

31-400-GP LOW POWER AC STRINGABLE SHELTER LIGHT

Part Number	Description
31-400-GP	LED AC General Purpose Lights
31-400GP-2B	2 LED AC General Purpose Lights, Vinyl Carry Bag 23-30-B
31-400GP-4C	4 LED AC General Purpose Lights, Transport Case 31-MC

Specifications	
Dimensions (without cords)	26.8 in. (680.7 mm)
Dimensions (with cords)	120.0 in. (3048.0 mm)
Major diameter	3.8 in. (96.5 mm)
Minor diameter	2.6 in. (66.0 mm)
Weight	3.9 lbs
Cubic Volume	113.0 cu. in.
Input Voltage	100-240 VAC
Power	20 Watts
Amps	.17 @ 120 VAC



31-400-24VDC LOW POWER DC STRINGABLE SHELTER LIGHT

Part Number	Description
31-400-24VDC	LED DC General Purpose Light
31-400-2B-24VDC	2 LED DC General Purpose Lights, Vinyl Carry Bag 23-30-B
31-400-4C-24VDC	4 LED DC General Purpose Lights, Transport Case 31-MC

Specifica	ations
Dimensions (without cord)	19.5 in. (495.3 mm)
Dimensions (with cord)	120.0 in. (3048.0 mm)
Major diameter	3.9 in. (99.1 mm)
Minor diameter	2.6 in. (66.0 mm)
Weight	3.2 lbs
Cubic Volume	89.0 cu. in.
Input Voltage	24 VDC nominal
Input Voltage Range	10-40 VDC
Power	20 Watts
Amps	0.83 DC-A @ 24 VDC



FLUORESCENT GENERAL PURPOSE STRINGABLE LIGHTS High Intensity Universal Lighting

Suitable for applications that do not involve EMI sensitivity or peripheral electronic equipment. They are available with optional 120V dedicated input voltage or 120/230V multiple voltage and meets U.S. and Canadian standards for water resistant portable lighting.

- Electronic Ballast Is More Efficient, Lighter Weight Than Magnetic Ballast Lights
- Interoperable With Jameson LED String Lights
- · Independent Pass-Through Power
- · Individual On-Off Switch
- Durable, Compact Design
- Lightweight For Easy One-Man Set Up
- Flicker Free

- · Shatterproof, Protective Tube Shield Protects Lamp
- Twin-tube lamp design
- · Low Amp Draw
- · Low Heat Signature
- Flicker Free
- Multi-Volt input available
- Maintenance Enclosures, Billeting, Decontamination Shelters



FLUORESCENT STRINGABLE SHELTER LIGHT

Part Number	NSN	General Stringable Lights - Single 120 VAC
31-5004M-IP	6230-01-485-6376	1 General Purpose String Light, 2 Hanging Straps
31-5004M	6230-01-483-7562	Kit: 4 General Purpose String Lights, 8 Hanging Straps
31-MC-5004MS		Kit: 4 General Purpose String Lights, 8 Hanging Straps, 2 Replacement Lamp Kits, Transport Case 31-MC
31-4B-5004M		Kit: 4 General Purpose String Lights, 8 Hanging Straps, Canvas Carry Bag 23-30-4L
31-1-50	6230-01-506-9387	Replacement Lamp Kit for General Purpose Lights
31-501-IP		General Purpose String Light, Multi-Volt, 2 Straps
31-501M-US		Kit: 4 General Purpose Lights, Multi-Volt, 8 Straps
31-MC-501M		Kit: 4 31-501-IP Lights, 2 Lamp Kits, 8 Straps, Transport Case 31-MC
31-36ST		Stringable, Twin Lamp, 36 Watt, Two Straps
30-4025EM	6230-01-446-2197	Stringable, Single Lamp Light, 40 Watt, 4 ft. Long

	Specifications	5
Part Number	31-5004M-IP	31-501-IP
Power		36 Watts
Input Voltage	120 VAC (60 Hz)	120 or 230 VAC (50 Hz)
Illumination		165 fc @ 18.0 in.
Dimensions (without cord)	31.9 in.	35.2 in.
Dimensions (with cord)		117.0 in.
Weight	3.4 lbs	4.2 lbs
Ballast Type		Electronic

STRINGABLE SHELTER LIGHTS International Configurations





EMI HARDENED STRINGABLE SHELTER LIGHT 31-502EU-IP with Schuko Plugs

31-302EU-IF WILL 30	CHILACTERIAS	
Part Number	Description	
31-501-AUS	Fluorescent General Purpose String Light, Multi-Volt, Type I Plug	
31-501-SH	Fluorescent General Purpose String Light, Schuko Plugs, 2 Hanging Straps, 120-230 VAC, 50-60 Hz	
31-501-TM	Fluorescent General Purpose String Light, Multi-Volt, Type M Plugs	
31-501-UK	Fluorescent General Purpose String Light, Multi-Volt, Type G Plugs	
31-501-I	Fluorescent General Purpose String Light, Multi-Volt, Type H plugs	
31-502EU-IP	Fluorescent General Purpose String Light, Multi-Volt, Schuko Type F plugs, CE Certified	
31-502-AUS	Fluorescent EMI Hardened String Light, Multi-Volt, Type I Plugs, CE Certified	
31-502-TM	Fluorescent EMI Hardened String Light, Multi-Volt, Type M Plugs, CE Certified	
31-502-UK	Fluorescent EMI Hardened String Light, Multi-Volt, Type G Plugs, CE Certified	
31-502-I	Fluorescent EMI Hardened String Light, Multi-Volt, Type H Plugs, CE Certified	
31-MC-502SH	Kit: 4 EMI Hardened String Lights in Transport Case, Schuko Plugs, Hanging Straps, 2 Lamp Replacement Kits, 120-230 VAC, 50-60 Hz, CE Certified	

ACCESSORIES FOR LED AND FLUORESCENT STRINGABLE LIGHTS

TRANSPORT CASE

Part Number	Description
31-MC	Transport Case - Holds 4 Fluorescent Stringable Lights, 53 x 17 x 17 in., 20.0 lbs
31-MCL	Transport Case - Holds 4 LED Stringable Lights, 53 x 17 x 7 in., 19.5 lbs

Case holds four stringable lights. Compliant to Federal Standards for drop testing, impact resistance, vibration and water immersion. Wheels and handles for easy portability. Custom foam lining cradles and protects lights. Compliant with DEF STAN 81-41/STANAG 4280



2-LIGHT CARRYING BAG

Part Number	Description
23-30-B	Vinyl Carrying Bag - Holds 2 Lights, 44 x 11.8 in., 1.1 lbs
Vinyl-coated pylon had holds two stringable lights. Features span	

Vinyl-coated nylon bag holds two stringable lights. Features snap closures and web handles.



4-LIGHT CARRYING BAG

Part Number	Description
23-30-4L	Canvas Carrying Bag - Holds 4 Lights, 8.5 x 8.5 x 38 in., 1.5 lbs
Canvas bag ho web handles.	olds four stringable lights. Features zipper closure and



EXTENSION CORD

Part Number	Description
31-10-EXT	10 ft. Extension Cord with In-Line Switch
shelter lights. S	ord with in-line switch to turn on/off entire string of Set up at the beginning of light string near shelter entry. proof and illuminated.





BLUE AND RED FILTERS

Part Number	Description
31-LMEFILT-B	General Purpose Fluorescent Light Filter - Blue
31-LMEFILT-R	General Purpose Fluorescent Light Filter - Red
31-MCPSFILT-B	Blue Filter for EMI Fluorescent Hardened Light
Filters for fluorescent string lights	

Part Number	Description
31-1-50	Replacement Lamp Kit for 50 Watt Fluorescent Lights NSN 6230-01-506-9387

FIELD-TOUGH MEDICAL LIGHTING

Compact, lightweight design with the rugged engineering and precision lighting required for field hospitals. Sand and splash resistant, the locking joints make it fully adaptable and secure.


Suitable for use as a minor surgical luminaire or luminaire for diagnosis in patient environment.

LED Technology

LEDs offer intense illumination 10 times brighter than traditional halogen field lights and have an exceptionally long life. Because LEDs have a low infrared content, they project minimal heat onto the patient.

No Shadow Interference

Patented 3-pod head eliminates shadow interference common with single point light sources.



PAXLIGHT® LED MEDICAL LIGHT Compact Precision Lighting

OVERHEAD MOUNT

Part Number	Description			
31-600P-CM	Ceiling/Wall Mount Kit: PAXLight Head, Power Supply (24V, A/C input), Rail Mount System, 2 Green Handles, Transport Case			
31-600P-CM-20LR	PAXLight with 20 in. Linear Rail Ceiling Mount			
31-600P-CM-AP	PAXLight with Adapter Plate For Ceiling Mount Without Linear Rail			
Light slides smoothly along rail and locks into position. The light head can be adjusted for custom light placement.				



MIL-SPEC TRANSPORT CASE INCLUDED

Part Number NSN		Description	
31-600P	6530-01-549-1089	PAXLight In Case	





WHEREVER THE JOB TAKES YOU, COUNT ON JAMESON™

10000



JAMESONTOOLS.COM

800.346.1956

PD_2045 REV 3/2023