



VERTICALITY LIGHTING

2023 PROFESSIONAL CATALOG





ccessing the inaccessible is a routine requirement for most professionals who use our products. And it's an honor for Petzl to contribute to their work. For the last 50 years, we've put our know-how and expertise to work to continue this mission. Rooted in our experience, we design and manufacture specialized products that provide our customers with the best performance and highest level of safety, so that every move they make during their workday is easier and more efficient — bringing the inaccessible within reach.

As for new 2023 products, hands-free lighting is taking the main stage, with a complete range of four ARIA headlamps, designed for all professionals in the generalist market, such as tradespeople, maintenance professionals, and stage workers. For rescuers, this year we're serving up an updated range of FALCON harnesses, revamped to give you more comfort, lighter weight, and of course, functional design. Speaking of harnesses, you'll also find a range of accessories that make carrying and accessing your tools easier than ever. You also don't want to miss the new TOOLBAG range, now with even more practical and innovative features! To top it all off, our updated PRO TRAXION and MINI TRAXION pulleys are sure to get your attention, as well as the incredible COEUR PULSE removable anchor.

You'll find many more new products as you go through these pages...

Happy reading and best of success in your endeavors!

The Petzl Team

We Are Petzl	2
Petzl Across the Globe	4
Our Pillars	5
Corporate Social Responsibility	9

Key New Verticality Products1Key New Lighting Products1





VERTICALITY

General Principles of Work at Height	18
Rope Access and Confined Space	20
Tree Care	26
Energy and Networks	30
Framing and Roofing	34
General Rescue Principles	38
Self-Rescue	40
On-Site Rescue	42
Technical Rescue	46
Cable Lift Evacuation	50
Harnesses	54
Helmets	78
Lanyards and Energy Absorbers	90
Mobile Fall Arresters	100
Connectors	106
Descenders	114
Rope Clamps	124
Pulleys	130
Anchors	138
Ropes	148
Packs and Accessories	156
Kits	162
Customizable Products	168

LIGHTING

A Range for Every Use

The Petzl Difference	175
Petzl Quality	176
Brightness and Burn Time	177
Environments and Standards	178
Headlamp Specifications	181
Powerful and Intelligent Headlamps	184
Compact and Durable Headlamps	190
	184 190 196
Compact and Durable Headlamps	190
Compact and Durable Headlamps Ultra-Compact and Versatile Headlamps	190



We PETZL.

This is see the world.

We are committed to creating safer places. For those who work and play in the vertical and dark worlds. For those who want to access their own inaccessible every day. We are independent and completely free to choose our own endeavors. To maintain industrial excellence, paying attention to our impact. To be pioneers in the pursuit of perpetual innovation. Sharing, educating, building. Together.

This is how we see the world.

We PETZL.





Access the inaccessible® "Accessing the inaccessible" is the driving force behind everything you do, whether you are moving towards a summit or descending into darkness. You're determined to get to ever-greater heights and through ever-deeper shadows. And you're always searching for better tools to do it: tools with superior performance, tools that are more reliable, tools so comfortable and ergonomic that they disappear into your hand. At Petzl, we share your determination. We've built our entire design and manufacturing philosophy around exceeding your needs in the field. It's what we've been doing for 50 years, and what we'll continue to do for years to come.





Petzl is a family business that, over the years, has become the largest European manufacturer of personal protective equipment for those who work and play in darkness or at height. All of our products are invented and developed at our headquarters in the heart of the French Alps.

Key Stats

The brand is present in over 55 countries.

85% of sales are made internationally.

More than million products are sold every year.

people use Petzl personal protective equipment every day.





An International Presence

- Headquarters in the French Alps, in the town of Grenoble
- American subsidiary in Salt Lake City, Utah
- Petzl subsidiaries and sales agencies: Austria, Benelux, Denmark, Finland, France, Germany, Italy, Norway, Spain, Sweden, Switzerland, UK, and China

1,000 employees across the globe.

4 production sites: 3 in France and 1 in Malaysia.

Petzi subsidiaries and sales agencies: Austria, Benelux, China, Denmark, Finland, France, Germany, Italy, Norway, Spain, Sweden, Switzerland, UK, USA.

About Petzl

Petzl Distributors



The Values That Motivate Us

For 50 years, Petzl has been built around four pillars, four fundamental values that motivate every decision we make: remaining a stable family business, encouraging innovation to imagine the best solutions, insisting on industrial excellence with the goal of zero defects, and remaining engaged with our communities by providing global best practices.

Learn more about each of our pillars.

■ 1. Family Ownership





Sébastien, Paul, and Olivier Petzl



Fernand in his workshop

The Petzl family business is not listed on the stock market. We're proud of our independence; we make our own choices, take responsibility for our decisions, and maintain a long-term, sustainable vision for the future. The confidence and satisfaction of our customers, our dealers, and our partners drives everything we do.





2. Innovative Spirit



Innovations That Challenge Convention

With the introduction of the first headlamp in 1973, the legendary GRIGRI assisted blocking belay device in 1991, and the MAESTRO rescue descender in 2019, Petzl ingenuity has always pushed standard practices forward. Since the creation of Petzl in 1970, our objective has always been to make progressing in dark or vertical spaces safer and more comfortable.

Going Farther

As passionate pioneers, we delight in creating new opportunities for our users to venture into ever more committing terrain — to go farther and higher, to work more efficiently, to maximize safety and to make what was inaccessible today accessible tomorrow.






© 2013 Retal Distribution - James Roh

Simplicity, Durability, Efficiency

The tools we make are conceived and constructed with an eye for simplicity, durability, and efficiency. For Petzl, being a pioneer has meant 50 years of passion, expertise, innovation, and continuous improvement. This approach to our craft and our business has allowed us to serve as a global expert, as we did in 2006 with the conception of the EXO personal escape system. At the request of, and in collaboration with, the firefighters of New York City, we were able to design an efficient solution that would allow easy escape in critical situations. It's an achievement that has been recognized with several awards, including best invention of the year by Time Magazine.

The Evolution of Petzl Headlamps



3. Industrial Excellence





Beyond the Standards

We have a deep responsibility to the people who trust us with their lives, and we develop, test, and qualify all of our products above required standards. Our design center, based in France, integrates all crafts that are related to the creation of products: mechanical, textile, electronic, optical, and technological. From the design and prototype phases, the reliability of a product and the safety of the user are continuously evaluated, with particular attention to risks of use.

With labs dedicated to product testing, we conduct dynamic fall and impact resistance tests, perform cyclical testing, and evaluate performance, as well as beam quality and burn times of our headlamps. This process includes rigorous field testing in order to test the ergonomics and reliability during real-world use.





Zero Defects - PPE (Personal Protective Equipment)

Reliability is at the center of our concerns: our goal is for our products to consistently function at the same level of excellence.

Our objective is to allow zero defective products to leave our facilities, which involves processes with significant extra costs at every stage of production.

As we navigate an increasingly globalized economy, we go to great lengths to support our distributors and dealers, and we are heavily involved in the fight against counterfeit products.

Production and Inspection

Petzl's production sites are located in France, in the towns of Crolles, Eybens, and Rotherens, as well as in Rawang, Malaysia. Remaining competitive and keeping the majority of our production in France means that we continuously optimize our production lines and reduce our waste. This production infrastructure is complemented by long-term partnerships with key suppliers in Europe and Asia.

Our purchasing and quality control teams work closely with suppliers, ensuring to the best of our abilities, product reliability and quality that meets or exceeds our strict requirements. Quality inspection is present throughout every step of the production process: machine inspection of operations, human inspection at key points, further reinforcement by errorproofing systems and final individual inspection of each product.

We regularly audit the methods, quality management systems, and CSR practices (Corporate Social Responsibility) of our suppliers and strategic partners, especially when it comes to their employees.



4. Community Engagement





Using Our Expertise to Serve Communities

Sharing technical knowledge and appropriate product uses is at the heart of what we do at Petzl. We produce high-quality technical content that is available to everyone and utilized by the different communities that we serve. With a focus on maximizing safety, this content is updated and enriched throughout the lifetime of our products to keep our customers informed and moving forward while they practice their sport or do their job.

International Collaboration

Across the world, we have partnerships with iconic athletes, influential figures, professionals who work in extreme conditions, NGOs, certifying bodies, and training centers operated by leading experts in the field. These collaborations help us co-create a world where we can all learn, share, and flourish. They also make it easier to promote best practices and standard uses. At the heart of our collaborations is always a passion for exploration, for a job well done, and for the pursuit of the inaccessible.





The Petzl Foundation is an integral part of Petzl

Through the Petzl Foundation, we support and initiate projects that help prevent accidents, preserve the environment, and improve knowledge of the natural world around us.

More information about the Petzl Foundation can be found on page 204.

Our approach to CSR is pragmatic, collaborative and positive. It's built on concrete actions, feedback from our stakeholders, and is solution-oriented, to encourage our teams and community to take action.

The safety and satisfaction of our customers remains our top priority. Beyond that, however, we're striving to create a more sustainable future.

Petzl has launched projects to improve our own economic, environmental, and social practices, as well as the practices of our suppliers in order to:

- Reduce our carbon intensity
- Reduce, reuse, and recycle our waste
- Improve our employee satisfaction
- Improve the labor conditions of our suppliers

"More than ever before, we're acutely aware that the choices we make today will have a lasting impact on the environment and will actively shape our own futures and the futures of our children. We're committed to using our creativity and our capacity to innovate in service of sustainably reducing our impact in a continuous drive for improvement."

Marie Pailler, CSR Manager and Sébastien Petzl, Director of CSR



Learn more

Four Actionable Commitments

At Petzl, we're focused on four commitments that respond to the primary concerns of over 2,000 of our internal stakeholders (employees, subsidiaries, family shareholders) and external stakeholders (clients, users, suppliers, associations, and NGOs). We are manifesting these four commitments through hands-on projects with measurable

Reduce Our Carbon Intensity

In 2020, we worked with Carbone 4 to measure the comprehensive carbon impact of our operations in 2019 — from the extraction of raw materials to the end of a product's life. Our footprint was equal to 45,000 metric tons of CO2. Three areas accounted for 75% of our emissions: raw materials (34%), transport of goods (24%), energy used to power our headlamps (17%).

In 2021, we created initiatives to reduce our carbon footprint: prioritize the use of materials with the least impact, improve the durability and repairability of our products, shrink the distances our goods travel, and reduce our energy consumption, By 2030, our goal is to reduce our total carbon footprint by 50% per euro in sales.





Reduce, Reuse, and Recycle Our Waste

The waste from our industrial and commercial operations produces a variety of pollutants. We're taking action in our factories, warehouses, and offices to reach three objectives by 2025:

- Eliminate single-use plastics in our packaging and supply chain
- Reuse 50% of our cardboard and palettes, recycle the rest
- Recycle 80% of our metal, plastic, cardboard and wood waste, put the rest towards energy recovery





Improve Our Employee Satisfaction

Our strong and consistent growth, coupled with the complex issues of the pandemic, has the potential to affect employee health. In 2021, we evaluated the satisfaction of all Petzl employees in France using the Wittyfit platform. The survey covers topics including organization and work load, autonomy, work/life balance, recognition, as well as purpose and values.

Using the results, we created action plans to improve satisfaction — some carried out by leadership and others co-created and lead by the teams.

In 2023, this satisfaction audit will be extended to all Petzl employees on a global level.





■ Improve the Labor Conditions of Our Suppliers

Since 2010, our responsible purchasing initiative has aimed to ensure that all our suppliers comply with the Petzl code of conduct. This code aligns with International Labor Organization (ILO) directives:

Our objectives are to improve social, environmental, health, and safety practices at all of our suppliers.

We've created an annual evaluation of CSR practices for suppliers representing 80% of our purchases. We've offered reinforced support for 25% of our suppliers in their continued improvement plans. We are also collaborating with other manufacturers to combine our audit efforts and reaffirm our CSR standards for common suppliers.





Key New Verticality Products





Harnesses

We've revamped the range of FALCON rescue harnesses, including the three models that give this line its excellent reputation — FALCON for suspended rescue, FALCON ASCENT for rope ascents, and FALCON MOUNTAIN for rescue operations using climbing techniques. These harnesses are now even more lightweight, comfortable, and ergonomic!



FALCON harnesses









Harness Accessories

Big changes are here on the harness accessory front, with a line of products that can be mixed, matched, and connected to make securely carrying your tools easier, without compromising accessibility and efficiency. You also don't want to miss the new TOOLBAG range, now with even more practical and innovative features!









page 71

Key New Verticality Products

Pulleys

Our pulley range is being refreshed and reinforced with the new 2023 iterations of the PRO TRAXION and MINI TRAXION progress-capture pulleys, ready to show off their excellent hauling efficiency.



Anchors

For years, the COEUR PULSE removable anchor has made its users rejoice — the updated version will be no different! As for the NAJA friction saver, we're certain it will quickly find its place in the toolboxes of tree care workers.



page 140





NEW 2023 Key New Lighting Products

Ultra-Compact and Versatile Headlamps

The ARIA headlamps are without a doubt the most exciting addition to the 2023 Petzl line-up. They're practical, lightweight, built for occasional or frequent use, and designed for tradespeople, maintenance professionals, and stage workers. We're introducing two different models, each available in a standard battery or rechargeable battery version.











Petzl's expertise in vertical terrain can be seen in its line of products specifically designed for work at height and rescue professionals. These products address many of the challenges that professionals face every day, such as repeated and intensive use of equipment, weather, or diverse terrain. They're ergonomic in design and are built to maximize simplicity and ease of use, all while meeting the highest standard of quality.



Equipment inspection and individual identification code

To make sure that your equipment is in good condition throughout its useful lifetime, it is necessary to inspect it regularly. Depending on the product's date of manufacture, the individual identification code can be structured in two ways, with 11 or 13 characters.



Special products in black

Certain products are also available in black; they are designed for professions in which stealth is essential.

GENERAL PRINCIPLES OF WORK AT HEIGHT

Warning

- · You must have understood and retained the information from your products' Instructions for Use to be able to apply the techniques presented in this document
- Learning appropriate techniques and methods of protection is your own responsibility. Petzl solutions are given for information purposes only, with no guarantee of their effectiveness in your specific working situation. The relevance of these solutions varies by context, so always carry out your own risk assessment in the field
- Mastering the techniques presented here requires specific training and practice. Work with a specialized organization for all of your training activities

General Information On Falls

The risk of falling is a key concept to master when working at height. The severity of a fall depends on independent factors:

• The weight of the user, including equipment:

The greater the weight, the more energy to be dissipated during the fall.

· The length of the fall:

The longer the fall, the more energy to be dissipated during the fall. The risk of hitting an obstacle is also


· The position relative to the anchor:

When the worker moves above their anchor, the severity of the potential fall increases. The fall factor concept is sometimes used to describe the worker's position relative to the anchor and the severity of the fall. This concept applies to climbing, restraint, or work-positioning situations, when a dynamic rope lanyard is used.

Precautions for the type of system used: the Instructions for Use specify the limitations for use of equipment, particularly in terms of fall distance and the worker's position relative to the anchor

Restraint

A restraint system limits the work zone, to help prevent the worker from entering an area that may present a fall risk. This system is not designed to arrest a fall from height.





Fall Arrest

The fall-arrest system is a belay system that is independent of the means of progression or work positioning.

The fall-arrest system prevents the user from falling to the ground in the event of a fall. Its role is to arrest the fall while limiting the impact force experienced by the user. It must therefore be used with enough clearance to allow for an unobstructed fall.





Work Positioning

A work-positioning system supports the user and allows them to be precisely positioned with the weight on their feet. This system is not designed to arrest a fall; the user must keep their body weight on the positioning system.

The work-positioning system must be used together with a fall-arrest system.





Suspension

The user is working while suspended when they no longer have any weight on their feet, but are supported primarily by the harness. The load is thus shared between the waistbelt and the leg loops/ seat



Impact Force

A fall-arrest system helps limit the impact force sustained by the user.

It is typically made up of an energy absorber that tears in order to limit the forces over a given stopping distance.

A dynamic rope lanyard has a low capacity for energy absorption. Its use requires taking great precautions: reducing the potential fall distance and staying in a work position below the anchor.

A webbing lanyard or a cable with no capacity for energy absorption cannot be used to arrest a fall.

Example for 100 kg

JANE or PROGRESS lanvard without energy absorber



Lanvard with ABSORBICA-I or Y energy absorber



Fc < 6 kN Fc > 6 kN

Fc > 6 kN

Clearance

Clearance is the minimum amount of clear space below the user that prevents the user from hitting an obstacle in the event of a fall

Clearance takes into account:

- Weight of the user
- Length of the fall
- Tearing length of the energy absorber
- Average height of the user
- Safety margin of 1 meter

Clearance Value

The tearing length of the energy absorber, depending on the fall, can only be known based on the manufacturer's information; this is why a clearance estimate is suggested in the Instructions for Use for each fall-arrest device.





Anticipating the Means of Rapid Evacuation

· Limiting the effects of inert suspension:


In the event of a fall where the worker loses consciousness or is incapacitated, inert suspension in the harness presents a mortal danger requiring an urgent response. Work teams must be equipped and trained to quickly evacuate an injured team member.

· Evacuating a victim without assistance:

Procedures for evacuating workers should be determined whenever a new worksite is established.

Releasable systems can be created when installing work ropes to allow evacuation from below.

Working alone must be prohibited: a worker may find themselves alone at height, but at least one person trained in evacuations should be present and equipped on site.



ROPE ACCESS AND CONFINED SPACE







PETZL SOLUTIONS




Rope access work situations often involve environments at significant height. Work can be performed outside or inside, or even in confined spaces, and is not all suited to collective protection. Work done in confined spaces carries additional difficulties related to lack of space and lack of means of autonomous progression.


Examples of operations:


- Placement of rockfall or stabilization nets over a road
- Structural inspection (such as bridge pilings)
- Exterior window cleaning on skyscrapers
- Inspection of tanks

Technical specifics:

- The work area is accessed with ropes by specialized workers trained in rope access techniques
- Access from above is preferred, as it is safer and simpler to set up









Temporary adjustable anchors.

To wrap around an existing structure by precisely adjusting the length of the anchor.



Temporary anchors with multiple configurations.

To best adapt to a situation, whether by connecting directly to the anchor, or connecting to a structure by wrapping around it or using a choker hitch.



Gated ventral attachment point on ASTRO harnesses




The ventral attachment point on ASTRO harnesses is gated for optimal integration of equipment.

Lowering


The RIG descender attaches to the large metal D.

The PODIUM seat connects to the pin with shackles, allowing a direct connection to the descender while preserving ventral attachment point mobility.



Ascending


The CROLL ventral rope clamp connects to the small metal D for greater efficiency on rope ascents.



1. Combined lowering/raising system

Advantage: quick transitions between modes (lowering/raising)


• Disadvantage: rope length is four times the travel distance




2. Independent lowering/raising systems

Advantage: the length of the rope equals the travel distance

 Disadvantage: rigging is required to transition between lowering and raising





How to use the TWIN RELEASE

PETZL

Not all tree work can be done using exterior means such as elevated platforms or ladders. In this case, to move and work, the arborist uses rope progression techniques.

Examples of operations:

- Ornamental tree trimming, to adapt the tree to its environment or to change its overall aesthetic
- Maintenance trimming to remove dead wood and dying branches
- Tree removal (progressive cutting of the trunk from the top) if diseased or presenting a hazard

Technical specifics:

- Access from the base of the tree generally starts by throwing a weighted bag with line attached, which is used to install the access rope on an anchor up in the tree
- · While moving about on the branches, the arborist keeps their weight on the work rope for greater stability and to reduce potential fall distance
- When using any cutting tool (handsaw, chainsaw), the arborist must use two independent belay systems















Tree Access



Doubled rope ascent technique

The arborist ascends the access rope (purple). In the event of a problem, such as a hornet attack, they can self-evacuate with the work rope (blue). A mule knot or releasable knot secures the ZIGZAG.


This versatile ascent technique is adaptable to many situations and allows an access rope to be available during work.



Single rope ascent technique

The access rope is attached to the base of the tree and runs through an appropriate anchor in the tree. It will also be used for work. On a single rope, the ZIGZAG must only be used with the CHICANE.


This technique allows for rapid rescue and efficient climbing with the KNEE ASCENT knee ascender.



Movement Within the Tree

Moving within the tree with two anchors

Using two systems simultaneously on two separate anchors provides optimal balance while cutting and facilitates movement.



ENERGY AND NETWORKS

PETZL

These fields are characterized by structures such as towers, antennas, and wind turbines. The modes of progression are varied and directly related to the structure itself.

Examples of operations:

- Work on high tension lines
- Tower construction
- Maintenance operations in wind farms

Technical specifics:

- The user generally progresses using lifeline, cable or rail type permanent fall arrest systems
- Without access to these, the user must maximize their own safety using personal protective equipment: energy-absorbing lanyard or mobile fall arrester on rope



















Descending on a GRILLON 20 m lanyard


The GRILLON lanyard is attached to the ventral attachment point of the VOLT harness.




Dropped Object Prevention Solution

All products in the line allow you to adapt depending on the weight and type of tools to be secured.

Examples of possible combinations:



PARTNER CHECK



FRAMING AND ROOFING



At this type of work site, the risk of slipping and falling is higher. A safety device must be installed to guard against these hazards.

Examples of operations:


- Framing a building under construction
 Roof repair or waterproofing
- · Roof inspection on industrial sites

Technical specifics:

- When the situation allows, accessing the work area is done using an elevated work platform and the worker secures themselves with an energy-absorbing
- Lacking collective protection, the worker is required to use a fall-arrest system
- Fall-arrest systems are also required when installing collective protection









1. Roof access

Installing a rope with releasable anchor; backed up ascent with the ASAP.









• Working in the center of the roof (limited access zone)







· Working at the edges






With individual positioning system and collective protection.













37

GENERAL RESCUE PRINCIPLES

Inert suspension in a harness, even for a short time. can cause serious physiological harm. In the event of an accident, it is important to respond quickly with the appropriate technique.

Self-Rescue

On sites where the main access could be cut off by fire, people must be ready to quickly evacuate the building. They have evacuation kits. These kits are either portable or installed permanently on the structure. When there is no existing anchor, a hook-based system can be used. In both cases, teams must be regularly trained so as not to panic in the event of a fire.

On-Site Rescue

When a worksite is being set up, the company must establish a risk prevention plan (inventory of risk situations):

- 1. It must protect the personnel from falls from height. The solutions chosen, whether collective or individual, must protect the team members while they work.
- 2. In the event of an incident, the company must be prepared with rescue systems for accessing, releasing, and evacuating the victim. These solutions are established with:
- Ready-to-use rescue kits, adaptable to many situations and simple to use
- Personal equipment for the worker at height (solution requiring experienced and well-trained teams) In both cases, the teams undergo regular training, so they can respond quickly in the event of an accident.


Technical Rescue

Technical rescue teams must be able to respond quickly in any situation. They must choose the quickest, most effective way to access the victim.

- When access is easy or possible by motorized means, they can easily transport the rescue equipment
- In more difficult access situations, they may use rope access techniques from above or below, and their equipment will be lightweight and versatile
- Finally, a helicopter can be used when victim access is complicated and/or remote, for example in the mountains

Cable Lift Evacuation


Cable lift evacuation operations follow an evacuation plan. Rescue kits are put together to meet the specific needs of each operator.



1. Accessing the victim


Accessing the victim can sometimes be complicated. Rope access techniques are used these cases. When access is possible from above, rescuers use rope descent techniques. If an access rope is in place, rescuers can ascend the rope using handled and ventral rope clamp techniques. In other situations, rescuers are obliged to use climbing techniques to reach the victim.





Example of access from below





2. Releasing the victim


Raising

This involves using a mechanical advantage pulley system in order to easily raise the victim. A rescuer working alone uses a mechanical advantage system to reduce effort. The disadvantage is that a long rope is required. If there are enough rescuers, a lower mechanical advantage is used to speed up the operation.


Counterbalance technique


This is a counterweight system. The rescuer is on one side. the victim on the other. The rescuer unweights the rope on the victim's side by pulling upward. The victim ascends and the rescuer descends. The advantage of this system is that it is easy to do with little equipment. Engaging the counterweight is the step that demands the most energy. After that, it is important to be careful to keep the system under control. Beware when there is a significant weight difference between the rescuer and the victim.





Example of counterbalance





3. Evacuating the victim

Downward, the evacuation is done with a descender. This is the easiest technique currently in use. When downward evacuation is impossible, the victim is evacuated upward or horizontally. Upward, rescuers use either a counterweight or hauling technique. Horizontally, one or more ropes are tensioned. One rope is used for carriage, another is used as a back-up belay, and another to move the litter.

Upward

Downward





Horizontally



Technical specifics:

- In this situation, the firefighter must be able to take advantage of any available anchor point inside the building, or as a last resort, a window sill
- The exit generally takes place in an extremely hot, smoke-filled, and hostile environment, adding to the limitations
- The maneuvers must be as simple as possible, for quick action even under intense duress








EXO AP HOOK


EXO AP HOOK is a personal escape system with an anchor hook, designed for situations where the possibility of finding an anchor point is uncertain. It has a self-braking system with anti-panic function for quickly moving horizontally, climbing through a window, and controlling or stopping a descent. If the user pulls too hard on the handle, the anti-panic function brakes and stops the descent automatically.



Going through a window while maintaining the anchor hook on the window sill.

Locking the left leg against the interior wall to control the movement.

Re-establishment below the window while holding the free end of the rope. Descending, one hand uses the handle to start the descent, and the other hand holds the rope to control it.



ON-SITE RESCUE





If a victim is not able to self-rescue, the on-site work team has to respond immediately and move them to safety.

Examples of operations:

- A team member accesses the victim, unhooks them, then lowers the victim unaccompanied
- A team member accesses the victim, releases them, then rappels down with the victim
- The victim is suspended on a preinstalled evacuation system that does not require a team member to access them directly

Technical specifics:

- Unaccompanied evacuation can generally be done using a ready-to-use rescue kit
- Accompanied descent requires proper training, as it implies a mastery of advanced rope access techniques
- In all cases, the rescue method should be as rapid as possible, in order to reduce the risk of suspension trauma, especially when the victim is unconscious





JAG RESCUE KIT

The ready-to-use reversible JAG RESCUE KIT is designed to easily release and lower a victim. It contains a JAG SYSTEM haul kit, a RING OPEN gated ring, an I'D EVAC descender, a CONNEXION FIXE 150 cm anchor strap, a BUCKET bag, and an AXIS 11 mm rope with two sewn terminations.




tion is non-exhaustive. Refer to the other pages as well as the Instructions for Use and technical manuals. Technical training is essential.


Release and evacuation of a victim on a CROLL

Rescue from below by a team member with their own equipment. The rescuer must carry out a risk assessment before responding and verify (among other things) that the victim's ropes are in good condition. The counterbalance system is used to transfer the victim onto the descender.

The rescuer ascends on the victim's safety line.

- The rescuer transfers themselves to the RIG descender, tethers to the victim, and moves the ASAP up above the victim.
- 2. The rescuer puts a second connection in place. They can then remove the equipment that is in the victim's way.





- 3. On the victim's rope, the rescuer installs a foot loop in counterbalance on the ASCENSION handled rope clamp.
- 4. In counterbalance on the foot loop, the rescuer prevents the rope from running through the CROLL and raises the victim. They remove the CROLL and take up as much rope slack as possible in the RIG descender.




5. The rescuer, hanging on the RIG, removes the ASCENSION. They install a braking carabiner and accompany the victim to the ground.



Release and rescue using a reversible rescue kit

- Unaccompanied evacuation (when victim doesn't require monitoring or for a free-hanging evacuation):
- 1. Victim suspended by a lanyard, with the energy absorber torn by the fall.
- 2. Hauling (allows the victim to be released).
- 3. Lowering the victim.










For more information, see technical tips at



TECHNICAL RESCUE





Technical rescue teams respond when the situation is especially difficult and requires significant resources to be deployed.

Rescue examples:

- Following a vehicle roll-over into a ravine, the victims are rescued via motorized means
- Evacuation of an injured worker from a location that is difficult to access
- Helicopter rescue operations in mountainous terrain

Technical specifics:

- Technical rescue teams have to operate on a variety of different types of terrain and have complete mastery of progression and belay techniques on a rope
- When the terrain allows, downward evacuation is preferred because of the gravity-assist
- Upward evacuation is a team effort that requires perfect coordination by everyone involved. It demands techniques which are sometimes particularly complex, such as creating a haul system using lightweight pulleys, or counterweight techniques





















PETZL

The MAESTRO enables controlled lowering of loads up to 250 kg (MAESTRO S) and 280 kg (MAESTRO L).




Rope redirect with SPIN L1D pulley

Rope redirect when raising: sheave rotates in the direction of the ascent.




Extra friction makes for a more comfortable descent: the sheave does not rotate, and the facets provide additional friction on the rope.



with REEVE

for clean and compact rigging of your highline rescue system.




Lowering with two MAESTROs in parallel, controlled by a single operator

One operator simultaneously controls the two devices to optimize load-sharing between the two ropes, while limiting the potential fall distance in case one rope fails.






Addition of a back-up system to address potential operator error.




Evacuation on a tensioned highline

The REEVE combines two pulleys with a rigging plate



Positioning the litter attendant with JAG SYSTEM

The JAG SYSTEM allows the attendant to efficiently adjust their position, even with all of their weight on the lanyard and without good support for the feet.






Hauling with MAESTRO or PRO TRAXION

The mechanical advantage of a haul system is a theoretical advantage, but efficiency is affected by several factors in practice: pulley efficiency, rope diameter, rate of hauling, regularity of movement...

Simple directional (1:1)



Here are some test results using a constant rate of 1.5 m/minute. Other results are available in the technical information at www.petzl.com

Haul system (3:1)



CABLE LIFT EVACUATION



If cable lift equipment fails, the operations manager must evacuate passengers according to the evacuation plan. This evacuation must be done within a predefined time frame and is generally conducted by the operations staff.

Technical specifics:


- Accessing the passengers is done by moving along the cable, from the towers
 These operations are managed
- These operations are managed simultaneously by multiple autonomous teams, generally made up of:
- Someone suspended on the cable who evacuates passengers and whose movements are protected by a team member on the tower
- on the lower

 Someone on the ground who receives passengers and guides the movement of the team member on the cable


 The success of these operations hinges
- The success of these operations hinges largely on the instruction, training and practice of the operations staff (at least once a year)









50 PETZL-COM





HARNESSES

Simple to use, comfortable, with numerous accessories and technically suited to the requirements of the work they are designed for, Petzl harnesses set the standard in terms of safety and efficiency for workers at height.



To give each user the best possible fit, Petzl harnesses are adjustable at the waist, shoulders, and leg loops. They are equipped with different types of buckles:



FAST buckles FAST buckles are fastened

and unfastened quickly and easily without loss of adjustment, even when wearing gloves.



Self-locking buckles

These buckles do not require re-threading to be locked: they adjust easily in seconds.

General Purpose Harnesses

Fall-Arrest Harnesses

Fall-arrest harnesses with a simple, lightweight design.


















































Fall-Arrest and Work-Positioning Harnesses

Fall-arrest and work-positioning harnesses that are comfortable and easily donned.







Versatile and very comfortable harnesses for fall arrest, work positioning, and suspension.



















Specialized Harnesses

Rope Access Harnesses

Very comfortable harnesses, with integrated ventral rope clamp to facilitate ascending a rope.

















Tree Care Harnesses

Lightweight harnesses suitable for various rescue environments.













Very comfortable harnesses, with attachment bridge for greater freedom of movement in the trees

Equipment designed for rope rescue (such as in confined spaces or on cable lifts).





Certified to European and Russian standards, these harnesses are designed specifically for fall arrest. More specifically, they allow for the attachment of ABSORBICA energy-absorbing lanyards or an ASAP or ASAP LOCK mobile

· Lightweight, ergonomic design

NEWTON harnesses are designed to avoid interfering with the movement of the worker. The anatomical and lightweight design is close-fitting yet allows optimal freedom of movement



How to put on the NEWTON harness

· Easy to use



Easy to fasten and unfasten harness

The FAST LT PLUS sternal buckle allows the harness to be quickly and easily fastened and unfastened without loss of adjustment, even with gloves. The buckle's locking system limits the risk of accidental unfastening.



Ready access to tools

The equipment loops simplify tool organization, and the slots allow a TOOLBAG pouch to be added.

Versatile



Textile sternal attachment point Lightweight and abrasion-resistant,

the textile sternal attachment point allows attachment of a fall-arrest



Metal dorsal attachment point

Made of anodized aluminum for high strength, the dorsal attachment point allows attachment of a fall-arrest

· Great simplicity



NEWTON harnesses have color-coded (yellow/ black) straps allowing rapid identification of the upper and lower parts of the harness before donnina.



NEWTON harnesses

NEWTON European Version

Fall-Arrest Harness

NEWTON is a lightweight, ergonomic fall-arrest harness. It is easy to use and its straps are colorcoded to make donning easier. The harness allows immediate access to tools, with equipment loops and slots for the TOOLBAG pouch. Its textile sternal attachment point and metal dorsal attachment point provide tremendous versatility. It is certified to European and Russian standards.

Quick donning



Equipped with padded shoulder straps and FAST LT buckles on the leg loops, the NEWTON FAST harness dons very easily with both feet on the ground, without loss

NEWTON FAST European Version

Quick-donning fall-arrest harness

NEWTON FAST is a lightweight, ergonomic fall-arrest harness that can be quickly donned. It is equipped with padded shoulder straps and FAST LT buckles on the leg loops, allowing the harness to be donned with both feet on the ground, without loss of adjustment. The harness allows immediate access to tools, with equipment loops and slots for the TOOLBAG pouch. Its textile sternal attachment point and metal dorsal attachment point provide tremendous versatility. It is certified to European and Russian standards.

Optimal Comfort



The NEWTON EASYFIT harness is designed to keep its shape, and includes two pockets for stowing small items. The leg loops are padded and equipped with FAST LT buckles, enabling the harness to be easily donned while keeping both feet on the ground, without loss of adjustment.



NEWTON EASYFIT European Version

Comfortable and quick-donning fall-arrest harness

NEWTON EASYFIT is a comfortable, ergonomic fall-arrest harness that can be quickly donned. It is equipped with padded shoulder straps and FAST LT buckles on the leg loops, allowing the harness to be donned with both feet on the ground, without loss of adjustment. Its lightweight, breathable design offers two zippered pockets for storing small items. The harness allows immediate access to tools, with equipment loops and slots for the TOOLBAG pouch. Its textile sternal attachment point and metal dorsal attachment point provide tremendous versatility. It is certified to European and Russian standards.

Accessories



HI-VIZ Vest for NEWTON Harnesses

Fluorescent-colored vest with reflective strips makes the worker highly visible in a variety of lighting conditions. It installs quickly and easily on NEWTON, NEWTON FAST, and NEWTON EASYFIT harnesses. The sternal buckle, multiple attachment points, and lanyard connector parking all remain accessible during use for optimal freedom of movement.



Leg Loop Padding for NEWTON Harnesses

Leg loop padding that can be added to NEWTON and NEWTON FAST harnesses to increase comfort. or used as replacement padding on NEWTON EASYFIT harnesses.





































Certified to North American, European, and Russian standards, these harnesses are designed specifically for fall arrest. More specifically, they allow for the attachment of ABSORBICA energy-absorbing lanyards or an ASAP or ASAP LOCK mobile

· Lightweight, ergonomic design

NEWTON harnesses are designed to avoid interfering with the movement of the worker. The anatomical and lightweight design is close-fitting yet allows optimal freedom of movement



How to put on the NEWTON harness

· Easy to use



Easy to fasten and unfasten

The FAST LT PLUS sternal buckle allows the harness to be quickly and easily fastened and unfastened without loss of adjustment, even with gloves. The buckle's locking system limits the risk of accidental unfastening.



Lanyard connector parking

The harnesses have a parking system for fall-arrest lanyard connectors on each shoulder strap. In the event of a fall, the system releases the MGO connector and allows the absorber to be deployed.

Versatile

PETZL.COM



The harnesses have a metal dorsal attachment point that allows attachment of a fall-arrest system and a textile dorsal attachment point that allows attachment of a self retracting fall-arrest system.

· Easy harness inspection



The sternal and dorsal attachment points are equipped with visual indicators; a red tag appears after a fall to indicate that the harness must be retired.

· Great simplicity



NEWTON harnesses have color-coded (yellow/ black) straps allowing rapid identification of the upper and lower parts of the harness before donnina.



NEWTON International Version

NEWTON harnesses

Fall-Arrest Harness

NEWTON is a lightweight, ergonomic fall-arrest harness. It is easy to use and its straps are colorcoded to make donning easier. The harness allows immediate access to tools, with equipment loops and slots for the TOOLBAG pouch. Its textile sternal attachment point and metal and textile dorsal attachment points provide tremendous versatility. It ergonomically stows MGO connectors and has

fall indicators. It is certified to North American, European, and Russian standards.

Quick donning



Equipped with padded shoulder straps and FAST LT PLUS buckles on the leg loops. the NEWTON FAST harness dons very easily with both feet on the ground, without loss of

NEWTON FAST International Version

Quick-donning fall-arrest harness

NEWTON FAST is a lightweight, ergonomic fall-arrest harness that can be quickly donned. It is equipped with padded shoulder straps and FAST LT PLUS buckles on the leg loops, allowing the harness to be donned with both feet on the ground, without loss of adjustment. The harness allows immediate access to tools, with equipment loops and slots for the TOOLBAG pouch. Its textile sternal attachment point and metal and textile dorsal attachment points provide tremendous versatility. It ergonomically stows MGO connectors and has fall indicators. It is certified to North American, European, and Russian standards.

Optimal comfort



The NEWTON EASYFIT harness is designed to keep its shape, and includes two pockets for stowing small items. The leg loops are padded and equipped with FAST LT PLUS buckles, enabling the harness to be easily donned while keeping both feet on the ground, without loss of adjustment.



NEWTON EASYFIT International Version

Comfortable and guick-donning fall-arrest harness

NEWTON EASYFIT is a comfortable, ergonomic fall-arrest harness that can be quickly donned. It is equipped with padded shoulder straps and FAST LT PLUS buckles on the leg loops, allowing the harness to be donned with both feet on the ground, without loss of adjustment. Its lightweight, breathable design offers two zippered pockets for storing small items. The harness allows immediate access to tools, with equipment loops and slots for the TOOLBAG pouch. Its textile sternal attachment point and metal and textile dorsal attachment points provide tremendous versatility. It ergonomically stows MGO connectors and has fall indicators. It is certified to North American, European, and Russian standards.

Accessories



HI-VIZ Vest for NEWTON Harnesses

Fluorescent-colored vest with reflective strips makes the worker highly visible in a variety of lighting conditions. It installs quickly and easily on NEWTON, NEWTON FAST, and NEWTON EASYFIT harnesses. The sternal buckle, multiple attachment points, and lanyard connector parking all remain accessible during use for optimal freedom of movement.



Leg Loop Padding for NEWTON Harnesses

Leg loop padding that can be added to NEWTON and NEWTON FAST harnesses to increase comfort. or used as replacement padding on NEWTON EASYFIT harnesses.



































These harnesses help provide fall protection for the worker and enable them to position themselves at a workstation, with a GRILLON lanyard, for example. Additionally, they are specifically designed to facilitate vertical progression on a rail or cable (European versions

· Quick and easy donning



VOLT and VOLT WIND harnesses are very quick to don. The waistbelt and leg loops are equipped with FAST LT PLUS/FAST LT buckles, allowing the harness to be easily donned while keeping both feet on

· Optimal comfort



Comfortable work positioning

Wide, semi-rigid waistbelt and leg loops give excellent support. The lightweight, breathable construction maximizes air flow

Ventral attachment point suitable for vertical progression on a rail or cable

The LADDER CLIMB attachment point allows for ventral attachment of the fallarrest trolley, which distributes the load on the waistbelt, providing optimal comfort. In the event of a fall, the attachment point automatically moves upward to a sternal position to help keep the body in a vertical post-fall position (only on European versions).



Folding side attachment points

Side attachment points can be folded down to prevent them snagging accidentally when not in use

· Easy to use



The harnesses have a parking system for the MGO connectors on fall-arrest lanyards on each shoulder strap. In the event of a fall, the system releases the MGO connectors and allows the absorber to be deployed.

· For work on towers and antennas



VOLT harnesses have a wide waisthelt with equipment loops on the back for easy organization of work tools

· For work inside wind turbine towers

VOLT WIND harnesses have dorsal wear protectors to reduce wear on the straps when moving about inside a wind turbine tower.



VOLT harnesses

VOLT® European Version

Fall-arrest and work-positioning harness with attachment point for vertical progression on rail or cable

The VOLT fall-arrest and work-positioning harness is very quick to don, thanks to the FAST LT PLUS and FAST LT buckles that allow it to be donned with both feet on the ground. The wide, semi-rigid waistbelt and leg loops provide excellent support. Its lightweight, breathable construction maximizes air flow. Its LADDER CLIMB attachment point allows for ventral attachment of the fall-arrest trolley, providing optimal comfort during progression. It is certified to European and Russian standards.



VOLT® International Version

Fall-arrest and work-positioning harness

The VOLT fall-arrest and work-positioning harness is very quick to don, thanks to the FAST LT PLUS buckles that allow it to be donned with both feet on the ground. The wide, semi-rigid waistbelt and leg loops provide excellent support. Its lightweight, breathable construction maximizes air flow. It features a textile dorsal attachment point designed for connecting a self-retracting fall-arrest system. It is certified to North American and European standards.



VOLT WIND harnesses

VOLT® WIND European Version

Fall-arrest and work-positioning harness for the wind power industry with attachment point for vertical progression on rail or cable

The VOLT WIND fall-arrest and work-positioning harness is very quick to don, thanks to the FAST LT PLUS and FAST LT buckles that allow it to be donned with both feet on the ground. The wide, semi-rigid waistbelt and leg loops provide excellent support. Its lightweight, breathable construction maximizes air flow. Its LADDER CLIMB attachment point allows for ventral attachment of the fallarrest trolley, providing optimal comfort during progression. It has wear protectors on the waistbelt and dorsal point to limit wear when moving about inside the wind turbine tower. It is certified to Furonean and Russian standards



VOLT® WIND International Version

Fall-arrest and work-positioning harness for the wind power industry

The VOLT WIND fall-arrest and work-positioning harness is very quick to put on, thanks to the FAST LT PLUS buckles that allow it to be donned with both feet on the ground. The wide, semi-rigid waistbelt and leg loops provide excellent support. Its lightweight, breathable construction maximizes air flow. It features a textile dorsal attachment point designed for connecting a self-retracting fallarrest system. It has wear protectors on the waistbelt and dorsal point to limit wear when moving about inside the wind turbine tower. It is certified to North American and European standards







How to install the VOLT seat

Seat for VOLT® Harnesses

Seat for VOLT harnesses for greater comfort while suspended

The seat for the VOLT harness attaches to the designated slots on the harness. It provides additional comfort during prolonged suspension.



































These harnesses are used for fall protection, for positioning at a workstation, and for working comfortably while suspended.

Comfortable construction



Wide, semi-rigid waistbelt and leg loops give excellent support. The lightweight, breathable construction maximizes air flow.

Convenient buckle system



Easy to adjust

The AVAO harnesses can be adjusted at the waistbelt and shoulder straps. These adjustment points are equipped with self-locking DOUBLEBACK buckles. These do not require re-threading to be locked: the harness adjusts easily in seconds.

Available in easier donning version

The leg loops of AVAO harnesses are equipped with FAST / FAST LT buckles that facilitate donning the harness with both feet on the ground or with large footwear, without loss of adjustment, even when wearing gloves.

· Efficiently organize work tools



AVAO harnesses are equipped with six equipment loops on the sides and at the rear of the waistbelt. They are shaped to facilitate clipping carabiners. Each harness also has slots designed for the CARITOOL tool holder and the TOOLBAG tool pouch.

· Lanyard connector parking



The harnesses have a parking system for fall-arrest lanyard connectors on each shoulder strap. In the event of a fall, the system releases the MGO connector and allows the absorber to be deployed.

A complete solution, with dorsal attachment point



The AVAO BOD and AVAO BOD FAST full-body harnesses are equipped with a dorsal attachment point for connecting a fall-arrest system. In the event of a fall on this attachment point, a shorter adjustment of the length between the waistbelt and the leg loops means the load is taken up on the leg loops, allowing the user to remain suspended longer while awaiting rescue.

AVAO® BOD / AVAO® BOD FAST European Version

Comfortable harness for fall arrest, work positioning, and suspension

The AIAO BOD fall-arrest, work-positioning, and suspension harness is designed for greater comfort in a variety of different situations. The wide, semi-rigid waistbelt and leg loops provide excellent support. Its lightweight, breathable construction maximizes air flow. The shoulder straps have a system for stowing the fall-arrest lanyard connectors and keeping them within reach. The DOUBLEBACK self-locking buckles at the rear of the harness, between the waistbelt and the leg loops, allow for a shorter adjustment when the dorsal attachment point is used. The harness also makes it easier to carry and organize work tools, with multiple gear loops and slots for attaching CARITOOL tool holders and TOOLBAG tool pouches. The harness is fastened with a SCREW-LOCK manual locking carabiner and is certified to European and Russian standards. AVAO BOD Fabtures leg loops with DOUBLEBACK self-locking buckles; AVAO BOD FAST has leg loops with FAST LT buckles.



AVAO® BOD / AVAO® BOD FAST International Version

Comfortable harness for fall arrest, work positioning, and suspension

The AIAO BOD fall-arrest, work-positioning, and suspension harness is designed for greater comfort in a variety of different situations. The wide, semi-rigid waistbelt and leg loops provide excellent support. Its lightweight, breathable construction maximizes air flow. The shoulder straps have a system for stowing the fall-arrest lanyard connectors and keeping them within reach. The DOUBLEBACK self-locking buckles at the rear of the harness, between the waistbelt and the leg loops, allow for a shorter adjustment when the dorsal attachment point is used. The harness also makes it easier to carry and organize work tools, with multiple gear loops and slots for attaching CARITOOL tool holders and TOOLBAG tool pouches. The harness has an integrated fall indicator on the dorsal attachment point and is fastened with a TRIACT-LOCK automatic locking carabiner. It is certified to North American and European standards. AIAO BOD features leg loops with DOUBLEBACK self-locking buckles; AIAO BOD FaST has leg loops with FAST buckles.

Lightweight and flexible solution



Combining a sit harness with a separate chest harness is a more lightweight solution if the user does not need a dorsal attachment point. It is also a solution for hard-to-fit body types, as it allows users to combine different seat and chest harness sizes.



TOF

Chest harness for sit harness

The TOP chest harness transforms AVAO SIT, AVAO SIT FAST, FALCON, FALCON MOUNTAIN, and SEQUOIA SRT sit harnesses into fall-arrest harnesses. The padded shoulder straps are widely spaced to reduce neck chafing. When the waistbelt is loaded, the straps help distribute the load over the shoulders. They also have a system for stowing the fall-arrest lanyard connectors and keeping them within reach.



AVAO® SIT / AVAO® SIT FAST

Comfortable sit harness for work positioning and suspension

The AVAO SIT work positioning and suspension sit harness is designed for greater comfort in a variety of situations. The wide, semi-rigid waistbelt and leg loops provide excellent support. Its lightweight, breathable construction maximizes air flow. The harness also makes it easier to carry and organize work tools, with multiple gear loops and slots for attaching CARITCOL tool holders and TOOLBAG tool pouches. This sit harness is designed to be converted into a fall-arrest harness when combined with a TOP chest harness, or into a rope access harness when combined with a TOP chest harness. The AVAO SIT leg loops have DOUBLEBACK self-locking buckles; AVAO SIT FAST leg loops have FAST LT buckles.





























Designed for rope access, these harnesses allow the worker to be protected in the event of a fall and to position themselves at the workstation. The gated ventral attachment point facilitates rope ascents and makes working while suspended more comfortable.

· Efficiently integrate equipment



The gated attachment point allows the user

- CROLL ventral rope clamp on the ventral point for greater efficiency on rope ascents
 - PROGRESS lanvard directly on the ventral attachment point
- PODIUM seat on the axle of the attachment point, allowing the load to be supported directly by the descender, while offering mobility at the ventral attachment

· Efficiently organize work tools



ASTRO harnesses are equipped with six equipment loops on the sides and at the rear of the waistbelt. They are shaped to facilitate clipping carabiners. Each harness also has slots designed for the CARITOOL tool holder and the TOOLBAG tool pouch.

· Ultra-comfortable design



The waistbelt and the leg loops of ASTRO harnesses are semi-rigid and wide in order to limit pressure points and provide effective support. These two zones are sculpted. and lined with breathable foam padding for optimal comfort while suspended, and for good ventilation. This construction also facilitates harness donning.

· Convenient buckle system



Easy to don

The leg loops of ASTRO harnesses are equipped with FAST / FAST LT buckles that facilitate donning the harness with both feet on the ground or with large footwear, without loss of adjustment, even when wearing gloves.

Easy to adjust



The waisthelt and shoulder strans are equipped with self-locking DOUBLEBACK / DOUBLEBACK PLUS buckles for quick and easy adjustment

· A complete solution,



ASTRO BOD FAST full-body harnesses are equipped with a dorsal attachment point for attaching a fall-arrest system. In the event of a fall on this attachment point, a shorter adjustment of the length between the waistbelt and the leg loops means the load is taken up on the leg loops, allowing the user to remain suspended longer while awaiting rescue.

with dorsal attachment point



ASTRO® BOD FAST European Version

Ultra-comfortable rope access harness

ASTRO harnesses





ASTRO® BOD FAST International Version

Ultra-comfortable rope access harness

With an integrated CROLL L ventral rope clamp, the ASTRO BOD FAST harness is designed for greater efficiency and comfort during rope ascents. The gated ventral attachment point allows you to efficiently integrate equipment (such as rope clamp or seat). The wide, semi-rigid waistbelt and leg loops provide excellent support. They are contoured and lined with breathable foam padding for comfort while suspended. The DOUBLEBACK self-locking buckles at the rear of the harness, between the waistbelt and the leg loops, allow for a shorter adjustment when the dorsal attachment point is used. The harness also makes it easier to carry and organize work tools. with multiple gear loops and slots for attaching CARITOOL tool holders and TOOLBAG tool pouches. It has a fall indicator on the dorsal attachment point and is certified to North American and European standards. ASTRO BOD FAST (international version) features leg loops with FAST buckles.

· Lightweight and flexible solution



Combining a sit harness with a separate chest harness is a more lightweight solution if the user does not need a dorsal attachment point. It is also a solution for hard-to-fit body types, as it allows users to combine different seat and chest harness sizes

TOP CROLL® S

Chest harness for sit harness, with integrated CROLL S ventral rope clamp

The TOP CROLL S integrates a CROLL S ventral rope clamp to transform ASTRO SIT FAST, AVAO SIT, AVAO SIT FAST, FALCON, FALCON ASCENT, and SEQUOIA SRT harnesses into rope access harnesses. The textile sternal attachment point optimally reduces weight and bulk. The padded shoulder straps are widely spaced to reduce neck chafing. When the waistbelt is loaded, the straps help distribute the load over the shoulders. The rear connections on each side of the waistbelt offer excellent stability.



TOP CROLL® L

Chest harness for sit harness, with integrated CROLL L ventral rope clamp

The TOP CROLL L integrates a CROLL L ventral rope clamp to transform ASTRO SIT FAST, AVAO SIT, AVAO SIT FAST, FALCON, FALCON ASCENT and SEQUOIA SRT harnesses into rope access harnesses. The padded shoulder straps are widely spaced to reduce neck chafing. When the waistbelt is loaded, the straps help distribute the load over the shoulders.



ASTRO® SIT FAST

Ultra-comfortable sit harness for rope access

The ASTRO SIT FAST rope access sit harness features a gated ventral attachment point that allows you to efficiently integrate equipment (such as rope clamp, lanyard, or seat). The wide, semi-rigid waistbelt and leg loops provide excellent support. They are contoured and lined with breathable foam padding for comfort while suspended. The harness also makes it easier to carry and organize work tools, with multiple gear loops and slots for attaching CARITOOL tool holders and TOOLBAG tool pouches. This sit harness is designed to be converted into a full-body harness when combined with a TOP CROLL S or L chest harness. The ASTRO SIT FAST features leg loops with FAST LT buckles.





PODIUM

Seat for prolonged suspension

The PODIUM provides optimal comfort during prolonged suspension. The wide seat offers excellent stability. Rigid sides prevent the webbing straps from cutting into the thighs. The easy-to-use seat has two gear loops and a rear hook, making it easier to store in order to facilitate movement. It connects to ASTRO BOD FAST and ASTRO SIT FAST harnesses with two shackles (find a description of the shackles on page 71).





































These harnesses are designed for arborists: they allow great mobility in the tree and optimally distribute the load between the waistbelt and the leg loops. They also provide excellent lumbar support in the many work phases where the arborist has their weight on the harness.

Comfortable



The semi-rigid, extra-wide waistbelt provides excellent support for the user. It is also sculpted and lined with foam padding for improved comfort while suspended.

• Ergonomic



Gated attachment points

The gated attachment points facilitate connection of a ZILLON or MICROFLIP lanyard. They also allow installation of several attachment bridges (adjustable or fixed), as well as accessories like RING attachment rings or SWIVELs, directly on the attachment bridge



Easy to don

The leg loops of SEQUOIA harnesses are equipped with FAST LT PLUS buckles that facilitate donning the harness with both feet on the ground or with large footwear, without loss of adjustment. even when wearing gloves.

Accessories

Accessories for the SEQUOIA line of harnesses allow each user to adapt the equipment to their needs.



· For single rope ascent



The SEQUOIA SRT features a ventral attachment point for installing a ZIGZAG mechanical Prusik with the CHICANE and KNEE ASCENT accessories.

techniques



SEQUOIA SRT harness

SEQUOIA® SRT

Tree care sit harness for single-rope ascent techniques

The SEQUOIA SRT is a tree care sit harness for single rope ascent techniques. It has a ventral attachment point that allows a ZIGZAG or ZIGZAG PLUS mechanical Prusik to be installed with CHICANE and KNEE ASCENT accessories. The extra-wide, semi-rigid waistbelt and leg loops provide comfort for the arborist. It is equipped with DOUBLEBACK PLUS self-locking buckles on the waistbelt and FAST LT PLUS buckles on the leg loops. The gated attachment points allow the user to easily connect a ZILLON or MICROFLIP lanyard, or to install several attachment bridges and accessories directly on the bridge. The harness also makes it easy to carry and organize work tools, with multiple equipment loops and slots for attaching CARITOOL tool holders.

· For doubled rope ascent techniques



The SEQUOIA harness waistbelt is equipped with a FAST buckle for quick and simple fastening and unfastening without loss of adjustment, even while wearing gloves.



SEQUOIA®

Tree care sit harness for doubled rope ascent techniques

The SEQUOIA is a tree care sit harness for doubled rope ascent techniques. The extra-wide, semi-rigid waistbelt and leg loops provide comfort for the arborist. The waistbelt is equipped with a FAST buckle for guick and easy fastening and unfastening without loss of adjustment, even while wearing gloves. The leg loops have FAST LT PLUS buckles. The gated attachment points allow the user to easily connect a ZILLON or MICROFLIP lanyard, or to install several attachment bridges and accessories directly on the bridge. The harness also makes it easy to carry and organize work tools, with multiple equipment loops and slots for attaching CARITOOL tool holders.





Shoulder Straps (only for SEQUOIA® SRT)

Shoulder straps for SEQUOIA SRT sit harness designed for taking the load from the waistbelt and redistributing it to the shoulders for improved comfort. They connect to the ventral attachment point of the harness and to the two slots at the rear of the waistbelt.



Seat

Wide seat for a comfortable working position while suspended. The width is adjustable, reducing bulk and making it easier to move within the tree. It connects to the two gated points on the SEQUOIA and SEQUOIA SRT arborist sit harnesses, using the two shackles.



Adjustable Attachment Bridge

Adjustable attachment bridge for SEQUOIA and SEQUOIA SRT harnesses allows quick and precise adjustment of the position of progression tools installed on the bridge.



Attachment Bridge

Attachment bridge for connection to the two gated attachment points of the SEQUOIA and SEQUOIA SRT arborist sit harnesses, to optimize lateral mobility.



The RING connection ring can be used to create multiple anchors or be installed directly onto the SEQUOIA and SEQUOIA SRT harnesses' attachment bridges to improve the arborist's lateral mobility.



Shackles for connecting a seat. Find a description of the shackles on page 71.

































Designed for rescuers, these harnesses are lightweight for increased mobility and rapid movement during operations. Having the choice between several different models allows you to choose the best fit for different environments that may be encountered in the field.

· Comfortable, lightweight design



Comfortable, lightweight design

The semi-rigid and slim waistbelt and leg loops with 3D foam padding provide the range of FALCON harnesses with an optimal comfort-to-weight ratio to limit bulk.



Compact side attachment points

The textile side attachment points on harnesses in the FALCON range are designed for occasional use and limit bulk and weight.

Ergonomic



Easy to adjust

The FALCON and FALCON ASCENT narnesses feature DOUBLEBACK PLUS self-locking buckles on the waistbelt and FAST LT buckles on the leg loops, making them quick and easy to put on and adjust

· Efficiently organize equipment and work tools



Equipment loops and slots

The range of FALCON harnesses feature equipment loops on the sides and at the rear of the waistbelt. Each harness also has slots designed for the CARITOOL tool holder and the TOOLBAG tool pouch.

· For working while suspended



The metal ventral attachment point on the FALCON harness distributes the load between the waistbelt and the leg loops while suspended.



FALCON harnesses

FAI CON

Lightweight sit harness for suspended rescue

FALCON is a lightweight sit harness designed for rescue operations involving suspension. The metal ventral attachment point distributes the load between the waistbelt and leg loops. The design is lightweight and comfortable, joining the slim, semi-rigid waistbelt and leg loops with 3D foam padding. It provides optimal balance between low weight and comfort, as well as reduced bulk, when you're standing, moving, or hanging. The DOUBLEBACK PLUS self-locking buckles on the waistbelt and the FAST LT buckles on the leg loops make it guick and easy to put on and adjust. The rear buckle allows a TOP or TOP CROLL L chest harness to be attached.

· For efficiency when ascending



The two-part ventral attachment point of the FALCON ASCENT harness increases the efficiency of rope ascents when using a CROLL ventral rope clamp.



FALCON ASCENT

Lightweight and comfortable sit harness for rescue operations and work involving

FALCON ASCENT is a lightweight sit harness designed for rescue operations and work involving rope ascent. The two-part ventral attachment point fastens with an OMNI carabiner and provides greater efficiency when ascending a rope. The design is lightweight and comfortable, joining the slim, semi-rigid waistbelt and leg loops with 3D foam padding, which provides optimal balance between low weight and comfort, as well as reduced bulk. The DOUBLEBACK PLUS self-locking buckles on the waistbelt and the FAST LT buckles on the leg loops make it quick and easy to put on and adjust. The rear buckle allows a TOP CROLL L chest harness to be attached.

· For operations using climbing techniques



The textile bridge construction of the FALCON MOUNTAIN harness favors progression with climbing techniques and makes it comfortable to walk in.



FALCON MOUNTAIN

Ultra-lightweight and comfortable sit harness for rescue operations that involve climbing techniques

FALCON MOUNTAIN is an ultra-lightweight sit harness designed for rescue operations that involve climbing techniques. Its ventral attachment point has a textile bridge for mobility when progressing and comfort when walking. The design is very lightweight and comfortable, joining the slim, semirigid waistbelt and leg loops with 3D foam padding, which provides an optimal balance between low weight and comfort, as well as reduced bulk. The DOUBLEBACK self-locking buckles on the waistbelt and leg loops make it quick and easy to put on and adjust. The rear plastic loop allows a TOP or TOP CROLL L chest harness to be attached.

Accessory





CHEST'AIR

Chest harness for sit harnesses

The CHEST'AIR chest harness transforms the FALCON, FALCON MOUNTAIN, AVAO SIT, and SEQUOIA SRT sit harnesses into fall-arrest harnesses. With multiple certifications, CHEST'AIR can be attached to a climbing or mountaineering harness to keep a victim upright during a rescue. It simply connects to the ventral attachment point of the sit harness and fastens via the FAST LT buckle at the chest, for quick donning. It adapts easily to different body types with its DOUBLEBACK PLUS self-locking buckles on the shoulder straps and ventral strap. Made with 3D foam padding, the CHEST'AIR chest harness provides additional comfort while hanging.



Evacuation Triangles

Evacuation triangles are mainly used for rescue on cable lifts and by firefighters. They allow unequipped people to be evacuated in minimal time.



THAI FS

Safety chest collar and comfortable evacuation triangle with shoulder straps

The THALES safety chest collar and evacuation triangle is designed for rescue operations. cable lift evacuations, and helicopter evacuations. The chest collar configuration allows the evacuee to be secured in an emergency and then evacuated with the triangle. Passing from the chest collar configuration to the triangle configuration is quick with the use of three hook and loop straps. The ergonomic shape of the seat and the presence of shoulder straps makes suspension more comfortable than with a classic evacuation triangle. Color-coding differentiates the back and seat, as well as the different straps and closure system, making it easier to put on the evacuee. The high-strength TPU tarp material allows regular to intensive use.



PITAGOR

Comfortable evacuation triangle with shoulder straps

The PITAGOR rescue triangle is designed for rescue operations and cable lift evacuations. The ergonomic shape of the seat and the presence of shoulder straps makes suspension more comfortable than with a classic evacuation triangle. Color-coding differentiates the back and seat, as well as the closure system, making it easier to put on the evacuee. The high-strength TPU tarp material allows regular to intensive use.

Rescue Litter



Tilting device for NEST litter

The STEF tilting device joins the three connection points of the NEST litter and allows it to be easily tilted according to the terrain. It has three Am'D TRIACT-LOCK connectors for automatic locking of the connection points, and a swivel for precise orientation of the litter.



Litter for confined spaces

The NEST litter was developed in partnership with the French national caving rescue organization. It allows a victim to be transported horizontally, vertically, or at an angle. It handles easily and simplifies loading the victim. It is suitable for technical rope rescue, particularly in confined spaces.



The bag for the NEST litter allows it to be transported and stored. The openings at either end allow the handles of the litter to protrude, for easier handling. It is equipped with three handles and a bandolier system for easier transport.





RING2RING

Rigid double ring for sit harnesses with textile bridges

Specifically designed to be used on sit harnesses with textile bridges, the RING2RING accessory is primarily for use during helicopter rescue. Its function as an additional attachment ring allows the rescuer to better organize their equipment at the attachment point and makes it easier for the winch operator to access the connection point when connecting the rescuer.





RING2SIDE

Accessory that allows you to convert a textile lateral attachment point into a metal attachment point

The RING2SIDE accessory allows you to convert a textile lateral attachment point into a metal attachment point on the FALCON and FALCON ASCENT harnesses. Its large ring and intuitive clipping orientation makes it easier to attach equipment. It can also be folded down to avoid being snagged when not in use.



Spreader for harnesses

Spreader for full-body harnesses or sit harnesses used in conjunction with a chest harness allowing upright descent (for confined spaces).



Installing and uninstalling the CARITOOL



Harness tool holder

The CARITOOL tool holder provides one-handed tool access and storage. The stabilizing clip allows it to slip onto the harness straps and stay in place. The gate has a protective feature that limits accidental snagging. It is available in two sizes



RING OPFN

Multidirectional gated ring

See page 112 for details on the RING OPEN gated ring



Shackles for connecting a seat. Connects to the gated attachment point on a harness, allowing you to efficiently integrate equipment.



Lanyard Connector Parking

Lanyard connector parking accessory (pack of 2)

Lanyard connector parking accessories install on the shoulder straps of VOLT, VOLT WIND, AVAO BOD, AVAO BOD FAST, and ASTRO BOD FAST harnesses and TOP, TOP CROLL S, and TOP CROLL L chest harnesses. They allow the MGO connectors on fall-arrest lanyards to be stowed on each shoulder strap, keeping the connectors within reach and the lanyard out of the user's way. In the event of a fall, the system releases the MGO connectors and allows the absorber to be deployed.



PORTO

Webbing equipment loop

Webbing equipment loop that attaches to a pack's internal loop for organizing equipment.



BOITBAG

Equipment pouch for organizing a hammer, bolting gear, and other equipment. It has two pockets and exterior holster.





































Petzl offers a complete solution that secures equipment when working at height to help prevent tools from being dropped. These products were designed in accordance to the ANSI/ISEA 121-2018 standard for dropped object prevention solutions.










• TOOLINK S & TOOLTAPE For tools up to 2.3 kg

• TOOLINK M

• TOOLINK L For tools up to 5 kg

For tools up to 3 kg









TOOLBAG 1.5

Small-volume tool pouch

system is easy to use with one hand. It can be connected to the harness using the INTERFAST accessory, reducing bulk on the harness and making the pouch more accessible. It is durably constructed and can be used on a daily basis without worrying about wear.

TOOLBAG 3

Medium-volume tool pouch

The TOOLBAG 3 tool pouch allows you to store tools. The opening and closure system is easy to use with one hand. It can be connected to the harness using the INTERFAST accessory, reducing bulk on the harness and making the pouch more accessible. It is durably constructed and can be used on a daily basis without worrving about wear.

TOOLBAG 6

Large-volume tool pouch

The TOOLBAG 6 tool pouch allows you to carry a large number of tools. The opening and closure system is easy to use with one hand. It can be connected to the harness using the INTERFAST accessory, reducing bulk on the harness and making the pouch more accessible. It is durably constructed and can be used on a daily basis without worrying about wear.

INTERFAST

Quick connection accessory for the TOOLBAG and TOOLEASH

INTERFAST is an accessory that allows you to connect a TOOLBAG tool pouch and a TOOLEASH dropprevention tether. It is versatile and compatible with any harness that has slots. The design is compact and durable to limit bulk on the harness and keep all the attached elements secure when working at height.

TOOLEASH

Extendable drop-prevention tether for tools weighing up to 5 kg

The TOOLEASH extendable tether allows you to attach tools to prevent dropping them when working at height. The high-strength elasticized tether is compact on your harness. The versatile connection system allows you use it as a long-term tool tether or switch between tools, depending on your needs. TOOLEASH is part of a complete solution for dropped tool prevention.

TOOLINK S and TOOLTAPE

Attachments for tools weighing up to 2.3 kg (pack of 5 TOOLINK S tether and a TOOLTAPE adhesive)

TOOLINK S is an attachment that allows you to connect and secure a tool with no connection hole and a smooth, straight handle when working at height. It can be installed on tools weighing up to 2.3 kg, using

TOOLTAPE adhesive. The ergonomic connection point allows you to quickly clip and unclip, so it's easy to use.

TOOLINK M

Attachment for tools weighing up to 3 kg with a connection hole (pack of 5)

TOOLINK M is an attachment that allows you to connect and secure a tool weighing up to 3 kg with an integrated connection hole when working at height. The ergonomic connection point allows you to quickly clip and unclip, so it's easy to use.

TOOLINK I

Attachment for tools weighing up to 5 kg (pack of 5)

TOOLINK L is an attachment that allows you to connect and secure a heavier tool weighing up to 5 kg when working at height. The ergonomic connection point allows you to quickly clip and unclip, so it's easy to use.

MINO

Non-PPE accessory carabiner

This product is not PPE (Personal Protective Equipment). Find a description of the MINO on page 160.









































	References	Certifications	References	Certifications		Damed						I	Heimht	Weight
				Octunications		Dorsal	Sternal	Ventral	Side	Size	Waistbelt	Leg Loops	Height	
						'							,	
	C073AA01		C073BA01							1	70 - 93 cm	47 - 62 cm	165 - 185 cm	900 g 1125 g (4)
NEWTON	C073AA02		C073BA02			•	•	-	-	2	83 - 120 cm	50 - 65 cm	175 - 200 cm	900 g 1155 g (4)
NEWTON	C073CA01		C073DA01 C073IA00 (1)	CE EN 361						1	70 - 93 cm	47 - 62 cm	165 - 185 cm	1010 g 1355 g (4)
	C073CA02	CE EN 361 EAC UKCA	C073DA02 C073IA01 (1)	EAC ANSI Z359.11 CSA Z259.10		•	•	-	-	2	83 - 120 cm	50 - 65 cm	175 - 200 cm	1050 g 1395 g (4)
	C073EA00	JSFAD	C073FA00	JSFAD						0	65 - 80 cm	44 - 59 cm	160 - 180 cm	1310 g 1655 g (4)
NEWTON EASYFIT	C073EA01		C073FA01			•	•	-	-	1	70 - 93 cm	47 - 62 cm	165 - 185 cm	1370 g 1715 g (4)
	C073EA02		C073FA02							2	83 - 120 cm	50 - 65 cm	175 - 200 cm	1420 g 1765 g (4)
rnoccoc	C073GA00	CE EN 20471 ANSI 107		_				_			_		_	380 g
iriesses	C073HA00	CSA Z96 UKCA												500 g
TON Harnesses	C073JA00	-	-	-		-	-	-	-	-	-	-	-	70 g
tioning Harnesses														2100 a
														2100 g 2300 g (4)
VOLT		CE EN 361	C072CA01	ANSI Z359.11		•	•	• (5)	•	1	70 - 93 cm	47 - 62 cm	165 - 185 cm	2150 g 2350 g (4)
		EN 358 EN 813 EAC		CSA Z259.10 CE EN 361 CE EN 358	_									2230 g 2430 g (4)
		UKCA JSFAD		UKCA JSFAD										2150 g 2350 g (4)
VOLT WIND						•	•	• (5)	•					2200 g 2400 g (4)
	C072BA02		C072DA02							2	83 - 120 cm	50 - 65 cm	175 - 200 cm	2280 g 2480 g (4)
	C072EA00	CE EN 358 (3) UKCA (3)	-	ANSI Z359.11 (6) CSA Z259.10 (6) UKCA (3)		-	-	-	-	-	-	-	-	1050 g
Work Positioning	and Suspension													
Work i osidoning,	C071AA00		C071CA00							0	65 - 80 cm	44 - 59 cm	160 - 180 cm	2045 g 2215 g (4)
AVAO BOD	C071AA01		C071CA01			•	•	•	•	1	70 - 93 cm	47 - 62 cm	165 - 185 cm	2090 g 2260 g (4)
	C071AA02	CE EN 361 EN 358	C071CA02	ANSI Z359.11 NFPA 2500 class III						2	83 - 120 cm	50 - 65 cm	175 - 200 cm	2170 g 2340 g (4)
	C071BA00 C071BA03 (1)	EN 813 EAC UKCA	C071DA00 C071DA03 (1)	CE EN 361 CE EN 358 CE EN 813						0	65 - 80 cm	44 - 59 cm	160 - 180 cm	2000 g 2350 g (4)
AVAO BOD FAST		JOPAU		. UKCA		•	•	•	•	1	70 - 93 cm	47 - 62 cm	165 - 185 cm	2045 g 2400 g (4)
	C071BA02									2	83 - 120 cm	50 - 65 cm	175 - 200 cm	2125 g 2485 g (4)
	C081AA00 C081AA01 (1)	CE EN 361 (2) EAC UKCA	-	-		-	•	-	-	-	-	-	160 - 200 cm	660 g
	C079AA00									1	70 - 93 cm	47 - 62 cm	165 - 185 cm	1175 g
AVAO SIT	C079AA01					-	-	•	•	2	83 - 120 cm	50 - 65 cm	175 - 200 cm	1190 g
	C079AA03 (I)	CE EN 358 EN 813 EAC	-	-						0	65 - 80 cm	44 - 59 cm	160 - 180 cm	1115 g
		UKCA												
AVAO SIT FAST	C079BA01	UNON				-	-	•	•	1	70 - 93 cm	47 - 62 cm	165 - 185 cm	1130 g
	EASYFIT Irrnesses TON Harnesses VOLT VOLT WIND Work Positioning, AVAO BOD	NEWTON NEWTON FAST C073GA00 C073GA00 C073GA00 C073EA00 C073EA00 C073EA00 C073HA00 C073HA00 C072AA01 C072AA02 C072AA02 C072AA02 C072BA01 C072BA02 C072BA01 C071BA01 C071	NEWTON FAST C073AA02 NEWTON FAST C073CA02 C073EA00 NEWTON EASYFIT C073EA00 NEWTON EASYFIT C073EA00 C073EA00 C073EA00 C073EA00 C073EA00 C073HA00 C073HA00 C073HA00 C073HA00 CE EN 20471 ANSI 107 CSA 236 UKCA UKCA TON Harnesses C073JA00 CE EN 20471 ANSI 107 CSA 236 UKCA C072AA00 VOLT C072AA00 CO72AA00 C072AA00 C072BA00 C072BA00 C072BA00 C072BA00 C072BA00 C072BA00 C072BA00 C072BA00 C071BA00 AVAO BOD C071BA00 C071BA00 C071BA01 C071BA03 (1) C071BA02 C071BA00 C071BA01 C071BA01 C071BA03 (1) C071BA02 C071BA00 C071BA01 C071BA01 C071BA01 C071BA01 C071BA02 C071BA01 C071BA01 C071BA01 C071BA02 C071BA01 C071BA01 C071BA01 C071BA01 C071BA02 C071BA01 C071BA01 C071BA01 C071BA01 C071BA01 C071BA02 C071BA01 C071BA02 C071BA01 C071BA01 C071BA01 C071BA01 C071BA02 C071BA01	NEWTON C073AA02 C073BA02 C073BA02 C073BA02 C073BA02 C073BA02 C073BA02 C073BA02 C073BA00 C073BA01 C073BA02 C073BA00 C073BA01 C073BA02 C073BA02 C073BA02 C073BA02 C073BA02 C073BA02 C073BA02 C073BA02 C073BA00 C073BA02 C073BA00 C073BA02 C073BA00 C073BA00 C073BA02 C073BA00 C	NEWTON	NEWTON	NEWTON C073A402	NEWTON COTGRAND2 COTGRAND2 COTGRAND2 COTGRAND2 COTGRAND COTGRA	NEWTON GUTSAA02 GE EN 361 GUTSAA02 GE EN 361 GUTSAA02 GUTSAA02 GUTSAA02 GUTSAA03 GUTSAA03	NEWTON C073AA02 C073AA02 C073AA02 C073AA02 C073AA01 C1 EN 301 C	NEWTON COSTANAZE NEWTON COSTANAZE NEWTON COSTANAZE OCITARAZE OCITARAZE	NEWTON COTSMAD COTSMAD	NOWTON PAPER 1	NEWTON 1001-040



BOLTBAG

C11 A




		European	n Versions	Inter	national Versions			Attachm	ent Points			:	Sizes		101
		References	Certifications	References	Certifications		Dorsal	Sternal	Ventral	Side	Size	Waistbelt	Leg Loops	Height	Weight
pe Access Harnesse	s			LC003BA00											
	¥)	C083AA00	CE EN 361 EN 358	C083BA00 C083BA03 (1)	ANSI Z359.11, ANSI Z459.1 NFPA 2500 class III						0	65 - 80 cm	44 - 59 cm	160 - 180 cm	2020 g / 2480 g
STRO BOD FAST		C083AA01	EN 813 FN 12841 type B	C083BA01 C083BA04 (1)	CSA Z259.10, CE EN 361, EN 358 EN 813		•	•	•	•	1	70 - 93 cm	47 - 62 cm	165 - 185 cm	2065 g / 2530 g
	<i>E2E</i>	C083AA02	EAC UKCA	C083BA02	EN 12841 type B UKCA, JSFAD						2	83 - 120 cm	50 - 65 cm	175 - 200 cm	2145 g / 2620 g
	<u> </u>			C083BA05 (1)											
OP CROLL S	/\	C081BA00	CE EN 361 (2) EN 12841 type B EAC, UKCA, JSFAD	-	-		-	•	-	-	=	-	-	160 - 200 cm	515 g
OP CROLL L		C081CA00	CE EN 361 (2) EN 12841 type B EAC, UKCA, JSFAD	-	-		-	•	-	-	-	-	-	160 - 200 cm	600 g
		C085AA00									0	65 - 80 cm	44 - 59 cm	160 - 180 cm	1025 g
STRO SIT FAST	200	C085AA01	CE EN 358 EN 813	-	_		_	_	•	•	1	70 - 93 cm	47 - 62 cm	165 - 185 cm	1040 g
		C085AA02	EAC UKCA								2	83 - 120 cm	50 - 65 cm	175 - 200 cm	1055 g
ODIUM		S071AA00	-	-	-		-	-	-	-	-	-	-	-	1060 g
		301 11 0 100													1000 g
ee Care Harnesses															
		C069BA00									0	65 - 80 cm	44 - 59 cm	-	1580 g
	SEQUOIA SRT	C069BA01	CE EN 250				-	-	•	•	1	70 - 93 cm	47 - 62 cm	-	1630 g
QUOIA		C069BA02	CE EN 358 EN 813	-	_						2	83 - 120 cm	50 - 65 cm	-	1700 g
		C069AA00	EAC UKCA								0	65 - 80 cm	44 - 59 cm	-	1480 g
	SEQUOIA	C069AA01					-	-	-	•	1	70 - 93 cm	47 - 62 cm	-	1530 g
		C069AA02									2	83 - 120 cm	50 - 65 cm	-	1600 g
oulder Straps		C069DA00	-	-	-		-	-	-	-	-	-	-	-	190 g
at		S069AA00	-	-	-		-	-	-	-	-	-	-	-	920 g
justable Attachment Br	idge	C69R	-	-	-		-	-	-	-	-	-	-	-	220 g
		n C069CA00									S				65 g
achment Bridge		n C069CA01	_	-	_		_	_	_	_	М	1 .	_	_	70 g
		n C069CA02									1	1			75 g
											_				9
escue Harnesses			1						,				,		,
		C038DA02 (1)	CE EN 813								0	65 - 80 cm	44 - 59 cm	-	900 g
	FALCON	C038DA00 / C038DA03 (1)	CE EN 358 EAC	-	-		-	-	•	•	1	70 - 93 cm	47 - 62 cm	-	915 g
EW2023		C038DA01 / C038DA04 (1)	UKĆA								2	83 - 120 cm	50 - 65 cm	-	945 g
ALCON (FALCON ASCENT	C038EA00	CE EN 813 CE EN 358				_	_			1	70 - 93 cm	47 - 62 cm	-	800 g
LEGGIN U	TALOON ASOLINI	C038EA01	CE EN 358 EAC, UKCA				_	_	•	•	2	83 - 120 cm	50 - 65 cm	-	830 g
	FALCON	C038FA00	CE EN 813, CE EN 358 EN 12277 type C		_						1	70 - 93 cm	47 - 62 cm	-	670 g
	MOUNTAIN	C038FA01	EAC, UKCA	-	-		-	-	•	•	2	83 - 120 cm	50 - 65 cm	-	700 g
HEST'AIR NEW2023		C098AA00	CE EN 361 (3), CE EN 12277 type D, EAC, UKCA	-	-		-	•	-	-	-	-	-	-	525 g
vacuation Triangles ar	nd Litter		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,												
HALES		C061AA00	CE EN 1497, CE EN 1498		_										4045 -
IALES		CUSTAAUU	types A & B, EASA CM-CS-005, UKCA	=	-		-	-	-	-	-	-	-	-	1315 g
TAGOR		C060AA00	CE EN 1497, CE EN 1498 type B, EASA CM-CS-005, UKCA	-	-		-	-	-	-	-	-	-	-	1300 g
EST		S061AA00	-	-	-		-	-	_	-	-	-	-	-	13,1 kg
ref		S059AA00 / S059BA00 (5)	_	1.	_		-	_	_	_	_	_	_	_	640 g / 620 g
ag for NEST Litter		S062AA00	-	-	-		-	-	-	-	-	-	-	-	1860 g
				1								1		1	1
	References	Certif	ications	Color	Weight	;				References		Certi	fications	Volume	Weight
arness Accessories								cessories (co	ontinued)						
W2023 RING2RING	C030AA00		2275 type Q, UKCA, EAC	-	100 g		NEW2023 INTE			S051AA00		4		-	55 g
V2023 RING2SIDE	C030BA00		e M, UKCA, EAC	-	75 g		NEW2023 TOO			S049AA00		1		-	56 g
Т	L54	CE, I	UKCA	-	520 g		NEW2023 TOO		LTAPE	S050AA00		1		-	8 g
RITOOL S	P042AA00		_		35 g		NEW2023 TOO	LINK M		S050BA00		ΔΝΕΙΛΕΕ	A 121-2018	-	11 g
ARITOOL L	P042AA01				75 g		NEW2023 TOO	LINK L		S050CA00			.A 121-2010	-	16 g
NG OPEN	P28	CE EN 3	62, UKCA	-	70 g		NEW2023 TOO	LBAG 1.5		S047BA00				1,5	100 g
nackles	C087AA00		-	-	20 g		NEW2023 TOO	LBAG 3		S047BA01		1		31	140 g
		1										1			045 -
anyard	C088AA00			Yellow	45		NEW2023 TOO	LBAG 6		S047BA02				61	245 g
nyard onnector Parking	C088AA00		-	Yellow Black	45 g		NEW2023 TOO	LBAG 6		S047BA02				61	245 g

6 PETZLOOM 77

(1) Black harness, (2) with ASTRO SIT FAST, AVAO SIT, AVAO SIT FAST, FALCON, FALCON ASCENT, SEQUOIA SRT harnesses, (3) with FALCON, FALCON MOUNTAIN, AVAO SIT, SEQUOIA SRT harnesses, (4) international version, (5) for NEST litter before 2020.

HELMETS

Essential for work at height and certain industrial activities, helmets provide the user with effective protection from falling objects, or in the event that the user falls.



Comfortable Helmets

Helmets with webbing suspension for optimal comfort.











Lightweight Helmets

Lightweight, compact helmets with hybrid construction liner (EPP and EPS foams).











Protective Eye and Face Shields

Protective eye and face shields for VERTEX and STRATO helmets.





















Hats and Balaclava Hats and balaclava for protection against rain and cold.

































Essential for work at height and certain industrial activities, helmets provide the user with effective protection from falling objects, or in the event that the user falls. With a very secure fit, Petzl helmets are comfortable to wear in a variety of different situations. With a complete line of entirely modular accessories, they meet the diverse needs of professionals.

• Excellent fit on the head



CENTERFIT adjustment

The CENTERFIT adjustment system allows the helmet to be perfectly centered on the head. The headband is easy to adjust by simultaneously rotating the two side adjustment wheels, even while wearing gloves.



FLIP&FIT system

The FLIP&FIT system immediately positions the headband in a low position, to provide a secure fit on the head. The headband folds into the shell for easy storage and transport.

• DUAL chinstrap strength is adjustable, to adapt to a variety of different work situations



The DUAL chinstrap allows the worker to adjust chinstrap strength in order to adapt the helmet

to different environments: work at height (EN 12492) or on the ground (EN 397). The clip has two positions, corresponding to the following two uses:

- Higher strength to limit the risk of the helmet coming of in a fall (strength > 50 daN)

- Lower strength to limit the risk of strangulation, by releasing if snagged when user is

at ground level (strength < 25 daN)

Solution for Different	Protection Needs		Unventilated Shell		th Ventilated Shell
				W.	
		VERTEX	STRATO	VERTEX VENT	STRATO VENT
PENETRATION IMPACT PROTECTION	Protection against falling objects		•		•
VENTILATION	Ventilation holes allow airflow through the helmet		-		•
ELECTRICAL PROTECTION	Protection against electrical hazards		•		-
MOLTEN METAL PROTECTION	Protection against molten metal splash		•	•	-
LATERAL DEFORMATION	Protection against lateral deformation		•		•

• Modular accessories

Extensive line of protective eye and face shields, headlamps, and accessories

- Eye shields, face shields for protection against electric arc hazards, specific shields for tree care Headlamps for lighting
- Nametag holder, nape protector, helmet protectors, chinstraps



































· A variety of choices



Available in assorted colors

VERTEX helmets are available in seven standard colors; STRATO helmets are available in four colors. VERTEX and STRATO helmets are also available in two HI-VIZ versions, with a fluorescent outer shell (yellow or orange), phosphorescent clips, and reflective bands for optimal visibility of the worker, day or night.

Multiple certifications

Depending on the model, Petzl helmets meet the requirements for the following certifications:

- European EN 397, EN 12492 and EN 50365
- American ANSI Z89.1
- Canadian CSA Z94.1
- Russian FAC
- Australian AS/NZS 1801

· Easy to install and modular design

All Petzl helmets can be adapted to additional needs for protection or lighting in just a few seconds, thanks to the EASYCLIP system and a variety of inserts.






The EASYCLIP system allows quick installation of a protective shield. EASYCLIP is easy to install and is compatible with all Petzl helmets and shields. It comes with every protective eve and face shield

· Petzl Custom for helmets





a logo and reflective stickers Pre-mount Petzl eye and

of your choice onto the helmet, for a ready-made solution, with each helmet delivered in an individual transport pouch. Available for orders of 20 helmets or more.

Comfortable construction



VERTEX helmets have a six-point webbing suspension system, conforming to the shape of the head for maximum comfort. Shock absorption is achieved through deformation of the external shell.





Comfortable helmet

The VERTEX helmet is very comfortable, with its six-point textile suspension and CENTERFIT and FLIP&FIT systems, which provide a secure fit on the head. The adjustable-strength chinstrap makes it ideal for both work at height and on the ground. The unventilated outer shell protects against electrical hazards, molten metal splash, and flames. With its potential for integration of a Petzl headlamp, hearing protection, and multiple accessories, it is an entirely modular helmet, meeting the additional needs of professionals.



VERTEX® HI-VIZ

Comfortable high-visibility helmet

VERTEX and VERTEX VENT helmets

The high-visibility version features a fluorescent outer shell with phosphorescent clips and reflective bands for optimal visibility of the worker, day or night.



VERTEX® VFNT

Comfortable ventilated helmet

The VERTEX VENT helmet is very comfortable, with its six-point textile suspension and CENTERFIT and FLIP&FIT systems, which provide a secure fit on the head. The adjustable-strength chinstrap makes it ideal for both work at height and on the ground. It has ventilation holes with sliding shutters to allow airflow through the helmet. With its potential for integration of a Petzl headlamp, hearing protection, and multiple accessories, it is an entirely modular helmet, meeting the additional needs of professionals.



VERTEX® VENT HI-VIZ

Comfortable, ventilated, high-visibility helmet

STRATO and STRATO VENT helmets

The high-visibility version features a fluorescent outer shell with phosphorescent clips and reflective bands



for optimal visibility of the worker, day or night.

Lightweight construction



The liner of STRATO helmets is designed in two parts: EPP (expanded polypropylene) and EPS (expanded polystyrene), for reduced weight. Shock absorption is achieved through deformation of the liner.



STRATO®

Lightweight helmet

The STRATO helmet is very lightweight and comfortable, with CENTERFIT and FLIP&FIT systems which provide a secure fit on the head. The adjustable-strength chinstrap makes it ideal for both work at height and on the ground. The unventilated outer shell protects against electrical hazards, molten metal splash, and flames. With its potential for integration of a Petzl headlamp, hearing protection, and multiple accessories, it is an entirely modular helmet, meeting the additional needs of professionals.



STRATO® HI-VIZ

Lightweight, high-visibility helmet

The high-visibility version features a fluorescent outer shell with phosphorescent clips and reflective bands for optimal visibility of the worker, day or night.



STRATO® VENT

Lightweight, ventilated helmet

The STRATO VENT helmet is very lightweight and comfortable, with CENTERFIT and FLIP&FIT systems which provide a secure fit on the head. The adjustable-strength chinstrap makes it ideal for both work at height and on the ground. Ventilation holes allow airflow through the helmet. With its potential for integration of a Petzl headlamp, hearing protection, and multiple accessories, it is an entirely modular helmet, meeting the additional needs of professionals



STRATO® VENT HI-VIZ

Lightweight, ventilated, high-visibility helmet

The high-visibility version features a fluorescent outer shell with phosphorescent clips and reflective bands for optimal visibility of the worker, day or night.





































Protective Eve and Face Shields





Accessories



► How to install a face shield



VIZIR

Eye shield with EASYCLIP system for VERTEX and STRATO helmets

The VIZIR eye shield protects the eyes against projectile hazards. It is easy to install on VERTEX and STRATO helmets with the EASYCLIP attachment system. It also has scratch-resistant and anti-fog coatings.



VIZIR SHADOW

Tinted eye shield with EASYCLIP system for VERTEX and STRATO helmets

The VIZIR SHADOW eye shield provides eye protection against projectile hazards. It is easy to install on VERTEX and STRATO helmets with the EASYCLIP attachment system. It has a level 2.5 solar protection filter, and anti-scratch and anti-fog treatments.



Face shield for protection against electric arc hazards, with EASYCLIP system for VERTEX and STRATO helmets

The VIZEN face shield protects against electric arc hazards. This full-coverage shield offers face and eye protection while preserving peripheral vision. It is easily installed on VERTEX and STRATO helmets using the EASYCLIP attachment system. It also has scratch-resistant and anti-fog coatings.



Face shield for tree care for VERTEX and STRATO helmets, with EASYCLIP system The VIZEN MESH face shield protects against flying wood chips and shavings. This full-coverage shield

offers complete face protection while providing good visibility. It is easily installed on VERTEX and STRATO helmets using the EASYCLIP attachment system.



Nametag Holder for VERTEX® and STRATO® Helmets

The nametag holder for VERTEX and STRATO helmets allows quick identification of the worker. It is easy to install and provides effective rain protection for business cards.



Nape Protector for VERTEX® and STRATO® Helmets

The nape protector for VERTEX and STRATO helmets provides effective sun and rain protection for the nape of the neck. Fluorescent colors give the worker optimal visibility, night and day. Available in two colors.



Protector for VERTEX® Helmet

The protector for the VERTEX helmet is easy to install and protects the shell from soiling and splash.



Protector for STRATO® Helmet

The protector for the STRATO helmet is easy to install and protects the shell from soiling and splash.




Storage Bag for VERTEX® and STRATO® Helmets

Storage bag to protect VERTEX and STRATO helmets during storage and transport. Accessories are also protected in a closed interior compartment.



DUAL Chinstrap for VERTEX® and STRATO® Helmets

It allows the worker to modify chinstrap strength in order to adapt the helmet to different environments: work at height or on the ground. Available in two colors and in a long version.

































Accessories



Headband With Comfort Foam for VERTEX® and STRATO® Helmets Ready-to-install headband with comfort foam (standard or absorbent), to extend the life of a VERTEX or STRATO belimet. Pack of 5.



Comfort Foam for VERTEX® and STRATO® Helmets

Comfort foam (standard or absorbent), to be installed on the headband of a VERTEX or STRATO helmet, to prolong its life.



Upper Foam for STRATO® Helmet

Upper foam installs on the liner of the STRATO helmet, to extend its life. It is comfortable, absorbent, and machine-washable



Transparent Stickers for VERTEX® and STRATO® Helmets

Transparent stickers allow VERTEX and STRATO helmets to be customized using a permanent marker or laser printer.



Reflective Stickers for VERTEX®

Reflective stickers for increased visibility of VERTEX helmets.



Reflective Stickers for STRATO®

Reflective stickers for increased visibility of STRATO helmets.







Buff® is a trademark and property of Original Buff®



LINER

Breathable cap for wicking perspiration

LINER is a breathable cap for wicking perspiration and drying quickly. The seamless fitted design makes it comfortable to wear under a helmet, without getting in the way.



BEANIE

Protective cap for cold and wind


BEANIE is a cap that protects the head on cold and windy days. The design, specific to each zone, optimizes thermal insulation and regulates moisture. The seamless fitted design and side vents make it comfortable to wear under a helmet, without getting in the way.



BALACI AVA

Balaclava for protection against cold and wind

BALACLAVA protects the head, face, and neck on cold, windy days. The design, specific to each zone, optimizes thermal insulation and regulates moisture. The seamless fitted design and multiple side vents make it comfortable to wear under a helmet, without getting in the way.



Helmets



		European Certifications	U.S. Certifications	Canadian Certification	Russian Certification	Australian Certification		IMPACT PROTECTIO			RATION ECTION		CHINSTRA STRENGT		VENTILATION		LECTRICA ROTECTIO		MOLTEN METAL PROTECTION	FL	AME STANCE	LATERAL DEFORMATION	L	DW RATURE	HIGH VISIBILITY	Head Circumference	Weight	000.7
							EN 397	EN 12492	ANSI Z89.1	EN 397	ANSI Z89.1	EN 397 (3)	EN 12492 (4)	ANSI Z89.1	EN 12492	EN 397	EN 50365	ANSI Z89.1	EN 397	EN 397	ANSI Z89.1	EN 397	EN 397	ANSI Z89.1	ANSI Z89.1	Head		
Comfortable	A010AA01	CE 80 397	ANSI Z89.1 Type I Class E	CSA Z94.1 Type I Class E (5)	EAC	AS/NZS 1801	•		•	•	•			•	_	•	•	•	•	•	•	•		•	_	53-63 cm	490 g	
VERTEX	A010AA04 A010AA05 A010AA06	EN 12492 (6) UKCA	Type I Class E	(5)	LAC	A3/N23 1001									·				·			·			-	cm	450 g	(
VERTEX HI-VIZ	A010DA00 A010DA01	CE EN 397 EN 50365 EN 12492 (6) UKCA	ANSI Z89.1 Type I Class E	CSA Z94.1 Type I Class E (5)	EAC	AS/NZS 1801	•	•	•	•	•	•	•	•	-	•	•	•	•	•	•	•	•	•	•	53-63 cm	495 g	
	A010CA00	CE EN 12492 EN 397 UKCA	ANSI Z89.1 Type I Class C	-	EAC	-	•	•	•	•	•	•	•	•	•	_	-	-	•	•	•	•	•	•	-	53-63 cm	490 g	į.
VERTEX VENT	A010CA04 A010CA05 A010CA06		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,																									-
VERTEX VENT HI-VIZ	A010EA00 A010EA01	CE EN 12492 EN 397 UKCA	ANSI Z89.1 Type I Class C	-	EAC	-	•	•	•	•	•	•	•	•	•	-	-	-	•	•	•	•	•	•	•	53-63 cm	495 g	
Lightweight H	A020AA00	CE EN 397 (1) EN 50365 (2) UKCA	ANSI Z89.1 Type I Class E	-	EAC	-	•	•	•	•	•	•	•	•	-	•	•	•	•	•	•	•	•	•	-	53-63 cm	435 g	
STRATO HI-VIZ	A020CA00 A020CA01	CE EN 397 (1) EN 50365 (2) UKCA	ANSI Z89.1 Type I Class E	-	EAC	-	•	•	•	•	•	•	•	•	-	•	•	•	•	•	•	•	•	•	•	53-63 cm	445 g	
STRATO VENT	A020BA00 A020BA01 A020BA02 A020BA03	CE EN 12492 UKCA	ANSI Z89.1 Type I Class C	-	-	-	•	•	•	•	•	•	•	•	•	-	-	-	-	-	-	•	•	•	-	53-63 cm	415 g	CUS
STRATO VENT HI-VIZ	A020DA00 A020DA01	CE EN 12492 UKCA	ANSI Z89.1 Type I Class C	-	-	-	•	•	•	•	•	•	•	•	•	-	-	-	-	-	-	•	•	•	•	53-63 cm	425 g	

LANYARDS AND ENERGY ABSORBERS

Whether for work positioning or to have an energy absorber that limits the force transmitted to the user in the event of a fall, Petzl offers a complete line of lanyards for different applications.




Depending on the model, the ends of Petzl lanyards are equipped with plastic sheaths or with a STRING. These items help keep the connector positioned on the major axis and make it easier to clip. They also protect the ends from abrasion due to repeated rubbing.




Plastic sheath STRING

General Purpose Lanyards



Specialized Lanyards



Positioning lanyards allow the user to position themselves precisely at a workstation, with feet supported on the structure. They can adapt to different anchoring configurations.

Versatile



Double mode use

The GRILLON lanvard can be used in double mode (on the harness side attachment points) when the user works with weight on their feet. This type of attachment provides better load distribution on the belt. The user precisely adjusts their position by pressing on the lanyard's pivoting cam.



Single mode use

When the anchor is located above the user, the GRILLON lanyard is connected to the harness ventral attachment point, so that the load is comfortably distributed between the waistbelt and leg loops. The user adjusts their position by operating the handle, while holding the free end of the lanyard.

· Easy to handle



Sewn terminations with plastic sheaths

Sewn terminations increase strength (compared to a knotted termination) while reducing bulk. These plastic sheaths protect the stitching from abrasion and facilitate handling by holding the connector in position.

· Differentiation of lanyard lengths



Lanyard length can be immediately identified by a color-coded label at the connector end.

· Petzl Custom for work-positioning lanyards





- Petzl Custom allows you to choose: · Lanyard type: Standard
- or high-strength rope
- Lanyard color Lanvard length
- Type of lanyard-end connectors and harness connector

The assembly of various components of your choice offers a ready-made solution specific to the user

· Without connector



GRILLON lanyards are sold without connectors, so that they can be combined with different connector types, depending on the user's requirements.



GRILLON

Adjustable lanyard for work positioning

The GRILLON adjustable lanyard is used to make work-positioning systems to complement a fall-arrest system. Its length can be very easily and precisely adjusted as necessary for comfortable positioning at the workstation. Depending on the configuration, it can be used in single or double mode. GRILLON is available in seven lengths (2, 3, 4, 5, 10, 15 and 20 m), and also in black. It is certified to North American, European, and Russian standards.

GRILLON PLUS



The GRILLON PLUS lanyard is used to make work-positioning systems, to complement a fallarrest system. Its length can be very easily and precisely adjusted as necessary for comfortable positioning at the workstation. The aramid fiber rope provides excellent abrasion resistance. Depending on the configuration, it can be used in single or double mode. GRILLON PLUS is available in two lengths: 2 and 3 m, and is certified to North American, European, and Russian standards

· With HOOK connector



GRILLON HOOK lanyards are equipped with a HOOK auto-locking connector, ideal for connections using the harness side attachment points.

GRILLON HOOK European Version

Adjustable work-positioning lanyard with HOOK connector

The GRILLON HOOK adjustable lanyard is used to make work-positioning systems to complement a fall-arrest system. Its length can be very easily and precisely adjusted as necessary for comfortable positioning at the workstation. Its HOOK connector is ideal for using the lanvard in double mode on the harness side attachment points. The GRILLON HOOK (European version) is available in four lengths (2, 3, 4 and 5 m) and is certified to European and Russian standards.

GRILLON HOOK International Version

Adjustable work-positioning lanyard with HOOK connector

The GRILLON HOOK adjustable lanyard is used to make work-positioning systems to complement a fall-arrest system. Its length can be very easily and precisely adjusted as necessary for comfortable positioning at the workstation. Its HOOK connector is ideal for using the lanyard in double mode on the harness side attachment points. GRILLON HOOK (international version) is available in four lengths (2, 3, 4 and 5 m) and is certified to North American and European standards.

· With MGO connector



GRILLON lanyards, in combination with an MGO auto-locking connector, are ideal for connection to metal structures or to large-diameter cables and bars.



GRILLON MGO

Adjustable work-positioning lanyard with MGO connector

The GRILLON MGO lanyard is used to make work-positioning systems to complement a fallarrest system. Its length can be very easily and precisely adjusted as necessary for comfortable positioning at the workstation. Connector with large gate opening is ideal for connection to metal structures or to large-diameter cables and bars. GRILLON MGO is available in two lengths: 2 and 3 m, and is certified to North American and European standards.




































These lanyards are used when there is a fall hazard and they are connected to the sternal or dorsal attachment point on the harness. The integrated absorber provides energy absorption in a fall, limiting the impact force on the user.

· Progressive energy absorption adapted to the user's weight



In the event of a fall, the tearing of the energy absorber webbing limits the impact force on the user. The lanyards are designed for users who weigh between 50 and 130 kg. The progressive tearing of the webbing reduces the deceleration on lightweight

· Compact and abrasion-resistant energy absorber



The energy absorber is very compact to avoid hindering the user's movements or interfering with work. A durable fabric pouch helps protect the energy absorber from abrasion and potential contaminants.

· Different connectors depending on the type of structure



MGO or MGO OPEN large-opening connectors

MGO and MGO OPEN connectors allow for connection to metal structures or to large-diameter cables and bars. Lanyards without connectors can be equipped with MGO OPEN 60 or 110 connectors that can be re-used if the lanvard is damaged.



Classic connectors

Lanyards without connectors can be equipped with classic aluminum (OK, Am'D, and Rm'D) or steel connectors (OXAN TRIACT-LOCK). They enable connection to lifelines or to single anchor points.


· Available in several lengths, with or without a connector

ABSORBICA lanyards are available in two lengths:

- 150 cm of elasticized webbing, to avoid hindering progression

They are available with or without a connector, according to user needs.

· For progression on a lifeline without passing intermediate anchors



especially for protection on a horizontal lifeline or on an elevated platform.

· For progression on a vertical


structure or a lifeline and when

passing intermediate anchors

The ABSORBICA-Y lanyards with two

the two arms.

arms allow for continuous protection by successively detaching and re-attaching



ABSORBICA®-I

Single lanyard with integrated energy absorber

ABSORBICA-I single lanyards

ABSORBICA-I is a single lanyard with compact energy absorber, designed for progression on a horizontal lifeline (rope or cable) or on an elevated platform, without passing intermediate anchors. It functions with users weighing between 50 and 140 kg. It has several installation options on the harness and can be used with different types of connectors. It is available in two lengths: 80 or 150 cm versions (without connectors). The 150 cm version has an elasticized arm to avoid hindering progression. Depending on the connectors used, ABSORBICA-I is certified to American, European, and Russian standards.



Adjustable single lanyard with integrated energy absorber

ABSORBICA-I VARIO is an adjustable single lanyard with compact energy absorber designed for progression on a horizontal lifeline (rope or cable) or on an elevated platform, without passing intermediate anchors. It functions with users weighing between 50 and 140 kg. It features the VARIO adjustment system, allowing the lanyard length to be adjusted in order to reduce potential fall height. Depending on the connectors used, ABSORBICA-I VARIO is certified to American, European, and Russian standards.



ABSORBICA-Y double lanyards

ABSORBICA®-Y

Double lanyard with integrated energy absorber

ABSORBICA-Y is a double lanyard with compact energy absorber, designed for progression on a vertical structure or a horizontal lifeline, and for passing intermediate anchors. It functions with users weighing between 50 and 140 kg. It has several installation options on the harness and can be used with different types of connectors. It is available in two lengths: 80 or 150 cm versions (without connectors). The 150 cm version has elasticized arms to avoid hindering progression. Depending on the connectors used, the ABSORBICA-Y is certified to American, European, and Russian standards.

ABSORBICA®-Y MGO European Version

Double lanyard with integrated energy absorber and MGO connectors

ABSORBICA-Y MGO is a double lanyard with compact energy absorber, designed for progression on a vertical structure or a horizontal lifeline, and when passing intermediate anchors, It functions with users weighing between 50 and 140 kg. It is available in two lengths: 80 or 150 cm versions (without connectors). The 150 cm version has elasticized arms to avoid hindering progression. With two MGO large-opening connectors, it is certified to European and Russian standards.

Double lanyard with integrated energy absorber and MGO connectors

ABSORBICA-Y MGO is a double lanyard with compact energy absorber, designed for progression on a vertical structure or a horizontal lifeline, and when passing intermediate anchors. It functions with users weighing between 50 and 140 kg. It is available in two lengths: 80 or 150 cm versions (without connectors). The 150 cm version has elasticized arms to avoid hindering progression. Equipped with two large-opening MGO connectors and a Bm'D connector with a CAPTIV positioning bar, it is certified to American, European

energy absorber. It is designed for vertical progression on very large structures and when passing intermediate anchor points. It functions with users weighing between 50 and 140 kg. The TIE-BACK system allows the lanyard end to be reconnected to the intermediate tie-back ring to fit around structures with a very large cross-section. The arms are elasticized to avoid hindering progression. It is available with or without connectors and is certified to American, European, and Russian standards.



Using the ABSORBICA-Y TIE-BACK





Fall-Arrest Lanyards



ABSORBICA®

Compact energy absorber

ABSORBICA is a compact energy absorber, for use in combination with a JANE lanyard to make a fall-arrest lanyard. Equipped with tear-webbing inside a pouch that opens on each end, the absorber is protected from abrasion, while allowing for regular inspection. It has two options for installation on the harness, according to the frequency of manipulation.

JANE-I

Single lanyard for making a fall-arrest lanyard

JANE-I is a non-adjustable dynamic rope lanyard that can be combined with an ABSORBICA energy absorber to make a single lanyard with energy absorber. The plastic sheath helps hold the carabiner in position and facilitates clipping while protecting the termination from abrasion. It can be used to set up a temporary anchor. It is available in three lengths: 60, 100, and 150 cm.

JANE-Y for Fall-Arrest Lanvard

Double lanyard for making a fall-arrest lanyard

JANE-Y for fall-arrest lanyard is a non-adjustable dynamic rope lanyard that can be combined with an ABSORBICA energy absorber to make a double lanyard with energy absorber. The plastic sheaths help hold the carabiners in position and facilitate clipping while protecting the terminations from abrasion. It has two symmetrical ends and is available in two lengths: 60 and 100 cm.

Progression Lanvards for Rope Access



PROGRESS ADJUST-Y

Double adjustable progression lanyard

PROGRESS ADJUST-Y is a double adjustable progression lanyard that enables continuous connection for different types of progression (such as rope ascent or moving along a fixed line). Using the ADJUST rope adjuster, the length of the adjustable arm can be quickly and easily adjusted. The TANGA accessory and the plastic sheath help hold the connectors in a good position for easy clipping.

PROGRESS ADJUST-I

Single adjustable progression lanyard

PROGRESS ADJUST I is a single adjustable progression lanyard that, when combined with another lanyard, allows continuous connection for different types of progression (such as rope ascent or moving along a fixed line). Using the ADJUST rope adjuster, the length can be quickly and easily adjusted. Reversible, the ADJUST rope adjuster can be placed on the anchor or on the harness ventral attachment point. The CAPTIV ADJUST and STUART accessories help hold the connectors in a good position for easy clipping.

JANF-Y

Double progression lanyard

JANE-Y is a double progression lanyard that allows continuous connection during rope ascents. The plastic sheaths help hold the carabiners in position and facilitate clipping while protecting the terminations from abrasion. It has a 60 cm long arm and a 30 cm short arm.

Work-Positioning Lanyard



PROGRESS ADJUST-I

Adjustable positioning lanyard

When combined with a fall-arrest device, the PROGRESS ADJUST-I adjustable positioning lanyard enables comfortable positioning at a workstation when the user has support for their feet. Using the ADJUST rope adjuster, the length can be quickly and easily adjusted. The CAPTIV ADJUST and STUART accessories help hold the connectors in a good position for easy clipping. Depending on the configuration, it can be used in single or double mode. The PROGRESS ADJUST-I positioning lanyard is available in three lengths (2, 3, and 5 m).

Tree Care Lanyards



ZILL ON

Adjustable work-positioning lanyard for tree care

The ZILLON work-positioning lanyard for tree care adjusts easily with only one hand, even when loaded. It is designed for use in double mode on the harness side attachment points, or in single mode on the ventral attachment point with the hand on the free end. The yellow color makes it highly visible. ZILLON lanyard ropes are also available individually.



Easy to adjust with one hand, due to the progressive locking/ unlocking action of the device.



Pulley mounted on sealed ball bearings allows slack to be taken up easily.



MICROFLIP

Reinforced adjustable positioning lanyard for tree care work

MICROFLIP is a reinforced adjustable lanyard designed for positioning in tree care work. Its cable core reduces the risk of severing the lanyard and facilitates moving about on the trunk. The yellow color makes it highly visible. MICROFLIP lanyard ropes are also available individually.



MICROGRAB

Replacement cam-loaded rope clamp for MICROFLIP

Replacement rope clamp for MICROFLIP, featuring an ergonomic cam and integrated cam spring.



Helivac Lanyards



I FZARD

Helivac lanyard with securing of the drop-off/recovery phases

The LEZARD lanyard is designed for helivac at altitude. It allows the drop-off/recovery phases to be secured due to the adjustable arm that can be instantly ejected to free the victim, the rescuer, and the helicopter if the latter needs to suddenly leave its stationary position. Operating the LEZARD helivac lanyard is easy, with color-coded attachment elements that can be instantly identified and the ADJUST rope adjuster that can quickly and precisely adjust lanyard length.



IGUANE

Helivac lanyard for ground drop-off/recovery

The IGUANE lanyard is designed for ground helivac. Easy to use, with color-coded attachment elements that can be instantly identified. Lanyard available in two lengths.



The lower ends are equipped with STRING, which helps hold the carabiner in position and protects the webbing from wear.

Lanyard-End Connectors



VERTIGO TWIST-LOCK

Connector for progression lanyard

See page 111 for details on the VERTIGO TWIST-LOCK connector.



EASHOOK OPEN

Connector with gated connection point for double lanyard and work-positioning lanyard

See page 111 for details on the EASHOOK OPEN connector.



MGO OPEN

Auto-locking directional connector with large gate opening and a gated connection point

See page 111 for details on the MGO OPEN connector.

		Lengths	Certifications	Weight
Work-Positioning La	nyards and Lanyards	for Rope Access or Tree Care		
GRILLON	L052AA00/01/02/03/ 04/05/06	Adjustable to 2 m / 3 m / 4 m / 5 m / 10 m / 15 m / 20 m	ANSI Z359.3 CSA Z259.11	480 - 1875 g
a	L052AA07/08 (noir)	Adjustable to 2 m / 3 m	CE EN 358 EN 12841 type C	480 - 560 g
GRILLON PLUS	L052EA00/01	Adjustable to 2 m / 3 m	EAC " UKCA	435 - 515 g
GRILLON HOOK European version	L052BA00/01/02/03	Adjustable to 0 m / 0 m / 4 m / 5 m	CE EN 358, EN 12841 type C, EAC, UKCA	635 - 875 g
GRILLON HOOK international version	L052CA00/01/02/03	Adjustable to 2 m / 3 m / 4 m / 5 m	ANSI Z359.3, CSA Z259.11 CE EN 358, EN 12841 type C, EAC, UKCA	770 - 1010 g
GRILLON MGO	L052DA00/01	Adjustable to 2 m / 3 m	ANSI Z359.3, CSA Z259.11 CE EN 358, EN 12841 type C, EAC, UKCA	1220 - 1300 g
JANE-Y	L051AA00	1 arm, 60 cm 1 arm, 30 cm	CE EN 354 ANSI Z359.3 EAC, UKCA	130 g
PROGRESS ADJUST-Y	L044AA00	1 fixed arm, 65 cm 1 arm adjustable up to 95 cm	CE EN 358 EAC, UKCA	230 g
	L044BA00	1 arm adjustable up to 1 m		185 g
PROGRESS	L044BA01	1 arm adjustable up to 2 m	CE EN 358 ANSI Z359.3 CSA Z259.11	300 g
ADJUST-I	L044BA02	1 arm adjustable up to 3 m	EAC UKCA	370 g
	L044BA03	1 arm adjustable up to 5 m	5.1.04	510 g
ZILLON	L22A 025/040/055	Adjustable to 2.5 m / 4 m / 5.5 m	CE EN 358, UKCA	570 - 900 g
MICROFLIP	L33 025/040/055	Adjustable to 2.5 m / 4 m / 5.5 m	CE EN 358, EAC, UKCA	750 - 1355 g
MICROGRAB	B53A	÷	CE EN 358 (1), EN 567 NFPA 2500 Technical Use, EAC, UKCA	150 g

		Connectors	Lengths Without Connectors	Lengths With Connectors	Certifications	Weight
Fall-Arrest Lanyards	;					
ABSORBICA-I	L011AA00	-	80 cm	90 - 130 cm (Depending on connectors)		270 g
ABSONBICA-I	L013AA01	-	150 cm	160 - 200 cm (Depending on connectors)	CE EN 355 (2)	320 g
ABSORBICA-I VARIO	L016AA00	-	100 - 150 cm	110 - 200 cm	ANSI Z359.13 12 féet (3) EAC UKCA	280 g
ABSORBICA-Y	L012AA00		80 cm	90 - 130 cm (Depending on connectors)	JSFAD	370 g
ABSORBICA-Y	L014AA01	-	150 cm	160 - 200 cm (Depending on connectors)		430 g
ABSORBICA-Y MGO	L012CA00	Ends:	80 cm	130 cm	CE EN 355 (2) EAC	1290 g
European Version	L014CA01	2 x MGO	150 cm	200 cm	UKĆA JSFAD	1350 g
ABSORBICA-Y MGO	L012BA00	Ends:	80 cm	110 cm	ANSI Z359.13 12 feet ANSI Z359.12	1850 g
International Version	L014BA01	2 x MGO - Bm'D	150 cm	180 cm	CÉ EN 355 EAC, UKCA, JSFAD	1910 g
ABSORBICA-Y	L015AA00	-	450	160 - 200 cm (Depending on connectors)	CE EN 355 (2)	550 g
TIE-BACK	L015BA00	Ends: 2 x MGO - Bm'D	150 cm	180 cm	ANSI Z359.13 12 féet (3) EAC, UKCA, JSFAD	2030 g
ABSORBICA	L010AA00	-	22 cm	-	CE EN 355 EAC, UKCA, JSFAD	140 g
	L050BA00	=	60 cm	=	CE EN 354 EN 795 type B	100 g
JANE-I	L050BA01	-	100 cm	-	ANSI Z359.3 ANSI Z459.1	120 g
	L050BA02	-	150 cm	-	CSA Z259.11 EAC, UKCA	145 g
JANE-Y for Fall-Arrest	L051AA02	-	60 cm	-	CE EN 354 ANSI Z359.3	145 g
Lanyard	L051AA01	-	100 cm	-	UKCA	185 g

		Connectors	Lengths	Certifications	Weight
Helivac Lanyards					
LEZARD	L01	3 x VERTIGO TWIST-LOCK 1 x VERTIGO WIRE-LOCK	2 x 35 cm fixed arms, 1 ejectable arm, adjustable to 95 cm	CE UKCA	880 g
ICHANE	L001AA00	2 x VERTIGO TWIST-LOCK	2 x 25 cm fixed arms	CE EN 354	390 g
IGUANE	L001AA01	1 x Am'D TWIST-LOCK	2 x 35 cm fixed arms	UKCA	395 g
IGUANE					_

MOBILE FALL ARRESTERS

Installed on a lifeline, mobile fall arresters follow the user automatically as they move, whether on an inclined or vertical surface. In the event of a shock load or sudden acceleration, they lock onto the rope and stop the fall.



Mobile Fall Arresters

Installed on a lifeline, mobile fall arresters will lock in the event of a shock load or sudden acceleration.

For fall protection

Mobile fall arrester that can be combined (or not) with an ASAP'SORBER or ASAP'SORBER AXESS energy absorber.





• For fall protection, with locking function

Mobile fall arrester with locking function, used with an ASAP'SORBER or ASAP'SORBER AXESS energy absorber.



Absorbers for Mobile Fall Arresters

These energy absorbers are for use only with an ASAP or ASAP LOCK mobile fall arrester. They limit the impact force transmitted to the user in the event of a fall.





Ropes for Mobile Fall Arresters

Ropes with sewn terminations for use with ASAP and ASAP LOCK mobile fall arresters.
















Installed on a safety rope, the ASAP and ASAP LOCK mobile fall arresters connect to the harness fall-arrest attachment point. They follow the user in their movements, and in the event of a shock load or sudden acceleration, the devices lock and stop the fall.

· Constant fall protection



Integrated locking

In the event of a sudden movement due to a fall, slide, or uncontrolled descent, the ASAP and ASAP LOCK mobile fall arresters lock on the rope and stop the worker's fall, even if they grab the device with their hands.

These mc well on ve to a variet

Effective in many different situations

These mobile fall arresters work equally well on vertical or angled ropes, to adapt to a variety of different worksite situations.


Simple to use



Quick installation

These mobile fall arresters may be quickly and easily installed anywhere on the rope by simply retracting the locking wheel.

No user action required





Compatible with all Petzl energy absorbers

To meet different user needs, the mobile fall arresters are compatible with all of the energy absorbers in the line: ASAP'SORBER (20 and 40 cm) and ASAP'SORBER AXESS.

For fall protection

Depending on the use, the ASAP mobile fall arrester can be combined (or not) with an ASAP'SORBER energy absorber.



ASAP®

Mobile fall arrester for rope

With its unique locking system, the ASAP sets the standard in fall protection for workers at height. In normal use, the device moves freely along the rope without any manual intervention and follows the user in all their movements. In the event of a shock load or sudden acceleration, the ASAP locks on the rope and stops the user. Depending on the intended use, the ASAP may also be combined with an ASAP'SORBER or ASAP'SORBER AXESS energy absorber to work at a distance from the rope.

• For fall protection, with locking function

The ASAP LOCK has a locking function allowing users to reduce the potential fall distance. Additionally, it is drop-resistant when passing intermediate anchors. It is used with an ASAP'SORBER energy-absorber.



ASAP® LOCK

Mobile fall arrester for rope, with locking function

The ASAP LOCK mobile fall arrester is designed to facilitate handling during rope ascents. In normal use, the device moves freely along the rope without any manual intervention and follows the user in all their movements. In the event of a shock load or sudden acceleration, the fall arrester locks on the rope and stops the user. The integrated locking function allows the user to immobilize the device in order to reduce the potential fall distance. The connection arm makes the system drop-resistant when passing intermediate anchors. The ASAP LOCK is used with an ASAP SORBER or ASAP SORBER AXESS energy absorber to work at a distance from the rope.



How to install the ASAP and ASAP LOCK on a lifeline







Weight per Meter

Absorbers for Mobile Fall Arresters



ASAP'SORBER

Energy absorber for ASAP and ASAP LOCK

The ASAP'SORBER energy absorber may only be used with an ASAP or ASAP LOCK mobile fall arrester. It allows the user to work at a distance from the rope, in order to protect it during certain work phases. Equipped with tear-webbing inside a pouch that opens on each end, the absorber is protected from abrasion, while allowing for regular inspection. It is available in two lengths to provide the best balance between distance from the rope and reduced fall distance.



ASAP'SORBER AXESS

Energy absorber for an ASAP or ASAP LOCK for a maximum load of 250 kg

The ASAP'SORBER AXESS energy absorber may only be used with the ASAP or ASAP LOCK mobile fall arrester. It allows the user to work at a distance from the rope, in order to protect it during certain work phases. Equipped with tear-webbing inside a pouch that opens on each end, the absorber is protected from abrasion, while allowing for regular inspection. It can be used in two-person rescue situations for a maximum load of 250 kg.

Ropes for Mobile Fall Arresters



ASAP'AXIS 11 mm

Low stretch kernmantle rope with sewn termination and integrated energy dissipater, for use with an ASAP mobile fall arrester

The ASAP'AXIS 11 mm low stretch kernmantle rope with sewn termination and integrated energy dissipater is designed for use with an ASAP mobile fall arrester. The energy dissipater is integrated with the rope and meets the requirements of the European EN 353-2 standard for fall protection. The standard diameter provides a good grip for easier handling. EverFlex technology provides great flexibility and consistent performance over time. The sewn termination features the STUART accessory that helps keep the connector in position to facilitate handling. Rope available in six lengths.



AXIS 11 mm With Sewn Termination

Low stretch kernmantle rope with sewn termination for use with an ASAP LOCK mobile fall arrester

The AXIS 11 mm low stretch kernmantle rope with sewn termination is designed for use with an ASAP LOCK mobile fall arrester and an ASAP SORBER or ASAP SORBER AXESS energy absorber. It has a sewn termination with a protective sheath that helps keep the connector in position, allowing it to meet the requirements of the European EN 353-2 standard for fall protection. The standard diameter provides a good grip for easier handling. EverFlex technology provides great flexibility and consistent performance over time. Rope available in six lengths.



RAY 11 mm With Sewn Termination

Static rope with sewn termination for use with ASAP and ASAP LOCK mobile fall arresters

The RAY 11 mm static rope with sewn termination is designed for use with an ASAP or ASAP LOCK mobile fall arrester. It has low elongation under load, allowing it to meet the requirements of the ANSI 2589.15 American fall protection standard. The standard diameter provides a good grip for easier handling, EverFlex technology provides great flexibility and consistent performance over time. The sewn termination with protective sheath helps keep the connector in position and facilitates handling. Rope available in five lengths.

			Certifications	Weight	4
Mobile Fall Arresters					
ASAP	B070AA00	An ASAP'SORBER of CE EN 353-2, UKCA when used with an O An ASAP'SORBER of ANSI Z359.15 when used with an A a Bm'D or OXAN TRI and a RAY 11 mm st. EAC when used with an OXAN TRI when used with an OXAN TRI CEAC	K TRIACT-LOCK carabiner and an EN 1891 type A 10-13 mm rope. r ASAP'SORBER AXESS energy absorber can be used when needed.	295 g	9
ASAP LOCK	B071BA00	and an EN 1891 type CE EN 353-2, UKCA when used with an A and an AXIS 11 mm I ANSI Z359.15 when used with an A a Bm'D or OXAN TRI and a RAY 11 mm st. EAC when used with an A	SAP'SORBER or ASAP'SORBER AXESS energy absorber, A 10 to 13 mm rope.	425 g	
		Length	Certifications	Weight	

			Length	Certifications	Weight	
Absorbers for Mo	bile Fa	II Arresters				
ASAP'SORBER	Ì	L071AA00	20 cm	CE EN 355 ANSI Z359.13 6 feet	125 g	
ASAF SURBER	İ	L071AA01	40 cm	EAC UKCA	145 g	-
ASAP'SORBER AXESS		L071CB00	40 cm	CE EN 355 ANSI Z359.13 6 feet UKCA	205 g	

Certifications

				l .	per wieter
Ropes for Mobi	le Fall Arre	sters			
	2	R074DA00	10 m		
	1	R074DA01	20 m		
ASAP'AXIS		R074DA02	30 m	CE EN 1891 type A	00 -
11 mm		R074DA03	40 m	UKCA	82 g
	9	R074DA04	50 m		
	1	R074DA05	60 m		
		R074BA00	10 m		
AXIS	- 6	R074BA01	20 m	CE EN 1891 type A	
11 mm		R074BA02	30 m	NFPA 2500 Technical Use	00 -
with sewn	- }	R074BA03	40 m	EAC	82 g
termination	1	R074BA04	50 m	UKCA	
		R074BA05	60 m		
	-	R100BA00	25 ft		
RAY	Ħ	R100BA01	50 ft	ANSI Z359.15	
11 mm with sewn	¥	R100BA02	75 ft	ANSI 2459.1	98 g
termination	8	R100BA03 100 ft NFPA 2500	NFPA 2500		
	8	R100BA04	200 ft		

CONNECTORS

To address various situations encountered in the field, Petzl offers several types of connectors, with different shapes, sizes, gate openings, and locking systems.



Specific features on Petzl connectors make them easy to use, offering smooth connection and disconnection.



Avoids the risk of snagging

To provide optimal efficiency, all Petzl carabiners use the Keylock system: the nose of the carabiner, where the body and gate meet, does not have a notch that could snag on anchors, ropes, harness equipment loops, or other gear.



Visual locking indicator

To facilitate equipment checks, SCREW-LOCK manual locking carabiners have a red band that is visible only when the carabiner is not locked.

Lightweight Carabiners

Aluminum carabiners designed for workers at height.



Ultra-Lightweight Carabiners

Compact aluminum carabiners for workers at height looking to reduce weight to a minimum.



High-Strength Carabiners

Carabiners suitable for difficult environments, primarily used for setting up anchors and for connecting to metal structures.







Lanyard-End Connectors

Connectors designed for lanyard ends.







Special Carabiners

Aluminum carabiners designed for specific uses: with groups, for additional braking with a descender, and for harness fastening.







Semi-Permanent Connectors

Connectors designed for semi-permanent connection of equipment.









Connector Positioning Accessories

Accessories that keep the carabiner correctly positioned in devices and at the end of a lanyard.
















Lightweight Carabiners

· Design facilitates handling



Fluid interior design

Fluid interior design limits the risk of having a catch point and facilitates rotation of the carabiner.



Optimal strength-to-weight ratio

The H cross-section provides an optimal strength-to-weight ratio and protects the markings from abrasion.

• Multiple locking systems depending on the intensity of use:

- For frequent use:



TRIACT-LOCK automatic system:


Unlocking is accomplished by raising, then turning the sleeve.



BALL-LOCK automatic system:

Unlocking is accomplished by pressing on the green indicator, then turning the sleeve. The green visual indicator is visible only when the gate is locked.

- For occasional use:



SCREW-LOCK manual system:

This system is ideal for harsh environments where contaminants (mud, ice) could cause an automatic locking system to jam. The red visual indicator is visible when the carabiner

• For connecting to equipment that has a large cross-section



The OK carabiner has a symmetrical oval shape for optimal loading of devices with a large cross-section, such as pulleys, rope clamps, or mobile fall arresters.



Lightweight oval carabiner

The lightweight OK carabiner is made of aluminum. It has an oval shape that allows optimal loading of devices with a large cross-section, such as pulleys, rope clamps, and mobile fall arresters. Its fluid interior design and Keylock system facilitate handling. It is available in three arresters, its fluid liftenful design and response system resimilar manual SCREV-LOCK. OR can be used with the CAPTIV bar to promote loading of the carabiner on the major axis, to limit the risk of rotation, and to keep it integrated with the device.

· For connecting equipment such as descenders or positioning lanyards



The Am'D carabiner has an asymmetrical D shape that is ideal for attaching equipment such as descenders or positioning lanyards.



Am'D

Lightweight asymmetrical carabiner

The Am'D lightweight asymmetrical carabiner is made of aluminum. It has a D shape particularly The Am D lightweight asymmetrical carabiner is made of auminium. It has a D snape particularly suited for connecting to diverse equipment such as descenders or positioning lanyards. Its fluid interior design and Keylock system facilitate handling. The Am'D carabiner is available in three locking systems: automatic TRIACT-LOCK or BALL-LOCK system, or manual SCREW-LOCK system. Am'D may be used with a CAPTIV positioning bar to promote loading of the carabiner along the major axis, to limit the risk of rotation, and to keep it integrated with the device.

· For connecting multiple items



The WILLIAM has an asymmetrical pear shape, with a large capacity for attaching multiple elements, and a large gate opening to facilitate their installation.



WILLIAM

Lightweight asymmetrical large-capacity carabiner

The lightweight WILLIAM large-capacity asymmetrical carabiner is made of aluminum. The pear shape makes it easy to attach multiple items. Its fluid interior design and Keylock system facilitate handling. The WILLIAM carabiner is available in three locking systems: automatic TRIACT-LOCK or BALL-LOCK, or manual SCREW-LOCK. WILLIAM can be used with the CAPTIV bar to promote positioning of the carabiner along the major axis, to limit the risk of rotation, and to keep it integrated with the device.































Ultra-Lightweight Carabiners



Sm'D

Ultra-lightweight asymmetrical carabiner

The compact Sm'D asymmetrical aluminum carabiner is recommended for workers at height looking to reduce weight to a minimum. The D shape makes it especially suitable for attaching devices. It is available in two locking systems (automatic TRIACT-LOCK system or manual SCREW-LOCK system), or without a locking system.

High-Strength Carabiners



OXAN

High-strength oval carabiner

OXAN is a high-strength steel carabiner designed for use in harsh environments. The oval, OWAN Is a might steming in steen carabiner to be loaded in the optimal position when setting up anchors or connecting to metal structures. It is available in two locking systems: automatic TRIACT-LOCK system or manual SCREW-LOCK system. OXAN TRIACT-LOCK is available in European or international versions. OXAN can be used with the CAPTIV bar to promote positioning of the carabiner along the major axis, to limit the risk of rotation, and to keep it



The oval, symmetrical shape allows the carabiner to be loaded in the optimal position when setting up anchors. Usage with the CAPTIV positioning bar promotes loading of the carabiner along the major axis, limits the risk of rotation, and keeps it attached to the device or lanyard.



VUI CAN

High-strength, large-capacity, asymmetrical carabiner

VULCAN is a high-strength steel carabiner designed for use in harsh environments. The largecapacity asymmetrical shape is ideal for setting multiple anchors. The VULCAN carabiner is available in two locking systems: automatic TRIACT-LOCK system or manual SCREW-LOCK system. VULCAN TRIACT-LOCK is available in European or international versions. VULCAN can be used with the CAPTIV bar to promote loading of the carabiner on the major axis, to limit the risk of rotation, and to keep it integrated with the device.





Bm'D

Lightweight asymmetrical high-strength carabiner

The Bm'D lightweight asymmetrical carabiner is made of aluminum. It has a D shape particularly suited for connecting to diverse equipment such as descenders or positioning lanyards. Its fluid interior design and Keylock system facilitate handling. The Bm'D carabiner has the TRIACT-LOCK automatic locking system. The sleeve is reinforced for greater inward and lateral gate strength. Bm'D may be used with a CAPTIV positioning bar to promote loading of the carabiner on the major axis, to limit the risk of rotation, and to keep it integrated with the device.



The sleeve is reinforced for greater inward and lateral gate strength.

Lanvard-End Connectors



VERTIGO TWIST-LOCK

Connector for progression lanyard

The VERTIGO TWIST-LOCK connector is designed for use on progression lanyards. The excellent grip and automatic locking system facilitate handling when passing intermediate anchors. The large opening and the Keylock system allow the connector to be easily connected. VERTIGO TWIST-LOCK may be used with a CAPTIVO positioning bar to promote loading of the carabiner on the major axis, to limit the risk of rotation and, to keep it integrated with the device.



FASHOOK OPEN

Connector with gated connection point for double lanyard and work-positioning

The EASHOOK OPEN connector is designed for use at the ends of a double lanyard or workpositioning lanyard. The gated connection point allows the connector to be directly attached to the lanyard. If the lanyard is damaged, the connector can be reused. The excellent grip and automatic locking system facilitate handling when passing intermediate anchors.



MGO OPEN

Auto-locking directional connector with large gate opening and a gated

MGO OPEN is an auto-locking directional connector with a large gate opening for connection to metal structures or to large-diameter cables and bars. It has a gated connection point for attachment to different types of lanyards. If the lanyard is damaged, the connector can be reused. MGO OPEN is available in two versions: 60 and 110 mm.

Special Carabiners





Am'D PIN-LOCK

Asymmetrical aluminum carabiner, unlocks with a tool

The Am'D PIN-LOCK asymmetrical aluminum carabiner is designed for use with groups. It secures the connection of the participant with a PIN-LOCK system, which can only be opened by the operator with a specific unlocking tool. Am'D PIN-LOCK may be used with a CAPTIV positioning bar to promote loading of the carabiner along the major axis, to limit the risk of rotation, and to keep it integrated with the device.



FRFINO 7

Carabiner with friction spur for descenders

The FREINO Z carabiner has a friction spur for adding or adjusting friction during the descent. It is easy to use and compatible with I'D S, I'D L, I'D EVAC, and RIG self-braking descenders. When rotated, it makes the descender drop-resistant when being transferred from the equipment loop to the ventral attachment point or anchor. The FREINO Z has the TRIACT-LOCK automatic locking system.



OMNI

Multidirectional semi-circle carabiner

Multidirectional semi-circle OMNI carabiner for fastening the FALCON ASCENT harness and for attaching a CROLL ventral rope clamp. It is available in two locking systems: automatic TRIACT-LOCK system or manual SCREW-LOCK system.

PETZL.COM



































111

Semi-Permanent Connectors



RING OPEN

Multidirectional gated ring

The RING OPEN gated ring is designed for semi-permanent connection of equipment. The round shape allows it to function optimally in all directions. It has a large opening that allows installation of ropes with sewn terminations



DELTA

Triangular steel quick link

When closed with a wrench, this steel quick link becomes a semi-permanent anchor ring.



GO

Oval steel quick link

When closed with a wrench, this steel quick link becomes a semi-permanent anchor ring.



DEMI ROND

Semi-circle aluminum alloy quick link

When closed with a wrench, this aluminum quick link is used to fasten harnesses that have two attachment points that must be joined with a connector.

Connector Positioning Accessories



CAPTIV

Connector positioning bar (pack of 10)

The CAPTIV positioning bar promotes loading of the carabiner on the major axis, limits the risk of rotation, and keeps it integrated with the device or lanyard. CAPTIV is compatible with OK, Am'D, WILLIAM, OXAN, VULCAN, Bm'D carabiners, and the ROLLCLIP A pulley carabiner.



CAPTIVO

Positioning bar for the VERTIGO TWIST-LOCK connector (pack of 10)

The CAPTIVO positioning bar secures the connector to the lanyard, promotes loading of the connector on the major axis, and limits the risk of rotation. CAPTIVO is only compatible with the VERTIGO TWIST-LOCK connector.



CAPTIV ADJUST

Carabiner positioning bar combined with an ADJUST rope adjuster

The CAPTIV ADJUST positioning bar promotes loading of the carabiner on the major axis and helps hold the ADJUST rope adjuster in the proper position to reduce the risk of accidental release. It helps keep the lanyard and rope adjuster integrated with the carabiner, reducing the risk of losing them. CAPTIV ADJUST is compatible with OK, Am'D, Bm'D, and OXAN carabiners.



STUART

Connector positioning accessory (pack of 10)

STUART helps keep the connector in the correct position and facilitates clipping. It is compatible with most auto-locking connectors.



TANGA

Connector positioning ring (pack of 10)

The TANGA positioning ring helps hold the connector in the correct position.



STRING

Accessory for maintaining connector orientation and protecting the webbing (pack of 10) STRING helps maintain the proper orientation of the connector and protects the webbing from wear.


It is available in two sizes.

		Locking	References		Q	- 0•	9	Certifications	Weight	OR
Lightweig	ht Car	abiners						·		
		TRIACT-LOCK	M33A TL / TLN (1)	22 mm					75 g	
ОК	0	BALL-LOCK	M33A BL	23 mm	25 kN	8 kN	7 kN	CE EN 362, EN 12275 class B	75 g	
		SCREW-LOCK	M33A SL / SLN (1)	22 mm	-			UKCA	70 g	O.
		TRIACT-LOCK	M34A TL / TLN (1) / TLY (2)	24 mm					75 g	
Am'D		BALL-LOCK	M34A BL / BLY (2)	25 mm	27 kN	8 kN	7 kN	CE EN 362, EN 12275 class B NFPA 2500 Technical Use EAC UKCA	75 g	
		SCREW-LOCK	M34A SL / SLN (1)	25 mm				UKCA	70 g	
		TRIACT-LOCK	M36A TL / TLN (1) / TLY (2)	27 mm					90 g	1
WILLIAM	\bigcap	BALL-LOCK	M36A BL / BLY (2)	27 mm	27 kN	8 kN	8 kN	CE EN 362, EN 12275 class B NFPA 2500 Technical Use EAC	90 g	
	0	SCREW-LOCK	M36A SL / SLN (1)	28 mm	_			ÜKČA	85 g	
Illtra-Ligh	tweial	nt Carabiners								•
Old Light	tweigi	TRIACT-LOCK	M39A TL / TLN (1)	18 mm				CE EN 362, EN 12275 type B	55 g	
Sm'D	n	SCREW-LOCK	M39A SL / SLN (1)	20 mm	23 kN	8 kN	7 kN	EAC UKCA	45 g	
	•	Non-Locking	M39A S / SN (1)	23 mm				CE EN 12275 type B, UKCA	40 g	
High-Stre	nath C	arahinere								
riigii-Strei	igui c	TRIACT-LOCK	M72A TL	22 mm				CE EN 362, NFPA 2500 Technical Use, EAC, UKCA	195 g	
OXAN	Ω	European version TRIACT-LOCK	M72A TLA / TLN (1)	20 mm	38 kN	16 kN	15 kN	CE EN 362, ANSI Z359.12, NFPA 2500 Technical Use, CSA Z259.12, EAC, UKCA	230 g	
070 114	U	international version		22 mm	- 00 KIV	10 10	10 KIV	CE EN 362, NFPA 2500 Technical Use	-	
		TRIACT-LOCK	M72A SL / SLN (1)					EAC, UKCA	185 g	
	0	European version TRIACT-LOCK	M073BA00	28 mm	_			CE EN 362, NFPA 2500 General Use EAC, UKCA CE EN 362, ANSI Z359.12, NFPA 2500	245 g	(
VULCAN	U	international version	M073CA00 / 01 (1)	26 mm	45 kN	16 kN	18 kN	General Use, CSA Z259.12, EAC, UKCA	265 g	
		SCREW-LOCK	M073AA00 / 01 (1)	29 mm				CE EN 362, NFPA 2500 General Use EAC, UKCA	235 g	
Bm'D	U	TRIACT-LOCK	M032AA00 / 01 (1)	18 mm	32 kN	16 kN	10 kN	CE EN 362, ANSI Z359.12, ANSI Z459.1 NFPA 2500 Technical Use, CSA Z259.12, EAC, UKCA	105 g	
Lanyard-E	nd Co	nnectors								
VERTIGO TWIST-LOCI	v N	TWIST-LOCK	M40A RLA	25 mm	25 kN	10 kN	8 kN	CE EN 362, EN 12275 class B & K UKCA	100 g	
EASHOOK OPEN	8	Automatic	M043AA00 / 01 (1)	25 mm	25 kN	-	10 kN	CE EN 362 EAC, UKCA	160 g	
MGO OPEN 60	Q	Automatic	MGOO 60	63 mm				CE EN 362	490 g	0
MGO	0	Automatic	M080AA00	110 mm	- 23 kN	-	23 kN	CE EN 362 EAC UKCA	930 g	(
OPEN 110	À	ratoriatio	1110007 0 100	11011111						
Special Ca	arabin		MOAA EL (v.d)					OF FN 000 FN 40075 sleep D		3
PIN-LOCK	U	PIN-LOCK	M34A PL (x 1) M34AB PL (x 10)	25 mm	27 kN	8 kN	7 kN	CE EN 362, EN 12275 class B EAC, UKCA	80 g	٦
FREINO Z	0	TRIACT-LOCK	M042BA00	18 mm	23 kN	8 kN	8 kN	CE EN 362, EN 12275 class B NFPA 2500 Technical Use EAC, UKCA	75 g	
OMNI	\bigcirc	TRIACT-LOCK	M37 TL	22 mm	20 kN	15 kN	7 kN	CE EN 362, EN 12275 class B UKCA	90 g	
		SCREW-LOCK	M37 SL					UKCA	85 g	-
Semi-Perr	nanen	t Connectors								
RING OPEN	0	Gated Ring	P28	11 mm	23 kN	23 kN	-	CE EN 362, UKCA	70 g	d
	_	Quick Link	P11	12 mm	45 kN	10 kN			150 g	
DELTA	\Box	Quick Link	P11 8, P11 8B, P11 8BN (1)	10 mm	27 kN	10 kN	1	OF FN OCC.	85/95 g	
GO	0	Quick Link	P15	16 mm	25 kN	10 kN	-	CE EN 362 type Q UKCA	60 g	•
DEMI ROND		Quick Link	P18	10 mm	25 kN	10 kN	1		55 g	
SZIVII I TOTAL	_	Color En il	0		LORIV	101014	I	1	55 g	

(1) Black connectors

(2) Gold connectors

Descenders are designed to help regulate friction and control the descent on a fixed rope. They allow a worker to position themselves at any point on the rope. Certain Petzl descenders can also be used as belay devices.



Self-Braking Descenders
Self-braking descenders with ergonomic handle
and AUTO-LOCK system allow a comfortably
controlled descent and easy positioning at the
workstation. These devices are designed for work
at height, rope access, and technical rescue and evacuation.











Open auxiliary brake



Closed auxiliary brake

Descenders for Technical Rescue

Descenders with integrated progress-capture pulley and AUTO-LOCK system to facilitate lowering and raising heavy loads.





Mechanical Prusiks for Tree Care

Mechanical Prusiks allow the user to move around efficiently in a tree while benefiting from the handling of a classic Prusik pulley system.













Standard Descenders

Descenders with a simple design, using the friction between the rope and the device to brake a descent. The speed of the descent is regulated by varying the grip on the free end of the rope.









Personal Escape System

Rescue device that allows a single person to get themselves out of a building or structure in the event of an emergency. It has a multipurpose anchor hook adapted for locations where the possibility of finding an anchor point is uncertain.









Self-Braking Descenders

Easy to use, self-braking descenders adapt to a variety of situations encountered during work at height, rope access work, or technical rescue: descending, work positioning, short rope ascents, belaying with climbing techniques.

· Easy to use



AUTO-LOCK system The AUTO-LOCK system

allows users to easily position themselves at a workstation without having to manipulate the handle or tie off the device: as soon as the user releases the handle, the rone is automatically locked in the device.



Installing the rope

The device has a safety gate on the moving side plate that allows the rope to be easily installed while the device remains connected to the harness.



Comfortable, controlled descent

The ergonomic handle allows unlocking the rope and comfortably controlling the descent. Two descent modes are possible: on the side plate or in the V-shaped friction channel.

Versatile




Self-braking descenders are versatile and can be used for both descents and short rope ascents.

Wear-resistant



The stainless steel wear plate improves durability by reinforcing the rope friction zone.

• With anti-panic function and anti-error catch



Designed for work at height, rope access, and technical rescue and evacuation, these devices are equipped with an anti-panic function and an anti-error catch, to reduce the risk of an accident due to user error. They are also compatible with auxiliary brakes, which help increase the friction for lowering heavy loads.




I'D self-braking descenders with anti-panic function



Self-braking descender with anti-panic function for work at height and rope access work The self-braking I'D S descender is primarily designed for work at height and rope access work. It has an ergonomic handle that allows comfortable descent control. The integrated anti-panic function and anti-error catch reduce the risk of an accident due to user error. The AUTO-LOCK system allows users to easily position themselves at the workstation without having to manipulate the handle or tie off the device. Once locked, the rope can be taken up without having to manipulate the handle. The safety gate allows the rope to be installed with the device remaining connected to the harness. I'D S is compatible with 10 to 11.5 mm ropes and allows handling of loads up to 250 kg.



ľD® I



The I'D L self-braking descender is primarily designed for rescue. It has an ergonomic handle that allows comfortable descent control. The integrated anti-panic function and anti-error catch reduce the risk of an accident due to user error. The AUTO-LOCK system allows users to position themselves without having to manipulate the handle or tie off the device. Once locked, the rope can be taken up without having to manipulate the handle. The safety gate allows the rope to be installed with the device remaining connected to the harness. I'D L is compatible with 12.5 to 13 mm ropes and allows handling of loads up to 280 kg.



I'D® FVAC

Self-braking descender with anti-panic function for lowering from an anchor

The I'D EVAC self-braking descender is primarily designed for lowering from an anchor. The ergonomic handle is specifically oriented for managing a load from the anchor and offers comfortable descent control. The integrated anti-panic function and anti-error catch reduce the risk of an accident due to user error. The AUTO-LOCK system allows the rope to be automatically locked without having to manipulate the handle or tie off the device. Once locked, the rope can be taken up without having to manipulate the handle. The safety gate allows the rope to be installed with the device remaining connected to the anchor. I'D EVAC is compatible with 10 to 11.5 mm ropes and allows handling of loads up to 250 kg.



Accessories



Open Auxiliary Brake for I'D®

Open auxiliary brake for I'D S. I'D L. and I'D EVAC self-braking descenders

The open auxiliary brake is designed for I'D self-braking descenders. It is used to add friction depending on the load and rope diameter, and allows the rope to be inserted or removed at any time.



Closed Auxiliary Brake for I'D®

Closed auxiliary brake for I'D S, I'D L, and I'D EVAC self-braking descenders

The closed auxiliary brake is designed for I'D self-braking descenders. It is used to add friction depending on the load and rope diameter and provides a constant redirect of the rope.





The BIG descender is compact and lightweight. and designed for experienced rope access workers.



RIG®

Compact self-braking descender for rope access, designed for experienced users

RIG is a compact self-braking descender for rope access, designed for experienced users. It has an ergonomic handle that allows comfortable descent control. The AUTO-LOCK system allows users to easily position themselves at the workstation without having to manipulate the handle or tie off the device. Once locked, the rope can be taken up without having to manipulate the handle. The safety gate allows the rope to be installed with the device remaining connected to the harness.

Descenders for Technical Rescue

These descenders offer the versatility required for technical rescue operations: lowering, hauling, handling heavy loads, use in the primary system or in a back-up belay.

· Easy rope installation



Markings on the device make rope installation quick and easy.

· Comfortable, controlled descent, even with heavy loads



The ergonomic handle and integrated brake enable a comfortably controlled descent.



Excellent hauling efficiency



The integrated progress-capture pulley with very large diameter sheave mounted on sealed ball bearings rotates in only one direction for excellent hauling efficiency. The lower connection point can be used to create different types of haul systems.

· AUTO-LOCK system: automatically locks the rope



AUTO-LOCK

The AUTO-LOCK system allows automatic locking of the rope when the handle is not in use. Once locked, the rope can be taken up without having to manipulate the handle.

MAESTRO S

Ø 10.5 to 11.5 mm





MAESTRO® S

Descender with integrated progress-capture pulley for loads up to 250 kg, compatible with 10.5 to 11.5 mm ropes

MAESTRO descenders with integrated progress-capture pulley

MAESTRO S is a descender designed for technical rescue operations. It makes it easier to manipulate heavy loads when lowering or hauling, and may be used in both the primary system or in a back-up belay. This versatility allows rescuers to adapt to a variety of different situations they may encounter on the rescue scene. The ergonomic handle and integrated brake enable a comfortably controlled descent. Shifting from lowering position to raising position is immediate, without the need to transfer the load. The integrated progress-capture pulley has a large diameter sheave mounted on sealed ball bearings, providing excellent hauling efficiency. The AUTO-LOCK system automatically locks the rope when the handle is not in use. Once locked, the rope can be taken up without having to manipulate the handle. The MAESTRO S descender is compatible with 10.5 to 11.5 mm ropes and allows handling of loads up

MAESTRO L

Ø 12.5 to 13 mm

№ 280 kg



MAESTRO® L

Descender with integrated progress-capture pulley for loads up to 280 kg, compatible with 12.5 to 13 mm ropes

MAESTRO L is a descender designed for technical rescue operations. It makes it easier to manipulate heavy loads when lowering or hauling, and may be used in both the primary system or in a back-up belay. This versatility allows rescuers to adapt to a variety of different situations they may encounter on the rescue scene. The ergonomic handle and integrated brake enable a comfortably controlled descent. Shifting from lowering position to raising position is immediate, without the need to transfer the load. The integrated progress-capture pulley has a large diameter sheave mounted on sealed ball bearings, providing excellent hauling efficiency. The AUTO-LOCK system automatically locks the rope when the handle is not in use. Once locked, the rope can be taken up without having to manipulate the handle. The MAESTRO L descender is compatible with 12.5 to 13 mm ropes and allows handling of loads up to 280 kg.






Mechanical Prusiks for Tree Care

Mechanical Prusiks allow arborists to optimize their movement within a tree. They are user-friendly and intuitive to use. To meet a variety of needs, they can be used on doubled ropes or a single rope.

· Intuitive design



The technique is identical to that of a classic Prusik pulley system, offering immediate usability. The device locks automatically once the friction chain is extended.

· For efficient movement



Smooth, precise rope feed The release lever is mounted on a spring for great precision when moving around. Adjusting the pressure on this lever controls the speed of movement.

Slack easily taken up



The pulley is mounted on sealed ball bearings to allow the slack to be taken up easily when moving around. The widely spaced side plates also contribute to smooth rope glide.

Versatile



Use on doubled ropes ZIGZAG and ZIGZAG PLUS allow use on doubled ropes.

Use on a single rope



They can also be used on a single rope, thanks to the CHICANE accessory, which offers more friction on the descent, and the KNEE ASCENT assemblies, which facilitate the ascent.

· Standard version




The lower attachment hole is fixed to maintain alignment of the device with the axis of the worker and to optimize grip.



7IG7AG®

Mechanical Prusik for tree care



· Version with high-efficiency swivel



The lower attachment hole with high-efficiency swivel provides stable and correct positioning of the mechanical Prusik and optimal rope glide through the device.

ZIGZAG PLUS mechanical Prusik

ZIGZAG® PLUS


Mechanical Prusik with high-efficiency swivel, for tree care

The ZIGZAG PLUS mechanical Prusik allows the user to move around efficiently in a tree using classic Prusik pulley system technique. The friction chain provides precision and fluidity when moving around. The pulley is mounted on sealed ball bearings to allow the slack to be taken up easily. Can be used on either doubled ropes or a single rope, providing great versatility. The lower attachment hole with highefficiency swivel provides stable and correct positioning of the mechanical Prusik and optimal rope glide through the device.

Accessory

CHICANE

Auxiliary brake for mechanical Prusik on single ropes, for tree care































Standard Descenders



HUIT

Figure-eight descender

Figure-eight descender, compact and lightweight. Square shape helps reduce rope twist.



RACK

Variable friction descender with brake bars

The design and configuration of the RACK bars make it easy to set up and insert the rope. Compact and lightweight, the device allows the user to adjust the amount of friction during the descent to adapt to changing conditions.

Personal Escape System



EXO® AP HOOK

Personal escape system with anchor hook

EXO AP HOOK is a personal escape system with a HOOK anchor hook, adapted for situations where the possibility of finding an anchor point is uncertain. It has a self-braking system with anti-panic function for quickly moving horizontally, climbing through a window, and controlling or stopping a descent. If the user pulls too hard on the handle, the anti-panic function brakes and stops the descent automatically. EXO AP HOOK also includes a rope that resists wear and high temperatures, an Am'D connector with CAPTIV positioning bar, and a bag for transporting and attaching the system directly to the harness. Other rope lengths and other types of connectors (such as the EASHOOK OPEN) are available by special order.



If the user pulls too hard on the handle, the anti-panic function brakes and stops the descent automatically



The anchor hook may be used around a structure, secured with a locking hitch.



Petzl Custom allows you to choose: Rope type: Standard or high-strength rope

- Rope color
- · Rope length
- CUSTOM Type of rope-end connectors and harness connector

The assembly of various components of your choice offers a ready-made solution specific to the user, delivered in a transport pouch or bag adapted to the length of the rope.

Because of the unique shape of the anchor hook, special Petzl training for the EXO AP HOOK is mandatory.

			Certifications	Rope Diameter Compatibility	Working Load Limit	Weight	3
Self-Braking Desc	enders						
ľDS		D020AA00 (yellow) D020AA01 (black)	EN 341 type 2 class A (1) CE EN 12841 type C (2) CE EN 15151-1 (3) ANSI Z359.9 (4) NFPA 2500 Technical Use (5) EAC, UKCA	10 to 11,5 mm	Lowering a heavy load up to 250 kg	600 g	
ľD L		D020BA00 (red) D020BA01 (black)	EN 341 type 2 class A (6) CE EN 12841 type C (7) ANSI Z359.9 (8) NFPA 2500 General Use (9) EAC, UKCA	12,5 to 13 mm	Lowering a heavy load up to 280 kg	600 g	Y
I'D EVAC		D020CA00 (yellow) D020CA01 (black)	EN 341 type 2 class A (1) CE EN 12841 type C (2) ANSI 2359.9 (4) NFPA 2500 Technical Use (5) EAC, UKCA	10 to 11,5 mm	Lowering a heavy load up to 250 kg	615 g	A
RIG		D021AA00 (yellow) D021AA01 (black)	CE EN 12841 type C (2) EN 341 type 2 class A (1) CE EN 15151-1 (10) ANSI Z359.9 (4) NFPA 2500 Technical Use (5) EAC, UKCA	10 to 11,5 mm	Lowering a heavy load up to 200 kg	400 g	0
Open Auxiliary Brak for I'D	е	D020DA00	-	-	-	20 g	9
Closed Auxiliary Bra for I'D	ike	D020EA00	-	-	-	20 g	
Rescue Descende	rs						
MAESTRO S		D024AA00	CE EN 12841 type C, EN 341 ANSI Z359.9 NFPA 2500 Technical Use EAC, UKCA	10,5 to 11,5 mm	Lowering a heavy load up to 250 kg	1100 g	۵
MAESTRO L		D024BA00	CE EN 12841 type C, EN 341 ANSI Z359.9 NFPA 2500 General Use EAC, UKCA	12,5 to 13 mm	Lowering a heavy load up to 280 kg	1100 g	•
Mechanical Prusik	s for Tre	e Care					-6
ZIGZAG	*	D022AA00	CE UKCA	11,5 to 13 mm	140 kg	365 g	
ZIGZAG PLUS		D022BA00	CE UKCA	11,5 to 13 mm	140 kg	425 g	(1)
CHICANE	C	D022CA00	CE, UKCA (with ZIGZAG or ZIGZAG PLUS mechanical Prusik)	11,5 to 13 mm	140 kg	255 g	
Standard Descend	lers						
HUIT	8	D02	-	8 to 13 mm (single and double rope)	100 kg	100 g	KI
RACK		D11	-	9 to 13 mm (single rope) 8 to 11 mm (double rope)	100 kg	470 g	CUSTO
Personal Escape S	System						
EXO AP HOOK		D031DA00	NFPA 2500 Escape Use	7,5 mm (EXO rope only)	140 kg	1470 g	2

(1) EN 341 type 2 class A when used with a PARALLEL 10.5 mm or AXIS 11 mm rope

(2) EN 12841 type C when used with a 10 to 11.5 mm EN 1891 A rope (3) EN 15151-1 when used with a 10 to 11 mm rope

- (4) ANSI 2359.9 when used with a 10 to 11.5 mm rope (5) NFPA 2500 Technical Use when used with a 10 to 11.5 mm rope

(6) EN 341 type 2 class A when used with a VECTOR 12.5 mm rope (7) EN 12841 type C when used with a 12.5 to 13 mm EN 1891 A rope (8) ANSI Z359.9 when used with a 12.5 to 13 mm rope


(9) NFPA 2500 Technical Use when used with a 12.5 to 13 mm rope (10) EN 15151-1 when used with a 9 to 11 mm rope





ROPE CLAMPS

Rope clamps are primarily used for progression on ropes and for setting up haul systems.



Optimal locking

Petzl frame-loaded rope clamps are designed to function optimally under many different conditions (wet, frozen, dirty ropes, for example). They are therefore equipped with a special stainless steel carn. Its unique design, the shape of its teeth, and its self-cleaning slot allow optimal grip on the rope without damaging it, while reducing the effort required to slide the device up the rope.

Rope Clamps for Progression Frame-loaded rope clamps are easy to install and specially designed for rope ascents (handled rope clamps, ventral rope clamps, and foot-mounted rope clamps).





































Rope clamp that can be used to ascend a fixed rope, or as progress capture in a haul system.



Back-Up Rope Clamp

Ultra-compact, lightweight rope clamp for occasional rope ascents and haul systems.







Cam-Loaded Rope Clamp Rope clamp designed for use in haul systems as a tractor or progress-capture device.











Rope Clamps for Progression



ASCENSION

Handled rope clamp for rope ascents

The ASCENSION handled rope clamp is designed for rope ascents and features an overmolded grip and ergonomic upper part for a comfortable and powerful grip when pulling with one or two hands. The ASCENSION handled rope clamp has a large lower hole for easily attaching two carabiners for a lanyard and foot loop.



The overmolded dual-density grip has an area for the index finger and a wide, supportive base to keep the hand from slipping. Ergonomic upper part maximizes power when pulling with two hands.



PROGRESS ADJUST-Y

Double adjustable progression lanyard

Find a description of the PROGRESS ADJUST-Y lanyard on page 96.



FOOTAPE

Adjustable webbing foot loop

The adjustable FOOTAPE foot loop is used with an ASCENSION or BASIC rope clamp for rope ascents. A height-adjustable elastic keeps the foot in the loop, regardless of shoe type.

FOOTCORD

Adjustable cord foot loop

The adjustable FOOTCORD foot loop is used with an ASCENSION or BASIC rope clamp for rope ascents. Its high-modulus polyethylene construction increases durability. A height-adjustable elastic keeps the foot in the loop, regardless of shoe type.



The LOOPING four-step etrier attaches to an ASCENSION rope clamp for rope ascents or directly onto an anchor for progression in overhangs.



CROLL®

Ventral rope clamp

Designed for rope ascents, the CROLL ventral rope clamp is simple to use, with a pinch opening system, which is totally integrated in the clamp to avoid any involuntary snagging. The attachment holes allow efficient positioning during ascents. It is available in two versions to adapt to different



SFCUR

Shoulder straps for positioning the CROLL ventral rope clamp

SECUR shoulder straps position the CROLL ventral rope clamp and attach to AVAO SIT. FALCON, FALCON ASCENT, and SEQUOIA SRT harnesses.



ASCENTREE

Double-handled rope clamp for tree care

Handled rope clamp designed for double rope ascents, the ASCENTREE has ergonomic handles allowing a comfortable and powerful grip when pulling. Catch/cam unit is totally integrated to prevent any involuntary snagging.



Foot-mounted rope clamp

The PANTIN foot-mounted rope clamp is used with the CROLL, ASCENSION, or ASCENTREE rope clamps to make rope ascents faster and less tiring. It is available in right- and left-foot versions.



Catch to keep the rope in the device during rope ascents.



Installing the KNEE ASCENT

KNEE ASCENT LOOP

Knee ascender assembly with foot loop to facilitate ascents on a single rope,

The KNEE ASCENT LOOP assembly facilitates the arborist's ascent when using the ZIGZAG or ZIGZAG PLUS mechanical Prusik on a single rope. It contains an upper strap, a CROLL L rope clamp, a lower strap with foot loop, and a TOOLBAG 1.5 tool pouch. The system is fully adjustable and adapts to different body types.



Knee ascender assembly with boot connector, facilitating single rope ascents,

The KNEE ASCENT CLIP assembly facilitates the arborist's ascent when using the ZIGZAG or ZIGZAG PLUS mechanical Prusik on a single rope. It contains an upper strap, a CROLL L rope clamp, a lower strap with connector that attaches to the sewn webbing on the top of the arborist's boot, and a TOOLBAG 1.5 tool pouch. The system is fully adjustable and adapts to different body types.



Versatile Rope Clamp



BASIC

Compact, versatile rope clamp

The BASIC rope clamp is very compact, making it easy to grip.

The large lower hole allows lanyard and foot loop carabiners to be easily connected.

Back-Up Rope Clamp



TIBLOC

Back-up rope clamp

Extremely compact and lightweight, the TIBLOC is a back-up rope clamp for ascending ropes or setting up haul systems.

Cam-Loaded Rope Clamp



RESCUCENDER

Openable cam-loaded rope clamp
Simple to use and ergonomic, the RESCUCENDER is an openable cam-loaded rope clamp designed for use in haul systems as a tractor or progress-capture device.



Openable guided cam allows easy installation or removal of the rope clamp at any point on the rope.




The safety catches are equipped with indicators that show when they are unlocked.

			Certifications	Rope Diameter Compatibility	Weight	36
Rope Clamps for Prog	gression					
ASCENSION	00	B17ALA (left-handed, black/yellow) B17ALN (left-handed, black) B17ARA (right-handed, black/yellow) B17ARN (right-handed, black)	CE EN 567, EN 12841 type B NFPA 2500 Technical Use EAC UKCA	8 to 13 mm	165 g	Y
FOOTAPE		C47A	-	-	65 g	10
FOOTCORD	13	C48A	-	-	40 g	
LOOPING		C25	-	-	145 g	U
CROLL S	E	B16BAA	CE EN 567, EN 12841 type B NFPA 2500 Technical Use EAC UKCA	8 to 11 mm	85 g	
CROLL L		B016AA00	CE EN 567, EN 12841 type B NFPA 2500 Technical Use EAC UKCA	8 to 13 mm	140 g	Ö
SECUR	\bigvee	C74A	-	-	135 g	8
ASCENTREE		B19AAA	CE UKCA	8 to 13 mm	330 g	
PANTIN	T	B02CLA (left foot) B02CRA (right foot)	The PANTIN is not an item of PPE	8 to 13 mm	85 g	-6
Catch for PANTIN		B02210 (for left foot PANTIN) B02200 (for right foot PANTIN)	-	-	25 g	
KNEE ASCENT LOOP		D022DA00	-	8 to 13 mm	280 g	
KNEE ASCENT CLIP	ė ė	D022EA00	-	8 to 13 mm	285 g	** 2
Versatile Rope Clamp)					KIT .
BASIC		B18BAA	CE EN 567, EN 12841 type B EAC UKCA	8 to 11 mm	85 g	C
Back-Up Rope Clamp						CUSIOM
TIBLOC	D	B01BN	CE EN 567 EAC UKCA	8 to 11 mm	35 g	
Cam-Loaded Rope C	lamp					
RESCUCENDER	<u></u>	B50A	CE EN 567, EN 12841 type B NFPA 2500 Technical Use EAC UKCA	9 to 13 mm (1) 10 to 13 mm (2)	260 g	
		·				

(1) For the CE EN 567 standard, (2) for the other standards.


PULLEYS

Pulleys are used for raising equipment and for making haul systems in a rescue situation. Some of them can be combined with a rope clamp to facilitate maneuvers; others allow movement along rope or cable.



Two factors determine a pulley's efficiency:

- Sheave size: the larger the sheave diameter, the higher the efficiency
- · Bushings and bearings:
- Self-lubricating bushings are efficient, but they must be regularly maintained - Sealed ball bearings are very efficient, and they do not require any maintenance



High-Efficiency Pulleys With Swivel

High-performance pulleys equipped with a swivel, making them drop-resistant while installing the rope.



















Versatile, high-performance pulleys adapted for intensive use.











High-Efficiency Pulleys

Pulley-carabiners with excellent efficiency.











Pulleys with an integrated progress-capture system may be used to replace a traditional pulley/rope clamp setup in haul systems.









Prusik Pulleys

Single Pulleys

High-performance pulleys designed for use with za Prusik friction hitch to build a lightweight progresscapture system. The shape of the side plates allows the knot to be released when it stops against the pulley.















Lightweight, versatile pulleys designed for situations that do not require a high level of efficiency (such as redirecting the rope).











Transport Pulleys Pulleys designed for movement along a rope or cable.















Ready-to-use kit, designed to easily pick off and lower (or simply pick off) a victim.















High-Efficiency Pulleys With Swivel





SPIN L1 and SPIN L2 pulleys

SPIN L1

Very high efficiency single pulley with swivel

Possible to open, even when attached to the anchor, the SPIN L1 pulley is designed for maximum simplicity in setting up haul or load deviation systems and tensioned highlines. The large-diameter sheave mounted on sealed ball bearings gives it excellent efficiency. The swivel facilitates handling, allowing the pulley to be oriented under load and to directly connect carabiners, ropes, or slings.



SPIN I 2

Very high efficiency double pulley with swivel

Possible to open, even when attached to the anchor, the SPIN L2 is a double pulley designed for maximum simplicity when setting up haul systems or tensioned highlines. The two parallel-mounted sheaves and auxiliary attachment point allow the pulley to be used to set up various types of complex haul systems. The large-diameter sheaves mounted on sealed ball bearings provide excellent efficiency. The swivel facilitates handling, allowing the pulley to be oriented under load and to directly connect carabiners, ropes, or slings.



SPIN L1D pulley



SPINI 1D

Very high efficiency single pulley with one-way rotation and swivel

Possible to open, even when attached to the anchor, the SPIN L1D pulley is designed to be used in conjunction with a descender for maximum simplicity when setting up a deviation for a heavy load. The faceted sheave only rotates in one direction, providing excellent efficiency when hauling, and adding friction zones for the rope for additional braking when lowering. The swivel facilitates handling, allowing the pulley to be oriented under load and to directly connect carabiners, ropes, or slings.



SPIN S1 and SPIN S1 OPEN pulleys



SPIN S1

Very high-efficiency, compact single pulley with swivel

Possible to open, even when attached to the anchor, the SPIN S1 pulley is designed for maximum simplicity in setting up haul or load deviation systems and tensioned highlines. Compact, reducing weight and bulk, which is especially useful during technical rescue. The sheave mounted on sealed ball bearings provides excellent efficiency. The swivel facilitates handling, allowing the pulley to be oriented under load and to directly connect carabiners, ropes, or slings.



PETZL.COM

SPIN S1 OPEN

Very high-efficiency, compact single pulley with gated swivel

Possible to open, even when attached to the anchor, the SPIN S1 OPEN pulley is designed for maximum simplicity in setting up haul or load deviation systems and tensioned highlines. Compact, reducing weight and bulk, which is especially useful during technical rescue. The sheave mounted on sealed ball bearings provides excellent efficiency. The swivel facilitates operations, allowing the pulley to be oriented under load. The opening gate on the swivel makes the pulley compatible with a wide variety of products, (tripod, REEVE pulley, PAW rigging plates, and more) reducing bulk during setup.

High-Efficiency Pulleys



PARTNER

Ultra-compact, high-efficiency pulley

The PARTNER is an ultra compact, extremely lightweight pulley. It is designed for daily tasks and on-site rescue.



RESCUE

High strength, very high efficiency pulley

The very high efficiency RESCUE pulley is designed for intensive use by rescue professionals.

Pulley-Carabiners





ROLLCLIP A

Pulley-carabiner that facilitates installation of the rope when pulley is connected to

ROLLCLIP A is a pulley-carabiner with the gate opening on the pulley end, to facilitate rope installation when the pulley is fixed to the anchor. It is available with an automatic TRIACT-LOCK locking system, or without a locking system. ROLLCLIP A may be used with a CAPTIV positioning bar to promote loading of the carabiner on the major axis, to limit the risk of rotation and to keep it integrated with the device.





ROLLCLIP Z

Pulley-carabiner that facilitates installation on anchors and devices

ROLLCLIP Z is a pulley-carabiner with the gate opening on the non-pulley end, to facilitate installation on anchors and devices. It is available in two locking systems: automatic TRIACT-LOCK system or manual SCREW-LOCK system.

Progress-Capture Pulleys



PRO TRAXION

Very high-efficiency, drop-resistant progress-capture pulley with swivel

Possible to open, even when attached to the anchor, the PRO TRAXION progress-capture pulley is designed for setting up haul systems. With a large diameter sheave mounted on sealed ball bearings and excellent efficiency, it is particularly suitable for hauling heavy loads. The swivel makes it easier to operate, allowing the pulley to be oriented under load and for carabiners, ropes, or slings to be directly






MINI TRAXION

Compact and drop-resistant high-efficiency progress-capture pulley

Possible to open, even when attached to the anchor, the MINI TRAXION progress-capture pulley is designed for setting up haul systems. With a medium-diameter sheave and great efficiency, it is particularly suitable for hauling mid-weight loads. It is compact, with minimized weight and bulk, which is especially useful during technical rescue and rope access work.







Triple-action opening of the moving side plate is quick and easy, even with gloves.



The rope can be installed in the MINI TRAXION pulley when it is connected to the anchor.



































133

Prusik Pullevs



MINI

Highly efficient and lightweight Prusik pulley

The MINI compact pulley offers a lightweight solution for setting up progress-capture haul systems.



GEMINI

Highly efficient and lightweight double Prusik pulley

GEMINI is a compact double pulley for setting up progress-capture haul systems of high mechanical



MINDER

High strength, very high efficiency Prusik pulley

MINDER is a high-strength pulley designed for rescue professionals, for setting up progress-capture haul systems.



NIWT

High-strength, very high efficiency double Prusik pulley

TWIN is a high-strength double pulley designed for rescue professionals. It can be used to set up progress-capture haul systems of high mechanical advantage.

Single Pulleys



MOBIL F

Versatile ultra-compact pulley

Compact and extremely lightweight, the MOBILE pulley is designed for a variety of uses.



FIXE

Versatile compact pulley

Versatile and compact, the FIXE pulley allows quick installation onto the rope.

Transport Pulleys



Carriage pulley for rescue on a tensioned highline

Combining two pulleys and a rigging plate, the REEVE carriage pulley is an integrated solution designed to simplify setting up rescue systems on tensioned highlines. The compact design limits the number of connectors and the height of the system. Two large-diameter sheaves mounted on sealed ball bearings provide excellent efficiency when moving. Multiple connection holes to directly attach ropes, slings, or carabiners, allowing for better organization.



REEVE carriage pulley



Triple-action opening of the moving side plates is quick and easy, even with aloves.



Two red indicators provide a visual warning when the moving side plates are unlocked.



TANDEM® / TANDEM® SPEED

Double pulleys for tensioned highlines

TANDEM and TANDEM SPEED are designed for tensioned highlines on cables or ropes, and can accept up to three connectors to facilitate operations. TANDEM is used on a rope. TANDEM SPEED can also be used on a cable because of its wear-resistant sheaves mounted on sealed ball bearings.



KOOTFNAY

Knot-passing pulley

KOOTENAY is a knot-passing pulley that allows passage of joining knots.

The large-diameter sheave mounted on sealed ball bearings provides excellent efficiency.



ROLLCAB

Roller for movement along cable

ROLLCAB is a roller designed for movement and evacuation along mechanical lift cables.



Haul System



JAG SYSTEM

Haul kit

The JAG SYSTEM haul kit is designed for pick-offs, making a releasable anchor, or tensioning a system, with a 4:1 mechanical advantage and excellent efficiency (sheaves with sealed ball bearings). The collapsed kit is highly compact, allowing it to be used even when the distance to the anchor is very short. The JAG SYSTEM haul kit is guick and easy to deploy: it is ready to use due to the flexible cover that helps prevent the risk of tangling. The haul end is color-coded for instant identification. It is available in three lengths: 1, 2, and 5 meters.



JAG TRAXION

High-efficiency double progress-capture pulley

The JAG TRAXION double progress-capture pulley is designed for use with the JAG pulley to make a 4:1 haul system. Sheaves with sealed ball bearings provide excellent efficiency.



High-efficiency double pulley

The JAG double pulley is designed for use with the JAG TRAXION double progress-capture pulley to make a 4:1 haul system. Sheaves with sealed ball bearings provide excellent efficiency.

Haul System



TWIN RELEASE progress-capture pulley

TWIN RELEASE

Releasable double progress-capture pulley for haul systems

Releasable, the TWIN RELEASE progress-capture pulley is designed to set up 4:1 haul systems for work in confined spaces or for technical rescue. It's possible to release the cam using the ergonomic handle. When lowering heavy loads, the brake integrated into the moving side plate and the main faceted sheave with single-direction rotation offer additional braking and better control. The two sheaves provide excellent hauling efficiency. The swivel facilitates handling, allowing the pulley to be oriented under load and to directly connect carabiners, ropes, or slings.






Release of the cam and passage of the rope through the brake integrated into the main moving side plate, allows comfortable and precise control when lowering.



The cam can be locked in the open position to make it easier to feed slack.

			Certifications	Rope Diameter Compatibility	Sheave Diameter	Ball Bearings	Efficiency	Working Load Limit	Weight
High-Efficie	ncy Pul	leys With Swi	vel						
SPIN L1	8	P001BA00 P001BA01 (1)	CE EN 12278 NFPA 2500	7 to 13 mm	38 mm		95 %	4 x 2 = 8 kN	290 g
SPIN L2	ê	P001CA00 P001CA01 (1)	Pulley General Use UIAA UKCA	7 10 13 11111	30 ITIM	•	95 %	8 kN (3)	480 g
SPIN L1D	8	P001AA00	CE (2) NFPA 2500 Pulley General Use UKCA	8 to 13 mm	40 mm	•	93 %	3 x 2 = 6 kN	425 g
SPIN S1	8	P002AA00 P002AA01 (1)	CE EN 12278 NFPA 2500 Pulley Technical Use UIAA UKCA	7 to 11 mm	25 mm	•	91 %	2,5 x 2 = 5 kN	145 g
SPIN S1 OPEN	8	P002BA00							160 g
High-Efficie	ncy Pul	leys							
PARTNER		P52A	CE EN 12278 UKCA	7 to 11 mm	25 mm	•	91 %	2,5 kN x 2 = 5 kN	56 g
RESCUE		P50A P50AN (1)	CE EN 12278 NFPA 2500 General Use UKCA	7 to 13 mm	38 mm	•	95 %	4 kN x 2 = 8 kN	185 g
Pulley-Cara	biners								
ROLLCLIP A	00	P74 TL	CE EN 362 EN 12275 EN 12278 EAC, UKCA	7 to 13 mm	18 mm	•	85 %	2 kN x 2 = 4 kN	115 g
A.P.	W W	P74	CE EN 12275 EN 12278 EAC, UKCA						105 g
ROLLCLIP Z	00	P75 TL P75 SL	CE EN 362 EN 12278 EAC UKCA	7 to 13 mm	18 mm	•	85 %	2 kN x 2 = 4 kN	110 g

			Certifications	Rope Diameter Compatibility	Sheave Diameter	Ball Bearings	Efficiency	Working Load Limit	Weight
Progress-Ca	apture I	Pulleys							
PRO TRAXION	}	P055AA00	CE EN 567 EN 12278 EN 12841 type B NFPA 2500 Technical Use	8 to 13 mm	38 mm	•	95 %	Pulley: 11.5 kN x 2 = 23 kN Rope Clamp: 4 kN	295 g
NEW2023 MINI TRAXION		P054AA00	Technical Use Pulley and Rope grab UKCA	7 to 11 mm	32 mm	•	93 %	Pulley: 10 kN x 2 = 20 kN Rope Clamp: 4 kN	150 g
Prusik Pulle	evs								
MINI		P59A	CE EN 12278 NFPA 2500 Technical Use UKCA	7 to 11 mm	25 mm	•	91 %	2,5 kN x 2 = 5 kN	80 g
GEMINI	(P66A	CE EN 12278 NFPA 2500 Technical Use UKCA	7 to 11 mm	25 mm	•	91 %	2 x 1,5 kN x 2 = 6 kN	135 g
MINDER		P60A	CE EN 12278 NFPA 2500 General Use UKCA	7 to 13 mm	51 mm	•	97 %	4 kN x 2 = 8 kN	295 g
TWIN		P65A	CE EN 12278 NFPA 2500 General Use UKCA	7 to 13 mm	51 mm	•	97 %	2 x 3 kN x 2 = 12 kN	450 g
Single Pulle	ys								
MOBILE		P03A	CE EN 12278 UKCA	7 to 13 mm	21 mm	-	71 %	2,5 kN x 2 = 5 kN	75 g
FIXE	8	P05W P05WN (1)	CE EN 12278 UKCA	7 to 13 mm	21 mm	-	71 %	2,5 kN x 2 = 5 kN	90 g
Transport P	ulleys								
REEVE		P005AA00	CE EN 12278 NFPA 2500 General Use UKCA	7 to 13 mm	38 mm	•	95 %	4 kN x 2 = 8 kN	650 g
TANDEM	\(\text{\ti}\xititt{\text{\ti}\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\text{\tex{\tex	P21	CE EN 12278 UKCA	Rope ≤ 13 mm	21 mm	-	71 %	10 kN	195 g
TANDEM SPEED	**	P21 SPE	CE EN 12278 UKCA	Rope ≤ 13 mm Cable ≤ 12 mm	27,5 mm	•	95 %	10 kN	270 g
KOOTENAY		P67	CE EN 12278 UKCA	8 to 19 mm	76 mm	•	-	5 kN x 2 = 10 kN	1390 g
ROLLCAB	1	P47	CE EN 1909 UKCA	Cable ≤ 55 mm	55 mm	-	-	5 kN	1470 g
Haul Systen	n								
JAG SYSTEM	1 m 2 m 5 m	P044AA00 P044AA01 P044AA02	CE EN 358 EAC UKCA	8 mm	-	•	91 %	6 kN	610 g 805 g 1460 g
JAG TRAXION	9	P54	CE EN 567 NFPA 2500 Technical Use UKCA	8 to 11 mm	25 mm	•	91 %	2 x 1,5 kN x 2 = 6 kN	145 g
JAG	•	P45	CE EN 12278 NFPA 2500 Technical Use UKCA	8 to 11 mm	25 mm	•	91 %	2 x 1,5 kN x 2 = 6 kN	120 g
TWIN RELEASE	&	P001DA00	CE EN 567 EN 12278 (4) NFPA 2500 Pulley General Use NFPA Rope Grab Techical Use (5) UKCA	8 to 13 mm	40 mm 38 mm	•	95 %	280 kg	800 g
					<u> </u>				



Anchors are the link between the safety system and the structure or terrain. To complement the standard anchor equipment, Petzl offers a lifeline device specific to horizontal progression and a complete set of accessories.



Rock and Concrete Anchors

Elements that allow installation of temporary or permanent fixed anchors.



























Rigging Equipment
Swivels provide a solution to help prevent twisting and tangling ropes, especially when hauling. Rigging plates allow the workstation to be organized and increase the number of anchoring options. Rings allow multiple anchors to be organized.

















Anchor Slings and Straps


Slings and anchor straps designed for setting up temporary anchors.







Temporary Horizontal Lifeline



Anchor Straps for Tree Care Friction savers for tree care.







PETZL

Rock and Concrete Anchors

COEUR BOLT STEEL / STAINLESS / HCR Anchors comprised of a COEUR hanger, a nut, and a bolt (pack of 20)

Different steels suited to various environments

Petzl anchors (hangers and bolts) use different types of steels to adapt the anchor to the environment in which it is used:

- Standard steel, designed for interior uses or non-permanent installations: COEUR BOLT STEEL
- 316L high quality stainless steel, designed for typical exterior uses: COEUR BOLT STAINLESS
- HCR 904 (High Corrosion Resistance) stainless steel, designed for ultra-corrosive environments: COEUR BOLT HCR

Hangers (COEUR STEEL, COEUR STAINLESS and COEUR HCR) and bolts (BOLT STEEL, BOLT STAINLESS, and BOLT HCR) are also available separately (pack of 20).



COEUR PULSE 12 mm

Removable anchor with locking function

The COEUR PULSE 12 mm is a removable, high-quality stainless steel anchor that can be installed and removed for reuse very simply and rapidly without tools. The locking function limits the risk of accidental removal. The COEUR hanger can rotate during installation and when laterally loaded during use, allowing it to better align with the systems in place.



The anchor can be installed and removed for reuse very

simply and rapidly, without tools.



Manual screw-lock function limits the risk of involuntary removal.



How to install and inspect COEUR PULSE anchors

COLLINOX

Forged stainless steel glue-in bolt (pack of 10)



AMPOULE COLLINOX

Resin glue for COLLINOX (pack of 10)



BAT'INOX

Forged stainless steel glue-in bolt (pack of 10)



AMPOULE BAT'INOX

Resin glue for BAT'INOX (pack of 10)

Rigging Equipment



MICRO SWIVEL

Compact gated swivel

The compact, gated MICRO SWIVEL is designed for attachment to a locking carabiner, It helps prevent twisting of lanyards and allows correct positioning of devices. Its design without bearings allows it to turn freely when not loaded and to stop moving when loaded in order to hold the devices in position.



SWIVEL OPEN

Gated swivel with sealed ball bearings

The SWIVEL OPEN gated swivel features a large opening and can be attached to a wide range of products (such as pulleys or lanyards). It reduces the bulk and weight of component systems and solves the twisting and tangling problems of ropes and lanyards. Sealed ball bearings offer excellent performance and reliability.



SWIVE

Ball bearing swivel

Available in two sizes, the SWIVEL prevents the rope from twisting when the load is turning. Sealed ball bearings offer excellent performance and reliability.



PAW

Rigging plate

Available in three sizes, the PAW rigging plate can be used to organize a workstation and set up multi-anchor systems. The hole design allows ropes or slings to be threaded for direct connection. Made of forged aluminum, it offers an excellent strength-to-weight ratio.



RING

Connection ring

The RING connection ring can be used to create multiple anchors or be installed directly onto the SEQUOIA and SEQUOIA SRT harnesses' attachment bridges to improve the arborist's lateral mobility.



RING OPEN

Multidirectional gated ring

See page 112 for details on the RING OPEN multidirectional gated ring.




























Anchor Slings and Straps



ANNEAU

Sewn sling

ANNEAU is an open loop sling available in four lengths, color-coded for easy identification of length.



ST'ANNEAU

Lightweight sewn sling

ST ANNEAU is a lightweight alternative to classic slings, available in three lengths, with color coding for easy identification of length.



PUR'ANNEAU

Ultra-light sewn sling

PUR'ANNEAU is a very lightweight sling with exceptional durability, thanks to its high-modulus polyethylene construction. It is particularly supple, for easy handling. Available in three lengths, color-coded for easy identification of length.



CONNEXION FIXE

Anchor stran

CONNEXION FIXE is a durable anchor strap with two forged steel attachment points. It offers several configurations for setting up an anchor: directly to an anchor point or around a suitable structure. It is available in three lenaths (100, 150, and 200 cm).



CONNEXION VARIO

Adjustable anchor strap

CONNEXION VARIO is a durable and adjustable anchor strap equipped with two forged steel attachment points. It offers several configurations for setting up an anchor: directly to an anchor point or around a suitable structure. The strap length can be adjusted using the adjustment buckle. A system keeps the remaining webbing stowed. It is available in two versions: 30 to 200 cm and 200 to 400 cm.



WIRE STROP

Anchor strap

WIRE STROP is an anchor strap made of 6.5 mm diameter galvanized steel with two terminations of different sizes. It offers several configurations for setting up an anchor: directly to an anchor point or around a suitable structure. The plastic sheath helps hold the connector in position and facilitates clipping. It is available in five lengths (50, 100, 150, 200, and 300 cm).



Anchor strap with two terminations of different sizes. The plastic sheath helps hold the connector in position and facilitates clipping.



It offers several configurations for setting up an anchor: directly to an anchor point or around a suitable structure.

Quick-Adjustment Anchors



GRILLON Anchor

Quick-adjustment anchor

The adjustable GRILLON anchor can be used to quickly set a fixed anchor point. The length of rope required to set it is easily adjusted with the integrated self-locking device. The removable protective sheath allows smoother rope glide while protecting the rope from abrasive surfaces. It is available in four lengths.



PROGRESS ADJUST-I Anchor

Lightweight quick-adjustment anchor

Lightweight and compact, the PROGRESS ADJUST-I adjustable anchor can be used to quickly set up a fixed anchor point. The rope length required to set it up is easily adjusted with the ADJUST rope adjuster. The removable protective sheath protects the rope while enhancing rope glide. It is available in three lengths: 2, 3 and 5 m.

Temporary Horizontal Lifeline



GRILLON Lifeline

Temporary horizontal lifeline

GRILLON allows a horizontal lifeline to be installed quickly when there is a large work area to cover. The integrated self-blocking device allows easy adjustment of length, depending on the distance between two anchor points. It is available in four lengths to adapt to a variety of different situations.



Solar panel installation, France © 2022 Petzl Distribution - Vuedici.org - Laurent Moretton

Anchor Straps for Tree Care



Efficient



The EJECT and NAJA friction savers are adjustable so they can adapt to different branch diameters.

The EJECT and NAJA friction savers are both equipped with a pulley mounted on

sealed ball bearings. This improves rope

glide through the anchor and optimizes

rope ascents and movement in the tree.

• EJECT: Adjustable friction saver with choking function

The adjuster on the EJECT friction saver allows you precisely select the length of the strap to wrap or choke the tree trunk or branch. It is also possible to link two anchors for small branches. Unlocking the system is simple and quick, making it easy to retrieve from the ground




EJECT



adjustable friction saver

EJECT



Designed for tree care, the EJECT friction saver allows the work rope to be set up without damaging the tree, even in narrow forks. It offers multiple setup configurations on one or two branches and has a choke adjuster that allows precise length adjustment of the friction saver. Rope ascents and movement in the tree are optimized with the very high-efficiency pulley, which facilitates rope glide at the anchor. The included retrieval ball makes the system easily retrievable from the ground.



Strap for EJECT

Strap for EJECT adjustable friction saver


This strap is specially designed for the EJECT adjustable friction saver. It can be used to replace the original strap or link two straps together to lengthen the friction saver and enable work on larger-diameter trees. It is available in two lengths: 150 and 250 cm.



Retrieval ball for EJECT

Retrieval ball for EJECT adjustable friction saver

With a diameter of 21 mm, this retrieval ball is specially designed for the EJECT adjustable friction saver. It enables guick and easy system retrieval from the ground.





The EJECT and NAJA friction savers' thin construction reduces the risk of snagging during retrieval. The specially-designed retrieval balls make it easy to unlock the systems from the ground.

· NAJA friction saver featuring a strap with four different adjustment positions

The NAJA friction saver's adjustable strap has four different positioning loops, allowing you to better adapt to the diameter of the tree trunk or branch



NAJA

Friction saver for tree care that is easily retrievable from the ground, with an integrated pulley and a strap with different adjustment positions

Designed for tree care, the NAJA friction saver allows the work rope to be set up without damaging the tree. The strap has four different adjustment positions to adapt to different branch diameters. Rope ascents and movement in the tree are optimized with the high-efficiency pulley, which facilitates rope glide at the anchor. The included retrieval ball makes the system easily retrievable from the ground.



Strap for NAJA

Strap for NAJA adjustable friction saver

This strap is specially designed for the NAJA adjustable friction saver. It can be used to replace the original strap or link two straps together to lengthen the friction saver and enable work on larger-diameter trees. It is available in two lengths: 150 and 250 cm.



Retrieval Ball for NAJA

Retrieval ball for NAJA adjustable friction saver

With a diameter of 21 mm, this retrieval ball is specially designed for the NAJA adjustable friction saver. It enables quick and easy system retrieval from the ground.



























PETZL.

Anchor Straps for Tree Care



TREESBEE

Friction saver for tree care, designed for ropes with spliced terminations

The TREESBEE anchor strap is used to improve rope glide at the anchor while protecting the tree from abrasion. It is designed for ropes with spliced terminations (the splice goes through the small ring). The galvanized steel rings provide great durability.

		Certifications	Diameter	Shear Strength in 50 MPa Concrete	Pull-Out Strength in 50 MPa Concrete	Weight
Rock and Concrete And	chors					
COEUR BOLT	P36BA 10	EN 959	10 mm	23 kN	15 kN	110 g
STEEL	P36BA 12	EN 959	12 mm	23 KIN	18 kN	135 g
COEUR BOLT	P36BS 10	EN 959	10 mm	25 kN	15 kN	110 g
STAINLESS	P36BS 12	EN 959	12 mm	25 KIN	18 kN	135 g
COEUR BOLT HCR	P36BH 12	EN 959	12 mm	25 kN	18 kN	145 g
COEUR STEEL	P36AA 10	EN 705 A	10 mm			65 g
COEUR STEEL	P36AA 12	EN 795 A	12 mm	=	=	60 g
COEUR STAINLESS	P36AS 10	EN 795 A	10 mm			65 g
COEUR STAINLESS	P36AS 12	EN 795 A	12 mm	-	-	60 g
COEUR HCR	P36AH 12	EN 795 A	12 mm	=	-	60 g
NEW2023 COEUR PULSE 12 mm	G037BA00	CE EN 795 B, EN 959, TS 16415 UKCA	12 mm	25 kN	20 kN	140 g
COLLINOX	G100AA00	EN 959	10 mm	25 kN	15 kN	95 g
AMPOULE COLLINOX	G101AA00	=	=	=	=	14 g
BAT'INOX	G102AA00	EN 959	14 mm	25 kN	15 kN	250 g
AMPOULE BAT'INOX	G103AA00	=	=	=	=	20 g

			Certifications	Breaking Strength	Weight		
Rigging Equipment							
MICRO SWIVEL		P58 XSO	CE, EAC, UKCA	23 kN	75 g		
SWIVEL OPEN		P58 SO	CE, EAC, NFPA 2500 Technical Use, UKCA	23 kN	130 g		
SWIVEL	S	P58 S	CE, EAC ,NFPA 2500 Technical Use, UKCA	23 kN	95 g		
SWIVEL	L	P58 L	CE, EAC, NFPA 2500 General Use, UKCA	36 kN	150 g		
	S	G063AA00 / G063AA00 (1)	95	36 kN	60 g		
PAW	М	G063BA00 / G063BA01 (1)	CE NFPA 2500 General Use UKCA	45 kN	180 g		
	L	G063CA00 / G063CA01 (1)	GROA	50 kN	350 g		
DING	S	C04620	CE	23 kN	40 g		
RING	L	C04630	UKCA	20 KIN	70 g		

		Certifications	Length	Breaking Strength	Weight
Anchor Slings and Stra	ıps				
	C40A 60, C40 60N (1)		60 cm		60 g
ANNEALL	C40A 80, C40 80N (1)	CE EN 566 CE EN 795 B EAC UKCA	80 cm	00 141	80 g
ANNEAU	C40A 120, C40120 N (1)	EAC UKCA	120 cm	- 22 kN	100 g
	C40A 150] [150 cm		135 g
	C07 24		24 cm		10 g
ST'ANNEAU	C07 60	CE EN 795 B UKCA	60 cm	22 kN	20 g
	C07 120		120 cm		40 g
	G006AA00		60 cm		18 g
PUR'ANNEAU	G006AA01	CE EN 795 B UKCA	120 cm	22 kN	32 g
	G006AA02		180 cm		48 g
	G010AA00		100 cm		355 g
CONNEXION FIXE	G010AA01	CE EN 795 B	150 cm	25 kN	415 g
	G010AA02	CE EN 795 B NFPA 2500 General Use ANSI Z359.18 CSA Z259.15-17	200 cm		475 g
	G011AA00	- CSA Z259.15-17 UKCA	30 - 200 cm		810 g
CONNEXION VARIO	G011AA01	1	200 - 400 cm	- 25 kN	950 g
	G200AA00		50 cm		220 g
	G200AA01	CE EN 795 B	100 cm	1	320 g
VIRE STROP	G200AA02	CE EN 354 TS 16415 (2)	150 cm	23 kN	420 g
	G200AA03	NFPA 2500 Technical Use ANSI Z359.18 UKCA	200 cm		520 g
	G200AA04	-	300 cm	-	720 g
Quick Adjustment And	hors and Temporary Hor	izantal Lifalina			
kulok Aujustinent And	L052AA00	Zontar Enemie	2 m	-	480 g
		-			
	L052AA01		3 m	-	560 g
GRILLON		-		-	560 g 640 g
Anchor	L052AA01 L052AA02 L052AA03	CE EN 795 B&C EAC	3 m 4 m 5 m		640 g
Anchor GRILLON	L052AA02	CE EN 795 B&C EAC UKCA	4 m	-	640 g 720 g
Anchor GRILLON	L052AA02 L052AA03	CE EN 795 B&C EAC UKCA	4 m	-	640 g 720 g 1075 g
Anchor GRILLON	L052AA02 L052AA03 L052AA04	CE EN 795 B&C EAC UKGA	4 m 5 m 10 m	-	640 g 720 g 1075 g 1475 g
Anchor GRILLON jfelline	L052AA02 L052AA03 L052AA04 L052AA05 L052AA06	CE EN 795 B&C EAC UKGA	4 m 5 m 10 m 15 m 20 m	-	640 g 720 g 1075 g 1475 g 1875 g
Anchor BRILLON Ifeline PROGRESS ADJUST-I	L052AA02 L052AA03 L052AA04 L052AA05 L052AA06 L044BA01	UKCA	4 m 5 m 10 m 15 m 20 m 2 m	-	640 g 720 g 1075 g 1475 g 1875 g 300 g
Anchor BRILLON Ifeline PROGRESS ADJUST-I	L052AA02 L052AA03 L052AA04 L052AA05 L052AA06 L044BA01 L044BA02	- UKCA	4 m 5 m 10 m 15 m 20 m 2 m 3 m	-	640 g 720 g 1075 g 1475 g 1875 g 300 g 370 g
Anchor BRILLON Jelline PROGRESS ADJUST-I Anchor	L052AA02 L052AA03 L052AA04 L052AA05 L052AA06 L044BA01 L044BA02 L044BA03	UKCA	4 m 5 m 10 m 15 m 20 m 2 m	-	640 g 720 g 1075 g 1475 g 1875 g 300 g
Anchor SRILLON Jfeline PROGRESS ADJUST-I Anchor	L052AA02 L052AA03 L052AA04 L052AA05 L052AA06 L044BA01 L044BA02 L044BA03	UKCA CE EN 795 B EAC UKCA	4 m 5 m 10 m 15 m 20 m 2 m 3 m	-	640 g 720 g 1075 g 1475 g 1875 g 300 g 370 g
Anchor SRILLON Ifeline PROGRESS ADJUST-I Anchor Anchor Straps for Tree	L052AA02 L052AA03 L052AA04 L052AA05 L052AA06 L044BA01 L044BA02 L044BA03	UKCA	4 m 5 m 10 m 15 m 20 m 2 m 3 m	-	640 g 720 g 1075 g 1475 g 1875 g 300 g 370 g
GRILLON Anchor GRILLON Ifeline PROGRESS ADJUST-I Anchor Anchor Straps for Tree	L052AA02 L052AA03 L052AA04 L052AA05 L052AA06 L044BA01 L044BA02 L044BA03 Care G001AA00	CE EN 795 B EAG, TS 18415, UKCA	4 m 5 m 10 m 15 m 20 m 2 m 3 m 5 m	- - - - - - - - 25 kN	640 g 720 g 1075 g 1475 g 1875 g 300 g 370 g 510 g
Anchor SRILLON Lifeline PROGRESS ADJUST-I Anchor Anchor Straps for Tree	L052AA02 L052AA03 L052AA04 L052AA05 L052AA06 L044BA01 L044BA02 L044BA03 Care G001AA00	CE EN 795 B EAC, TS 16415, UKCA	4 m 5 m 10 m 15 m 20 m 2 m 3 m 5 m		640 g 720 g 1075 g 1475 g 1875 g 300 g 370 g 510 g
Anchor SRILLON Lifeline PROGRESS ADJUST-I Anchor Straps for Tree	L052AA02 L052AA03 L052AA04 L052AA05 L052AA06 L044BA01 L044BA02 L044BA03 Care G001AA00	CE EN 795 B EAG, TS 18415, UKCA	4 m 5 m 10 m 15 m 20 m 2 m 3 m 5 m	- - - - - - - - 25 kN	640 g 720 g 1075 g 1475 g 1875 g 300 g 370 g 510 g
Anchor Straps for Tree Strap for EJECT	L052AA02 L052AA03 L052AA04 L052AA05 L052AA06 L044BA01 L044BA02 L044BA03 Care G001AA00	CE EN 795 B EAC, TS 16415, UKCA	4 m 5 m 10 m 15 m 20 m 2 m 3 m 5 m		640 g 720 g 1075 g 1475 g 1875 g 300 g 370 g 510 g
Anchor SRILLON Jelline PROGRESS ADJUST-I Anchor Anchor Straps for Tree EJECT Strap for EJECT Retrieval Ball for EJECT	L052AA02 L052AA03 L052AA04 L052AA06 L052AA06 L044BA01 L044BA02 L044BA03 Care G001AA00 G002AA01	CE EN 795 B EAC, TS 16415, UKCA	4 m 5 m 10 m 15 m 20 m 2 m 3 m 5 m		640 g 720 g 1075 g 1475 g 1875 g 300 g 370 g 510 g
PROGRESS ADJUST-I Anchor Straps for Tree SJECT Strap for EJECT Retrieval Ball for EJECT	L052AA02 L052AA03 L052AA04 L052AA06 L052AA06 L044BA01 L044BA02 L044BA03 Care G001AA00 G002AA00 G002AA01	CE EN 795 B EN 12278 EAC, TS 16415, UKCA	4 m 5 m 10 m 15 m 20 m 2 m 3 m 5 m 150 cm 150 cm		640 g 720 g 1075 g 1475 g 1875 g 300 g 370 g 510 g 490 g 140 g 8 g
PROGRESS ADJUST-I Anchor Straps for Tree SJECT Retrieval Ball for EJECT NEW2023 JAJA	L052AA02 L052AA03 L052AA04 L052AA05 L052AA06 L044BA01 L044BA02 L044BA03 Care G001AA00 G002AA01 G003AA00 G004AA00	CE EN 795 B EAC, TS 16415, UKCA CE EN 795 B, EN 12278 EAC, TS 16415, UKCA CE EN 795 B, EN 12278 EAC, TS 16415, UKCA	4 m 5 m 10 m 15 m 20 m 2 m 3 m 5 m 150 cm 150 cm		640 g 720 g 1075 g 1475 g 1875 g 300 g 370 g 510 g 490 g 140 g 8 g 400 g
Anchor SRILLON Ifeline PROGRESS ADJUST-I Anchor Anchor Straps for Tree SJECT Strap for EJECT Retrieval Ball for EJECT NEW2023 JAJA REW2023 RETRIEVAL BALL RETRIEVAL BALL	L052AA02 L052AA03 L052AA04 L052AA05 L052AA06 L044BA01 L044BA02 L044BA03 Care G001AA00 G002AA01 G003AA00 G004AA00	CE EN 795 B EAC, TS 16415, UKCA CE EN 795 B, EN 12278 EAC, TS 16415, UKCA	4 m 5 m 10 m 15 m 20 m 2 m 3 m 5 m 150 cm 150 cm 150 cm		640 g 720 g 1075 g 1475 g 1875 g 300 g 370 g 510 g 490 g 140 g 225 g 8 g 400 g
Anchor SRILLON Ifeline PROGRESS ADJUST-I Anchor Straps for Tree EJECT Strap for EJECT NEW2023 NAJA NEW2023 Retrieval Ball Retrieval Ball	L052AA02 L052AA03 L052AA04 L052AA06 L052AA06 L044BA01 L044BA02 L044BA03 Care G001AA00 G002AA01 G002AA00 G002AA00 G004BA00 G004BA00 G004BA00	CE EN 795 B EAC, TS 16415, UKCA CE EN 795 B, EN 12278 EAC, TS 16415, UKCA	4 m 5 m 10 m 15 m 20 m 2 m 3 m 5 m 150 cm 150 cm 150 cm		640 g 720 g 1075 g 1475 g 1875 g 300 g 370 g 510 g 490 g 140 g 225 g 8 g 400 g

(1) Black (2) two-person usage

The line of Petzl ropes is designed for professionals in the vertical world. They offer effective solutions for the requirements of various activities: rope access, technical rescue, industry.



Low Stretch Kernmantle Ropes

For Work at Height

Standard diameter low stretch kernmantle rope provides a good grip for easier handling.

For Rope Access

Low stretch kernmantle rope with small diameter provides very good performance in terms of flexibility and weight.

For Rescue

Low stretch kernmantle rope with a large diameter provides great strength and excellent handling when working with heavy loads.

For Tree Care

Low stretch kernmantle rope with splice provides optimal performance when used with the ZIGZAG and ZIGZAG PLUS mechanical Prusiks.

















Static Ropes

For long descents, when intermediate anchors are not possible.



Dynamic Rope

For progression using rock climbing techniques.



Technical Cord

Cord for setting up Prusik hitches, anchors, or haul systems.



Accessory Cord

Cord for guiding a victim during rescue or for hauling equipment.



Rope Accessories

Professional rope accessories.









Devices that protect the rope at friction zones.







PETZL.COM

149

Low Stretch Kernmantle Ropes

A specific construction for each use and a choice of lengths and colors according to user needs.



• EverFlex technology: provides flexibility and handling over time

This technology provides great flexibility over time and under many different conditions (such as water, dust, and mud). The flexibility allows it to maintain consistent handling over the long run and perform optimally with devices.

· Multiple certifications

Petzl low stretch kernmantle ropes are certified to the following standards:

- European: CE EN 1891 type A
- American: NFPA 2500 (except FLOW 11.6 mm and CONTROL 12.5 mm, which allow working in compliance with the ANSI Z133 standard)
- Russian: EAC

· Available in several lengths and colors

Petzl low stretch kernmantle ropes come in several standard lengths, according to user needs and activities.




For work at height, rope access work and rescue

They are also available in six colors for easy differentiation of kits, work ropes, safety ropes, and collective access ropes.



For tree care

They are available in two colors, to differentiate working ropes from access ropes





Petzl Custom allows you to choose:

- Rone color
- Rope length
- Type of termination (sewn or not, only on low stretch kernmantle ropes)

· For work at height

Standard diameter low stretch kernmantle rope provides a good grip and compatibility with most devices.



AXIS 11 mm

Low stretch kernmantle rope with good handling for work at height

The AXIS 11 mm low stretch kernmantle rope is designed for work at height. The standard diameter provides a good grip for easier handling. EverFlex technology provides great flexibility and consistent performance over time. Rope available in six colors and four lengths.





PARALLEL 10.5 mm

Low stretch kernmantle rope, flexible and lightweight for rope access

The PARALLEL 10.5 mm low stretch kernmantle rope is designed for rope access. The small diameter provides very good performance in terms of flexibility and weight. It has low elongation when under tension, increasing efficiency at the start of a rope ascent. EverFlex technology provides great flexibility and consistent performance over time. Rope available in six colors and four lengths.

· For rescue

Low stretch kernmantle rope with a large diameter provides great strength and excellent handling when working with heavy loads.



VECTOR 12.5 mm

Low stretch kernmantle, high-strength rope with excellent handling, for rescue

The VECTOR 12.5 mm low stretch kernmantle rope is designed for rescue. The very large diameter provides great strength and excellent grip when handling heavy loads. EverFlex construction provides great flexibility and consistent performance over time. Rope available in six colors and four lengths.

For tree care

Low stretch kernmantle rope with splice provides optimal performance when used with the ZIGZAG and ZIGZAG PLUS mechanical Prusiks.

Ø 11.6 mm



FI OW 11.6 mm

Flexible and lightweight low stretch kernmantle rope, for tree care

The FLOW 11.6 mm low stretch kernmantle rope is designed for tree care. The small diameter provides very good performance in terms of flexibility and weight. It has low stretch when loaded, increasing efficiency when moving through the tree. EverFlex technology provides great flexibility and handling over time. It comes with a splice at one end for optimal rope glide through devices like a friction saver or pulley, and through tree branches. The small size of the splice allows it to pass through the friction chain of the ZIGZAG and ZIGZAG PLUS mechanical Prusiks. Rope available in two colors and three lengths

Ø 12.5 mm



CONTROL 12.5 mm

Low stretch kernmantle, high-strength rope with excellent handling, for tree care

The CONTROL 12.5 mm low stretch kernmantle rope is designed for tree care. The large diameter provides high strength and excellent grip. EverFlex technology provides great flexibility and handling over time. It comes with a splice at one end for optimal rope glide through devices like a friction saver or pulley, and through tree branches. The small size of the splice allows it to pass through the friction chain of the ZIGZAG and ZIGZAG PLUS mechanical Prusiks. Rope available in two colors and three lengths.

Install a CONTROL rope in a ZIGZAG mechanical Prusik



Static Ropes



RAY 11 mm

Static kernmantle rope with good grip for work at height and technical rescue

The RAY 11 mm static rope is designed for work at height and technical rescue involving long descents when intermediate anchors are not possible. It has low elongation under load for optimal precision during progression and positioning. The standard diameter provides a good grip for easier handling. EverFlex technology provides great flexibility and consistent performance over time. Rope available in four colors and four lengths.

Dynamic Rope



MAMBO® 10.1 mm

Dynamic rope for progression using climbing techniques

The 10.1 mm diameter MAMBO dynamic rope is designed for work at height professionals who use climbing techniques for progression. The thick sheath improves abrasion resistance.

Technical Cord



SEGMENT 8 mm

Technical cord

The SEGMENT 8 mm technical accessory cord is used when setting up Prusik hitches, anchors, or haul systems. EverFlex construction provides great flexibility and consistent performance over time. Cord available in three lengths.

Accessory Cord



Cords

Accessory cords

These rugged and durable cords are for guiding a victim during rescue or for hauling equipment.

Available in four diameters, in a 120-meter roll

Rope Accessories



1, 12, 12, 12,

Rope End Identification Kit

The rope end identification kit can be used to replace old labels or to identify individual ropes for professional uses. It contains twenty pre-printed labels and twenty heat-shrink sheaths compatible with 10.5 to 13 mm ropes.

Ident The id

Identification Label for Petzl Ropes

Identification labels for marking Petzl professional ropes (pack of 10 pairs)

The identification labels can be used to replace old labels or establish a tracking system in order to more easily identify individual Petzl AXIS 11 mm, PARALLEL 10.5 mm, and RAY 11 mm ropes. They can quickly be installed on the end of the rope without using a tool. The labels are rigid, allowing for clear readability and longer-lasting markings.

	References
Rope End Identification Kit	R002AA00
Identification Label for Petzl Ropes	R004BA00 (AXIS 11mm) / R004AA00 (PARALLEL 10.5 mm) / R004CA00 (RAY 11 mm)

Rope Protectors



PROTEC

Flexible protection for a fixed rope

The PROTEC flexible protector is designed to protect a fixed rope from abrasion when working at height or during rescue. Easy to install and durable, it's made for regular to intensive use. Versatile, PROTEC fits most rope diameters used by professionals, as well as anchor strans.

PROTEC PLUS

High-strength flexible protection for a fixed rope

With the help of its aramid construction, the PROTEC PLUS flexible protector is designed to protect a fixed rope from particularly abrasive surfaces or heat when working at height or during rescue. Easy to install and versatile, PROTEC PLUS fits most rope diameters used by professionals, as well as anchor straps.



ROLLER COASTER

Reversible rope protector on bearings for a moving rope

The ROLLER COASTER protector is designed to help protect a moving rope from abrasion. Reversible, with different frame shapes on either side that allow it to adapt to flat or angled surfaces. Multiple connection holes allow the use of different attachment methods. It's possible to connect multiple modules to better adapt to different types of terrain.

		Colors	Lengths	European Certification	US Certification	Russian Certification	Weight per Meter
ow Stretch Ker	nmantle Ropes						
	R074AA03	White					
	R074AA04	Yellow					
	R074AA05	Black					
	R074AA38	Blue	50 m				
	R074AA39	Red					
	R074AA40	Orange					
	R074AA09	White		1			
	R074AA10	Yellow					
	R074AA11	Black	400				
	R074AA12	Blue	100 m				
	R074AA13	Red					
	R074AA14	Orange					
	R074AA21	White		1			
	R074AA22	Yellow					
	R074AA23	Black					
IIS	R074AA24	Blue	200 m			EAC	
mm	R074AA25	Red					
	R074AA26	Orange					
	R074AA28	White	500 m	CE EN 1891 type A	NFPA 2500 Technical Use		
	R074AA00	White		UKCA			82 g
	R074AA01	Yellow					
	R074AA02	Black	450.0				
	R074AA35	Blue	150 ft				
	R074AA36	Red					
	R074AA37	Orange					
	R074AA06	White		1			
	R074AA07	Yellow					
	R074AA08	Black	000 #				
	R074AA41	Blue	200 ft				
	R074AA42	Red					
	R074AA43	Orange					
	R074AA15	White		1			
	R074AA16	Yellow					
	R074AA17	Black	000 #				
	R074AA18	Blue	600 ft				
	R074AA19	Red					
	R074AA20	Orange					
	R074AA27	White	1200 ft	1			

		Colors		European	US	Russian	Weight
		Colors	Lengths	Certification	Certification	Certification	per Meter
Low Stretch Kernma	antle Ropes						
	R077AA03	White					
	R077AA04	Yellow					
	R077AA05	Black	50 m				
	R077AA35	Blue	30111				
	R077AA36	Red					
	R077AA37	Orange					
PARALLEL	R077AA09	White					
10.5 mm	R077AA10	Yellow					
	R077AA11	Black	100 m	CE EN 1891 type A	NEDA OFOO		
11111	R077AA12	Blue		type A UKCA	NFPA 2500 Technical Use	EAC	75 g
14111	R077AA13	Red		ONOA			
011111	R077AA14	Orange					
11111	R077AA21	White					
	R077AA22	Yellow					
	R077AA23	Black	200 m				
	R077AA24	Blue					
	R077AA25	Red					
	R077AA26	Orange					
	R077AA28	White	500 m				
	R078AA03	White					
	R078AA04	Yellow					
	R078AA05	Black	50 m				
	R078AA38	Blue					
	R078AA39	Red					
	R078AA40	Orange		_			
	R078AA09	White					
	R078AA10	Yellow					
	R078AA11	Black	100 m				
	R078AA12	Blue					
	R078AA13	Red					
	R078AA14	Orange		-			
	R078AA21	White				EAC	
	R078AA22	Yellow					
	R078AA23 R078AA24	Black Blue	200 m				
VECTOR							
12.5 mm	R078AA25	Red					
35 6 6 6	R078AA26	Orange White	500 m	CE EN 1891			
	R078AA28 R078AA00	White	500 m	CE EN 1891 type A	NFPA 2500 General Use		111 g
	R078AA01	Yellow		UKCA			
	R078AA02	Black					
	R078AA35	Blue	150 ft				
	R078AA36	Red					
	R078AA37	Orange					
	R078AA06	White		-			
	R078AA07	Yellow					
	R078AA08	Black					
	R078AA41	Blue	200 ft				
	R078AA42	Red					
	R078AA43	Orange					
	R078AA15	White		1			
	R078AA16	Yellow					
	R078AA17	Black					
	R078AA18	Blue	600 ft				
	R078AA19	Red					
	R078AA20	Orange					
	R078AA27	White	1200 ft	†			
					-	1	

				Colors	Lengths	European Certification	US Certification	Russian Certification	Weight per Meter																			
Low Streto	h Kernmar	ntle Ro	opes																									
			R079AA00	Green	0.5																							
	0.0		R079AA01	Orange	35 m																							
FLOW			R079AA02	Green		CE EN 1891 type A	ANSI Z133		400 -																			
11.6 mm	Ш		R079AA03	Orange	45 m	UKCA	ANSI Z I 33	-	102 g																			
	• •		R079AA04	Green	60 m																							
			R079AA05	Orange	60111																							
			R080AA00	Green	35 m																							
	00		R080AA01	Orange	35111																							
CONTROL			R080AA02	Green	45 m	CE EN 1891 type A	ANSI Z133	_	115 g																			
12.5 mm			R080AA03	Orange	40111	UKCA	ANGIZIOS	_	1139																			
	2 2		R080AA04	Green	60 m																							
			R080AA05	Orange	00111																							
Static Rop	es																											
			R100AA00	White																								
			R100AA01	Black	450.0																							
			R100AA02	Yellow	150 ft																							
			R100AA03	Blue																								
	S S S S		R100AA04	White		1		-																				
			R100AA05	Black			ANSI Z359.15 ANSI Z459.1 NFPA 2500 Technical Use CI 1801		98 g																			
RAY 11 mm			R100AA06	Yellow	200 ft	-																						
			R100AA07	Blue																								
	8 8 8		R100AA08	White																								
			R100AA09	Black	600 ft																							
			R100AA10	Yellow																								
			R100AA11	Blue																								
			R100AA12	White	1200 ft																							
Dynamic R	lope																											
-			R32AC 050	Turquoise																								
	70 70		R32AD 050	Green	50 m																							
MAMBO			R32AC 060	Turquoise		CE EN 892																						
10.1 mm			R32AD 060	Green	60 m	UIAA UKGA	-	-	65 g																			
	##		R32AC 070	Turquoise	70	1																						
			R32AD 070	Green	70 m																							
Technical (Cord							· 																				
	1		R076AA00		50 m																							
SEGMENT	1		R076AA03	White	100 m	CE EN 564	NFPA 2500	_	43 g																			
8 mm	Ì		R076AA06		200 m	UKCA	Escape Use																					
	0																											
Accessory		4	DOMANAGE	0					40 =																			
		4 mm	R044AA00	Orange					10 g																			
Cords		5 mm	R045AA00	Red	120 m	CE EN 564 UKCA	-	-	15 g																			
		6 mm	R046AA00 R047AA00	Green					24 g																			
		7 mm	nu4/AAUU	Blue					31 g																			
Rope Prote	ectors																											
PROTEC			R003AA00	-	-	-	-	-	130 g																			
PROTEC PL	LUS		R003BA00	-	-	-	-	=	135 g																			
ROLLER CO			R005AA00	-	-	-	-	-	470 g																			

PACKS AND ACCESSORIES

To work comfortably, you need the right tools: packs, gloves, and accessories. Petzl offers an entire line of innovative accessories, the result of numerous years of experience in the field.



Transport Bags

Robust and comfortable, these large-capacity bags are designed for organizing and transporting equipment to the worksite.











Packs

Comfortable and rugged, these packs are designed for organizing and carrying equipment in a vertical environment.







Freestanding Bags

Placed on the ground, these packs keep their shape even when empty, for easy access to the inside of the pack.















Tree Care Accessories

Specific products that help with placing an access rope in a tree.









Gloves

Protective gloves.









Accessories











Transport Bags



DUFFEL 65

Medium-capacity transport bag

Designed to be carried in multiple ways, DUFFEL 65 is a convenient, ergonomic bag with a volume of 65 liters. The back and shoulder straps are padded for comfort when used as a backpack. It is versatile and can be carried in multiple ways, with removable shoulder straps. The large opening allows easy access to equipment, including two pockets in the inner flap and a large side pocket for a helmet or shoes. A large transparent area allows rapid identification of the bag. It is constructed of high-strength TPU tarp material for intensive use.



DUFFEL 85

Large-capacity transport bag

Designed to be carried in multiple ways, DUFFEL 85 is a convenient, ergonomic bag with a volume of 85 liters. The back and shoulder straps are padded for comfort when used as a backpack. It is versatile and can be carried in multiple ways, with removable shoulder straps. The large opening allows easy access to equipment, including two pockets in the inner flap and a large side pocket for a helmet or shoes. A large transparent area allows rapid identification of the bag. It is constructed of high-strength TPU tarp material for intensive use.





Large D-shaped opening for easy equipment organization.



Padded, adjustable back and shoulder straps for comfortable carrying.

Packs



PERSONNEL 15L

Durable small-capacity pack

The PERSONNEL is a durable and lightweight 15 liter backpack. It is made of PVC-free material, and its welded construction provides great strength. It is made for use under difficult conditions, and also has an ID card pocket.



PORTAGE 30L

Durable medium-capacity pack

The PORTAGE is a durable and comfortable 30 liter backpack. It is made of PVC-free material, and its welded construction provides great strength. With its padded shoulder straps, it is comfortable during long carries. It is made for use under difficult conditions, and also has an ID card pocket,



TRANSPORT 45L

Durable large-capacity pack

The TRANSPORT is an especially comfortable and durable 45 liter backpack. It is made of PVC-free material, and its welded construction provides great strength. It is ideal for long-distance carries with its padded back panel, waistbelt and shoulder straps. It is made for use under difficult conditions, and also has an ID card pocket.

Freestanding Bags



BUCKET 15

Small-capacity freestanding bag

Simple and durable, the BUCKET 15 rope bag allows you to store up to 45 meters of 11 mm diameter rope. It remains upright and keeps its shape, even when empty, for easy access to the inside of the bag. It has an exterior pocket to store personal items and a marking area to quickly identify the contents of the bag. Its construction of TPU tarp material allows regular to intensive use. Available in three colors: yellow, red, and black.



BUCKET 30

Medium-capacity freestanding bag

Simple and durable, the BUCKET 30 rope bag allows you to store up to 110 meters of 11 mm diameter rope. It remains upright and keeps its shape, even when empty, for easy access to the inside of the bag. It has padded shoulder straps for comfortable carrying, an exterior pocket to store personal items, and a marking area for quick identification of the contents of the bag. Its construction of TPU tarp material allows regular to intensive use. Available in three colors: yellow, red, and black.



BUCKET 45

Large-capacity freestanding bag

Simple and durable, the BUCKET 45 rope bag allows you to store up to 185 meters of 11 mm diameter rope. It remains upright and keeps its shape, even when empty, for easy access to the inside of the bag. It has padded shoulder straps for comfortable carrying, an exterior pocket to store personal items, and a marking area for quick identification of the contents of the bag. Its construction of TPU tarp material allows regular to intensive use. Available in three colors: yellow, red, and black.





BUCKET bags can store up to 45 meters (BUCKET 15), 110 meters (BUCKET 30) or 185 meters (BUCKET 45) of 11 mm diameter rope



A roll top closure provides optimal protection against moisture.



TARP PRO

Large rope tarp

TARP PRO is a large rope tarp. It provides a 100 x 100 cm area to protect the rope from dust and dirt and can be quickly and easily stored in the BUCKET 30 or BUCKET 45 rope bags.





























PETZL

Tree Care Accessories



JET

Throw-bag

Double-layer construction gives the JET throw-bag excellent longevity. Streamlined shape facilitates passage through tree branches. It is available in three versions: 250, 300, and 350 g.



AIRLINE

Throw-line

The AIRLINE throw-line offers an excellent compromise between flexibility and rigidity, for an accurate throw without the formation of knots as it comes out of the bag. The excellent sheath-core bond maintains a round cross-section, providing good rope glide through the tree. It is available in two lengths: 60 and 300 meters.



JET throw-bag

WARNING

for California

Residents



ECLIPSE

Storage for throw-line

ECLIPSE provides easy storage for AIRLINE throw-lines and JET throw-bags. The double bottom allows two throw-lines to be stored separately. Once folded into the small bag, it all fits perfectly into the BUCKET pack.

Gloves



CORDEX

Lightweight belay/rappel gloves

These lightweight belay/rappel gloves combine the durability of a work glove with the precise fit and dexterity of a thinner glove. Double-layered leather protects the palm and other high-wear areas. The back is made of abrasion-resistant, breathable stretch nylon, providing comfort and fit. The low profile neoprene cuff with Velcro closure features a reinforced carabiner hole for attaching the gloves to your harness.



CORDEX PLUS

Belay/rappel gloves

These medium weight belay/rappel gloves offer extra protection without sacrificing dexterity. Double-layer leather and padding protect the palm from heat generated during long rappels or lowers. Fingertips and other high-wear areas are reinforced for increased durability. The back is made of leather with abrasion-resistant stretch nylon at key flex areas. The low profile neoprene cuff with Velcro closure features a reinforced carabiner hole for attaching the gloves to your harness.

CORDEX and CORDEX PLUS gloves



WARNING for California Residents

This product can expose you to chemicals including hexavalent chromium, which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Accessories



MINO

Non-PPE accessory carabiner

MINO is a small, lightweight accessory carabiner ideal for hanging accessories on your harness. It is ergonomic and easy to use, even with gloves. MINO is sold individually or with two additional accessories (CAPTIV-type anti-rotation bar and LOCK-type locking bar). This product is not PPE (Personal Protective Equipment).



SPATHA

Knife with carabiner hole

The SPATHA knife is designed to accompany the worker at height during all daily tasks. The profile of the blade allows easy cutting of ropes and cords. It has a carabiner hole for easily attaching the knife to the harness. It is easy to manipulate with its textured wheel, even when wearing gloves, and can be locked in the open position.



CRAB 6

6-point crampons

Six-point crampons, adaptable to all shoe sizes, used for moving over talus and snow- and ice-covered slopes.

			Capacity	Weight	
Transport Bags					
DUFFEL 65	S045AA00 (y		65	1350 g	
DOTT EE GO	S045AA02 (b		551	1000 g	
DUFFEL 85	S045AA01 (y		851	1550 g	
	S045AA03 (b	olack)			
Packs					
PERSONNEL 15L	S44Y 015		15	450 g	
PORTAGE 30L	S43Y 030		30 I	850 g	
TRANSPORT 45L	S42Y 045		45 I	1250 g	
Freestanding Bags					
	S001AA00 (y	/ellow)	151		
UCKET 15	S001BA00 (n	red)		465 g	
	S001CA00 (b	olack)			
	S001AA01 (y	vellow)		735 g	
SUCKET 30	S001BA01 (r	red)	30 I		
	S001CA01 (b	olack)			
	S001AA02 (y	vellow)	45	890 g	
UCKET 45	S001BA02 (r	red)			
	S001CA02 (b	olack)			
TARP PRO	S001DA00		-	210 g	
Tree Care Accessories					
	S02Y 250		-	250 g	
JET 🧸 🧂 👵	S02Y 300		-	300g	
000	S02Y 350			350 g	
AIDLINE S	R02Y 060		-	2,1 g/m	
AIRLINE	R02Y 300		-	2,1 g/m	
ECLIPSE S.	S03Y		-	500 g	
		Size	Hand Circumference	Color Certifications	

			Size		Hand Circumference	Color	Certifications	
Gloves								
	110	K52 SN	S	8	20 cm			(
	All fu	K52 MN	М	8,5	21,5 cm	Black		(
		K52 LN	L	9	23 cm	Black		
	-	K52 XLN	XL	9,5	24,5 cm		CE EN 420 EN 21420	_
CORDEX		K52 XST	XS	7,5	19 cm		EN 388 (2133) EAC	(
	Alle	K52 ST	S	8	20 cm		UKCA	
		K52 MT	М	8,5	21,5 cm	Beige		
		K52 LT	L	9	23 cm			
		K52 XLT	XL	9,5	24,5 cm			- 1
	all a	K53 SN	S	8	20 cm			`
	Wille.	K53 MN	М	8,5	21,5 cm	Disale		
	100	K53 LN	L	9	23 cm	Black		
	100	K53 XLN	XL	9,5	24,5 cm		CE EN 420 EN 21420	¥
CORDEX PLUS		K53 XST	XS	7,5	19 cm		EN 388 (3133) EAC	CU
. 200	all it	K53 ST	S	8	20 cm		UKCA	
	1000	K53 MT	М	8,5	21,5 cm	Beige		
	10-16	K53 LT	L	9	23 cm			(E
	-	K53 XLT	XL	9,5	24,5 cm			

Accessories	
MINO NEW2023	M007AA00 (without accessories) / M007BA00 (with accessories)
SPATHA	S92AN
CRAB 6	64160

PETZLOM 161






Helping users to easily get equipped or to update their equipment, Petzl proposes kits for installing a temporary vertical lifeline, protecting falls, work positioning, or evacuating a victim.



Temporary Vertical Lifelines and Fall-Arrest Kits
Temporary vertical lifelines and ready-to-use kits designed for belaying and fall protection.









Fall-Arrest and Work-Positioning Kits
Ready-to-use kit designed to protect against falls and for positioning at a workstation.



Rescue Kit

Ready-to-use kit, designed to pick off and lower a victim.












Temporary Vertical Lifelines and Fall-Arrest Kits



ASAP® VERTICAL LIFELINE

Vertical lifeline for protection against falls with ASAP mobile fall arrester

ASAP VERTICAL LIFELINE is a temporary vertical lifeline designed for belaying and to protect against falls from height. It contains an ASAP mobile fall arrester, an ASAP'SORBER energy absorber, three OK TRIACT-LOCK carabiners, an ANNEAU open loop sling, an ASAP'AXIS 11 mm rope with sewn termination and integrated energy dissipater, a weight, and a BUCKET bag. It is available in two lengths.



- page 103




- page 104



- page 109 -



ANNEAU ASAP'AXIS 11 mm BUCKET 30 - page 142 -- page 104



ASAP® FALL ARREST KIT

Kit for protection against falls, with NEWTON harness and ASAP mobile fall arrester

ASAP FALL ARREST KIT is a ready-to-use kit designed to protect against falls from height. It contains a NEWTON fall-arrest harness, an ASAP mobile fall arrester, an ASAP'SORBER energy absorber, three OK TRIACT-LOCK carabiners, an ANNEAU open loop sling, an ASAP'AXIS 11 mm rope with sewn termination and integrated energy dissipater, a weight, and a BUCKET bag. The kit is available in two sizes and two lengths.















ASAP® LOCK VERTICAL LIFELINE

Vertical lifeline for protection against falls with ASAP LOCK mobile fall arrester

ASAP LOCK VERTICAL LIFELINE is a temporary vertical lifeline designed for belaying and to protect against falls from height. It contains an ASAP LOCK mobile fall arrester with locking function, an ASAP'SORBER energy absorber, two OK TRIACT-LOCK carabiners, an ANNEAU open loop sling, an AXIS 11 mm rope with sewn termination, a weight, and a BUCKET bag. It is available in two lengths.



ASAP LOCK









BUCKET 30





ASAP LOCK FALL ARREST KIT is a ready-to-use kit designed to protect against falls from height. It contains a NEWTON fall-arrest harness, an ASAP LOCK mobile fall arrester with locking function, an ASAP'SORBER energy absorber, two OK TRIACT-LOCK carabiners, an ANNEAU open loop sling, an AXIS 11 mm rope with sewn termination, a weight, and a BUCKET bag. The kit is available in two sizes and two lengths.







OK TRIACT-LOCK ANNEAU





AXIS 11 mm





BUCKET 30



How to use the ASAP and ASAP LOCK on a lifeline

Temporary Vertical Lifelines and Fall-Arrest Kits



ABSORBICA®-Y FALL ARREST KIT

Kit for protection against falls, with NEWTON EASYFIT harness and ABSORBICA-Y MGO 150 lanvard

ABSORBICA-Y FALL ARREST KIT is a ready-to-use kit designed for fall protection. It is optimized for work at height requiring connection to metal structures or large-diameter cables and bars. The kit contains a NEWTON EASYFIT fall-arrest harness, a 150 cm ABSORBICA-Y double lanyard with energy absorber and MGO large-opening connectors, an OK TRIACT-LOCK carabiner, a CAPTIV positioning bar, and a BUCKET bag. It is available in two sizes.











Fall-Arrest and Work-Positioning Kit



FALL ARREST AND WORK POSITIONING KIT

Fall-arrest and work-positioning kit with VOLT harness, ABSORBICA-Y MGO 150 lanyard, and GRILLON HOOK

FALL ARREST AND WORK POSITIONING KIT is a ready-to-use kit designed to protect against falls and for positioning at a workstation. It is optimized for work at height requiring connection to metal structures or large-diameter cables and bars. The kit contains a VOLT fall-arrest and work-positioning Structures of large-distribute causes and pairs. The first contains a volt rain-ground making harmers, a 150 cm ABSORBICA-Y double lanyard with energy absorber and MGO large-opening connectors, a 2-meter GRILLON HOOK adjustable work-positioning lanyard, two OK TRIACT-LOCK carabiners, two CAPTIV positioning bars, and a BUCKET bag. It is available in two sizes.

















CAPTIV

BUCKET 30

K090AA00

K090AA01

K090AA02

Rescue Kit

JAG RESCUE

Rescue Kit



JAG RESCUE KIT

Reversible rescue kit with JAG SYSTEM haul kit and I'D EVAC descender

The JAG RESCUE KIT is a ready-to-use reversible rescue kit designed to easily pick off and lower a victim. It contains a JAG SYSTEM haul kit, a RING OPEN gated ring, an I'D EVAC descender with integrated brake, a CONNEXION FIXE 150 cm anchor strap, a BUCKET bag, and an AXIS 11 mm rope with two sewn terminations. It is available in three lengths: 30, 60, and 120 m.









I'D EVAC











Available in Custom version

		Contents of Kit	Harness Size	Rope Length	Weight
Temporary Ver	tical Lifeline	s and Fall-Arrest Kits			
ASAP VERTICAL	K091AB00	ASAP ASAP'SORBER 40 cm OK, TRIACT-LOOK (x3)		10 m	2485 g
LIFELINE	K091AB01	ANNEAU 150 cm ² AXIS 11 mm rope with sewn termination am ² 1 weight BUCKET 30	-	20 m	3285 g
ASAP LOCK VERTICAL	K092AA00	ASAP LOCK ASAP SORBER 40 cm OK TRIACT-LOCK (x2)		10 m	2615 g
LIFELINE	K092AA01	ANNEAU 150 cm ² AXIS 11 mm With Sewn Termination 1 weight BUCKET 30	-	20 m	3415 g
	K093AB00		1	10 m	3535 g
ASAP FALL ARREST KIT	K093AB01	NEWTON European Version ASAP ASAP'SORBER 40 cm OK TRIACT-LOCK (x3)	2	10 m	3565 g
	K093AB02	ANNEAU 150 cm ² AXIS 11 mm rope with sewn termination and integrated energy dissipater 1 weight BUCKET 30	1	20 m	4335 g
	K093AB03		2	20 m	4365 g
	K094AA00		1	10 m	3665 g
ASAP LOCK FALL ARREST	K094AA01	NEWTON European Version ASAP LOCK ASAP SORBER 40 cm OK TRIACT-LOCK (x2)	2	10 m	3695 g
KIT	K094AA02	ANNEAU 150 cm * AXIS 11 mm With Sewm * AXIS 11 mm With Sewm Termination 1 weight BUCKET 30	1	20 m	4465 g
	K094AA03		2	20 m	4495 g
ABSORBICA-Y FALL ARREST	K095AC00	NEWTON EASYFIT International Version ABSORBICA-Y European Version 150 cm MGO OK TRIACT-LOCK (x1)	1		3620 g
KIT	K095AC01	CAPTIV(xt) BUCKET 30	2		3670 g
Fall-Arrest and	Work-Positi	ioning Kit		_	
FALL ARREST AND WORK	K096AB00	ABSORBICA-Y European Version 150 cm MGO GRILLON HOOK European Version 2 m OK TRIAGT-LOCK (p2) CAPTIV (p2)	1		4970 g
POSITIONING KIT	K096AB01	OK TRIACT-LÖCK (x2) CAPTIV (x2) BUCKET 30	2		5050 g

I'ID EVAC CONNEXION FIXE 150 cm AXIS 11 mm With Sewn Termination BUCKET 30 or BUCKET 45



60 m

120 m











Thanks to the service offered by Petzl Custom, you can customize certain Petzl products. We're able to manufacture and assemble ready-made products to meet specific user needs or to identify a product with a company's colors or logo, for example. To take advantage of Petzl Custom, simply contact your regular Petzl dealer and place your order.



Customizable Helmets





Customizable Work-Positioning Lanyard



Customizable Kit



Customizable Personal Escape System




Customizable Ropes and Cords









Customizable Helmets



VERTEX® CUSTOM

Customizable helmet from the VERTEX range

Petzl Custom offers customized helmets from the VERTEX range. There is a choice of shell (with or without ventilation) and of color (standard or fluorescent). Stickers with a logo and/or names can be printed, and colored reflective bands may be added. A wide range of accessories (chinstraps, protective eye and face shields, helmet protectors, nape protectors, name-tag holders, beanies) are available and may be pre-mounted. They are packaged individually for a ready-to-go solution. Minimum order quantity: 20 units.



STRATO® CUSTOM

Customizable helmet from the STRATO range

Petzl Custom can customize one of the helmets in the STRATO range. There is a choice of shell (with or without ventilation) and of color (standard or fluorescent). Stickers with a logo and/or names can be printed, and colored reflective bands may be added. A wide range of accessories (chinstraps, protective eye and face shields, helmet protectors, nape protectors, name-tag holders, beanies) are available and may be pre-mounted. They are packaged individually for a ready-to-go solution. Minimum order quantity: 20 units.





































Customizable Work-Positioning Lanyard



GRILLON CUSTOM

Customizable work-positioning lanyard

Petzl Custom can customize a work-positioning lanyard from the GRILLON range. You can choose the type of rope (standard or high-strength), the color, and the length (up to 20 meters). You can also choose the color of the device. The lanyard can be equipped with connectors for attachment to the harness or for the end. The GRILLON CUSTOM lanyard is packaged individually for a ready-to-go solution. GRILLON CUSTOM replacement ropes are also available individually.

Customizable Kit



JAG RESCUE KIT CUSTOM

Reversible and customizable rescue kit with JAG SYSTEM haul kit and I'D descender

Petzl Custom allows you to customize a JAG RESCUE KIT. Choice of color and length are offered for the AXIS 11 mm rope, from 10 to 185 meters. You can also choose anchor type, haul kit length, and either the I'D S or I'D EVAC self-braking descender with anti-panic function. The kit is delivered in a bag that corresponds to the selected rope length for a ready-to-go solution.

Customizable Personal Escape System



EXO® CUSTOM

Customizable personal escape system

Petzl Custom offers customized EXO personal escape systems. Choice of rope color and length, up to 150 meters, are available. You can also choose a descender with or without anti-panic function. The system can be equipped with connectors for attachment to the anchor and to the harness. The EXO CUSTOM personal escape system can be delivered in a bag for a ready-to-go solution. EXO CUSTOM replacement ropes are also available individually.

Customizable Ropes and Cords



Customizable technical cord

Petzl Custom offers customized SEGMENT cords. We offer the choice of length (up to 2000 meters) and the option to add a manufactured sewn termination to one or both ends. The SEGMENT 8 mm CUSTOM cord is packaged individually for a ready-to-go solution.

PARALLEL 10.5 mm CUSTOM

Customizable low stretch kernmantle rope for rope access

Petzl Custom can customize a PARALLEL 10.5 mm rope. We offer the choice of color, length (up to 700 meters), and the option to add a manufactured sewn termination to one or both ends Markings at the end of the rope can also be customized with a heat-shrink cover or laser-marked rigid identification label. The PARALLEL 10.5 mm CUSTOM rope is packaged individually for a ready-to-go

DURALINE 10.5 mm CUSTOM

High-strength, low stretch kernmantle rope that is customizable and made for work at height, rope access, and rescue

The DURALINE 10.5 mm CUSTOM low stretch kernmantle rope is designed for work at height. rope access, and rescue. Its aramid fiber sheath provides better resistance to abrasion, wear, and heat, than a classic rope. The thin diameter makes it flexible and lightweight. It's equipped with a rigid identification label on the end of the rope for better tracking and durability. The length and packaging are customizable to meet the needs of the user.

AXIS 11 mm CUSTOM

Customizable low stretch kernmantle rope for work at height

Petzl Custom can customize an AXIS 11 mm rope. We offer the choice of color, length (up to 700 meters), and the option to add a manufactured sewn termination to one or both ends. Markings at the end of the rope can also be customized with a heat-shrink cover or laser-marked rigid identification label. The AXIS 11 mm CUSTOM rope is packaged individually for a ready-to-go solution.

RAY 11 mm CUSTOM

Customizable static kernmantle rope for work at height and technical rescue

Petzl Custom can customize a RAY 11 mm rope. We offer the choice of color, length (up to 500 meters), and the option to add a manufactured sewn termination to one or both ends. The RAY 11 mm CUSTOM rope is packaged individually for a ready-to-go solution.

VECTOR 12.5 mm CUSTOM

Customizable low stretch kernmantle rope for rescue

Petzl Custom can customize a VECTOR 12.5 mm rope. We offer the choice of color, length (up to 500 meters), and the option to add a manufactured sewn termination to one or both ends. The VECTOR 12.5 mm CUSTOM rope is packaged individually for a ready-to-go solution

	References	
VERTEX CUSTOM	A010XY	
STRATO CUSTOM	A020XY	
GRILLON CUSTOM	L052XYXX	4
JAG RESCUE KIT CUSTOM	K090XY	
EXO CUSTOM	D030XYXX	ı
SEGMENT 8 mm CUSTOM	R076DA	
PARALLEL 10.5 mm CUSTOM	R077XY	
DURALINE 10.5 mm CUSTOM	R075XY	d
AXIS 11 mm CUSTOM	R074XY	
RAY 11 mm CUSTOM	R100XY	6
VECTOR 12.5 mm CUSTOM	R078DA	






































The Petzl headlamp range covers the full spectrum of professional needs, from intensive to occasional use, and for different work environments that require varying degrees of brightness.

Professions	Industry, Maintenance, Inspection, and Rescue	Industry, Energy and Networks, Construction, Maintenance	Workshop, Maintenance, and Stage Work
Frequency of Use	Intensive	Frequent	Occasional to Frequent
User Needs	- Very powerful, intelligent lighting - Long burn time - Durable - Water resistant (DUO RL, DUO S, DUO Z1, and DUO Z2 - ATEX certification (DUO Z1 and DUO Z2)	- ATEX or HAZLOC certification - Compact - Durable - Water resistant - Long burn time	- Powerful lighting - Durable and water resistant (IKO7 and IP67) - Lightweight and compact - Very long burn time - Versattile - RGB lighting (Black models of ARIA 1 and 2)
Petzl Solutions	Powerful and Intelligent Headlamps	Compact and Durable Headlamps	Ultra-Compact and Versatile Headlamps
	DUO RL DUO S DUO Z1 DUO Z2 SWIFT RL PRO	PIXA 21 PIXA 3R PIXA 3 PIXA 2	ARIA 2R NEW 2023 ARIA 1R NEW 2023 ARIA 1 Emergency Headlamp e+LITE

Intelligent lighting for greater convenience and performance





This exclusive technology developed by Petzl instantly provides the right lighting at the right time, without any need for manual operation. Burn time is optimized so you can remain focused on the activity.


REACTIVE LIGHTING® technology provides:

- Intelligent lighting

- Hands-free lighting for greater convenience and performance
- Longer burn time

Available on the DUO RL and SWIFT RL PRO headlamps.

Come face-to-face without blinding each other, for better teamwork






Once activated, the FACEZFACE function triggers a sensor that detects other DUO headlamps within 8 meters and automatically dims the lighting whenever they face each other. The light returns to its original intensity once the other headlamp is no longer in its line of sight.

Available on DUO S, DUO Z1, and DUO Z2 headlamps.

Choose the battery type that fits your needs





The HYBRID CONCEPT design allows Petzl's compact headlamps to run on either the CORE rechargeable battery or three AAA/LR03 batteries


without an adapter

- CORE rechargeable battery is an economical solution for frequent and/or intensive use
- AAA/LR03 batteries for occasional use with very long burn time


Available on lamps in the ARIA line.

Compatibility with a variety of helmet types


All Petzl headlamps are designed to be worn on the head or a helmet, and allow the headlamp to be tilted:







 On Petzl helmets, using specific mounting plates that are available as accessories



• On other helmets, using adhesive plates that are available as accessories

PETZL.COM

175

Choosing a Petzl headlamp means selecting a work tool designed to withstand the most severe conditions of use while providing maximum reliability:

Optical quality for optimal visual comfort

Petzl headlamps provide maximum visual comfort for the user: lighting is uniform and has no bright point in the center, no spotting, no dark areas. Each batch of LEDs is tested and selected according to proper color homogeneity, low energy consumption, and high luminous flux. Each Petzl headlamp is individually inspected before leaving the factory. These operations include a test to measure lighting performance and beam homogeneity with the help of a digital camera.



central bright spot: blinding



visual defects: lack of precision, discomfort, fatique

Perfectly uniform beam: user comfort

Testing from design to manufacturing

Each model must pass particularly stringent tests: - For shock resistance, fall resistance, and crushing (including at low temperatures)

- For functional reliability (mechanical endurance)
- Individual inspection and test at the end of the assembly line (final quality check)
- For water resistance




Consideration of photobiological risk

Petzl has chosen to present information in its product instructions about the risks to the eyes associated with LED lighting. For this, the company uses the IEC 62778 and EN 62471: 2008 standards, Photobiological safety of lamps and devices using lamps. This standard classifies lamps according to risk groups.


The risk groups are as follows:

- Risk group 0: no risk
- Risk group 1: low risk. The product presents no risk related to exposure limits under normal usage conditions
- Risk group 2: moderate risk. The reflex to look away from the lamp suffices to reduce the risk



A question of balance

Brightness and burn time are two inextricably linked parameters of any headlamp, regardless of its lighting technology. For a given quantity of energy, increasing the brightness automatically decreases burn time, and vice versa.




The different lighting technologies used in Petzl headlamps make it possible to meet your needs, depending on what you want:



Prioritizing burn time: STANDARD LIGHTING


Brightness decreases gradually as the batteries are drained. It is the most common technology.





Prioritizing guaranteed brightness over time: CONSTANT LIGHTING

Brightness stays constant as the batteries drain. When the batteries are almost drained, the headlamp switches automatically to reserve lighting, with weaker output that prolongs lighting time.






Optimized lighting performance: REACTIVE LIGHTING®

Brightness varies according to the user's need. Intelligent lighting optimizes battery life, offering longer burn time.





Brightness: the shape of the beam directly affects lighting distance

Lighting distance depends directly on brightness, but mainly on the shape of the beam. In fact, given the same brightness, lighting distance will vary depending on the shape of the beam.

Petzl indicates the different lighting modes available for each headlamp. These modes correspond to specific conditions of use: close-range work, moving around, seeing at a distance.















177

PETZL.COM




Hazardous Areas

If an explosion hazard is identified in an environment, the hazardous areas are classified as areas at risk, depending on the prevalence and type of combustible, gas or dust. All of the materials used in these zones must conform with current regulations for this type of zone (ATEX and/or HAZLOC).

Classification of ATEX / HAZLOC zones

Explosive Atmosphere	Gas Type C	ombustible	Dust Type Combustible				
	ATEX	HAZLOC	ATEX	HAZLOC			
Permanent or Long-Term	ZONE 0	Class I Div 1	ZONE 20	Class II Div 1			
Occasional	ZONE 1	Class I Div 1	ZONE 21	Class II Div 1			
Accidental	ZONE 2	Class I Div 2	ZONE 22	Class II Div 2			

Example of ATEX zone (gas type combustible)





How to read an ATEX marking

Example:	⟨£x⟩ II 2 G	Ex ib	IIB	T4	Gb
DUO Z1	€x II 2 D	Ex ib	IIIB	T135°	Db

II 2 G ATEX CODING										
II 2 GD										
Equipment group	Equipment category									
l. mining	M1: energised									
I. mining										
		Gas	Dust							
	1: very high protection	0	20							
II: non-mining	2: high protection	1	21							
	2	22								
	II Equipment group I: mining	II 2 Equipment group Equipment category I: mining M1: energised M2: de-energised* 1: very high protection								

^{*} in presence of explosive atmosphere

IIB GAS GROUPS							
Gas group	Representative test gas						
I	Methane (mining only)						
IIA	Propane						
IIB	Ethylene						
IIC	Hydrogen						

Gases are classified according to the ignitability of gas-air mixture.

Refer to IEC/EN 60079-20-1 for classification of common gases and vapors.

T4 / T135° TEMPERATURE CLASS							
T class	Maximum surface temperature						
T1	450°C						
T2	300°C						
T3	200°C						
T4	135°C						
T5	100°C						
Т6	85°C						

Ex ib	ELECTRICAL P	ROTECTION CO	NCEPT	S		
Standard IEC/EN	Code		Zone			
	Ex ia		0	20		
60079-11	Ex ib	Intrinsic Safety	1	21		
	Ex ic	Guioty	2	22		

IIIB DUST GROUPS									
Dust group	Representative test dust								
IIIA	Combustible flyings								
IIIB	Non-conductive dust								
IIIC	Conductive dust								

Gb / Db equipment protection level							
Equipment protection level	Zone						
Ga	0						
Gb	1						
Gc	2						
Da	20						
Db	21						
Dc	22						
Ma	energised*						
Mb	de-energised*						

G = Gas, D = Dust, M = Mining

Lighting performance as defined by the ANSI/PLATO FL 1 protocol

Petzl has chosen to comply with the ANSI (American National Standards Institute) FL.1 protocol to measure and demonstrate the lighting performance of our headlamps. This voluntary move allows users to easily compare the lighting performance of different headlamp models using standardized criteria.

Lighting Performance: How Is It Measured?



Brightness (lumens)

This measurement is taken between 30 and 120 seconds after the headlamp is turned on. It indicates the maximum light output when the lamp is first turned on using new batteries (included).



Burn time (hours)

This is the length of time for which lighting remains optimal, from the moment the lamp is turned on until it drops to 10% of maximum light output. It then switches to reserve lighting.



Lighting distance (meters)

This is the maximum distance between the lamp and the location where only 0.25 lux of illumination remains. The measurement is taken when the lamp is turned on, using new batteries. Lighting distance depends directly on brightness, but mainly on the shape of the beam.



Reserve lighting (outside of the ANSI/PLATO FL 1 protocol)

In addition to these measures, Petzl offers reserve lighting, Reserve lighting provides a minimum light level to be able to move around. However, the lighting may be insufficient for certain activities (such as precision work or inspection).

The IP Protection Index



A headlamp's resistance to solids and/or liquids is indicated by its IP rating. This index classifies the level of protection offered by equipment against intrusions by solids (e.g. dust) and liquids (e.g. water, oil) according to the IEC 60529 standard.

Understanding the protection index

Rating

Protection

Level of protection against solid objects

P67 Level of protection against liquids

Protection against solid objects

X = Not measured

0 = Not protected

1 = Protected against projection of solids ≥ 50 mm in diameter

2 =Protected against projection of solids ≥ 12.5 mm in diameter

3 =Protected against projection of solids ≥ 2.5 mm in diameter

4 =Protected against projection of solids ≥ 1 mm in diameter

5 = Protected against dust (limited ingress, no harmful deposits)

6 = Completely protected against dust

Protection against liquids

X = Not measured

0 = Not protected

1 = Protected against vertically falling water drops

2 = Protected against water drops (15° from vertical)

3 = Protected against rain (60° from vertical)

4 = Protected against splashing water

5 = Protected against water jets

6 = Protected against powerful water jets

7 = Temporary immersion (-1 meter for 30 minutes)

8 = Prolonged immersion (deeper than 1 meter for period defined by manufacturer)

9 = Prolonged immersion (deeper than 1 meter) and protection against pressure-washing

PETZLCOM * in presence of explosive atmosphere

Choosing your Petzl headlamp for hazardous areas in accordance with regulations:

			(Ex)	Hazloc	IP67 -1m WATER-PROOF	STANDARD BATTERIES	RECHAR- GEABLE
DUO Z1		E80BHR E80BHR UK	ATEX zone 1/21 II 2 GD Ex ib IIB T4 Gb IIB T135° C Db Ambient temperature: -20° C to +40° C	-	•	-	•
DUO Z2		Е80АНВ	ATEX zone 2/22 II 3 GD Ex ic IIB T4 Gc IIIB T135° C Dc Ambient temperature: -20° C to +40° C	-	•	•	-
PIXA Z1	NA.	E78DHB 2	ATEX zone 1/21 Il 2 GD Ex ib IlB T4 Gb IllB T135° C Db Ambient temperature: -20° C to +40° C	-	•	•	-
PIXA 3R	Control of the Contro	E78CHR 2 E78CHR 2UK	ATEX zone 2/22 II 3 GD Ex ic IIB T4 Gc IIIC T135° C Dc Ambient temperature: -30° C to +40° C	-	•	-	•
PIXA 3		E78CHB 2	ATEX zone 2/22 II 3 G Ex nA ic IIB T4 Gc, II 3 D Ex tc IIIC T135° C Dc Ambient temperature: -30° C to +40° C	-	•	•	-
		E78CHB 2UL	-	HAZLOC Class I Div 2 Groups C, D Class II Div 2 Group G Temperature code T4 Ambient temperature: -30° C to +40° C	•	•	-
PIXA 2		E78BHB 2	ATEX zone 2/22 II 3 G Ex nA ic IIB T4 Gc, II 3 D Ex tc IIIC T135° C Dc Ambient temperature: -30° C to +40° C	-	•	•	-
FIAM 2	ma D	E78BHB 2UL	-	HAZLOC Class I Div 2 Groups C, D Class II Div 2 Group G Temperature code T4 Ambient temperature: -30° C to +40° C	•	•	-
PIXA 1		E78AHB 2	ATEX zone 2/22 II 3 G Ex nA ici IIB T4 Gc, II 3 D Ex tc IIIC T135° C Dc Ambient temperature: -30° C to +40° C	-	•	•	-
FIAM I	900	E78AHB 2UL	-	HAZLOC Class I Div 2 Groups C, D Class II Div 2 Group G Temperature code T4 Ambient temperature: -30° C to +40° C	•	•	-



Brightness is the total quantity of light emitted by a lamp. It is expressed in lumens. The greater the quantity of light, the better you see. The value indicated is that of the most powerful lighting level (MAX POWER).



Petzl headlamps that work with rechargeable batteries.



Lighting distance is linked to brightness and beam shape. It is expressed in meters and indicates the range of usable lighting. The value indicated is the maximum value.



Petzl headlamps that work with regular batteries (included).



Burn time expresses the length of time a headlamp functions with power sufficient for carrying out an activity. It is expressed in hours. The value indicated is the maximum value.



Headlamp meeting ATEX certification requirements for work in hazardous environments.



When the battery is almost drained, the headlamp switches automatically to reserve lighting to provide minimum lighting for several hours.



Headlamp meeting HAZLOC certification requirements for work in hazardous environments.



Flood beam designed for proximity lighting, to see up close or around the feet. The wide angle provides a very wide and comfortable field of vision.



Retter resistance to chemicals




Mixed beam consists of a flood beam and a focused component, allowing both proximity lighting and longer-range vision for moving around.



The IP rating on a headlamp indicates its degree of resistance to intrusions:

IPX4: Water-spray and weather resistant IPX7: Resistant to temporary immersion (in up to 1 meter for 30 minutes) IP67: Resistant to dust and temporary immersion





Narrow beam allows focused lighting on a target in order to see objects or people at a distance.



The IK rating on a headlamp indicates its degree of protection against impacts.

IK07: Protected against 2 joules impact, equivalent

to the impact of a 0.5 kg mass dropped from 400 mm above the impacted surface.



Red lighting for more comfortable night vision. This lighting allows good vision without blinding the user or members of a group.



The weight indicated is that of the headlamp with its energy source (regular or rechargeable batteries).



Red, green, and blue lighting allows the user to better see contrasts in the lit object in certain situations.



Resistance to falls (2 m).



Red and/or white strobe lighting allows you to signal and be more easily located, for example in an emergency.



Resistance to crushing (80 kg).




		STANDARD LIGHTING	CONSTANT	REACTIVE LIGHTING®	MAX BRIGHTNESS	MAX DISTANCE ANSI/PLATO FL 1	MAX BURN TIME	RESERVE LIGHTING	LARGE	MIXED	FOCUSED	RED LIGHTING	RGB LIGHTING	WHITE / RED STROBE	FACE FACE FACE FACE FUNCTION	HYBRID CONCEPT	RECHAR- GEABLE	STANDARD BATTERIES	(Ex) ATEX	Hazloc HAZLOC	INGRESS PROTECTION	IK IMPACT PROTECTION	WEIGHT
Powerful an	d Intelligent Headla	mps -	•	•	2800 lm	255 m	72 h	•	•	•	•	-	-	-	-	-	• wall	-	-	-	IP67	-	390 g
DUO S		-	•	-	1100 lm	200 m	23 h	•	•	•	•	-	-	-	•	-	• wall	-	-	-	IP67	-	370 g
DUO Z1		-	•	-	360 lm	115 m	23 h	•	•	•	•	-	-	-	•	-	• wall	-	ATEX zone 1/21 II 2 GD Ex ib IIB T4 Gb IIIB T135° C Db Ambient temperature: -20° C to +40° C	-	IP67	-	370 g
DUO Z2		-	•	-	430 lm	120 m	15 h 30	•	•	•	•	-	-	-	•	-	-	4 x AALR06	ATEX zone 2/22 II 3 GD Ex ic IIB T4 Gc IIIB T135° C Dc Ambient temperature: -20° C to +40° C	-	IP67	-	360 g
SWIFT RL PRO	THE STATE OF	•	-	•	900 lm	150 m	100 h	•	-	•	•	•	-	-	-	-	● USB	-	-	-	IPX4	-	123 g
Compact an	d Durable Headlam	ps •	-	-	100 lm	95 m	56 h	•	•	•	•	-	-	-	-	-	-	2 x AA LR06	ATEX zone 1/21 II 2 GD Ex ib IIB T4 Gb IIIB T135° C Db Ambient temperature: -20° C to +40° C	-	IP67	-	170 g
PIXA 3R		-	•	-	90 lm	90 m	11 h 30	•	•	•	•	-	-	-	-	-	• wall	-	ATEX zone 2/22 II 3 GD Ex ic IIB T4 Gc IIIC T135° C Dc Ambient temperature: -30° C to +40° C	-	IP67	-	145 g
PIXA 3	A STATE OF THE STA	-	•	-	100 lm	90 m	26 h	•	•	•	•	-	-	-	-	-	-	2 x AA LR06		HAZLOC Class I Div 2	IP67	-	160 g
PIXA 2	THE SE	=	•	-	80 lm	55 m	26 h	•	-	•	-	-	-	-	-	-	-	2 x AA LR06	ATEX zone 2/22 II 3 G Ex nA ic IIB T4 Gc II 3 D Ex tc IIIC T135° C Dc Ambient temperature: -30° C to +40° C	Groups C, D Class II Div 2 Group G Temperature code T4	IP67	=	160 g
PIXA 1		-	•	-	60 lm	15 m	16 h	•	•	-	-	-	-	-	-	-	-	2 x AA LR06		Ambient temperature: -30° C to +40° C	IP67	-	160 g
NEW2023	act and Versatile He	adlamps	_	_	600 lm	115 m	100 h	•			_	_	_	_	_		•	_	-	-	IP67	IK07	95 g
ARIA 2R		•			450 lm	75	110 h	•									USB				IP67	IK07	
ARIA 1R	703	•	-	-	450 IM	75 m	TION	•	•	-	-	-	•	-	-	•	USB	3 x	-	-	IP67	IKU/	94 g
ARIA 2	Car 18	•	-	-	450 lm	100 m	100 h	•	•	•	-	-	black version	black version	-	•	-	AAA LR03	-	-	IP67	IK07	106 g
ARIA 1	W. S	•	-	-	350 lm	70 m	110 h	•	•	-	-	-	• black version	black version	-	•	-	3 x AAA LR03	-	-	IP67	IK07	105 g
Emergency e+LITE	Headlamp	•	-	-	40 lm	15 m	9 h 30	-	•	-	-	•	-	•	-	-	-	2 x lithium CR2032	-	-	IPX7	-	26 g
																		CH2032					

Lighting specifications are subject to change: check www.petzl.com

POWERFUL AND INTELLIGENT HEADLAMPS

Powerful and intelligent headlamps designed for intensive use by maintenance, industrial, or rescue professionals.



Ultra-powerful, rechargeable multi-beam headlamp featuring REACTIVE LIGHTING® technology. 2800 lumens



DUO S

Ultra-powerful, rechargeable multi-beam headlamp, featuring the FACE2FACE anti-glare function. 1100 lumens



Powerful, rechargeable multi-beam headlamp with FACE2FACE anti-glare function, certified for use in ATEX hazardous areas.



DUO Z2

Powerful multi-beam headlamp that runs on standard batteries, with FACE2FACE anti-glare function, for use in ATEX hazardous areas. 430 lumens



SWIFT RL PRO

Ultra-powerful, lightweight rechargeable headlamp with multi-beam and REACTIVE LIGHTING® technology for proximity and distance vision. White or red lighting for stealth. 900 lumens



Accessories





































Ultra-bright with 2800 lumens and multi-beam lighting to suit a wide variety of situations.







DUO Z1

Powerful, rechargeable multi-beam headlamp with FACE2FACE anti-glare function, certified for use in ATEX hazardous areas. 360 lumens

DUO Z1 is a headlamp with a maximum 360 lumens of lighting in BOOST mode that runs on a rechargeable battery. It is multi-beam, and has four lighting modes, making it adaptable to a variety of situations: close-range work, proximity lighting, movement, and long-range vision. Featuring the FACE2FACE anti-glare function, the DUO Z1 headlamp allows those working in a group to face each other without blinding one another, enabling them to work more effectively together. It can be worn on VERTEX and STRATO helmets with the included mounting plates. It meets ATEX zone 1/21 (II 2 GD Ex ib IIB T4 Gb IIIB T135° C Db) certification requirements for work in hazardous areas.

Pack of five DUO Z1 headlamps - comes with charging rack that allows simultaneous charging





DUO RL headlamps









Aluminum lamp body provides excellent fall, crush, and impact resistance.



х5





DUO 72

of five batteries

Pack of 5 DUO Z1

Pack of 5 DUO Z1 headlamps with charging rack

Powerful multi-beam headlamp that runs on standard batteries, with FACE2FACE anti-glare function, for use in ATEX hazardous areas. 430 lumens The DUO Z2 headlamp provides a powerful 430 lumens in BOOST mode and runs on regular batteries. It is multi-beam, and has four lighting modes, making it adaptable to a variety of situations: close-range work, proximity lighting, movement, and long-range vision. Featuring the FACE2FACE anti-glare function, the DUO Z2 headlamp allows those working in a group to face each other without blinding one another, enabling them to work more effectively together. It can be worn on VERTEX and STRATO helmets with the included mounting plates. It meets ATEX zone 2/22 (II 3 GD Ex ic IIB



Ultra-powerful, rechargeable multi-beam headlamp featuring REACTIVE LIGHTING® technology. 2800 lumens


Designed for technical rescue and worksites, the DUO RL rechargeable headlamp provides 2800-lumen brightness. With its REACTIVE LIGHTING® technology, a sensor analyzes the ambient light and automatically adjusts brightness to user requirements. Manual operation is minimized and burn time is optimized, so the user can remain focused on the activity. The aluminum lamp body provides excellent impact resistance. The DUO RL is waterproof and ideal for use in wet environments.



IP 67



Dustproof and waterproof in up to 3 meters of fresh water for 30 minutes.





R2 rechargeable 3200 mAh Lithium-Ion battery with four-level gauge, for precise monitoring of battery charge level.



DUO S, DUO Z1, and DUO Z2 headlamps



DUO S

Ultra-powerful, rechargeable multi-beam headlamp, featuring the FACE2FACE anti-glare function. 1100 lumens

Ultra-powerful with 1100 lumens in BOOST mode, the DUO S runs on a rechargeable battery. It is multi-beam, and has five lighting modes, making it adaptable to a variety of situations: close-range work, proximity, movement, rapid movement and long-range vision. Featuring the FACE2FACE anti-glare function, the DUO S headlamp allows those working in a group to face each other without blinding one another, to work together more effectively. It can be worn on VERTEX and STRATO helmets with the included mounting plates.



Accessories

Rechargeable battery for DUO RL and DUO S headlamps

T4 Gc IIIB T135° C Dc) certification requirements for work in hazardous areas.



Quick Charger Quick wall charger for R2 rechargeable battery



Extension Cord for Headlamp Extension cord for DUO RL and DUO S headlamps



ACCU 2 DUO Z1 Rechargeable battery for DUO Z1 headlamp, usable in ATEX zone



ACCU 2 DUO Z1 Charger Wall charger for ACCU 2 DUO Z1 rechargeable battery



5 DUO Z1 Charaina Rack Charging rack which allows simultaneous charging of five DUO Z1 headlamp



PRO ADAPT

Adhesive accessory for mounting a DUO headlamp on a variety of different helmet types































SWIFT® RL PRO

Ultra-powerful, lightweight rechargeable headlamp with multi-beam and REACTIVE LIGHTING® technology for proximity and distance vision. White or red lighting for stealth. 900 lumens

Designed for the workshop, small maintenance jobs, or concerts and shows, the SWFT RL PRO rechargeable headlamp provides 900-lumen brightness. With its REACTIVE LIGHTING® technology, a sensor analyzes the ambient light and automatically adjusts brightness to user requirements. It also has red lighting for stealth. SWIFT RL PRO is intuitive, with a single button for easy control over all lamp functions. The five-level gauge allows precise monitoring of the battery charge level. The lamp is compatible with Petzl helmets, and mounting accessories allow it to be attached to a variety of helmet types.





Longer burn time, greater visual comfort, and less manual operation with REACTIVE LIGHTING® mode: the light sensor automatically adjusts brightness and beam pattern, optimizing battery life.

Accessories



ACCU SWIFT® RL PRO

Rechargeable battery for SWIFT RL PRO headlamp

High-capacity Lithium-Ion 2350 mAh rechargeable battery for the SWIFT RL PRO headlamp. It provides excellent lighting performance, even at low temperatures. It charges directly via built-in micro USB port and has a charging indicator light.



Rubber headband for PIXA or SWIFT RL PRO headlamp, compatible with a variety of helmet types



PIXADAPT

Accessory for mounting a PIXA or SWIFT RL PRO headlamp on a helmet







UNI ADAPT

Adhesive clip for mounting a Petzl headlamp on a variety of helmet types (pack of 4)



POCHE PIXA® & SWIFT® RL PRO

Carry pouch for PIXA and SWIFT RL PRO headlamps

R2 E103CA00	168 g
Quick Charger E55800 E55800 UK	145 g
Extension Cord for Headlamp E55950	75 g
ACCU 2 DUO Z1 E80001	168 g
ACCU 2 DUO Z1 Charger E080AA00	170 g
5 DUO Z1 Charging Rack E80003	1440 g
PRO ADAPT E80004	48 g

		Weight
UNI ADAPT NEW2023	E000BA00	10 g
ACCU SWIFT RL PRO	E810BA00	50 g
RUBBER	E78002	-
PIXADAPT	E78005	20 g
POCHE PIXA & SWIFT RL PRO	E78001	44 g
Spare Part		
Spare headband for DUO	E51999	-

								INSI/PLATO FL	1												
	Certifications	STANDARD LIGHTING	CONSTANT LIGHTING	REACTIVE LIGHTING®	Lighting Color	Lighting Modes	MAX BRIGHTNESS	MAX DISTANCE	MAX BURN TIME	Weight											
						Proximity (2)	25 - 120 lm	18 m	24 - 72 h												
						Movement (2)	50 - 250 lm	32 m	12-38 h												
		-	-	•		Rapid Movement (2)	100-550 lm	75 m	6-24 h												
						Maximum Power (2)	150-2800 lm	255 m	1h30 - 18 h												
						Focused (2)	100-900 lm	235 m	3-24 h												
	CE						Proximity (2)	80 lm	16 m	24 h											
OLIO BI	UKCA				White	Movement (2)	200 lm	32 m	12 h	390 g											
103AA00		-	•	-		Rapid Movement (2)	450 lm	70 m	6 h												
						Maximum Power (2)	1800 lm	200 m	1h30												
						Focused (2)	700 lm	230 m	3 h												
				$\vdash \vdash \vdash$		Survival Mode: Low	20 lm	8 m	72 h												
		-	-	-		Survival Mode: High	100 lm	26 m	24 h												
						Close-Range Work	80 lm	20 m	23 h												
						Proximity	180 lm	35 m	12 h 30												
						Movement	330 lm	70 m	6 h												
	CE	_		-	White	Rapid Movement	700 lm	160 m	3 h	370 g											
UO S BOCHR	UKCA			-	vviite	Distance Vision	450 lm	190 m	4 h 30	370 g											
BOCHR UK						BOOST Mode	1100 lm	200 m	_												
									Reserve Lighting) Im for 45 m	l in									
						Close-Range Work	70 lm	20 m	23 h												
						Proximity	170 lm	35 m	12 h												
- 10	CE ATEX zone 1/21	-	-	-	-	-	-	-				Movement	300 lm	90 m	7 h						
JO Z1 IOBHR	ATEX zone 1/21 II 2 GD Ex ib IIB T4 Gb IIIB T135° C Db								•	-	White	Distance Vision	140 lm	100 m	17 h	370 g					
OBHR UK ODHR	Ambient temperature: -20° C to +40° C																BOOST Mode	360 lm	115 m	_	
ack of 5 JO Z1)								Reserve Lighting) lm for 1 h 3	I 80										
						Close-Range Work	50 lm	17 m	15 h 30	_											
						Proximity	120 lm	30 m	6 h 45												
	ATEX zone 2/22 II 3 GD Ex ic IIB T4 Gc IIIB T135° C Dc	Эс												Movement	220 lm	80 m	2 h				
- E	IIIB T135° C Dc Ambient temperature: -20° C to +40° C	-	•	-	White	Distance Vision	180 lm	120 m	2 h 45	360 g											
UO Z2 BOAHB	(1)					BOOST Mode	430 lm	115 m	21140												
						Reserve Lighting		10 lm for 1 h	1												
						Close-Range Work	10 lm	12 m	100 h												
						Proximity	200 lm	55 m	5 h												
	•			White	Movement	550 lm	110 m	2 h	123 g												
1					Distance Vision	250 lm	95 m	4 h													
CE					- Distance vision		at 700 m fo														
WIFT RL RO	L UKCA				i idu	Close-Range Work	100 lm	35 m		10 - 50 h											
310AA00						Proximity	300 lm	35 m	5 - 40 h												
	-	-	•	White	Movement	900 lm		2 - 30 h													
								150 m													
						Distance Vision	550 lm	150 m	4 - 50 h												

(1) Certifications guaranteed only with alkaline batteries, (2) Factory setting, programmable by user.

Lighting specifications are subject to change: check www.petzl.com

COMPACT AND DURABLE HEADLAMPS

Headlamps designed for frequent use, for the energy and networks, and building and maintenance markets.



PIXA Z1

Headlamp for use in ATEX hazardous areas, suitable for proximity lighting, movement, and long-range vision. 100 lumens



Rechargeable headlamp for use in ATEX hazardous areas, suitable for proximity lighting, movement, and long-range vision. 90 lumens





PIXA 3

Headlamp for proximity lighting, movement, and long-range vision. Available in ATEX or HAZLOC versions. 100 lumens



PIXA 2

Headlamp suitable for proximity lighting and movement. Available in ATEX or HAZLOC versions. 80 lumens



PIXA 1

Headlamp for proximity lighting. Available in ATEX or HAZLOC versions. 60 lumens



Accessories



PRADAPTT

RUBBER

FOR PIXA SIR



































· Guaranteed lighting over time



LIGHTING

CONSTANT LIGHTING technology allows lighting to remain stable as the batteries drain. When the batteries are almost drained, the headlamp switches automatically to reserve lighting, with weaker output that prolongs lighting time (except PIXA Z1).

· For close-range work, movement, and long-range vision



















PIXA® 71

PIXA Z1 headlamp

Headlamp for use in ATEX hazardous areas, suitable for proximity lighting. movement, and long-range vision. 100 lumens

The PIXA Z1 headlamp is durable and versatile. The multi-beam adapts to a variety of different situations: close-range work, movement, and long-range vision. It meets ATEX zone 1/21 (II 2 GD Ex ib IIB T4 Gb IIIB T135° C Db) certification requirements for work in hazardous areas.

• Lamps for use in hazardous areas: ATEX or HAZLOC certification





Designed to withstand the harshest environments, PIXA headlamps can be used in explosive atmospheres. Depending on the model, they are certified ATEX or

Learn about choosing the ATEX or HAZLOC headlamp that best meets your needs, page 180.











Rechargeable headlamp for use in ATEX hazardous areas, suitable for proximity lighting, movement, and long-range vision. 90 lumens

The PIXA 3R headlamp is a durable, rechargeable headlamp suitable for frequent use by professionals. The multi-beam adapts to a variety of different situations: close-range work, movement, and long-range vision. CONSTANT LIGHTING technology: brightness does not gradually decrease as the batteries are drained. It meets ATEX zone 2/22 (II 3 GD Ex ic IIB T4 Gc IIIC T135° C Dc) certification requirements for work in hazardous areas.

· Rugged, durable construction



Lockable rotary switch

Easy to use, even when wearing gloves. May be locked to prevent inadvertently turning on the light, with a storage position that protects the lens.









PIXA® 3

Headlamp for proximity lighting, movement, and long-range vision. Available in ATEX or HAZLOC versions. 100 lumens

The PIXA 3 headlamp is durable and versatile. The multi-beam adapts to a variety of different situations: close-range work, movement, and long-range vision. CONSTANT LIGHTING technology: brightness does not decrease gradually as the batteries are drained. Available in two versions: ATEX zone 2/22 (II 3 GD Ex nA ic IIB T4 Gc tc, IIIC T135° C Dc) or HAZLOC (Class I Div 2 Groups C, D and Class II Div 2 Group G. T4).



of a professional work site

Great mechanical strength Shocks, falls, crushing; these lamps endure the daily rigors

and movement









PIXA® 2

Headlamp suitable for proximity lighting and movement. Available in ATEX or HAZLOC versions. 80 lumens

The PIXA 2 is a durable headlamp that offers comfortable lighting for tasks close at hand and helps maximize safety when the worker is moving around. CONSTANT LIGHTING technology: brightness does not decrease gradually as the batteries are drained. Available in two versions: ATEX zone 2/22 (II 3 GD Ex nA ic IIB T4 Gc tc, IIIC T135° C Dc) or HAZLOC (Class I Div 2 Groups C, D and Class II Div 2 Group G. T4).



Waterproof and chemical resistant PIXA headlamps are waterproof (IP67) and have been tested for resistance to various chemicals.

· For close-range work

· For close-range work











PIXA® 1

The PIXA 1 is a durable headlamp offering lighting that allows the user to work comfortably on tasks close at hand. CONSTANT LIGHTING technology: brightness does not decrease gradually as the batteries are drained. Available in two versions: ATEX zone 2/22 (II 3 GD Ex nA ic IIB T4 Gc tc, IIIC T135° C Dc) or HAZLOC (Class I Div 2 Groups C, D and Class II Div 2 Group G, T4).













Accessories



PIXADAPT

Accessory for mounting a PIXA or SWIFT RL PRO headlamp on a helmet

The PIXADAPT is a part that allows the user to mount or unmount a PIXA or SWIFT RL PRO headlamp on a helmet anytime, while maintaining the ability to tilt the lamp. PIXADAPT is compatible with Petzl helmets with or without eye shield. For other helmets, verify compatibility with the helmet



Rubber headband for PIXA or SWIFT RL PRO headlamp, compatible with a variety of helmet types

The RUBBER headband adapts to a variety of different helmets on the market and holds a PIXA or SWIFT RL PRO headlamp securely in position.



Rechargeable Battery for PIXA® 3R 930 mAh Lithium-Ion Polymer rechargeable battery

Rechargeable Lithium-Ion polymer battery, 930 mAh, recharges separately or on the headlamp for quick charge.



POCHE PIXA® & SWIFT® RL PRO

Carry pouch for PIXA and SWIFT RL PRO headlamps


Accessories		Weight
PIXADAPT	E78005	20 g
RUBBER	E78002	-
Rechargeable Battery for PIXA 3R	E78003	37 g
POCHE PIXA & SWIFT RL PRO	E78001	44 g
Spare Parts		
PIXA Headband	E78900 2	-
Plate With Helmet Clip for PIXA	E78901	-

				ANSI/PLATO FL 1				
	Certifications	CONSTANT LIGHTING	Lighting Modes	MAX BRIGHTNESS	MAX DISTANCE	MAX BURN TIME	Weight	
	CE		Close-Range Work	30 lm	15 m	56 h		
24	ATEX zone 1/21 Il 2 GD Ex ib IIB T4 Gb IIIB T135° C Db Ambient temperature: -20° C to +40° C UKCA		Movement	70 lm	50 m	23 h		
E78DHB 2	IIIB T135° C Db Ambient temperature:	-	Distance Vision	100 lm	95 m	16 h	170 g	
IXA Z1	UKCA (1)		Reserve Lighting		5 lm for 20 h			
			STANDARD Setting					
			Close-Range Work	20 lm	15 m	11 h 30		
			Movement	55 lm	45 m	5 h		
			Distance Vision	90 lm	90 m	3 h 30		
			Reserve Lighting) lm for 1 h :			
			MAX AUTONOMY Setting		7 1111 101 1111			
ri e	CE ATEX TODA 0/00		Close-Range Work	20 lm	15 m	11 h 30		
E78CHR 2	ATEX zone 2/22 II 3 GD Ex ic IIB T4 Gc IIIC T135° C Dc		_				145 g	
E78CHR 2UK	Ambient temperature: -30° C to +40° C		Movement	20 lm	30 m	11 h 30	140 g	
(A 3R	UKCA		Distance Vision	20 lm	50 m	11 h 30		
VA 3H			Reserve Lighting	10) lm for 1 h 3	30		
			MAX POWER Setting		ı			
			Close-Range Work	90 lm	25 m	3 h		
			Movement	90 lm	55 m	3 h		
			Distance Vision	90 lm	90 m	3 h 30		
			Reserve Lighting	10) lm for 1 h	30		
E78CHB 2	CE ATEX zone 2/22 II 3 G Ex nA ic IIB T4 Gc, II 3 D Ex tc IIIC T135° C Dc Ambient temperature: -30° C to +40° C UKCA		Close-Range Work	20 lm	15 m	26 h		
PRIS TO	(1) HAZLOC Class I Div 2 Groups C, D Class II Div 2 Group G Temperature code T4 Ambient temperature	- •	Movement	60 lm	45 m	6 h 30	160 g	
(A 3 E78CHB 2UL			Distance Vision	100 lm	90 m	3 h 30		
	-30° C to +40° C		Reserve Lighting	10 lm for 13 h				
E78BHB 2	CE ATEX zone 2/22 II 3 G Ex nA (c IIB 14 Gc, II 3 D Ex to IIIC 1135° C Dc Ambient temperature: -30° C to +40° C UKCA (1)		Close-Range Work	20 lm	25 m	26 h	400	
XA 2 E78BHB 2UL	HAZLOC Class Div 2 Groups C, D Class Div 2 Group G Temperature code T4 Ambient temperature: -30° C to +40° C	HAZLOC Class I Div 2 Groups C, D Class II Div 2 Group G Temperature code T4		Movement	80 lm	55 m	3 h 30	160 g
E/8BHB 2UL			Reserve Lighting	10 lm for 13 h				
E78AHB 2	CE ATEX zone 2/22 II 3 G Ex nA ic IIB 14 Gc, II 3 D Ex to IIIC 1135° C Dc Ambient temperature: -30° C to +40° C UKCA (1)		Close-Range Work	20 lm	10 m	16 h		
XA 1	HAZLOC Class I Div 2 Groups C, D Class II Div 2 Group G Temperature code T4	•	Movement	60 lm	15 m	3 h 30	160 g	
E78AHB 2UL	Ambient temperature: -30° C to +40° C		Reserve Lighting	10) Im for 6 h	30		

(1) Certifications guaranteed only with alkaline batteries

ULTRA-COMPACT AND VERSATILE HEADLAMPS

Ultra-compact and versatile headlamps designed for occasional or frequent use by tradespeople, maintenance professionals, or stage workers.



Compact, rechargeable, durable, and waterproof headlamp, with lighting designed for proximity vision and movement. 600 lumens





ARIA 1R

Compact, rechargeable, durable, and waterproof headlamp, designed for proximity lighting. 450 lumens





Compact, durable, and waterproof headlamp, suitable for proximity lighting and movement. 450 lumens





ARIA 1

Compact, durable, and waterproof headlamp designed for proximity lighting. 350 lumens





Accessories



























Ultra-compact emergency headlamp. 40 lumens

















Ultra-compact



Ultra-compact, ARIA headlamps can be easily stored in a toolbox.

· Waterproof and durable







ARIA headlamps are designed to meet the needs of professionals: waterproof (IP67), impact resistant (IK07), and fall resistant

· Easy to use



The single button on ARIA headlamp allows you to access every lamp function: on/off, lighting levels, lighting colors (black version only), lock, and battery level.

Practical



The HYBRID CONCEPT design allows the headlamps to function with standard AAA/ LR03 batteries or

with a CORE rechargeable battery. The headlamp automatically detects the energy source and optimizes lighting performance. With a rechargeable CORE battery, the lamp provides more brightness when it is turned on and throughout the duration of use.

SLOT ADAPT

The headband allows ARIA headlamps to be worn on the head or around the neck. They can also be mounted on a helmet, with mounts available as accessories: HELMET ADAPT (compatible with a variety of helmet types) and SLOT ADAPT (for helmets with compatible slots)

· For frequent use. lamps with rechargeable battery

Flood and mixed beam

















ARIA 2R

Compact, rechargeable, durable, and waterproof headlamp, with lighting designed for proximity vision and movement. 600 lumens

Casting 600 lumens, the compact and rechargeable ARIA 2R headlamp was specifically designed to be used by tradespeople and maintenance professionals. Durable, it is fall and impact resistant, waterproof and dustproof. Easy to use, with a single button for controlling all lamp functions. The wide, uniform beam provides comfortable proximity lighting and the mixed beam helps to maximize safety as you move around. It is convenient and can be worn on the head, around the neck, and on different types of helmets, using mounting plates that are available as accessories. ARIA 2R comes with the CORE rechargeable battery and is also compatible with three standard batteries, with its HYBRID CONCEPT design.











Compact, rechargeable, durable, and waterproof headlamp, designed for proximity lighting. 450 lumens

Casting 450 lumens, the compact and rechargeable ARIA 1R headlamp was designed to be used by tradespeople and maintenance professionals. Durable, it is fall and impact resistant. It is also dustproof and waterproof. Easy to use, with a single button for controlling all lamp functions. The uniform flood beam offers comfortable close-range vision. It is convenient and can be worn on the head, around the neck, and on different types of helmets, using mounting plates that are available as accessories. ARIA 1R comes with the CORE rechargeable battery and is also compatible with three standard batteries, with its HYBRID CONCEPT design.

· For occasional use, lamps with standard batteries

Flood and mixed beam













Compact, durable, and waterproof headlamp, suitable for proximity lighting and movement. 450 lumens

Casting 450 lumens, the ARIA 2 compact headlamp was designed to be used by tradespeople and maintenance professionals. Durable, it is fall and impact resistant. It is also dustproof and waterproof. Easy to use, with a single button for controlling all lamp functions. The wide, uniform beam provides comfortable proximity lighting and the mixed beam helps to maximize safety as you move around. It is convenient and can be worn on the head, around the neck, and on different types of helmets, using mounting plates that are available as accessories. ARIA 2 comes with three standard batteries and is also compatible with the CORE rechargeable battery, with its HYBRID CONCEPT design. The black headlamp features red/green/blue lighting.

Flood beam









110h

Compact, durable, and waterproof headlamp designed for proximity lighting.

Casting 350 lumens, the ARIA 1 headlamp was designed to be used by tradespeople and maintenance professionals. Durable, it is fall and impact resistant. It is also dustproof and waterproof. Easy to use, with a single button for controlling all lamp functions. The uniform flood beam offers comfortable close-range vision. It is convenient and can be worn on the head, around the neck, and on different types of helmets, using mounting plates that are available as accessories. ARIA 1 comes with three standard batteries and is also compatible with the CORE rechargeable battery, with its HYBRID CONCEPT design. The black headlamp features red/



green/blue lighting.







































ANSI/PLATO FL 1

Accessories



Rechargeable battery compatible with Petzl HYBRID headlamps

High-capacity 1250 mAh Lithium-lon rechargeable battery for Petzl headlamps featuring the HYBRID CONCEPT design: ARIA 1, ARIA 1R, ARIA 2, and ARIA 2R. It provides excellent lighting performance, even at low temperatures. It recharges directly with the integrated USB port. The CORE rechargeable battery offers an economical solution as the main power supply or as a back-up battery.





Plate for mounting a headlamp on a Petzl helmet

Plate for mounting a headlamp on a Petzl VERTEX or STRATO helmet, maintaining the ability to tilt the headlamp.





Adhesive plate for mounting a headlamp on a helmet

Adhesive plate for mounting a headlamp on a helmet, while maintaining the ability to tilt





UNI ADAPT

Adhesive clip for mounting a Petzl headlamp on a variety of helmet types



Spare ARIA Headband

Spare headband for headlamps from the ARIA range.



Pouch for storing ultra-compact headlamps from the ARIA range.

Emergency Headlamp







e+LITE®

Ultra-compact emergency headlamp. 40 lumens

Ultra-lightweight and highly compact, the e+LITE emergency headlamp is the one to always have with you. With a carrying case, it's always ready to use and can be stored with its batteries for ten years in a backpack, vest, or emergency kit, or used as a back-up headlamp. Its white or red, 40-lumen fixed lighting or strobe lighting helps you to be seen. The whistle integrated in the elastic headband allows the user to signal an emergency. Weighing only 26 grams, e+LITE



Its continuous or strobe lighting (white or red) allows you to be seen and to signal an emergency.

						ANSI/PLATO FL			
		Certifications	Lighting Color	Lighting Mode	MAX BRIGHTNESS	MAX DISTANCE	MAX BURN TIME	Weight	
				Proximity	7 lm	10 m	100 h		
10		CE		Movement	100 lm	60 m	7 h	95 g	
ABIA SB	E071AA00	UKCA	White	Distance Vision	600 lm	115 m	2 h		
NEW2023 ARIA 2R				Reserve Lighting		2 h			
				Proximity	7 lm	10 m	110 h		
		CE		Movement	100 lm	45 m	7 h		
ADIA 4D	E069CA00	UKCA	White	Distance Vision	450 lm	75 m	2 h	94 g	
NEW2023 ARIA 1R				Reserve Lighting		2 h			
				Proximity	7 lm	10 m	100 h		
		CE		Movement	100 lm	60 m	10 h	106 g	
NEW2028 ARIA 2	E070AA00	UKCA	White	Distance Vision	450 lm	100 m	2 h		
IEW2023 ARIA 2				Reserve Lighting		20 h	•		
				Proximity	7 lm	10 m	100 h		
_	E070BA00	CE UKCA	White Red	Movement	100 lm	60 m	10 h	106 g	
				Distance Vision	450 lm	100 m	2 h		
NEW2023 ARIA 2 RGB				Reserve Lighting		20 h			
ARIA 2 RGB				Continuous	4 lm	5 m	50 h		
			Green Blue	Strobe	Visible	Visible at 700 m for 300 h			
	E069AA00		White	Proximity	7 lm	10 m	110 h	105 g	
		CE UKCA		Movement	100 lm	45 m	12 h		
NEW2023 ARIA 1				Distance Vision	350 lm	70 m	2 h		
ANIA I				Reserve Lighting		20 h			
				Proximity	7 lm	10 m	110 h		
		CE UKCA	White Red Green Blue	Movement	100 lm	45 m	12 h	105 g	
	E069BA00			Distance Vision	350 lm	70 m	2 h		
NEW2023 ARIA 1 RGB	E069BA00			Reserve Lighting		20 h			
				Continuous	4 lm	5 m	50 h		
				Strobe	Visible at 700 m for 300 h				
	E02 P4	CE UKCA	White	Proximity	20 lm	13 m	9 h 30		
				Movement	40 lm	15 m	3 h		
				Strobe	Visible at 100 m for 95 h		26 g		
+LITE				Proximity	Visible	Visible at 100 m for 15 h		1	
			Red	Strobe	Visible at 100 m for 70 h				

Accessories		Weight
CORE	E99ACA	23 g
NEW2023 SLOT ADAPT	E073BA00	11 g
NEW2023 HELMET ADAPT	E073AA00	22 g
NEW2023 UNI ADAPT	E000BA00	10 g
NEW2023 Spare ARIA Headband	E068AA01	24 g
SHELL L	E93990	41 g

Lighting specifications are subject to change: check www.petzl.com





Climbing

Whether climbing at a crag or on an indoor wall, Petzl is constantly imagining new solutions for dedicated climbers, or for those simply seeking a moment to recreate and be social.




Caving

Petz's roots are in subterranean exploration! For over 50 years, since the development of our very first headlamps, rope clamps and descenders, we have shared a profound connection with explorers of the deep.



Ice Climbing

Ice climbing is very technical and requires highly specialized equipment. Gullies, couloirs, icefalls: climbing these ephemeral formations always brings an extra bit of adventure.





Canyoning

A combination of hiking, climbing, and swimming in whitewater, canyoning has become a major outdoor activity in recent years, even outside the summer season.



Via Ferrata

Via ferrata is the most affordable way to discover the vertical environment via a route made up of cables, ladders, and steps on a rock wall. It's a wonderful introduction to more technical pursuits.

Nighttime Outdoor Activities Disconnect from everyday life and get back to nature for an evening, or a weekend. Make your days longer; watch the stars and the wildlife, or simply share a moment around a campfire, with family or friends.



Night Running

Get out of the house, tread the city streets or the trails; run for a different perspective on your daily life, to get closer to nature, or to train.



Tactical, Special Forces

Tactical operations in a hostile environment require maximum safety in every situation, so being able to count on the quality and performance of the equipment is essential.





Exploring New Horizons

The Petzl Foundation's mission is to support and initiate public interest projects through its activities in mountainous and vertical domains; projects that help bring balance to humankind's place in its natural, cultural, and economic environments. The foundation supports non-profit organizations through financial and equipment grants, as well as consultation and training.

Our courses of action:



Prevent accidents in vertical environments



Encourage mountain exploration



Support ecological transition in mountainous areas

Encourage ecological transition, a new Petzl Foundation support objective

Our goal is to support projects in areas of public interest that aim to regenerate biodiversity, capture or reduce carbon emissions in French mountain regions, and encourage education about climate change.



Snow drought on the Écrins massif, early March 2022.

Why should we participate in the ecological transition?

Mountainous areas are on the front line of climate change. While average global temperatures have increased by 1° C since 1850, the Alps have warmed 2.3° C. The consequences are already visible in the lack of snowfall and water resources, and increase in natural disasters. The current impacts at altitude are precursors to what will be experienced at lower elevations. It's urgent that we participate in and contribute to ecological transition in the mountains.

The Petzl Foundation will also plan to align with our Corporate Social Responsibility (CSR) strategy, which is committed to reducing our carbon intensity by 50 % from

Our eagerness to take action is emerging as we commit to doing our part in the ecological transition. In order to finance new projects, €100,000 has been added to the 2022 Petzl Foundation donation fund.

Petzl's effort to reduce CO2 emissions and combat erosion of biodiversity rests on two pillars:

- Reduce our carbon emissions via CSR projects carried out by all departments
- Reduce or capture carbon emissions from other groups (small towns, organizations, community groups) and contribute to regenerating biodiversity, with the help of projects supported by the Petzl Foundation



www.petzl.com

The site for professionals working at height and in dark environments.

- Discover Petzl's solutions for verticality and lighting
- · Check out tips and technical information on best practices for using Petzl products
- · Find all the Petzl news and reports on various trades: videos, news, portraits, and events

Pages to explore

Beyond our product offerings, Petzl offers a wide range of technical information: Instructions for Use, tech tips, PPE inspection records, and more.

Discover all the content pages on our website. Whether you are novice or expert in your field, Petzl shares its technical expertise to help you work more safely and efficiently.

On our product pages, you will find:

- Instructions for Use: they are the base of our technical information and provide the essentials for using your products. Remember to read them before using your products
- Technical tips, "by Petzl". They contain information complementary to the Instructions for Use: test results, feedback, and technical videos. Documents with all you need to know about your products!
- Records and procedures for PPE inspection: use them to inspect your PPE











© Petzl 2022



Petzl headquarters: PETZL INTERNATIONAL. Z.I. Crolles, 38920 CROLLES, FRANCE

Graphic design: Pierre Bena design - www.pierrebenadesign.com Product photos (non-contractual photos): © Petzl Kalice - www.kalice.fr Aurélie Jeannette, Photographer - www.aureliejeannette.com

Yannick Siegel

Digital Publication: Fluidbook.com

Subscribe to our newsletter and stay connected!

Find a Petzl dealer

See all Petzl Foundation projects

The activities depicted are inherently dangerous. All users must be trained and competent in the use of the equipment for these activities.