

'18-'23 Subaru Crosstrek Liftgate Light Upgrade Installation Instructions



1) REMOVE FACTORY HATCH LIGHT AND PLUG IN THE CONNECTOR TO THE BLACK END OF THE INCLUDED HARNESS.

2) GENTLY PRY BACK THE TRIM PANEL IN THE C PILLAR. REMOVAL IS NOT NECESSARY, PULL BACK FAR ENOUGH TO FEED THE SMALL RED CONNECTOR END OF THE HARNESS THROUGH.



3) PULL BACK THE FACTORY HARNESS BOOT FROM BOTH ENDS AND FEED THE HARNESS THROUGH.





4) REMOVE THE PLASTIC PANELS ALONG THE FRAME OF THE HATCH AND ROUTE THE SUPPLIED HARNESS ALONG THE FACORY LOOM. SECURE WITH ZIPTIES.

5) WITH A PRY TOOL, REMOVE THE FACTORY COVER IN THE LIFTGATE PANEL.

WE STRONGLY RECOMMEND REMOVING THE ENTIRE HATCH PANEL COVER TO INSTALL THE LIGHT HOUSING.

PAY ATTENTION TO THE HOOKS ON THE LIGHT HOUSING AS THEY MAY BREAK IF IMPROPERLY INSTALLED.



'18-'23 Subaru Crosstrek Liftgate Light Upgrade Installation Instructions (continued)



6) PLUG IN THE HARNESS INTO THE LIGHT HOUSING AND TEST BEFORE REASSEMBLING THE HATCH PANELS.

THE LARGE CONNECTOR IS NOT USED AT THIS TIME. DO NOT REMOVE THE PLUG TO AVOID SHORTING HAZARD.

CONGRATULATIONS! YOUR LIFTGATE LIGHT INSTALLATION IS NOW COMPLETE!

