19" Android Advertising Displays





Stunning displays that combine tablet-like aesthetics with a robust mild steel enclosure and tempered glass face

Plug and Play


Plug and Play is the most straightforward way to upload content to the screen. Simply load images and videos onto a USB stick, insert into the display, wait for your content to copy over and then remove. Your images and videos will now play in a continuous loop.



450cd/m² IPS Panel

Commercial grade IPS technology accurately displays image quality and colour depth with no fall-off in colour accuracy. These panels are designed to achieve ultimate lifelike colour temperature when used in either landscape or portrait.





Free Scheduling Software

These displays come with free scheduling software for displaying different content at different times of the day. If you prefer to keep it simple you can update the screen directly without using the software.



24/7 Commercial Use

These displays use a commercial grade LCD panel and LED backlight. They have the ability to be in constant use 24/7 for over 70,000 hours and have no external buttons or controls to avoid tampering.







Power Timer

The eco-friendly power timer allows you to assign daily or weekly on and off times for your screen meaning that it is only in use when it needs to be; improving your environmental efficiency.



Multiple Inputs


Should you need to use the screen as a monitor you can connect it to an external source, like a PC or media player, using the HDMI input or the VGA and 3.5mm audio jack inputs.






4 Audio in





Low Power Consumption

The LED backlight technology provides improved brightness and contrast. Their lifespan is drastically improved to over 70,000 hours and the power consumption is reduced by around 30%.



Scrolling Text

You can display a "ticker tape" style scrolling text message along the bottom of the screen, to help you get your message across or help highlight any specific promotions or offers.



SALE NOW ON - 30% OFF ALL FOOTWEAR - ENDS TONIGHT - SALE NOW ON - 30% OFF ALL

Giant Tablet Styling

Their tempered glass face, rounded corners, super slim profile and aluminium surround all add to the captivating tablet-like aesthetics as well as protecting the internal components from potential damage.



Wide Viewing Angle

Thanks to the IPS technology these displays provide fantastic image quality with a remarkable viewing angle of 178° in both landscape and portrait.



Free Wall Mount

A super slim wall mount is included at no extra cost, allowing you to mount your screen in either landscape or portrait orientation; ensuring that you have a complete turnkey solution.



Optional Network Upgrade

For a small charge you can upgrade your screen to be networked, allowing you to connect your screen via Wi-Fi, LAN or 4G, then remotely update it over the internet.















IPS PANEL





LANDSCAPE OR PORTRAIT ORIENTATION



CONNECT DEVICES



LED BACKLIGHT



OPTIONAL NETWORK UPGRADE













Panel 19 inch Panel 1 20 count (180 count) Panel 1 20 count (180 count) Panel 6 prightness (cul m) Panel 6 prightness (cul m) Panel 1 6 prightness (cul m) Viney 1 5 prightness (cul m) Audio 5 peaker Type Av Input 1 4 prightness Audio 4 prightness Av Input 1 4 prightness Audio 4 prightness Av Input 1 4 prightness Audio 4 prightness Av Input 1 4 prightness Av Input 1 1 prightness Av Input 1 1 prightness Power Consumption (W) 1 1 prightness Mechanical 1 1 prightness Mechanical 1 1 prightness Every Brightness 1 1 prightness Every Brightness 2 1 prightness			
Panel Display Area (mm) 408.6x229.6 Panel Aspect Ratio 16.9 Colour 16.7M Viewing Angle 17.78° Contrast Ratio 5000:1 Audio Spasker Type 5W, 80 kg ly2 AV Inputs Audio Audio Sockett (3.5mm) AV Inputs Audio Audio Sockett (3.5mm) Power Power Consumption (W) 1.6 Input Voltage AC110-240V (50Hz-60Hz) Input Voltage AC110-240V (50Hz-60Hz) Mechanical YESA Hols mm) 501.8222435.2 Package Size (WxH-ID mm) 578.418x118 48 Mechanical YESA Hols file 6.3 Met Weight (kg) 7.35 7.35 Cross Weight (kg) 7.35 7.35 Operating Emperature 0 "C to 50 "C Storage Temperature 30"C to 60"C Operating Humidity 108 No.80% Storage Temperature 10 C Quadrocre ARM Creat Al7, 1.6GHz CPU Quadrocre ARM Creat Al7, 1.6GHz CPU Quadrocre ARM Creat Al7, 1.6GHz			
Panel Aspect Ratio 16:99 Panel Brightness (cd/m²) 450 Colour 16:7M Viewing Angle 178° Cornard Ratio 50000:1 Audio 5peaker Type 5W.80 (k2) AV Inputs Video HDMI, VGA Power Consimption (W) 16 4 Input Voltage ACT10-240V (50Hz-60Hz) Mechanical YESA Holes (mm) 501x322x35;2 Package Size (Wh4Hz0 mm) 578x4H818 Mechanical YESA Holes (mm) 100x100 Mechanical YESA Holes (mm) 100x100 YESA Holes (mm) 100x100 100x100 Mechanical (kg) 6.3 7.35 Gross Weight (kg) 6.3 7.35 Gross Weight (kg) 9.73x18 9.00x100 Fenting Emperature 0°C to 50°C Environmental Media Formats Video (MPG, AVI, MPA, RM, RWB, TSI, Audio (MPA, WMA), Image UPG, GIF, BMP, PNG) Coperating Temperature Video (MPG, AVI, MPA, RM, RWB, TSI, Audio (MPA, WMA), Image UPG, GIF, BMP, PNG) Media Fo		Resolution	1920x1080
Panel Brightness (ed/m²) 450 Colour 16.7M Viewing Angle 1.78° Contrast Ratio 5000:1 Audio Speaker Type 55W, 80 (x2) AV Inputs Video HDMI, VGA Audio Audio Audio Socket (3.5mm) Power Power Consumption (W) 16 Input Voltage Act 110-240 (50Hr-40Hz) Mechanical VESA Hols (mm) 501x322x35.2 Power (blist film) 100x100 Mechanical VESA Hols (film) 100x100 Mechanical VESA Hols (film) 100x100 VEAL (Film) 100x100 100x100 Mechanical VESA Hols (film) 6.3 Cross Weight (kg) 6.3 7.35 Operating Temperature 0°C to 5° °C Environmental Storage Immediate 9°C to 50° °C Storage Humdity 10% to 80% Storage Film (film) 10% to 80% Media Resolution 1920x1080/10800x1920 CPU Quad-Core ARM Mortex A17, 1.66Hz <tr< td=""><td></td><td>Display Area (mm)</td><td>408.6x229.6</td></tr<>		Display Area (mm)	408.6x229.6
Colour 16.7M Viewing Angle 178° Contrast Ratio 50000:1 Audio Speaker Type 5W, 80 (x2) AV Inputs Video HDMI, VCA Audio Audio Socket (3.5mm) Power Power Consumption (W) 16 Input Voltage AC110-240V (50Hz-0Hz) Package Size (WH-HD mm) 501x322x35.2 Package Size (WH-HD mm) 578x418x118 Mechanical Yes Holes (mm) 100x100 Net Weight (kg) 6.3 Gross Weight (kg) 7.35 Storage Temperature 0°C to 50°C Storage Humidity 10% to 80% Operating Humidity 5% to 95% Media Formats Video (MPG, AVI, MPA, RNVB, TS), Audio (MPS, WMA), Image (JPG, GJF, BMP, PNG) Purport Purport Quad-Core ARM Cortex A17, 1.6GHz CPU Quad-Core ARM Cortex A17, 1.6GHz GPU Quad-Core ARM Malii-T764 RAM DDR3 2GB MOM 8GB eMMC USB 1 x USB (OTG/HOST), 4 x USB (HOST) LA		Aspect Ratio	16:9
Media Francis 178° Audio Speaker Type 5W, BQ, (x2) AV Inputs Video HDMI, VGA Power Power Consumption (W) 16 Input Voltage AC110-240V (50Hz-60Hz) Mechanical VESA Holes (mm) 501x32x35.2 Mechanical VESA Holes (mm) 100x100 Mechanical VESA Holes (mm) 100x100 Mechanical VESA Holes (mm) 100x100 Net Weight (kg) 6.3 3 Gross Weight (kg) 7.35 6 Gorarding Temperature 0 °C to 50 °C Operating Humidity 10% to 80% Storage Temperature 30°C to 60°C Operating Humidity 10% to 80% Storage Informats Video (MPG, AVI, MPA, RMYA, RMYA, RMYA, RMYA, RMYA, RMYA, LMGA, AUGI (MPR, WMA), Image (JPG, GIF, BMP, PNG) Cemputer Media Resolution 1920x1080/1080x1920 Cemputer QPU Quad-Core ARM Cortex AT7, 1.6GHz GPU Quad-Core ARM Cortex AT7, 1.6GHz GPU Quad-Core ARM Cortex ATM Cortex AT7, 1.6GHz USB <td>Panel</td> <td>Brightness (cd/m²)</td> <td>450</td>	Panel	Brightness (cd/m²)	450
Audio Speaker Type 5W, 8Q (x2) Al Inputs Video A Honly (CA) Power Audio Audio Socket (3.5mm) Power Power Consumption (W) 16 Input Voltage ACT101-240V (50Hz-60Hz) Input Voltage ACT101-240V (50Hz-60Hz) Mechanical Visite (WHxbD mm) 501x322x35.2 Mechanical VESA Holes (mm) 100x100 Net Weight (kg) 6.3 3 Gross Weight (kg) 7,35 3 Gross Weight (kg) 7,35 3 Storage Emperature 9 °C to 50 °C 3 Storage Emperature 9 °C to 50 °C 3 Storage Humidity 10% to 80% 3 Storage Florenture 9 °C to 50 °C 3 CPU Quad-Core ARM Cortex AIT, 1.6GHz 4 CPU Quad-Core ARM Cortex AIT, 1.6GHz 4 ACM DDR3 2GB 4 MEM POM 4 4 4 4 4 4 4 4 4 4		Colour	16.7M
Audio Speaker Type 5W, 80 (x2) AV Inputs Yideo HDMI, VGA Abulin Audio Audio Socket (3.5 mm) Power Power Consumption (W) 16 Input Voltage AC110-240V (50Hz-60Hz) Package See (MxHxbD mm) 501x322x35.2 Package See (MxHxbD mm) 578x418x118 Mechanical VESA Holes (mm) 100x100 Met Weight (kg) 6.3 Gross Weight (kg) 7.35 Operating Temperature 0°C to 50°C Operating Humidity 10% to 80% Storage Temperature 30°C to 50°C Operating Humidity 10% to 80% Storage Humidity 578x to 93% Media Resolution 1920x1080/1080/1980/1980/1990 Computer Media Resolution 1920x1080/1080/1980/1980/1990 Computer RAM DDR3 2GR GPU Quad-Core ARM Mail-TX64 Computer RAM DDR3 2GR ROM 3 GR BeMMC Computer Quad-Core ARM Mail-TX64 LOS 1 x USB (G		Viewing Angle	178°
AV Inputs		Contrast Ratio	5000:1
AV Inputs Audio Audio Socket (3.5mm) Power Onsumption (W) 1.6 Input Voltage ACT10~240V (50Hz~60Hz) Input Voltage ACT10~240V (50Hz~60Hz) Mechanical Filiation (Mrs.) 501x322x35.2 Package Size (WxHxD mm) 578x418x118 Mechanical Ket Weight (kg) 6.3 Cross Weight (kg) 7.35 Cross Weight (kg) 7.35 Storage Temperature 90°C to 50°C Operating Humidity 10% to 80% Storage Humidity 5% to 95% Media Formats Video (MPG, AVI, MPA, RM, RMS, TS), Audio (MPS, WMA), Image (JPG, GIF, BMP, PNG) Media Resolution 1920x1080/1080x1200 CPU Quad-Core ARM Cortex ATI, 1.66Hz GPU Quad-Core ARM Mortex ATI, 1.66Hz GPU Quad-Core ARM Mortex ATI, 1.46Hz Computer RAM DDR3 2GB MOM BORS 1.1 x USB (OTG/HOST), 4 x USB (HOST) LAN 1 x USB (OTG/HOST), 4 x USB (HOST) LAN 1 x USB (OTG/HOST), 4 x USB (HOST) LAN 1 x USB (OTG/HOST), 4 x USB (HOST)	Audio	Speaker Type	5W, 8Ω (x2)
Power Audio Audio Socket (3.5mm) Power Power Consumption (W) 16 Input Voltage AC110-240V (50Hz-60Hz) Power Input Voltage AC110-240V (50Hz-60Hz) Methodical Pokage Size (WxHxD mm) 501x32zx35.2 Pokage Size (WxHxD mm) 578x418x118 Methodical Net Weight (kg) 6.3 Foreiting Femperature 6.3 Operating Femperature 9°C to 50°C Operating Humidity 10% to 80% Storage Humidity 5% to 95% Video (MPG, AVI, MP4, RM, RWNB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Media Fesolution Yideo (MPG, AVI, MP4, RM, RWNB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Computer Pul Quad-Core ARM Cortex A17, 1.6GHz GPU Quad-Core ARM Cortex A17, 1.6GHz GPU Quad-Core ARM Mail-1764 Komputer RAM DBUS 2GB Computer RAM BUS 3GB eMMC Computer Pul Quad-Core ARM Mail-1764 Computer RAM DBUS 2GB Computer RAM		Video	HDMI, VGA
Power Input Voltage ACC110~240V (50Hz~60Hz) NEARAND RAME 10tit Size (WxHxD mm) 501x322x35.2 Mechanical YESA Holes (mm) 100x100 Mechanical VESA Holes (mm) 100x100 Net Weight (kg) 6.3 Gross Weight (kg) 7.35 Operating Temperature 0°C to 50°C Operating Humidity 10% to 80% Storage Humidity 5% to 95% Media Formats Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Media Resolution 1920x1080/1080x1920 CPU Quad-Core ARM Cortex A17, 1.6GHz GPU Quad-Core ARM Mail-T764 RAM DSR3 2GB COMPUTE 10M 8GB eMMC LAN 100M/1000M Ethernet (Network Version Only) Wi-Fi 802.11bg/n/ac (Network Version Only) Buletooth Bluetooth 4.0 OS Android 7.1 ACcessories Included Special Wall Mount, Scheduling Software, Remote Control, Key, User Manual Optional Network Upgrade, Touch Screen Version, Wall Mount, Floor Stand/Trolley, Ceiling Mount, Table Stand </td <td>AV Inputs</td> <td>Audio</td> <td>Audio Socket (3.5mm)</td>	AV Inputs	Audio	Audio Socket (3.5mm)
Injut Voltage		Power Consumption (W)	16
Mechanical Unit Size (WxHxD mm) 501x322x35.2 Package Size (WHxHzD mm) 578x418x118 Mechanical YESA Holes (mm) 10x100 Net Weight (kg) 6.3 Gross Weight (kg) 7.35 Operating Temperature 0 °C to 50 °C Storage Temperature -30°C to 60°C Operating Humidity 10x to 80% Storage Humidity 5% to 95% Media Formats Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GJF, BMP, PNG) Media Resolution 1920x1080/1080x1920 CPU Quad-Core ARM Cortex A17, 1.6GHz GPU Quad-Core ARM Mali-T764 RAM DDR3 2GB ROM 8GB eMMC USB 1 x USB (OTG/HOST), 4 x USB (HOST) LAN 100M/1000M Ethernet (Network Version Only) Wi-Fi 802.11b/g/n/ac (Network Version Only) Biluetooth Bluetooth 4.0 OS Android 7.1 Graphic Engine OpenGLES 1.1/2.0/3.0/31, OpenCL 1.1, Renderscript, Direct3D 11.1 McCessories OpenGLES 1.1/2.0/3.0/31, Vall Mount, Floor Stand/Trolley, Celling Mount, Table Stand <td>Power</td> <td></td> <td>AC110~240V (50Hz~60Hz)</td>	Power		AC110~240V (50Hz~60Hz)
Mechanical Package Size (WxHxD mm) 578x418x118 Mechanical VESA Holes (mm) 100x100 Met Weight (kg) 6.3 Gross Weight (kg) 7.35 Bervironmental Storage Temperature 0 °C to 50 °C Operating Humidity 10% to 80% Storage Humidity 5% to 95% Media Formats Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Media Formats Video (MPG, AVI, MP4, RM, RWVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) PU Quad-Core ARM Cortex A17, 1.6GHz GPU Quad-Core ARM Mail-T764 RAM DDR3 2GB ROM 8GB eMMC USB 1 x USB (OTG/HOST), 4 x USB (HOST) LAN 100M1/1000M Ethernet (Network Version Only) Wi-Fi 802.11b/g/n/ac (Network Version Only) Bluetooth Bluetooth 4.0 OS Android 7.1 Graphic Engine OpenGLE S 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Accessories All Cuded Special Wall Mount, Scheduling Software, Remote Control, Key, User Manual Optional Network		- Andrews Andr	
Net Weight (kg) 6.3 Gross Weight (kg) 7.35 Penvironmental 0 °C to 50 °C Environmental 5 torage Temperature -30°C to 60°C Operating Humidity 10% to 80% Storage Humidity 5% to 95% Media Formats Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Media Resolution 1920x1080/1080x1920 CPU Quad-Core ARM Cortex AI7, 1.6GHz GPU Quad-Core ARM Mali-T764 RAM DDR3 2GB ROM 8 GB eMMC USB 1 x USB (OTG/HOST), 4 x USB (HOST) LAN 100M/1000M Ethernet (Network Version Only) Wi-Fi 802.11b/g/n/ac (Network Version Only) Bluetooth Bluetooth 4.0 ACcessories OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Accessories Included Special Wall Mount, Scheduling Software, Remote Control, Key, User Manual Warranty Warranty Period 3 Year Warranty		Package Size (WxHxD mm)	578x418x118
Environmental Gross Weight (kg) 7.35 Environmental Operating Temperature 0 °C to 50 °C Environmental Storage Temperature -30°C to 60°C Operating Humidity 10% to 80% Storage Humidity 5% to 95% Media Formats Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Media Resolution 1920x1080/1080x1920 CPU Quad-Core ARM Cortex A17, 1.6GHz GPU Quad-Core ARM Mali-T764 RAM DDR3 2GB ROM 8GB eMMC USB 1 x USB (OTG/HOST), 4 x USB (HOST) LAN 100M/1000M Ethernet (Network Version Only) Wi-Fi 802.11b/g/n/ac (Network Version Only) Bluetooth Bluetooth 4.0 Oc Android 7.1 Graphic Engine OpenGL ES 1.1/2.0/30.3/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Accessories Opitonal Network Upgrade, Touch Screen Version, Wall Mount, Floor Stand/Trolley, Ceiling Mount, Table Stand Warranty Warranty Warranty	Mechanical	VESA Holes (mm)	100x100
Environmental O °C to 50 °C Environmental Storage Temperature -30°C to 60°C Operating Humidity 10% to 80% Storage Humidity 5% to 95% Media Formats Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Media Resolution 1920x1080/1080x1920 CPU Quad-Core ARM Cortex A17, 1.6GHz GPU Quad-Core ARM Mali-T764 RAM DDR3 2GB MC BGB eMMC USB 1 x USB (OTG/HOST), 4 x USB (HOST) LAN 100M/1000M Ethernet (Network Version Only) Wi-Fi 802.11b/g/n/ac (Network Version Only) Bluetooth Bluetooth 4.0 OS Android 7.1 Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Accessories Included Special Wall Mount, Scheduling Software, Remote Control, Key, User Manual Warranty Warranty Period 3 Year Warranty		Net Weight (kg)	6.3
Environmental Storage Temperature -30°C to 60°C Operating Humidity 10% to 80% Storage Humidity 5% to 95% Media Formats Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Media Resolution 1920x1080/1080x1920 CPU Quad-Core ARM Cortex A17, 1.6GHz GPU Quad-Core ARM Mali-T764 RAM DDR3 2GB MOM 8GB eMMC USB 1 x USB (OTG/HOST), 4 x USB (HOST) LAN 100M/1000M Ethernet (Network Version Only) Wi-Fi 802.11b/g/n/ac (Network Version Only) Bluetooth Bluetooth 4.0 OS Android 7.1 OS Android 7.1 Accessories Included Special Wall Mount, Scheduling Software, Remote Control, Key, User Manual Network Upgrade, Touch Screen Version, Wall Mount, Floor Stand/Trolley, Ceiling Mount, Table Stand Warranty Warranty		Gross Weight (kg)	7.35
Environmental Operating Humidity 10% to 80% Storage Humidity 5% to 95% Media Formats Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Media Resolution 1920x1080/1080x1920 CPU Quad-Core ARM Cortex A17, 1.6GHz GPU Quad-Core ARM Mali-T764 RAM DDR3 2GB MOM 8GB eMMC USB 1 x USB (OTG/HOST), 4 x USB (HOST) LAN 1000M/1000M Ethernet (Network Version Only) Wi-Fi 802.11b/g/n/ac (Network Version Only) Bluetooth Bluetooth 4.0 OS Android 7.1 Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Accessories Included Special Wall Mount, Scheduling Software, Remote Control, Key, User Manual Warranty Warranty		Operating Temperature	0 °C to 50 °C
Operating Humidity 10% to 80% Storage Humidity 5% to 95% Media Formats Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Media Resolution 1920x1080/1080x1920 CPU Quad-Core ARM Cortex A17, 1.6GHz GPU Quad-Core ARM Mali-T764 RAM DDR3 2GB ROM 8GB eMMC USB 1 x USB (OTG/HOST), 4 x USB (HOST) LAN 100M/1000M Ethernet (Network Version Only) Wi-Fi 802.11b/g/n/ac (Network Version Only) Bluetooth Bluetooth 4.0 OS Android 7.1 Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Accessories Included Special Wall Mount, Scheduling Software, Remote Control, Key, User Manual Warranty Warranty Period 3 Year Warranty		Storage Temperature	-30°C to 60°C
Media Formats Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Media Resolution 1920x1080/1080x1920 CPU Quad-Core ARM Cortex A17, 1.6GHz GPU Quad-Core ARM Mali-T764 RAM DDR3 2GB ROM 8GB eMMC USB 1 x USB (OTG/HOST), 4 x USB (HOST) LAN 100M/1000M Ethernet (Network Version Only) Wi-Fi 802.11b/g/n/ac (Network Version Only) Bluetooth Bluetooth 4.0 OS Android 7.1 Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Accessories Included Special Wall Mount, Scheduling Software, Remote Control, Key, User Manual Varranty Warranty Period 3 Year Warranty	Environmental	Operating Humidity	10% to 80%
Computer Media Resolution 1920x1080/1080x1920 Copu Quad-Core ARM Cortex A17, 1.6GHz GPU Quad-Core ARM Mali-T764 RAM DDR3 2GB ROM 8GB eMMC USB 1 x USB (OTG/HOST), 4 x USB (HOST) LAN 100M/1000M Ethernet (Network Version Only) Wi-Fi 802.11b/g/n/ac (Network Version Only) Bluetooth Bluetooth 4.0 OS Android 7.1 Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Accessories Included Special Wall Mount, Scheduling Software, Remote Control, Key, User Manual Optional Network Upgrade, Touch Screen Version, Wall Mount, Floor Stand/Trolley, Ceiling Mount, Table Stand Warranty Warranty Period 3 Year Warranty		Storage Humidity	5% to 95%
CPU Quad-Core ARM Cortex A17, 1.6GHz GPU Quad-Core ARM Mali-T764 RAM DDR3 2GB ROM 8GB eMMC USB 1 x USB (OTG/HOST), 4 x USB (HOST) LAN 100M/1000M Ethernet (Network Version Only) Wi-Fi 802.11b/g/n/ac (Network Version Only) Bluetooth Bluetooth 4.0 OS Android 7.1 Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Accessories Included Special Wall Mount, Scheduling Software, Remote Control, Key, User Manual Varranty Warranty Period 3 Year Warranty		Media Formats	Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG)
GPU Quad-Core ARM Mali-T764 RAM DDR3 2GB ROM 8GB eMMC USB 1 x USB (OTG/HOST), 4 x USB (HOST) LAN 100M/1000M Ethernet (Network Version Only) Wi-Fi 802.11b/g/n/ac (Network Version Only) Bluetooth Bluetooth 4.0 OS Android 7.1 Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Accessories Included Special Wall Mount, Scheduling Software, Remote Control, Key, User Manual Optional Network Upgrade, Touch Screen Version, Wall Mount, Floor Stand/Trolley, Ceiling Mount, Table Stand Warranty Warranty Period 3 Year Warranty		Media Resolution	1920x1080/1080x1920
Paranty RAM DDR3 2GB ROM ROM BGB eMMC 1 x USB (OTG/HOST), 4 x USB (HOST) LAN 100M/1000M Ethernet (Network Version Only) Wi-Fi Bluetooth Bluetooth OS Android 7.1 Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Accessories Network Upgrade, Touch Screen Version, Wall Mount, Floor Stand/Trolley, Ceiling Mount, Table Stand Warranty Warranty Warranty Page Accessories ROM BUBS BUBS BUBS BUBS BUBS BUBS BUBS BUBS		CPU	Quad-Core ARM Cortex A17, 1.6GHz
ROM8GB eMMCUSB1 x USB (OTG/HOST), 4 x USB (HOST)LAN100M/1000M Ethernet (Network Version Only)Wi-Fi802.11b/g/n/ac (Network Version Only)BluetoothBluetooth 4.0OSAndroid 7.1Graphic EngineOpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1AccessoriesIncludedSpecial Wall Mount, Scheduling Software, Remote Control, Key, User ManualWarrantyWarranty PeriodNetwork Upgrade, Touch Screen Version, Wall Mount, Floor Stand/Trolley, Ceiling Mount, Table Stand		GPU	Quad-Core ARM Mali-T764
Computer USB		RAM	DDR3 2GB
USB LAN 100M/1000M Ethernet (Network Version Only) Wi-Fi 802.11b/g/n/ac (Network Version Only) Bluetooth OS Android 7.1 Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Accessories Network Upgrade, Touch Screen Version, Wall Mount, Floor Stand/Trolley, Ceiling Mount, Table Stand Warranty Warranty Warranty Version 100M/1000M Ethernet (Network Version Only) 802.11b/g/n/ac (Network Version Only) 803.11b/g/n/ac (Network Version Only) 8		ROM	8GB eMMC
Wi-Fi 802.11b/g/n/ac (Network Version Only) Bluetooth Bluetooth 4.0 OS Android 7.1 Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Accessories Included Special Wall Mount, Scheduling Software, Remote Control, Key, User Manual Optional Network Upgrade, Touch Screen Version, Wall Mount, Floor Stand/Trolley, Ceiling Mount, Table Stand Warranty Warranty Period 3 Year Warranty	Computer	USB	1 x USB (OTG/HOST), 4 x USB (HOST)
Bluetooth 4.0 OS Android 7.1 Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Accessories Included Special Wall Mount, Scheduling Software, Remote Control, Key, User Manual Optional Network Upgrade, Touch Screen Version, Wall Mount, Floor Stand/Trolley, Ceiling Mount, Table Stand Warranty Warranty Period 3 Year Warranty		LAN	100M/1000M Ethernet (Network Version Only)
OS Android 7.1 Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Accessories Included Special Wall Mount, Scheduling Software, Remote Control, Key, User Manual Optional Network Upgrade, Touch Screen Version, Wall Mount, Floor Stand/Trolley, Ceiling Mount, Table Stand Warranty Warranty Period 3 Year Warranty		Wi-Fi	802.11b/g/n/ac (Network Version Only)
Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Accessories Included Special Wall Mount, Scheduling Software, Remote Control, Key, User Manual Optional Network Upgrade, Touch Screen Version, Wall Mount, Floor Stand/Trolley, Ceiling Mount, Table Stand Warranty Warranty Warranty Warranty Warranty Warranty		Bluetooth	Bluetooth 4.0
Accessories Included Special Wall Mount, Scheduling Software, Remote Control, Key, User Manual Optional Network Upgrade, Touch Screen Version, Wall Mount, Floor Stand/Trolley, Ceiling Mount, Table Stand Warranty Warranty Warranty Warranty Warranty Warranty		OS	Android 7.1
Accessories Optional Network Upgrade, Touch Screen Version, Wall Mount, Floor Stand/Trolley, Ceiling Mount, Table Stand Warranty Warranty Warranty Warranty Optional Network Upgrade, Touch Screen Version, Wall Mount, Floor Stand/Trolley, Ceiling Mount, Table Stand 3 Year Warranty		Graphic Engine	OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1
Optional Network Upgrade, Touch Screen Version, Wall Mount, Floor Stand/Trolley, Ceiling Mount, Table Stand Warranty Warranty Warranty	· ataa	Included	Special Wall Mount, Scheduling Software, Remote Control, Key, User Manual
Warranty	Accessories	Optional	Network Upgrade, Touch Screen Version, Wall Mount, Floor Stand/Trolley, Ceiling Mount, Table Stand
Technical Support Lifetime	74.F	Warranty Period	3 Year Warranty
	Warranty	Technical Support	Lifetime

Errors and omissions excepted





