

A SOLUTION FOR:

CONTINUOUS PROCESSING



MERROW 70-D3B-2 SPECIFICATIONS OPERATING SPEED: 2250 rpm STANDARD STITCH ECCENTRIC: 6 spi STITCH ECCENTRIC RANGE: 4-12 spi STANDARD NEEDLE: 8SDT **NEEDLE RANGE:** 3SDT - 8SDT STITCH TYPE 501 STITCH WIDTH: 5/8" (16mm) NUMBER OF THREADS

70-D3B-2

BUTTED SEAM MACHINE

The Industry Standard Sewing Machine for End-to-End Seaming of Piece Goods

- Table or Railway Mountable
- Single Thread Machine with Cutters
- Ideal for Seaming Dry Wovens
- Sews a Wide Variety of Materials

- 10 Year Warranty
- Designed and Engineered in the U.S.A.
- Parts and Service Available in 65 Countries
- For More Information Visit www.merrow.com

MERROW has the Widest **Variety of Sewing Machines** for End-to-End Seaming.

Machine produces a flat,

one-thread butted seam (standard configuration).

Machine is designed with a non-differential mechanism for

increasing the stitch count, particularly at selvages.



70



72

Т

STITCH **MULTIPLIER**

ROLL

HIGH PILE

SEAM

-D3B-2

-Y3B-2

HP

Machine creates a gap between the joined ends of the fabric.

Machine creates a rolled seam at

Machine is engineered for use

joined ends of fabric.

on high pile fabric.

machine.

Two-thread locked stitch

2-THREAD

NICKEL

Machine is chemically nickel plated for use in wet and harsh environments; extreme corrosion resistance.

CNP



Machine is designed to be mounted on a railway sewing system.

RAIL

SEWING MACHINE COMPANY

502 BEDFORD STREET FALL RIVER, MA 02720 USA 1001 800.431.6677 WWW.MERROW.COM

Denotes Styles/Options that are INCLUDED on this Model

Denotes Styles/Options that are **AVAILABLE for each Machine Class**