

JK-58450J

Computerized Double Needle Lockstitch Machine

Auto Cornering; Large Space



Suitable for clothing items such as


Umbrella, denim, T-shirt, etc. with chain stitching



Auto corner sewing.



Voice guide, one key to reset.



Built-in presser foot lifter.



One main shaft, stable and fast.

Model	Needle	Stitch Length (mm)	Needle Gauge (mm)	Presser Foot Lifting Height (mm)	Max. Speed (s.p.m)	Application	Function	Auto Corner Sewing	Large Hook	Volume (mm)	Weight (kg)
JK-58420B-003/JK-58420B-005	DP x 5 11-16#/14-22#	4/5	6.4	7-13	3000	A/H	Straight Stitch			725 x 320 x 675	47.5/58
JK-58450B-003/JK-58450B-005	DP x 5 11-16#/14-22#	5	6.4	7-13	3000	A/H	Corner Stitch			725 x 320 x 675	47.5/58
JK-58720B-003/JK-58720B-005	DP x 5 11-16#/14-22#	7	6.4	7-13	3000	A/H	Straight Stitch		√	725 x 320 x 675	47.5/58
JK-58750B-003/JK-58750B-005	DP x 5 11-16#/14-22#	7	6.4	7-13	3000	A/H	Corner Stitch		√	725 x 320 x 675	47.5/58
JK-58420J-403E/JK-58420J-405E	DP x 5 11-16#/14-22#	4/5	6.4	7-13	3000	A/H	Straight Stitch			725 x 320 x 675	53/63
JK-58450J-403E/JK-58450J-405E	DP x 5 11-16#/14-22#	5	6.4	7-13	3000	A/H	Corner Stitch			725 x 320 x 675	53/63
JK-58450J-413E/JK-58450J-415E	DP x 5 11-16#/14-22#	5	6.4	7-13	3000	A/H	Corner Stitch	√		725 x 320 x 675	53/63
JK-58720J-403E/JK-58720J-405E	DP x 5 11-16#/14-22#	7	6.4	7-13	3000	A/H	Straight Stitch		√	725 x 320 x 675	53/63
JK-58750J-403E/JK-58750J-405E	DP x 5 11-16#/14-22#	7	6.4	7-13	3000	A/H	Corner Stitch		√	725 x 320 x 675	53/63
JK-58750J-413E/JK-58750J-415E	DP x 5 11-16#/14-22#	7	6.4	7-13	3000	A/H	Corner Stitch	√	√	725 x 320 x 675	53/63

Note: 1.B is direct drive, Chinese hook is standard, the imported hook can be optional.

2.J is computerized, auto trimmer, auto reverse, auto presser foot lifter, auto wiper are as standard; the electronic thread tension is optional; the suffix is 103E/105E;

3. Optional needle positions for computerized (distance between needles mm): 1/8 (3.2) , 3/16 (4.8) , 1/4 (6.4) , 5/16 (7.9) , 3/8 (9.5) , 1/2 (12.7) , 5/8 (15.9) , 3/4 (19) , 7/8 (22.2) , 1 (25.4) ;

4. Optional needle spacing for direct drive (distance between needles mm):

1/8 (3.2) , 5/32 (4) , 3/16 (4.8) , 1/4 (6.4) , 5/16 (7.9) , 3/8 (9.5) , 7/16 (11.1) , 1/2 (12.7) , 5/8 (15.9) , 3/4 (19) , 7/8 (22.2) , 1 (25.4) , 1-1/4 (31.8) , 1-1/2 (38.1) , 1-5/8 (41.3) , 1-13/16 (46) .