(

Heated Display Merchandiser Assembly Instructions

Step 1

With the back of the unit facing you, un-screw both screws located under the top cover of the unit.





Step 4

Repeat step 3 for the other side glass.



Step 2

Remove the top cover and set aside.



Step 5

Put top cover back on and tighten screws (leave a little loose for fitting the front glass pieces in).





Step 3

Loosen the bottom screws located on the side. Do not take the screws out all the way. Slide the glass between the posts and when properly aligned tighten the screws.





Step 6

Insert the top of the front left glass into the top inner slot. Then place the bottom of the front left glass into the bottom inner slot. If need be, lift up the top cover a bit to fit glass in under. Remember to hold onto side glass pieces so they don't fall out.



Heated Display Merchandiser Assembly Instructions

Step 7

Insert the top of the front right glass into the top outer slot. Then place the bottom of the front left glass into the bottom outer slot. Turn unit around once front glass is in place and with the rear of the unit facing you, put in shelf adjustment bars to desired height. Insert shelves.





Step 8

Insert the top of the rear left glass into the top inner slot.

Then place the bottom of the rear left glass into the bottom inner slot.





Step 9

Insert the top of the rear right glass into the top inner slot. Then place the bottom of the rear right glass into the bottom inner slot. Tighten inside top cover screws.







HDassemblyinstruc_2page.indd 2 3/4/2011 3:10:40 PM