

Application:

- PET felt acoustic panels are designed for internal use in residential and commercial applications.
- The acoustics range is suitable for walls and ceiling covering, in room dividers or custom installations.

Materials:

PET FELT ACOUSTIC FABRICS

- PET Felt is made of recycled PET bottles which are tuned into a soft, sturdy felt material, which is long lasting, UV stabilized and has great acoustic performance.
- PET Felt is both - recycled and recyclable.

FIXING MATERIALS

- PET Felt backside is covered with self-adhesive tape with a synthetic rubber adhesive, a strong polyester carrier and siliconized plastic liner. The tape has an excellent tack and a good adhesive to high and low energy surfaces. The polypropylene liner provides extra strength in applications where the easy and fast peel off of the liner is of importance.

Daily cleaning:

- Use a vacuum cleaner for daily care.
- If there is a stain, it can be safely removed with a sponge and a cleaning agent (soap, detergent cleaner). Afterwards, rinse the panel with water and dry it.




Installation of panels:

- Installation of the panels is very easy, as the back of the panels is covered with strong self-adhesive tape (1).
- Use a level to glue the panels straight on the wall (2).
- After tearing off the tape liner, the panels are glued to a dry, flat surface (3).
- If you need to cut the panels to fit the room, the panels can be easily cut with a knife.



Tools required:



Wall panels

