

REDCAT 7

QUICK START GUIDE



REDCAT 71 QUICK START GUIDE

PARTS



2GT Gear Ring [F]

153 teeth, Diameter 98mm, width 8mm



- A. M48 Dust Cap/Thread
- B. Tilt Adapter
- C. Camera Angle Rotator
- D. Rotator Tension Knob
- E. Saddle Handlebar
- F. Helical Focuser with 2GT Gear Ring
- G. Arca Swiss/Vixen Plate
- H. Mounting Rings
- I. Dew Shield with Focus Tension Ring
- J. Super Bright Bahtinov Mask

Focuser Tension Adjustment [1]

Helical focuser tension can be adjusted using a dew shield which is also a focuser tension ring. To add the tension, you have to turn the dew shield counter clockwise. Focuser cannot be completely locked. Adding too much tension can damage the focuser.

Camera adapter

Remove part [A] M48 Dust Cap from the Redcat, make sure the [D] rotator tension knob is tightened then attach the T-Mount that is compatiable for your Camera or CCD.

Rotator

Loosen Rotator Knob part [D] to set camera to the desired angle. Please make sure the camera mount is tightened prior to this step.

Base Mounting Options

Mounting Plate [G] can be inverted for two types of mount, Arca Swiss or Vixen.

Remove screw on the bottom of the Mounting Ring, flip it over to change mount type, or slide forward/backward to change balance position. The default is Vixen.






REDCAT 71 OPTIONAL ACCESSORIES



Camera Mount

Canon / Nikon / Sony α / Fuji / Pentax / Micro 4/3

Cinematagraphy





Astrophotography



Red Dot Sight



Astro-Multispectra Filter
Astro Duo-Narrowband Filter



M-G50RIII + M-GR50IIRD (optional)

REDCAT 71 SPECIFICATION

· Focal Length: 348mm

Diameter : 71 mm Aperture : f/4.9

· Focuser : Helical Focuser

with 2GT Gear Ring

· Image Circle: >43mm

M102

• **Tube Length** (with dew shield): 435mm

• **Dew Shield Circumference** : 323.4mm

· Dew Shield Diameter : φ103mm





