



FEATURE

- With new digital design.
- With ring-shaped speech indicator light that can show the state of speech. Red light stands for in a speech, green light stands for waiting for a speech.
- The special designed microphone shield can eliminate the "poop-poop" low frequency sound even without using the windproof cotton cover.
- The chairman is unrestricted by microphone modes and number of speakers.
- The chairman unit has full-control priority and can be placed in any position of the loop. The units adopt hand-in-hand cascade connection mode, convenient for installation and maintenance.
- The reelable condenser microphone pole and professional large heart-shaped condenser microphones core make the unit a high sensitivity and intelligibility of the speech.
- The microphone has high and adjustable sensitivity.
- The power of the units is supplied by system host at 24V safe voltage.
- The units are connected by T- shaped 8-core cable.
- With two groups of 3.5mm stereo sound output socket, can be used for record and earphone connection.
- Built-in hi-fi speaker and volume control; with feedback inhibition function. The built-in hi-fi speaker will shut off automatically when the microphone is turned on.
- With discussion/automatic video-tracking function.

Website: www.starviewtech.asia or www.starviewtech.net | Email: sales@starviewint.com | Tell: +65 31575338

SPECIFICATIONS

STARVIEW STM-B06-C, STM-B06A-C		
Model	STM-B06-C	STM-B06A-C
Microphone Type	Heart Shaped Projection Electrets microphone	Heart Shaped Projection Electrets microphone
Frequency Response	80Hz-16KHz	80Hz-16KHz
Microphone Input Impedance	K Ω	K Ω
Sensitivity	-46dBV/Pa	-46dBV/Pa
Max SPL	100dB(THD>3%)	100dB(THD>3%)
S/N Ratio	>80dB	>80dB
Crosstalk	>70dB	>70dB
Dynamic Range	>80dB	>80dB
THD	<0.1%	<0.1%
Max Power Consumption	2W	2W
Earphone Load	8-32 Ω	8-32 Ω
Earphone Volume	40mW maximum	40mW maximum
Earphone Jack	3.5mm mono jack	3.5mm mono jack
Standard	IEC60914	IEC60914
Connector	Built-in 1.8m aviation plug (8 core)	Built-in 1.8m aviation plug (8 core)
Hand-in-hand Extension Port	Provided	Provided
Power Supply Mode	DC24V supplied by the hos	DC24V supplied by the hos
Color	Black	Black
Weight	0.86Kg	0.86Kg
Mic Tube Length	415m/460mm/480mm	415m/460mm/480mm
Dimension	144 x 128 x 62mm	144 x 128 x 62mm
Installation Way	Desktop	Desktop

Corporate offices

STARVIEW TECHNOLOGIES PTE LTD
 Singapore Headquarters
 60 Kaki Bukit Place
 #05-19 Eunos Techpark
 Singapore 415979

Tel: +65 3157 5338
 Fax: +65 3112 8181

Worldwide offices

STARVIEW TECHNOLOGIES VIETNAM
Hanoi Office
 R9, 33th Floor, C2 Building, D'Capitale,
 119 Tran Duy Hung Street,
 Trung Hoa – Cau Giay, Hanoi
Ho Chi Minh Office
 #C9-16, Block A, Sky Center Building,
 #10 Pho Quang Street,
 Tan Binh District, Ho Chi Minh City

Tel: (024) 66661268
 Hotline: 19008695
 Sale Contact: 0866.207.855

Representatives

Brazil
 Tel: +55 11 9-8244-7630

Germany
 Tel: +49 172 946 69 39

France - Benelux - Africa
 Tel: +33 782 702 214

**Southern, Eastern Europe
 & Middle East Operations**
 Tel: +420 602 66 75 66

