

SET UP INSTRUCTIONS

3684 - 40" TRANQUILLITY SPILL FOUNTAIN

3700 - 44" TRANQUILLITY SPILL FOUNTAIN W/ BIRDS

3521 - 25" THREE TIER TRANQUILLITY FOUNTAIN

Open the bag containing the pump kit **P22506.** In the kit you will find:

1 - 40225 (225 gallon per hour pump)

1 - rubber stopper

1 - tube of silicone

1 - 15" long piece of 3/4" clear tubing

1 - 4" long piece of 1" clear tubing

- 1. Place the pedestal on a firm and level area where fountain will remain. Place the largest shell on the pedestal.
- 2. Find the pump, the 3/4" clear tubing 15" long and the rubber stopper. Place pump in the pump house located in the center of the shell. Run the plug end of the electrical cord down the PVC insert located in the pump house and down through the pedestal base. Retrieve cord from under the pedestal and place in the groove in the bottom of the pedestal. Find the tube of silicone. Apply a dab of silicone in the hole that is in the rubber stopper. Slip the rubber stopper onto the power cord about 8" from the pump with the smaller end facing away from the pump. Apply silicone around the inside edge of the PVC insert located in the pump house and around the outside edge of the rubber stopper. Insert the rubber stopper snugly into the PVC pipe. Apply more silicone on top of the rubber stopper and around the power cord. Don't skimp on the silicone you want a watertight seal. Attach the piece of 3/4" clear tubing 15" long to the outlet side of the pump.
- 3. Position the largest shell on the pedestal and level. To level the shell, place the level on the top of the outside rim of the shell. Level in all directions. **Shim if needed.**
- 4. Find the second shell and run the 3/4" clear tubing up thru the PVC insert in the center housing of the shell. Position this shell on top of the pumphouse of the large shell and level as stated in step #3.
- 5. Before you trim the 3/4" clear tubing to length. Push the 3/4" clear tubing back down until the pump is resting on the bottom of the pumphouse. Cut the 3/4" clear tubing 5" above the top surface of the center housing of the second shell.
- 6. Find the third shell and run the 3/4" clear tubing up thru the PVC insert in the center housing of the shell. Position this shell on top of the center housing of the second shell and level in all directions.
- 7. Fountain #3700 44" TRANQUILLITY SPILL FOUNTAIN W/ BIRDS includes a bird finial. Position the bird finial around the center housing of the third shell.
- 7a. Fountain #3521 25" TRANQUILLITY FOUNTAIN includes a plain finial. Position the plain finial around the center housing of the third shell.
- 8. Find the drain plugs and insert them snugly into the drain insert located in the two larger fountain shells. Remove any tape and or dirt from the drain insert before you insert the drain plug.
- 9. Fill each shell with tap water and plug pump into a 110VAC GFCI protected outlet. Adjust water flow to the top shell using the dial type flow control located on the front of the pump until the desired result is achieved. Find the pump house plug and position it in the pump house opening in the large shell.

3684sup 4/4/18 3700sup 4/4/18 3521sup 4/4/18

