



MASSARELLI'S®

MAKERS OF FINE STONE GARDEN ACCENTS

SET UP INSTRUCTIONS

3417 THREE TIER TULIP LEAF FOUNTAIN

3537 78" FOUR TIER SONOMA FOUNTAIN

3523 95" SONOMA FOUNTAIN WITH CHERUB HOLDING GRAPES

3607 78" FOUR TIER HARVEST FOUNTAIN

Open bag containing the pump kit **P460BP**. In the kit you will find:

- | | | |
|---|---|--------------------|
| 1 - 40460 (460 gallon per hour pump) | 1 - 1/2" plastic tee | 1 - rubber stopper |
| 1 - 32" long piece of 1/2" clear tubing | 1 - 1/2" plastic ell | |
| 1 - 20" long piece of 1/2" kink free tubing | 1 - restrictor clamp (not used on these fountains) | |

1. Place pedestal on a firm level surface where fountain will remain. Place a brick under one side of pedestal. This will help you retrieve the power cord from under the pedestal. Place the largest shell on the pedestal.
2. Find the pump, 1/2" clear tubing and the rubber stopper. Attach one end of 1/2" clear tubing 32" long to pump. Place pump in pump house in center of shell and run the plug end of the electrical cord down the PVC pipe located in the pump house and down into the pedestal. Slip the rubber stopper onto the power cord with the smaller end facing away from the pump. Insert the rubber stopper snugly into the PVC pipe. Make sure the pump is seated on the bottom of the pump house. Adjust position of the rubber stopper on the power cord if necessary. Retrieve cord from under pedestal and place in groove in bottom of pedestal. Remove brick from under pedestal.
3. Position the largest shell on pedestal and level. To level shell, place level on top rim of the pump house in the center of shell. Level in (2) Two directions left to right and front to back. **Shim as needed.**
4. Find the second shell and run the 1/2" clear tubing up thru the PVC insert in the center housing of the shell. Position this shell on top of the large shell and level. To level shell, place level on center housing in center of shell. Level as stated in step #3. Cut 1/2" clear tubing 3" below the top surface of the center housing of second shell. Find 1/2" plastic tee and attach an end connection of the tee to the end of the 1/2" clear tubing.
5. Attach the remainder of the 1/2" clear tubing to the middle connection of the 1/2" plastic tee and place tubing in the groove located in the wall of the center housing of the second shell. Cut the 1/2" clear tubing about 1" past the outside wall. Find 1/2" plastic ell and attach it to the 1/2" clear tubing just outside the wall pointing down. Find the 1/2" kink free tubing 20" long and attach it to the opposite end connection of the 1/2" plastic tee located in the center housing of the second shell.

3417 THREE TIER TULIP LEAF FOUNTAIN

3537 78" FOUR TIER SONOMA FOUNTAIN

3607 78" FOUR TIER HARVEST FOUNTAIN

6. Find the third shell and run the 1/2" kink free 20" long tubing up thru the PVC insert in the center housing of the shell. Position this shell on top of the previous shell and level. To level shell, place level on center housing in center of shell. Level as stated in step #3.
Find the finial and remove any excess concrete or tape from both ends of copper pipe in the finial. Attach the piece of 1/2" kink free tubing, located in the center housing of the top shell, to the copper connection on the bottom of the finial. Adjust the length of the 1/2" kink free tubing so finial will sit properly. Position the finial on top of fountain.

3523 95" SONOMA FOUNTAIN WITH CHERUB HOLDING GRAPES

6. Find the third shell. Remove any excess concrete or tape from both ends of copper pipe in the shell. Place the third shell on top of the second shell. Have one person tilt and hold the third shell while another person attaches the piece of 1/2" kink free tubing to the copper connection on the bottom of the third shell. Position the third shell on top of the second shell and level. To level shell, place level on center housing in center of shell. Level as stated in step #3. Position statue on top of the third shell.

7. Find the drain plugs and insert them snugly into the drain insert located in the two larger shells. Fill shells with water and plug pump into a 110VAC GFCI protected outlet. **3400sup 6/26/08**