



MASSARELLI'S®

MAKERS OF FINE STONE GARDEN ACCENTS

SET UP INSTRUCTIONS

3627 50" THREE TIER PICASSO FOUNTAIN 3631 54" MIRABELLA SCALLOP FOUNTAIN

Open bag containing the pump kit **P22502**. In the kit you will find:

- 1 - KING 225 (225 gallon per hour pump)
- 1 - 1/2" plastic tee
- 1 - rubber stopper
- 1 - 1/2" plastic ell
- 1 - hose clamp
- 1 - 36" long piece of 1/2" clear tubing

1. Place pedestal on a firm level surface where fountain will remain. Place the largest shell on the pedestal.
2. Find the pump, 1/2" clear tubing 36" long and the rubber stopper. Attach one end of 1/2" clear tubing 36" long to outlet side of the pump with the hose clamp. Place pump in pump house in center of shell and run the plug end of the electrical cord down the PVC pipe located in the pump house and down into the pedestal. Retrieve cord from under pedestal and place in groove in the bottom of pedestal. Slip the rubber stopper onto the power cord with the smaller end facing away from the pump. Insert the rubber stopper snugly into the PVC pipe. Make sure the pump is seated on the bottom of the pump house. Adjust position of the rubber stopper on the power cord if necessary.
3. Position the largest shell on pedestal and level. To level shell, place level on top rim of the pump house in the center of shell. Level in (2) Two directions left to right and front to back. **Shim as needed.**
4. Find the second shell and run the 1/2" clear tubing up thru the PVC insert in the center housing of the shell. Position this shell on top of the large shell and level. To level shell, place level on center housing in center of shell. Level as stated in step #3.
Cut 1/2" clear tubing 1" below the top surface of the center housing of second shell. Find 1/2" plastic tee and attach an end connection of the tee to the end of the 1/2" clear tubing located in the center housing of the second shell. Make sure the pump is seated on the bottom of the pump house.
5. Attach the remainder of the 1/2" clear tubing to the middle connection of the 1/2" plastic tee and lay the tubing on top of the wall of the center housing of the second shell. Cut the 1/2" clear tubing about 1" past the outside wall. Find 1/2" plastic ell and attach it to the 1/2" clear tubing just outside the wall pointing down.
Find the remainder of 1/2" clear tubing and attach it to the end connection of the 1/2" plastic tee located in the center housing of the second shell.
6. Find the third shell and run the 1/2" clear tubing up thru the PVC insert in the center housing of the shell. Locate the groove in the bottom of the shell and position the groove over top on the 1/2" clear tubing. Position this shell on top of the previous shell and level. To level shell, place level on center housing in center of shell. Level as stated in step #3.
7. Find the finial. In the center of the finial you will see a PVC pipe. Place the finial on the center housing of the third shell along side of the 1/2" clear tubing. **Cut the 1/2" clear tubing one inch shorter than the height of the finial.** Insert the 1/2" clear tubing into the PVC pipe in the bottom on the finial and slide the finial down onto the center housing of the third shell. Find the two drain plugs and insert them snugly into the drain insert located in the two larger shells.
8. Fill shells with water and plug pump into a 110VAC GFCI protected outlet. To adjust the water flow to the finial, unplug the pump and remove the finial from the fountain. Cut the 1/2" clear tubing another 1/2" shorter. This will regulate the water flow from the finial until the desired result is achieved.

3627sup 3/21/09