



AdCoat Direct to Metal DTM Paint

2-Part Epoxy Acrylic Waterbased Coating

Instructions

AdCoat Direct to Metal DTM Paint is a tintable, two-component, waterbased coating which uses a 100% pure epoxy catalyst to ensure an extremely durable, bonded paint finish to metal surfaces.

This versatile product creates a tough, protective coating designed to provide lasting protection for metal items exposed to industrial environments. Ideal for tanks, oil rigs, metal railings, decks, iron work, framing and equipment.

- Direct to metal self priming formula—adheres to a variety of substrates painted and unpainted
- Superior long-term resistance to solvents, chemicals, abrasion and impact
- Safer and easier to use than solvent-based coatings
- Flash rust inhibiting formulation

The addition of acrylic resin provides added durability and makes it ideal for outdoor use. The cured finish easily stands up to the harshest of environments.

While other epoxy coatings fade and chalk when exposed to sunlight and certain interior lighting conditions, this unique formulation allows indoor and outdoor application without these signs of degradation. This same coating has been tested on the North Sea oil rigs and has shown no sign of peeling in over 5 years (and counting).

AdCoat DTM allows application to a variety of interior and exterior surfaces. The cured finish will resist gasoline, oil, transmission fluid, salt water, bleach and many other solvents and chemicals.

AdCoat DTM's two components are easily mixed and applied using standard metal painting methods. The product is available in white and can be ordered in custom colors. It is available in 1 gallon (77801) and 5 gallon (77805) kits..

SURFACE PREPARATION

The type and extent of surface preparation will vary with the nature of the surface, its condition and the type of exposure. The primary purpose of surface preparation is to remove all contaminants that would hinder proper adhesion and to render a sound clean substrate suitable for firm bonding. All surfaces must be clean, dry and free of dust, oil, grease, form releases,

AdCoat Industries

+1-954-916-7315

info@adcoatindustries.com • www.AdCoatIndustries.com

wax, polish, mold, mildew, loose rust scale, loose or peeling paint, salts and other debris or surface contaminants. Clean with a strong detergent or power washer to clean surface. For heavy oil deposits several cleanings may be necessary.

Warning: If you scrape sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and family by contacting the U.S. EPA/Lead Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead

For masonry surfaces: Newly poured concrete and pre-cast concrete floors must be allowed to cure for 60-90 days. Form release agents and laitance must be removed before painting. For smooth trowel concrete and heavy laitance deposits use a concentrated solution of cleaner.

On very smooth concrete: Use a mild etching (citric acid solution) to give substrate additional surface area or 'tooth'. Where vehicular tires will rest, sand the area with medium grit sand paper and clean prior to application.

Previously coated substrates: should have all peeling and scaling paint removed by a mechanical grinder, high pressure washer equipment, or sandblasting. Surface must then be cleaned. Rinse thoroughly and allowed to dry completely before painting.

APPLICATION

Mix Part A with Part B as supplied. Stir thoroughly for at least five minutes by hand or 2 minutes with a drill mixer. The product has a pot life of 6 hours so do not use product after this time.

Apply with a brush, roller or airless paint sprayer (tip size 019-021). Two coats are recommended. For ease of application, up to ½ pint of water per gallon may be added.

Coverage: Dependent upon surface porosity and application method.
First coat - up to 200 sq. ft. per gallon. Second coat - up to 250 sq. ft. per gallon.

Drying Time: Dependant upon weather conditions.
To touch - 2 hours // Dry hard - 12 hours // Vehicular Traffic/ Full Cure - 7 days.

LIMITATIONS:

DO NOT store or apply when surface or air temperature is below 45°F or above 90°F.
DO NOT reuse empty container. Recycle or dispose of material properly.
DO NOT apply if rain is forecasted within 24 hours.
DO NOT thin, add or mix any material with the coating unless approved by manufacturer.
DO NOT paint in direct sun or on hot surfaces that exceed 90°F.

SAFETY INFORMATION SUMMARY:

**KEEP OUT OF REACH OF CHILDREN.
DO NOT TAKE INTERNALLY.
KEEP FROM FREEZING.**

Read the material Safety Data Sheet (MSDS) for this product prior to use. Contain spilled material and remove with inert absorbent. Dispose of contaminate absorbent, container and unused contents in accordance with local, state and federal regulations.

WARNING! MAY CAUSE SKIN OR EYE IRRITATION.

CAUTION! Do not take internally. Avoid contact with eyes and skin. Wear protective clothing, gloves and eyewear. Wash hands after using. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection. Keep container closed when not in use. Do not transfer contents to other containers for storage.

First Aid: In case of contact with eyes and/or skin, flush area with clean water for a minimum of 15 minutes and, if irritation persists, seek medical attention. If ingested, seek medical attention immediately.

LIMITED WARRANTY

AdCoat Industries warrants that this product meets manufacturing specifications. If this product does not meet these specifications, the manufacturer will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. AdCoat Industries will not be responsible for (1) labor or the cost of labor for the removal or application of any product; (2) delivery delays or any costs incurred due to delivery delays.; or (3) any incidental or consequential damages, weather based on breach of expressed or implied warranty, negligence, strict liability, or any other legal theory.

It is our goal to provide our customers with accurate information. To the best of our knowledge, the data contained herein is true and accurate at the date of issuance, but is subject to change without notice. Data reflects information obtained through testing performed at optimum conditions. Actual results may vary.

AdCoat Industries

+1-954-916-7315

info@adcoatindustries.com • www.AdCoatIndustries.com