


Thermotec Open Cell
Backing Rod



Thermotec Open Cell Backing Rod is manufactured from open cell medium density polyurethane foam. The product is manufactured in a range of sizes and has excellent compression and recovery properties.

Material:	Low density polyurethane closed cell foam
Density:	27kg/m ³ nominal
Service Temperature:	-40C to +70C
Tensile Strength:	85KPa
Compression Set:	90%
Resilience:	40% minimum
Tear Resistance:	250 N/m minimum
Flexibility:	Excellent

- Compatible with all leading Sealants
- Available in full range of diameters – 10mm to 50mm
- Eliminates Sealant bubbling
- Round profile enables sealant to form correct profile for optimum movement
- Minimises the amount of sealant required
- Suitable for horizontal and vertical joints, internal walls, and glass applications
- Conforms easily to irregular shaped joints
- Does not discolour or stain
- Non-adhering to sealants
- Made in Australia

	STOCK CODE	Diameter (mm)	No. of coils per Bale	Coil/Length (metre)	Metres per Bale
Open Cell Backing Rod					
	424870010155	10	25	210	5250
	424870016155	16	20	150	3000
	424870022155	22	15	100	1500
	424870029155	29	15	60	900
	424870038155	38	15	30	450
	424870050155	50	15	20	300