

TECHNICAL FACT SHEET



60 Shore D hardness

Tough, with very high tear strength

Very good in short stroke, high cycle applications

High tolerance to shock loads, pressure spikes and vibration

Extremely good extrusion resistance. Will tolerate double the extrusion gap of bronze/ PTFE at the same pressure

Excellent resistance to wear and abrasion. It's the best polyurethane we know of in this respect

Excellent sliding characteristics

Replaces PTFE-based seals in most applications

Easy to fit. Elastomeric quality allows snap-on fit to pistons and snap-in fit to glands. No resizing!

Excellent leakage control, especially compared to PTFE



Brooklyn VIC 3012 03 9314 1620 vicsales@hsa.com.au

MELBOURNE EAST

5/640-680 Geelong Rd, 11/151-159 Princes Hwy, 10/504-508 Victoria St, Hallam VIC 3803 03 8764 0225 hallamsales@hsa.com.au sales@hsa.com.au

Wetherill Park NSW 2164 02 9725 1100

NEWCASTLE

5/10 Enterprise Dr, Beresfield NSW 2322 02 4028 6650 ntlsales@hsa.com.au

BRISBANE

9/27 Selhurst St. Coopers Plains QLD 4108 07 3188 1590 qldsales@hsa.com.au

ROTARY SEALS

5/10 Enterprise Dr, Beresfield NSW 2322 03 9584 3701 sales@rsau.com.au

