

### SAFETY DATA SHEET

This Safety Data Sheet complies with the Canadian Hazardous Products Regulations, the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard, 29 CFR 1910 (OSHA HCS), and the European Union Directives.

### 1 Product and Supplier Identification

1.1 Product: Soak Off

1.2 Product Use: Cosmetic Nail Gel/Acrylic Remover Solution/Solvent

1.3 Producer: Haigh Industries Inc.

#5-8118 North Fraser Way Burnaby BC Canada

**V5J 0E5** 

Telephone: (604) 278-5851

1.4 Supplier: As above

1.5 Emergencies (24-hour number): +1(604) 278-5851

#### 2 Hazards Identification

#### 2.1 Classification of product or mixture

Note to reader: This product in an untested mixture and GHS classification is based on the classification of the ingredients and their concentrations. Proprietary ingredients do NOT exhibit any health effects not listed in this SDS.

GHS Classification: Eye Irritation: Category 2A

Flammable Liquids: Category 2

Specific Target Organ Toxicity - Single Exposure: Category 3

**GHS Label Elements** 

Pictogram:





Signal Word: Warning

#### **GHS Hazard Statements:**

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

#### **GHS Precautionary Statements:**

Prevention:

P210 Keep away from heat, hot surface, sparks, open flames and other ignition

sources. No Smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof equipment. P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray
P264+265 Wash skin thoroughly after handling. Do not touch eyes.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower]

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P337+P317 If eye irritation persists: Get emergency medical help.

P370+P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to

extinguish.

Storage:

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/containers to an approved waste disposal plant.

**2.2 Hazards not otherwise classified (HNOC) or not covered by GHS:** Repeated exposure may cause skin dryness or cracking.

#### 2.3 Additional Information

#### **Primary Routes of Entry:**

Skin Contact: Yes
Skin Absorption: Yes
Eye Contact: Yes
Ingestion: Yes
Inhalation: Yes

#### Effects of Short Term (Acute) Exposure:

**Inhalation:** This product is a mild respiratory irritant. Vapours may cause drowsiness and dizziness.

**Skin Contact:** May cause dry skin or cracking.

**Eye Contact:** This product is an eye irritant. Exposure to the eye may cause symptoms which include a burning sensation, tearing, redness and swelling.

Ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**Medical Conditions Aggravated by Exposure:** Persons susceptible to skin problems may find that the use of this product will cause increased symptoms of existing skin problems.

# 3 Composition

#### 3.1 Mixture Composition

Component	CAS No.	EINECS No.	% (w/w)	GHS Classification
Acetone	67-64-1	200-662-2	80-90	Eye Irritation (Category 2A): H319
				Flammable Liquids (Category 2): H225
				STOT – SE (Category 3) H336
Ethyl Acetate	141-78-8	205-500-4	10-15	Eye Irritation (Category 2A): H319
				Flammable Liquids (Category 2): H225
				STOT – SE (Category 3) H336
Simmondsia Chinensis Seed Oil (Jojoba Oil)	90045-98-0	N/A	1-2	None assigned
Aloe Baradensis Leaf Extract	85507-69-3	287-390-8	1-2	None assigned
Fragrance			0.05	None assigned
Blue 1 – CI 42090	15792-67-3	239-897-0	>0.001	None assigned
Red 28 – CI 45410	18472-87-2	242-355-6	>0.001	None assigned

#### 4 First Aid Measures

#### 4.1 Description of First Aid Measures

**In Case of Eye Contact:** Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 20 to 30 minutes or until the chemical is removed, while holding the eyelid(s) open. Remove contact lenses if present and easy to do so. Seek medical advice.

In Case of Skin Contact: Remove contaminated clothing and shoes. Rinse skin with water/shower.

**If Inhalation:** Remove source of contamination or move victim to fresh air. If breathing is stopped, administer artificial respiration. Consult a physician.

**If Ingestion:** Do NOT induce vomiting. Rinse out mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on left side with head down to prevent aspiration of liquid into lungs. If swallowed, seek medical advice immediately.

# 4.2 Most Important Symptoms and Effects Acute and Delayed Effects of Short-Term (Acute) Exposure:

**Inhalation:** Vapours may cause drowsiness and dizziness. Mild respiratory irritant.

**Skin Contact:** Repeated exposure may cause skin dryness or cracking.

**Eye Contact:** This product is an eye irritant. Exposure to the eye may cause symptoms which include a burning sensation, tearing, redness and swelling.

**Ingestion:** May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Effects of Long-Term (Chronic) Exposure: Repeated exposure may cause skin dryness or cracking,

**Medical Conditions Aggravated by Exposure:** Persons susceptible to skin problems may find that the use of this product will cause increased symptoms of existing skin problems.

# 4.3 Indication of Any Immediate Medical Attention and Special Treatment Needed Treat symptomatically.

# **5 Fire Fighting Measures**

#### 5.1 Extinguishing Media

Suitable extinguishing media: Carbon dioxide (CO2), dry chemical, alcohol resistant foam.

Unsuitable extinguishing media: Do not use a solid water stream as it may spread the fire.

#### 5.2 Special Hazards Arising from Mixture

Highly flammable. May be ignited by open flame. Vapours are heavier than air and may spread along floors. Fire or intense heat may cause violent rupture of packages. The pressure in sealed containers can increase under the influence of heat. Development of hazardous combustion gases or vapours possible in the event of fire.

#### 5.3 Advice for Firefighters

Do not enter fire area without proper protection. Fight fire from a safe distance, upwind. Wear self-contained breathing apparatus and protective suit.

#### 5.4 Further Information

Remove container from danger zone and cool with water. Prevent extinguishing water from contaminating surface water or the ground water system.

Sensitivity to Impact: No

Sensitivity to Static Discharge: Yes

#### 6 Accidental Release Measures

#### 6.1 Personal Precautions, Protective Equipment and Emergency Procedures

Wear suitable protective equipment. Ventilate area. Extinguish any sources of ignition. Avoid breathing mist, vapour, dust, fumes, and spray. Keep people away from and upwind of spill/leak.

#### 6.2 Environmental Precautions

Ensure that any release of this material is contained to prevent leakage into waterways and sanitary sewers.

#### 6.3 Methods and Materials for Containment and Cleanup

**Remedial Measures:** Ventilate the area. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools. Remove all sources of ignition. Evacuate personnel to safe areas. Contaminated absorbent material may pose the same hazards as the spilled product. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

**Large Spills:** For large spills, dike area and prevent leakage into waterways or sanitary sewers. Recover using spark proof equipment and store in approved vented containers for re-use or disposal.

**Small Spills:** Small spills may be absorbed on an inert medium such as vermiculite or clay, then sweep into vented disposal containers.

#### 6.4 Reference to Other Sections

For disposal, see section 13.

# 7 Handling and Storage

#### 7.1 Precautions for Safe Handling

**Handling Procedures:** Wear proper protective equipment when handling this material. Only use non-sparking tools when handling this material. Use only in a well-ventilated area. Avoid breathing vapours. Avoid contact with skin, eyes, and clothing. Keep away from incompatibles. Keep away from heat, sparks, and open flame. No smoking. Keep containers closed when not in use. Empty containers retain residue (liquid and/or vapour) and can be dangerous. Wash thoroughly after handling.

#### 7.2 Conditions for Safe Storage

Store in a cool/well-ventilated place. Inspect periodically for damage or leaks.

#### 7.3 Specific End Use(s)

No other uses except those mentioned in Section 1.2.

### 8 Exposure Controls and Personal Protection

#### 8.1 Control Parameters

**Components with Workplace Control Parameters:** 

Component	Exposure Limits	Basis	Notes
Ethyl Acetate CAS No. 14178-8	400 ppm (1440 mg/m³) (TWA)	Canada, Alberta (OEL)	None
EINECS No. 205-500-4 Attracter	150 ppm (TWA)	Canada British Columbia (OEL)	None
Alliaciei	400 ppm (1440 mg/m³) (TWAEV)	Quebec (Regulation respecting health and safety) Schedule 1	None
		Part 1: Permissible exposure values for airborne contaminates	
	400 ppm (TWA)	USA (TLV)	None
	400 ppm (1400 mg/m <sup>3</sup> ) (TWA)	France (OEL)	None
	400 ppm (1500 mg/m³) (TWA)	Germany (OEL)	Exposure factor 2
	400 ppm (1400 mg/m³) (TWA)	Greece (OEL)	None
	200 mg/m <sup>3</sup> (TWA) 600 mg/m <sup>3</sup> (STEL)	Poland (OEL)	None
	400 ppm (1460 mg/m³) (TWA)	Spain (OEL)	None
Acetone	250 ppm (TWA)	ACGIH	None
CAS No. 67-64-1	500 ppm (STEL)	ACGIH	None
EINECS No. 200-662-2	250 ppm (590 mg/m³) (TWA)	NIOSH REL	None
	1000 ppm (2400 mg/m³) (TWA)	OSHA Z-1	None
	750 ppm (1800 mg/m³) (TWA)	OSHA P0	None
	1000 ppm (2400mg/m³) (STEL)	OSHA P0	None

#### 8.2 Exposure Controls

**Engineering Controls:** Use only in well-ventilated areas. Apply technical measures to comply with the occupational exposure limits. Where reasonably practical this should be achieved using local exhaust ventilation and good general extraction. In case of insufficient ventilation wear suitable respiratory equipment.

**Respiratory Protection:** General and local exhaust ventilation is recommended to maintain vapour exposures below recommended limits. In case of insufficient ventilation or where concentration is unknown, wear suitable respiratory equipment. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.

**Skin Protection:** Depending upon the conditions of use, protective gloves and clothing to prevent skin contact. Wear sufficient clothing to prevent skin contact.

**Eye and Face Protection:** Chemical splash goggles and/or face shield must be worn when a possibility exists for eye contact due to splashing or spraying liquid. Contact lenses should not be worn.

Footwear: No specific recommendation.

**Other:** Emergency eyes wash fountains should be available in vicinity of use. Do not eat drink or smoke when using this product.

**Control of Environmental Exposure:** Prevent further leakage or spillage, if safe to do so. Do not let product enter drains.

## 9 Physical and Chemical Properties

#### 9.1 Information on Basic Physical and Chemical Properties

Appearance:Clear liquidOdour:KetoneOdour Threshold:Not availablepH:Not available

Melting Point/Freezing Point: -94°C (based on ingredients)
Initial Boiling Point: 56°C (based on ingredients)
Flash Point: -18°C (based on ingredients)

Evaporation Rate: 5.6

Upper Flammable Limit:12.8% (based on ingredients)Lower Flammable Limit:2.5% (based on ingredients)

Vapour Pressure: 24.1 kPa @ 20°C (based on ingredients)

Vapour Density: 2.0

Relative Density: 0.791 @ 25°C (water=1)
Solubility: Completely soluble
Partition Coefficient: Log P(oct) = 0.24

**Autoignition Temperature:** 456°C (based on ingredients)

**Decomposition Temperature:** No data **Viscosity:** No data

**Explosive Properties:** May be sensitive to static discharge.

Oxidizing Properties: No data

#### 9.2 Other Safety Information

None

# 10 Stability and Reactivity

#### 10.1 Reactivity

Not normally reactive.

#### 10.2 Chemical Stability

Stable under normal conditions.

#### 10.3 Possibility of Hazardous Reaction

Exothermic reaction with:

Fluorine

Chlorosulfonic Acid Strong Oxidizing Agents Fuming Sulfuric Acid

Risk of explosion with: Lithium Aluminium Hydride

Alkali Metals Hvdrides

Alkaline Earth Metals

Vapours may form explosive mixtures with air

Violent reactions possible with: Strong Acids and Strong Bases

#### 10.4 Conditions to Avoid

Keep away from heat, flame, sparks and other ignition sources.

#### 10.5 Incompatible Materials

Strong oxidizing agents, aluminum, acids, bases, halogenated compounds, acid anhydrides, amines, rubber and various plastics.

#### 10.6 Hazardous Decomposition Products

In the event of a fire, the following can be released: Carbon oxides and other unidentified organic compounds.

## 11 Toxicological Information

#### 11.1 Information on Toxicological Effects

Note to reader: We do not test our products on animals. In compliance with current SDS preparation requirements, the values listed are published values for generic ingredients with known animal toxicity.

#### **Acute Toxicity**

Component	LD <sub>50</sub>	LC <sub>50</sub>
Acetone	5800 mg/kg (oral/rat)	30000 ppm (inhale/rat/4hr)
CAS No. 67-64-1	>15800 mg/kg (dermal/rabbit)	
EINECS No. 200-662-2		
Ethyl Acetate	5620 mg/kg (oral/rat)	19600 ppm (inhale/rat/4hr)
CAS No. 14178-8	>20000 mg/kg (dermal/rabbit)	
EINECS No. 205-500-4		

Abbreviation Key: N/p: not published, N/d: not determined, N/ap: not applicable, N/av: not available.

#### 11.2 Skin Corrosion/Irritation

May cause mild skin irritation.

#### 11.3 Serious Eye Damage/Eye Irritation

Components of this mixture may cause eye irritation, H319, Category 2A, Warning

#### 11.4 Respiratory or Skin Sensitization

May cause mild respiratory or skin irritation. Inhalation may cause headache, pain, nausea, vomiting or other central nervous effects.

#### 11.5 Germ Cell Mutagenicity

Contains no ingredients listed as a mutagen

#### 11.6 Carcinogenicity

Contains no ingredients listed as a carcinogen.

#### 11.7 Reproductive Toxicology

Not expected to have other reproductive effects.

#### 11.8 Specific Target Organ Toxicity – Single Exposure

Components of this mixture may cause drowsiness or dizziness, H336, Category 3, Warning

#### 11.9 Specific Target Organ Toxicity – Repeated Exposure

May cause skin dryness or cracking.

#### 11.10 Aspiration Hazard

No information available.

#### 11.11 Additional Information

None

# **12 Ecological Information**

# 12.1 Toxicity

	T	0	F	is	r

Acetone	LC <sub>50</sub>	96H	6210-8120 mg/L (Fathead Minnow)
Ethyl Acetate	LC <sub>50</sub>	96H	230 mg/L (Fathead Minnow)

#### To Algae:

Acetone	No data available		
Ethyl Acetate	NOEC	72H	>100 mg/L (Green Algae)

#### To Daphina:

Acetone	EC <sub>50</sub>	48H	12600-12700 mg/L
Ethyl Acetate	No data available		

#### 12.2 Persistence and Degradability

This product has not been tested. Acetone and Ethyl Acetate are considered readily biodegradable.

#### 12.3 Bio accumulative Potential

No data available

#### 12.4 Mobility in Soil

No data available

#### 12.5 Results of PBT and vPvB Assessment

Not conducted

#### 12.6 Other Adverse Effects

No data available

# 13 Disposal Considerations

#### 13.1 Waste Treatment Methods

**Product:** Review federal, provincial or state, and local government requirements prior to disposal. Store material for disposal as indicated in Storage Conditions. Disposal by controlled incineration or by secure land fill may be acceptable.

Contaminated Packaging: Dispose as above.

# **14 Transport Information**

#### Transport of Dangerous Goods (TDG and CLR):

UN Number	UN1993
UN Proper Shipping Name	FLAMMABLE LIQUID, N.O.S. (Acetone, Ethyl
	Acetate)
UN Transport Hazard Class(es)	3
Packing Group	II
Labels	3

#### International Air Transport Association (IATA):

UN Number	UN1993
UN Proper Shipping Name	FLAMMABLE LIQUID, N.O.S. (Acetone, Ethyl
	Acetate)
UN Transport Hazard Class(es)	3
Packing Group	II

Labels	3
Additional Information	Refer to the appropriate Packing Instruction, prior
	to shipping this material. Review all State and
	Operator Variations, prior to shipping this material.

**International Maritime Organization (IMO):** 

UN Number	UN1993
UN Proper Shipping Name	FLAMMABLE LIQUID, N.O.S. (Acetone, Ethyl
	Acetate)
UN Transport Hazard Class(es)	3
Packing Group	II
Labels	3
Additional Information	May be shipped as LIMITED QUANTITY when
	transported in containers no larger than 1.0 Litre, in
	packages not exceeding 30 kg gross mass.

## 15 Regulatory Information

15.1 CANADIAN FEDERAL REGULATIONS
CEPA, DOMESTIC SUBSTANCES LIST: Listed

15.2 UNITED STATES FEDERAL REGULATIONS
TOXIC SUBSTANCES CONTROL ACT (TSCA): All components are listed in the inventory.

California Proposition 65: No ingredients listed.

OSHA (29 CFR 1910 Subpart Z): Meets criteria for a hazardous substance.

CERCLA (40 CFR 302): No ingredients listed.

SARA 302 (40 CFR 355): No ingredients listed.

SARA 313 (40 CFR 372): No ingredients listed

SARA 311/312 (40 CFR 370): Flammable, serious eye damage or irritation, specific target organ toxicity

(single or repeated exposure)

Massachusetts Right to Know: Acetone

New Jersey Right to Know: Acetone

Pennsylvania Right to Know: Acetone

#### **16 Other Information**

Original Preparation Date: April 22, 2022

Prepared By: Haigh Industries Inc.

#5-8118 North Fraser Way

Burnaby BC Canada V5J 0E5

**Disclaimer:** This Safety Data Sheet (SDS) was prepared using information provided by ingredient supplier SDS and other relevant sources. This product has been classified using weight of evidence, expert judgment

#### Soak Off

and previous testing as per Part 1.3 of the Fifth Edition of The Globally Harmonized System of Classification and Labelling of Chemicals (GHS). The information in this SDS is offered for your consideration and guidance when exposed to this product. Haigh Industries Inc. expressly disclaims all expressed or implied warranties and assumes no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of Haigh Industries Inc.

Revisions: None