



L151824330

LED Ba15d Tube T18x45mm 10-24V 250Lm
3W 3000K 830 360° DC Clear Non-Dimmable

Marine & Industry, Tubular VR 10-24V



General		Energy		
Eprel registration no	1113043	Operating voltage	24 V	
Socket	Ba15d	Volt	10..24 V	
Bulb shape	T18	Frequency	50 Hz	
Width	18.00 mm	Watt	2.5..3 W	
Depth	18.00 mm	Current type	DC	
Height	45.00 mm	Power factor	1	
Finish	Clear	Energy efficiency class	G	
Colour	Colourless	Energy consumption	3 W	
Body material	Polycarbonat	Replacement wattage	25 W	
Lifespan	30000 hours	Lamp efficacy	83.33	
Switches	50000	LED		
Beam angle	360 °	Filament LED	No	
Dimmable	No	LED type	SMD 2835	
Degree of protection	IP20	Dimm type	Non-Dim	
Net weight	0.020 kg	Number of leds / sticks	24	
Warranty	2 years	Colour consistency SDCM	SDCM3	
Light		Dim to warm	No	
Kelvin	2900..3100 K	Adjustable beam angle	No	
Colour temp nr	829..831	Ordering details		
Stable lumen	250 lm	L151824330	Quantity pc(s)	EAN
Color Rendering Index (CRI)	80	Single package	1	8718739066502
		Inner carton	10	18718739066509
		Outer carton	100	28718739066506