



DISCLAIMER: We are not liable if you injure yourself while installing a Luimoto seat cover. Remember, **Safety First**, and to always wear your eye protection. To successfully install a Luimoto seat cover, it requires patience. This instruction sheet is meant only as a guide; there may be alternatives that may suit you better (**to have you install your seat cover with the best knowledge**). We strongly recommend working with another person and if you ever have any doubts, we recommend that you visit your local upholstery shop for installation.

For video demonstration please visit www.luimoto.com/video

Before you begin, please have these ready:

- eye protection
- a partner to help (recommended)
- staple gun and staples (6mm, 1/4")
- needle-nose pliers
- flat-head screwdriver
- clips




WE ARE ONLY HUMAN

For those who have little or no experience with the staple gun, you may find it difficult, or even frustrating at times. We know how it is, we've been there, but we have to start somewhere. The plastic on the seat pan is tough, and unless you have an air operated, or electrically operated staple gun, it will take force. Be patient and you will see that it's not bad at all!

BEFORE YOU BEGIN

You have a choice of either leaving your stock cover on or taking it off. To remove the cover, simply use a flat head screw-driver and get underneath the staple and loosen it with a twisting motion. Use needle nose pliers to remove the staple.



PLEASE REMOVE ANY HARDWARE THAT MAY GET IN THE WAY OF YOUR SEAT COVER INSTALL.

Please note: diagrams on the next page are only used as a general reference. Your seat may not look the same.

IF YOUR SEAT COVER IS MADE WITH: **SYNTHETIC SUEDE**

Before installing your suede seat cover you must install the plastic sheet.

The plastic sheet acts as a moisture barrier between the Suede and Foam.

If you decide to leave your OEM cover on, you do not have to install the plastic sheet.

Step 1. Remove OEM seat cover if applicable. (refer to Seat Cover Installation Instructions - BEFORE YOU BEGIN)

Step 2. (Optional) Apply spray glue on your seat.

Step 3. Carefully place the plastic sheet over your seat foam. Avoid wrinkling of the sheet. If there are difficult curves, you may use a blow dryer or heat gun to soften the sheet to mold better around curves.

Step 4. The plastic sheet should wrap around your seat. You may apply a small amount of adhesive along the bottom to secure the plastic sheet.

Step 5. Trim off any excess plastic.

Step 6. You may now proceed to the next instruction sheet for the seat cover install.

Luimoto Synthetic Suede Care Instructions

- * Use a soft nylon bristled brush to quickly remove dust off suede.
- * Wash your bike like you usually would with mild soap and water.
- * Soak up excess water with chamoise or sponge as soon as possible and allow 15 minutes of air drying under the sun.
- * It is normal to experience wrinkling in the fabric when wet. When it has dried, the suede will settle back into it's normal state.
- * Do not allow the suede to stay wet for long periods as water can seep into the foam.
- * Do not allow suede to sit under the sun all year round uncovered, the color may fade.
- * Following these steps should ensure long life of your Luimoto suede seat cover.


MARINE GRADE VINYL

Clean with mild soap and water. For stubborn stains you may try using a soft nylon bristle brush.



*IF APPLICABLE, REMOVE STRAP BEFORE BEGINNING

1. Slip the seat cover on over the seat. Be sure the arch of the seat cover matches up with the edge at the front of the seat. Place a clip at the front.



2. Pull the seat cover towards the rear, and again check to see if everything lines up. If so, staple a few staples at the rear of the seat.



3. Remove the clip at the front and staple along the front but do not staple the corners yet.



4. On one corner, grab the material and stretch it over to the underside. Staple it down keeping the material stretched. Once complete go to the other side and repeat the step.

5. Stretch the material on the side and clip it. Stretch the opposite side and staple along the sides. Go back to the other side, remove the clip and staple.




6. At the rear corners stretch and 'ruffle' the material, then staple.



FOLLOW US


Post your experience, check out cool bikes and updates!

luimotoproducts



<https://www.facebook.com/luimotoproducts/>

@luimoto



<https://www.instagram.com/luimoto/>