

Product MOSS-OAK ABS MD 55 PCT TEC LMR

Print Date 20.12.2023 Page 1 (6)

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name : MOSS-OAK ABS MD 55 PCT TEC LMR

 Sales Number
 : 00134823

 SDS Number
 : 300000469905

Use of the Substance/Mixture : Fragrance for consumer product

Company : IFF LMR Naturals

Parc Industriel Les Bois de Grasse 18-20 avenue Joseph Honoré Isnard

06130 Grasse

Telephone : +33492424344 Emergency telephone number : +33 3 8073 7878

2. HAZARDS IDENTIFICATION

GHS-Classification

Skin sensitisation, Category 1

GHS-Labelling

Symbol(s)

Signal word : Warning

Hazard statements : H317: May cause an allergic skin reaction.

Precautionary statements : P261: Avoid breathing dust.

P272: Contaminated work clothing should not be allowed out of the

workplace.

P280: Wear protective gloves.

P302 + P352: IF ON SKIN: Wash with plenty of water.

P333 + P317: If skin irritation or rash occurs: Get medical help.

P501: Dispose of contents/ container to an approved waste disposal

plant.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name of the substance : Evernia prunastri, ext.

Chemical characterization : absolutes

Molecular formula : UVCB

Molecular weight : 120.00 g/mol

CAS-No. : 90028-68-5, 68917-10-2

Version : 4

Revision Date : 12.06.2023



Product MOSS-OAK ABS MD 55 PCT TEC LMR

Print Date 20.12.2023 Page 2 (6)

4. FIRST AID MEASURES

Inhalation : Remove from exposure site to fresh air and keep at rest. If victim is

unconscious, remove foreign bodies from the mouth. If victim has stopped breathing, give artificial respiration. Obtain medical advice.

Skin contact : Remove contaminated clothes. Wash thoroughly with water (and

soap). Contact physician if symptoms persist.

Eye contact : Flush immediately with water for at least 15 minutes. Contact

physician if symptoms persist.

Ingestion : Rinse mouth with water and obtain medical advice.

Workplace facilities required : Where appropriate, use closed systems to transfer and process this

material.

If appropriate, isolate mixing rooms and other areas where this material is used or openly handled. Maintain these areas under

negative air pressure relative to the rest of the plant.

Notes to physician

Risks : May cause an allergic skin reaction.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Carbondioxide, dry chemical, foam.

Special protective equipment for

firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Avoid inhalation and contact with skin and eyes. A self-contained

breathing apparatus is recommended in case of a major spill.

Environmental precautions : Keep away from drains, surface- and groundwater and soil.

Methods for cleaning up : Clean up spillage promptly. Remove ignition sources. Provide

adequate ventilation or exhaust. Avoid excessive inhalation of dust and vapours. Contain and recover free product. Dispose of according

to the local regulations.

7. HANDLING AND STORAGE

Handling

Version : 4

Revision Date : 12.06.2023



Product MOSS-OAK ABS MD 55 PCT TEC LMR

Print Date 20.12.2023 Page 3 (6)

Advice on safe handling

: Avoid excessive inhalation of concentrated vapors. Follow good manufacturing practices for housekeeping and personal hygiene. Wash any exposed skin immediately after any chemical contact, before breaks and meals, and at the end of each work period. Contaminated clothing and shoes should be thoroughly cleaned before re-use.

If appropriate, procedures used during the handling of this material should also be used when cleaning equipment or removing residual chemicals from tanks or other containers, especially when steam or hot water is used, as this may increase vapor concentrations in the workplace air. Where chemicals are openly handled, access should be restricted to properly trained employees.

Keep all heated processes at the lowest necessary temperature in order to minimize emissions of volatile chemicals into the air.

Advice on protection against fire and explosion

Advice on protection against fire and : Keep away from ignition sources and naked flame.

Storage

Requirements for storage areas and containers

Store in a cool, dry, ventilated area away from heat sources. Keep containers upright and tightly closed when not in use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Verify if the substances declared in section 3 have relevant national exposure limits.

Appropriate engineering controls

Where appropriate, use closed systems to transfer and process this material.

If appropriate, isolate mixing rooms and other areas where this material is used or openly handled. Maintain these areas under negative air pressure relative to the rest of the plant.

Personal protective equipment

Respiratory protection

: Use local exhaust ventilation around open tanks and other open sources of potential exposures in order to avoid excessive inhalation, including places where this material is openly weighed or measured. In addition, use general dilution ventilation of the work area to eliminate or reduce possible worker exposures.

No respiratory protection is required during normal operations in a workplace where engineering controls such as adequate ventilation,

etc. are sufficient.

If engineering controls and safe work practices are not sufficient, an approved, properly fitted respirator with organic vapor cartridges or canisters and particulate filters should be used:

Version : 4

Revision Date : 12.06.2023



Product MOSS-OAK ABS MD 55 PCT TEC LMR

Print Date 20.12.2023 Page 4 (6)

a) while engineering controls and appropriate safe work practices

and/or procedures are being implemented; or

b)during short term maintenance procedures when engineering controls are not in normal operation or are not sufficient; or c)if normal operational workplace vapor concentration in the air is

increased due to heat; d)during emergencies; or

e)if engineering controls and operational practices are not sufficient to reduce airborne concentrations below an established occupational

exposure limit.

Hand protection : Avoid skin contact. Use chemically resistant gloves.

Eye/face protection : Use tight-fitting goggles, face shield or safety glasses with side

shields if eye contact might occur.

Skin and body protection : Choose body protection in relation to its type, to the concentration

and amount of dangerous substances, and to the specific work-place.

Protective measures : To the extent deemed appropriate, implement pre-placement and

regularly scheduled ascertainment of symptoms and spirometry testing of lung function for workers who are regularly exposed to

this material.

To the extent deemed appropriate, use an experienced air sampling expert to identify and measure volatile chemicals that could be present in the workplace air to determine potential exposures and to ensure the continuing effectiveness of engineering controls and

operational practices to minimize exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state : solid

Colour : orange to red

Odour : conforms to standard

Safety data

Flash point : > 110.00 °C

Vapour pressure : Note: Not applicable

10. STABILITY AND REACTIVITY

Conditions to avoid : Remarks: Direct sources of heat.

Hazardous decomposition products : Note: Carbon monoxide and unidentified organic compounds may

be formed during combustion.

Version : 4

Revision Date : 12.06.2023



Product MOSS-OAK ABS MD 55 PCT TEC LMR

Print Date 20.12.2023 Page 5 (6)

Hazardous reactions : Presents no significant reactivity hazard, by itself or in contact with

water. Avoid contact with strong acids, alkali or oxidizing agents.

Presents no significant reactivity hazard, by itself or in contact with

water.

11. TOXICOLOGICAL INFORMATION

Skin irritation : Skin irritation (, Guinea pig, 6 h, 12.% in diethyl phthalate)

12. ECOLOGICAL INFORMATION

Ecotoxicity effects

13. DISPOSAL CONSIDERATIONS

Product : Disposal together with normal waste is not allowed. Special disposal

required according to local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site

for recycling or disposal.

14. TRANSPORT INFORMATION

IATA

Not dangerous goods

IMDG

Not dangerous goods

15. REGULATORY INFORMATION

HMIS Classification : Health hazard: 2

Chronic Health Hazard: /

Flammability: 1

Physical and chemical hazards: 0

16. OTHER INFORMATION

Further information

In December 2003, the National Institute for Occupational Safety and Health ("NIOSH") published an Alert on preventing lung disease in workers who use or make flavorings [NIOSH Publication Number 2004-110]. In August 2004, the United States Flavor and Extract Manufacturers Association (FEMA) issued a report entitled "Respiratory Safety in the Flavor Manufacturing Workplace".

Version : 4

Revision Date : 12.06.2023



Product MOSS-OAK ABS MD 55 PCT TEC LMR

Print Date 20.12.2023 Page 6 (6)

Both of these reports provide recommendations for reducing employee exposure and for medical surveillance in the workplace. The recommendations in these reports are generally applicable to the use of any chemical in the workplace and you are strongly urged to review both of these reports.

The report published by FEMA also contains a list of "high priority" chemicals. If any of these chemicals are present in this product at a concentration >= 1.0% due to an intentional addition by IFF, the chemical(s) will be identified in this safety data sheet.

The information in this safety data sheet is based on the properties of the material known to IFF at the time the data sheet was issued. The safety data sheet is intended to provide information for a health and safety assessment of the material and the circumstances under which it is packaged, stored or applied in the workplace. For such a safety assessment International Flavors & Fragrances holds no responsibility. This document is not intended for quality assurance purposes.

Version : 4

Revision Date : 12.06.2023

Telephone: +33492424344 Telefax: +33493704326