















# Cord Operated Curtain Track Systems




# Application Chart

Dimension	Applications				Profile		Features / Options			Fitting Options			Fitting Surfaces		System			
	Weight Range	Single Stack	Pair Stack	Multiple Stack	Heavy Duty	Profile Number	Dimensions in mm	Min. Bending Radius (mm)	2C Gliders / Rollers	Smart Fix	Wave	Ceiling Fitting	Wall Fitting	Direct Fixing		Recess Fitting (Recess Profile)	Wood	Concrete
 kg	●	●	●			1082		100	●			●	●			●	●	3000
 kg	●	●	●			3841		200	●	●	●	●	●			●	●	3840
 kg	●	●	●			11190		260	●	●	●	●	●	●		●	●	3870
 kg	●	●	●	●		3982		200	●			●	●			●	●	3900
 kg	●	●	●	●		3971		250	●	●	●	●	●	●		●	●	3970
 kg	●	●	●	●		6371		500	●	●		●	●	●		●	●	6370

 kg Light-weight applications

 kg Medium-weight applications

 kg Heavy-duty applications



[www.silentgliss.co.uk](http://www.silentgliss.co.uk)

[www.silentglissglobal.com](http://www.silentglissglobal.com)

Silent Gliss Ltd  
Pyramid Business Park  
Poorhole Lane  
Broadstairs  
Kent  
CT10 2PT  
Great Britain

Tel: +44 (0) 1843 863571  
Fax: +44 (0) 1843 864503  
[info@silentgliss.co.uk](mailto:info@silentgliss.co.uk)

Silent Gliss Global Ltd  
Pyramid Business Park  
Poorhole Lane  
Broadstairs  
Kent  
CT10 2PT  
Great Britain

Tel: +44 (0) 1843 874250  
Fax: +44 (0) 1843 874457  
[info@silentglissglobal.com](mailto:info@silentglissglobal.com)