

# Juliet Travers

WALLPAPERS AND FABRICS

---

## Hanging Instructions

### IMPORTANT

**Before hanging check that rolls are undamaged, that numbers and letters are the same for each roll of this design and that all colours match.**

Please retain all batch labels until decorating is complete. Return any defective roll with its label to where it was purchased.

Take extra care when papering around electric light switches and power points. Do not allow excess moisture to drip onto electrical contacts.

### PREPARATION

Prepare walls by removing all traces of dirt, old wallpaper, distemper or loose paint. Roughen any painted surfaces with sandpaper. Ensure that the overall wall colour is a light, neutral colour with no obvious contrasting areas. Do not hang wall coverings on any wall with a history of damp. Fill any cracks and allow to dry before hanging. Absorbent surfaces can be sized with a weak solution of wallcovering adhesive following the manufacturers instructions.

### PASTE

**Please ensure that the same adhesive is used to hang both the lining paper and the wallcovering.**

**For optimum results use a high quality pre-mixed adhesive and follow manufacture's instructions.**

We strongly recommend that you use a water-soluble, starch based paste and with a relatively low water content. Generally cellulose based, self-mix or very fluid adhesives should be avoided.

Recommended paste types:

- Halls Beeline Ready Mixed Vinyl Adhesive (sold in tubs with a yellow lid)
- Albany Ready Mixed (sold in tubs with a yellow lid)
- Light Grade Ready Mixed Adhesive (sold in tubs with a black lid)

### LINING

All walls should be cross-lined with a plain white heavy grade paper lining paper. In the UK a suitable lining paper would be classified as "1000" or "1200" grade.

Lining paper should be allowed to dry completely before installing any Juliet Travers Ltd wallpapers.

### HANGING

The wall covering is pre-trimmed so it is not necessary to trim on site and the wall covering can be installed directly from the roll.

Always install a wall from left to right and continue around the room accordingly. Please take note of the repeat measurements so you allow for trimming.

**Evenly apply the adhesive directly onto the wall** using a brush or a short pile emulsion roller. It is not necessary to pre-cut the lengths of paper as it can be applied direct from the roll. Apply the wallcovering to the wall and smooth down with a good quality hanging brush or plastic spatula, working from the centre to the edges to remove any unwanted bubbles. Do not overlap and use butt joints.

**Carefully wipe off excess paste immediately with a clean damp sponge. Failure to do so may result in serious damage to the surface.**

After hanging 2 or 3 lengths inspect the result to ensure that there is no shading or other faults. **No claim for hanging costs will be allowed for goods hung in excess of one roll.**

## CLEANING YOUR WALLPAPER

If your wallpaper gets marked in any way, all Juliet Travers wallpapers are 'spongeable' which means you are able to gently wipe the effected area with a damp cloth. Please be careful when attempting to clean the wallpaper. Do not apply too much water to the cloth and do not wipe too vigorously otherwise you will damage the product. Juliet Travers Ltd wallpapers are not washable so if a damp cloth is unable to remove the dirt, the wallpaper should be left as it is and no further cleaning should be attempted.