



DUCKHOOK CUSTOMS

(262) 515-1817

DUCKHOOKCUSTOMS.COM

CONTACT@DUCKHOOKCUSTOMS.COM

INSTALLATION INSTRUCTIONS

1. REMOVE ALL PREVIOUS GRIP TAPE FROM SHAFT

2. MEASURE WHERE ON THE SHAFT THAT THE GRIP SHOULD "STOP". LINE UP THE DENSE CORK AT THE TOP WITH THE BUTT OF THE SHAFT, THEN END YOUR TAPE JUST BEFORE THE END OF THE GRIP IT MAY BE TOUGH TO TELL WHEN THE GRIP IS ON ALL THE WAY, SO THIS WILL LET YOU KNOW WHEN TO STOP PUSHING. LINE UP THE DENSE CORK AT THE TOP WITH THE BUTT OF THE SHAFT, THEN END YOUR TAPE JUST BEFORE THE END OF THE GRIP. (SEE PICS)

3. APPLY NEW GRIP TAPE SO IT RANGES FROM 0.580-0.600" THICK WITH ~1" OF OVERHANG TO TWIST AND TUCK INTO THE BUTT OF THE SHAFT.

NOTE: FOR SUSTAINABILITY PURPOSES, WE DO NOT USE ANY RUBBER ON OUR GRIP. IT IS IMPORTANT TO HAVE THE PROPER AMOUNT OF TAPE AT THE END TO FILL IN THE GAP (SEE PICS)

4. APPLY GRIP SOLVENT DIRECTLY TO SHAFT ONLY. THERE IS NO NEED TO FILL THE GRIP WITH SOLVENT.

NOTE: SOLVENT COULD AFFECT PAINT AND FINISH, SO HORIZONTAL CLAMPING IS RECOMMENDED

5. SLOWLY SLIDE THE GRIP OVER THE SHAFT UNTIL YOUR MEASURED OUT TAPE DISAPPEARS. DO NOT GO TOO FAST. THIS GRIP IS TIPPED WITH EXTRA DENSE CORK FOR DURABILITY, BUT AS WITH ANY GRIP, THE SHAFT COULD DAMAGE THE END IF SLID TOO QUICKLY.

6. CLEAN ANY EXCESS SOLVENT OR GRIP TAPE RESIDUE



CORRECT



INCORRECT





DUCKHOOK CUSTOMS

(262) 515-1817

DUCKHOOKCUSTOMS.COM

CONTACT@DUCKHOOKCUSTOMS.COM

THANK YOU FOR YOUR PURCHASE OF DUCKHOOK
CUSTOMS .38 SPECIAL CORK GRIP!

FOR MORE INFORMATION

CHECK OUT DUCKHOOKCUSTOM.COM FOR OUR WIDE VARIETY
OF CUSTOMIZATIONS. SEND IN YOUR CLUB OR CHOOSE FROM
OUR READY-TO-PLAY OPTIONS & ACCESSORIES.



FOLLOW US!

NEED INSPIRATION TO CUSTOMIZE YOUR PUTTER? CHECK US
OUT ON INSTAGRAM FOR ALL THE NEW THINGS WE ARE
DESIGNING



USE PROMO CODE: DUCK10 FOR 10% OFF
YOUR NEXT PURCHASE

**DUCKHOOK WAS FOUNDED BY THREE FRIENDS WITH THE INTENTION OF BRINGING
TOGETHER THE TRADITION & PASSION OF GOLF & THE GREAT OUTDOORS, WITH
NONE OF THE PRETENSION**