## Technical Specification

# CVOFIRE

### Madini – Gas Burner Tray

Index # 109, Rev-4 / 24-May-2019

#### **DESCRIPTION**

The Madini (drop in) gas burner with either Logs or Pebbles and has a flange for easy use in custom fireplace designs. The fire is operated by an RF Remote System with a handset, the remote is programmable and includes a thermostat to control room temperature, the remote system is battery powered.

The Madini is supplied with either a log or pebble set.

#### **CE APPROVAL**

The Madini is CE approved for I2H, I2E, I2E+ and is available for all European Countries using this gas type.

#### POWER RATING

Natural Gas Only – Heat Input on High 4.9kW, Heat Input on Low 2.4kW Approximate running costs per hour on high (subject to supplier tariff) 22p/hour.

#### **DIMENSIONS**

Please see page 2 for technical drawings and dimensions.

#### OTHER TECHNICAL INFORMATION

- 1. The Standard opening size for the Madini is 840mm (wide) x 250mm (height) with a minimum depth of 306mm. The burner must be positioned at the back of the enclosure and centrally positioned under the gather. If a non-standard enclosure, that does not comply with the CE approval then a flue specialist must be consulted to ensure that the final design is safe, and spillage cannot occur.
- 2. The fire is approved with a minimum flue diameter of 125mm, or minimum area of 125cm2.
- 3. The fire is CE approved with a minimum flue height of 2 metres from the top of the gather spigot.
- 4. A standard gather can be supplied as an optional extra with the fire and it is strongly advised to purchase the gather with the fire. Using a gather will reduce the possibility of debris falling into the



fire from the chimney stack and will help to reduce the draw when using a larger or longer flue system than the minimum allowed. This will also preserve some of the heat and increase the efficiency of the fire.

- 5. Remote system, the Madini is operated by a battery remote system that has 3x AA batteries within the body of the fire. The fire is operated by an RF handset which is programmable and includes a thermostat to control the room temperature.
- 6. An allowance is required around the burner tray for expansion under operation and adjustment.

CVO reserve the right to amend and improve the specification sheets without prior notice. If in doubt about any aspect of this specification, please call. The specification is not to be used to install the fireplace. Every fire is supplied with an official install booklet. Spirit Fires Limited own the Spirit, CVO and Firevault Trademarks. Copying and distribution of these specifications is not permitted without the permission of Spirit Fires Ltd.


All dimensions include a +/-2mm tolerance.

Spirit Fires Ltd, 4 Beaumont Square, Durham Way South, Newton Aycliffe, County Durham, DL5 6XN Sales: +44 (0)1325-301020 Office: +44 (0) 1325 327 221 Fax: +(0)1325 327 292 Email: sales@cvo.co.uk Web: www.cvo.co.uk




## Madini - Gas Burner Tray

Index # 109, Rev-4 / 24-May-2019



THE BURNER IS DESIGNED
TO BE DROPPED INTO AN
OPENING. THE GAS INLET IS
ON THE RIGHT HAND SIDE AT
THE BACK OR THE SIDE.
THERE IS AN OPTION TO BUY
A FIRE GRATE TO MAKE THE
BURNER FREE STANDING.
DUE TO MANUFACTURING
TOLERANCES NO WORK IS
TO COMMENCE UNTIL THE
BURNER UNIT IS ON SITE.



CVO reserve the right to amend and improve the specification sheets without prior notice. If in doubt about any aspect of this specification, please call. The specification is not to be used to install the fireplace. Every fire is supplied with an official install booklet. Spirit Fires Limited own the Spirit, CVO and Firevault Trademarks. Copying and distribution of these specifications is not permitted without the permission of Spirit Fires Ltd.

All dimensions include a +/-2mm tolerance.

Spirit Fires Ltd, 4 Beaumont Square, Durham Way South, Newton Aycliffe, County Durham, DL5 6XN Sales: +44 (0)1325-301020 Office: +44 (0) 1325 327 221 Fax: +(0)1325 327 292 Email: sales@cvo.co.uk Web: www.cvo.co.uk