

# BAT

## Interior Surface Mounted *Dual Power Tri-CCT* Batten Lights




- Input voltage: 220-240V
- Driver inbuilt
- Material: steel & PC
- Tri-CCT (3000K/ 4000K/ 5700K) in one fitting
- CCT switch inside the fitting
- Power factor: 0.9
- Ambient temperature: -20 to 40°C
- Not suitable for dimming
- Suitable for 2-way switching
- Suitable for use with 3 wire sensor
- **Large terminal block for easy installation**




**EASY FOR INSTALLATION**

 30,000hr Lifetime	 110° Beam Angle	<b>IP20</b> Rated	<b>3YEAR</b> Replacement Warranty
--	--	----------------------	---



**BAT001**



**BAT002**



**BACK PLATE**

Part No.	Description	Lumens						Dimensions	Box Weight	Box Dimensions	Carton Qty
		3000K		4000K		5700K					
<b>BAT001</b>	Batten LED S/M 10W/20W WH Tri L620mm	10W	20W	10W	20W	10W	20W	620x70x65 mm	1.0kg	62x7x8cm	1/9
		900lm	1800lm	1100lm	2200lm	1000lm	2000lm				
<b>BAT002</b>	Batten LED S/M 20W/40W WH Tri L1220mm	20W	40W	20W	40W	20W	40W	1220x70x65 mm	1.5kg	123x7x8cm	1/9
		1800lm	3600lm	2200lm	4400lm	2000lm	4000lm				