

Bimetal Thermometers, Every Angle

Crimped-on ring case stainless steel, turnable and adjustable

TBiGelChg 5"

TBiGelChgG 5"

Standard Versions

These thermometers are manufactured according to ASME B40.200, especially concerning the accuracy and the temperature ranges. Further information on selection and metrological features (e.g. temperature resistance) can be found in model overview 8000.

Measuring Unit

Bimetal coil

Accuracy (ASME B40.200)

Grade A $\pm 1\%$ of the measuring range

Case

With polished crimped-on ring, stainless steel 304

Degree of Protection (DIN EN 60 529/IEC 529)

IP65

Case Filling

For model TBiGelChgG

Temperature ranges:

from 0 °F up to +210 °F: glycerin

from -40 °F and above +210 °F up to +480 °F: silicone oil



Nominal Case Size

5"

Case Configuration

Connection temperature

sensor (stem):

pivot (every angle)

- adjustable approx. 135°

(90° downward, 45° upward)

- with straightened brackets turnable by 360° with respect to the case

Pivot joint:

centre back position

Temperature Ranges (ASME B40.200)

Spans from 110 °F to 900 °F

Measuring range = indication range

Temperature Sensor (Stem)

Made of stainless steel 316Ti

Max. static operating pressure: 25 bar

Stem models: B1 or B4.1

Stem Ø dF: $\frac{1}{4}$ " (6.35 mm), $\frac{5}{16}$ " (8 mm) or

$\frac{3}{8}$ " (9.52 mm)

Stem length L: from Lmin up to 16" (400 mm)

Please regard the minimum stem length depending on the active length (La) and stem model, see page 2

Window

Instrument glass

Dial

Aluminum white, scale black

Pointer

Aluminum black

Indication Adjustment ($\pm 4\%$)

Externally via screw

Ordering Information, Standard Ranges, Options

See page 3

Special Versions and Further Options

- Other stem models, connection threads and materials upon request
- Other temperature ranges and/or special scales, e.g. dual scale °C/°F, coloured fields or ranges, dial inscriptions
- Case parts stainless steel 316L (1.4404) upon request
- TBiGelChg, TBiGelChgG for ambient temperatures to -76 °F

Stem Models, Dimensional Data and Weights

Stem Models

		B1	B4.1									
Process connection	without screw fitting, plain stem	male thread, rigid										
		<table border="1"> <thead> <tr> <th>G</th> <th>SW</th> <th>i</th> </tr> </thead> <tbody> <tr> <td>1/2" NPT</td> <td>1.07"</td> <td>0.75"</td> </tr> <tr> <td>3/4" NPT</td> <td>1.07"</td> <td>0.75"</td> </tr> </tbody> </table>	G	SW	i	1/2" NPT	1.07"	0.75"	3/4" NPT	1.07"	0.75"	
G	SW	i										
1/2" NPT	1.07"	0.75"										
3/4" NPT	1.07"	0.75"										

Dimensional Data (inch) and Weights (lb)

NCS	b1	D	D1	d6	d7	f1	f3	s4	(approx.) weight ¹⁾	TBiGelChg 5"	TBiGelChgG 5"
5"	0.8	5.35	4.92	0.47	0.55	2.36	1.46	0.32	1.08	1.43	

Minimum Stem Length and Active Length

Stem model:	Length:	Thread:	Stem Ø dF:						
			1/4" (6.35 mm)			5/16" (7.94 mm)			
			Span (temperature difference) ΔT ²⁾						
all models	La	—	≥ 180 °F	= 150 °F	= 110 °F	≥ 150 °F	= 110 °F	all	
B1	Lmin	—	1.6"	2.4"	2.8"	1.6"	2.4"	2.2"	
B4.1	Lmin	1/2" NPT; 3/4" NPT	2.35"	3.15"	3.55"	2.35"	3.15"	3.0"	
others				upon request					

The minimum length **Lmin** is the smallest feasible stem length.

Important: Please note the technical information sheet T08-000-031 on the metrologically optimal stem length.

The active length **La** is the temperature-sensitive part of the stem.

¹⁾ The data are examples and relate to the version with stem B1, Ø dF 5/16", L=3.94".

²⁾ The temperature difference ΔT = 150 °F corresponds e.g. to the temperature range 0–150 °F but also -30/+120 °F, see table page 3.

Ordering Information

Basic Model:	Bimetal Thermometer Every Angle	TBiGeIChg
Case filling:	depending on version glycerin or silicone oil	G
Nominal case size:	case Ø 5"	5"
Stem position / case configuration:	centre back position, with pivot (every angle)	without code letters
Temperature ranges:	scale: 0 – 150 °F ΔT (°F): 150 0 – 200 °F 200 0 – 250 °F 250 0 – 300 °F 300 -50 / +130 °F 180 -40 / +160 °F 200 -30 / +120 °F 150 -10 / +100 °F 110 +20 / +240 °F 220 +30 / +140 °F 110 +40 / +400 °F 360 +50 / +300 °F 250 +50 / +500 °F 450 +80 / +800 °F 720 +150 / +700 °F 550	e.g. 0–250 °F e.g. -30/+120 °F
Stem:	without screw fitting, plain stem male thread, rigid	B1 B4.1
Stem Ø dF:	1/4", 5/16", 3/8"	dF = 1/4"
Stem length:	L in "	e.g. L = 10"
Process connection:	1/2" NPT or 3/4" NPT	e.g. 1/4" NPT
Options:	red mark plastic clip window case polished case filling temperature ranges from 0 °F to 210 °F: silicone oil stem length > 16" (400 mm), max. 32" (800 mm) instrument tag	on the dial red or green, external at crimped-on ring tempered safety glass stainless steel plate 12x55 mm (0.47x2.17") with wire mounting or sticker upon the case
Example:	TBiGeIChg 5", -30/+120 °F, B4.1, dF = 3/8", L = 10", 1/2" NPT	
Special Versions:	Please describe your requirements in cleartext!	