

WHEELED
SERIES **955**



SPECIFICATIONS

Interior dimensions	L22.0" × W17.0" × H10.2" L559mm × W432mm × H259mm
Exterior dimensions	L25.6" × W20.0" × H11.8" L650mm × W508mm × H300mm
Weight (empty)	18.40 lb 8.16 kg
Lid depth	2.1" 53mm
Base depth	8.1" 206mm
Max buoyancy	TBD
Temperature range	Min -20°F (-29°C) Max 140°F (60°C)
Airline cabin carry-on	No
Waterproof (IP67)	Yes
Warranty	Conditional lifetime guarantee

CERTIFICATIONS



IPX7 INGRESS PROTECTION - WATERPROOF



IP6X INGRESS PROTECTION - DUSTPROOF



ATA SPECIFICATION 300 - CATEGORY 1 IMPACT



ASTM D-4169 DC-18 - DROP TEST



ASTM D-4169 DC-18 - VIBRATION



ASTM D-4169 DC-18 - RAINFALL



MIL-STD-810F - IMMERSION

MATERIALS

Case shell – NK-7 high impact polypropylene

Latches – Nylon 66

Handle – NK-7 high impact polypropylene | TPE

Purge valve – Nylon 66 | Gore® membrane | Silicone washers

Pins/hardware – 304 stainless steel

Gasket – EPDM

Backing plate – NK-7 high impact polypropylene

Pull handle – Polycarbonate + ABS | Nylon | TPE

Wheels – Polyurethane | Polycarbonate

STANDARD FEATURES

- 1 - Powerclaw latching system
- 2 - Waterproof IP67 rated
- 3 - Impact resistant NK-7 resin
- 4 - Reinforced metal padlock holes
- 5 - Stackable
- 6 - 2-stage retractable handle
- 7 - Polyurethane wheels
- 8 - Side mounted spring loaded handles
- 9 - Automatic pressure release valve
- 10 - Integrated lid stay
- 11 - Removable lid
- 12 - Top and bottom panel mount
- 13 - 100% stainless steel hardware
- 14 - Lifetime guarantee



AVAILABLE COLORS



AVAILABLE OPTIONS



CUSTOM OPTIONS

