

## Wood burning heater Harvia Linear 22 GreenFlame ES

WKLI22GESM

*An elegant wood-burning stove for medium-sized saunas, Harvia Linear 22 GreenFlame ensures a clean and stable fire behind a large glass door, which creates a relaxing atmosphere in the sauna. You can now bathe with lower emissions than ever before.*

### Advantages

- Linear GreenFlame is a wood-burning stove with a large glass door and advanced combustion technology to ensure a clean burn and long service life.
- 20% lower particulate emissions and 70% lower carbon monoxide emissions.
- 90% larger glass door.
- The matte black colour and elegant design create a modern look in the sauna.
- Heat your bathwater efficiently with the Harvia Linear GreenFlame water tank models. The positioning of the water tank varies by model, ensuring that you can select the best solution for your sauna.  
ES, water tank at the front  
LS, water tank on the left side  
RS, water tank on the right side



### Features

Main material : Steel

H x W x D : 770.0 x 450.0 x 660.0 mm

Net weight (kg) : 60.4

Stone amount (kg) : 40.0

ID	GTIN	Power	Sauna room size min - max m3
WKLI22GESM	6417659029674	15.7 kW	9.0-18.0

## Spare parts

Product	ID	Pcs
Ashpan ES/SL	Z2ES-125	1
Furnace grate	ZKIP-10	1
Connection pipe	ZKIP-130	1
	ZROST-618	1

## Technical details

Technical data	Type / attribute	WKLI22GESM
	Color	Black
	Power output	15.7 kW
	Stone sizes	10-15 cm
	Stone amount (kg)	40
	Firewood max. Length in combustion chamber	390
Dimensions	Product width (mm)	450
	Product height (mm)	770
	Product depth (mm)	660
	Net weight (kg)	60.4
	Gross weight	63.1
	Package width	510
	Package height	790
	Package depth	750
	Water container volume (l)	20
Connections	Flue connection locations	Back, Top
	Chimney connection diameter	115
Safety and installation dimensions	Safety distance front (non-combustible materials)	500
	Safety distance front (combustible materials)	500
	Safety distance right side (combustible materials)	400
	Safety distance right side non-combustible materials	100
	Safety distance left side (combustible materials)	400
	Safety distance left side non-combustible materials	100
	Safety distance behind (non-combustible materials)	100
	Safety distance behind (combustible materials)	380
	Safety distance (Ceiling) (depends on connections and therefore from output, star/delta)	1265
Room min. height(depends on connections and therefore from output, star/delta)	2100	