



Part Number	IF-WFH3002
Dimensions	L - 4.0" x W - 4.0" x H - 1.25"
Software	V.0.0.25
Input Voltage	5VDC 50/60 Hz +/- 15%
Current Draw	100ma(standby)
Operating temperature	0-50c (32F to 122F)
Storage Temperature	0-65C (32F to 150F)
Start Up Scan Cycle	2 minutes
Bluetooth Broadcast Range	10m/30f (Line of Sight)
Communications Protocol	Bluetooth 4.0 LE / WiFi B/G/N 2.4ghz
Connection	USB Type C
Warranty	24 months RTB
Transmit Power 802.11b Average	+19dbm
Transmit Power 802.11n Average	+16dbm



## WiFi | Bluetooth Hub



### Dual Communication

Industry designed hub for safe and secure communication between smart bluetooth modules and remotes.



### Plug n Play

Easy to setup!. Just plug it in and connect to your network and you are all set. Customizable command control for each OEM or distributor.



### Data Diagnostics

Monitor usage, troubleshooting, models, serial numbers etc with optional data portal. Market directly to your customer with new products and features.



### Industry Built

Control your smart modules and remote controls from anywhere around the world with the WiFi | Bluetooth Hub.



### Cross Platform Compatibility

The WiFi Bluetooth hub works with all Flame-Flame-Tec and i-Flame smart products.



### Voice Control

The WiFi Bluetooth hub works with Alexa and Google Home\*.

Coming Soon.