## **TOTO**<sub>®</sub>

# ABF626N

### Aimes<sup>®</sup> Freestanding Bathtub

#### FEATURES

- 71-1/2" x 36-3/16" x 23-11/16"
- Luxuriously deep bathing well
- Cast-acrylic construction provides high durability
- Slip-resistant surface
- Drain with various finishes
- 2 Pillows

#### COLORS/FINISHES

- Shell Color #01 Cotton
- Drain #CP Polished Chrome #BN Brushed Nickel #PN Polished Nickel
- Pillows Neutral White



#### PRODUCT SPECIFICATION

The Aimes Freestanding Bathtub shall be 71-1/2" in length, 36-3/16" in width and 23-11/16" in height. Bath shall be free standing with drain. Bath shall have a slip-resistant surface and acrylic construction. Bath shall be TOTO Model ABF626N\_\_\_\_\_.

#### CODES/STANDARDS

- Meets and exceeds ANSI Z124.1.2, CSA B45
- Certifications: IAPMO(cUPC), State of Massachusetts, City of Los Angeles and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others
- Complies with CA Prop 65 warning requirements



#### Aimes<sup>®</sup> Freestanding Bathtub

#### **SPECIFICATIONS**

•	Size	71-1/2"L x 36-3/16"W x
•	Depth	23-11/16"H 19"
•	Water Depth	15.3″
•	Warranty	1 Year Limited Warranty on acrylic tub
		1 Year Limited Warranty
•	Material	on components and parts Cast Acrylic construction
٠	Shipping Weight	395 lbs.
٠	Shipping Dimensions	78"L x 48"W x 31"H
	<b>•</b> "	<b>a</b> a (1

- Gallons •
- 88 to overflow

#### **INSTALLATION NOTES**

Floor support under bath must provide a minimum of 75 lbs/square foot (366 kg/square meter) loading.

Check local codes for requirements on installing an ASSE 1070/ASME A112. 1070/CSA B125.70 compliant device in series with the tub faucet.

