

Technical Data Sheet

COBBLE STRIP

Paint Stripper



Characteristics & Technical Data

| | |
|------------|--------------------|
| Appearance | Amber Liquid |
| WT./Gal | 8.5 lbs. |
| Coverage: | 75 to 100 SqFt/Gal |

4. Properties & Special Features

- Commercial grade formulation.
- Easy to rinse.
- Eco friendly.
- Biodegradable.

5. Directions

Preparations: Before applying **Cobble Strip**, ensure all areas not being stripped are fully protected. Ensure all surfaces are dry prior to stripping. Water will deactivate the stripping action.

Applications: Stir the product thoroughly before use. **Cobble Strip** should be applied directly from the container using a roller, or sprayer.

Apply a liberal amount of Cobble Strip to the surface requiring stripping. Work **Cobble Strip** into grooved areas.

Allow **Cobble Strip** to stand for a minimum of 30 minutes. Weather conditions, type of coating being removed, and coating thickness will determine how long **Cobble Strip** must dwell for stripping action to develop.

After softening of paint film begins and film starts to wrinkle, or blister begin to pressure wash the coating off of the substrate. Water will deactivate the stripper. When removing the stripper with water, ensure that rinse water does not contact areas that have not yet been stripped.

Do NOT allow **Cobble Strip** to dry prior to removing it. When stripping large areas, it is recommended to divide into smaller sections and strip one section at a time rather than attempting to strip the entire project.

1. Manufacturer

SurfaceLogix – a Reliance Supply Company
1880 NW 18th Street
Pompano Beach, FL 33069

Phone: 954.971.9111
Fax: 954.971.6623
Email: support@surfacelogix.net
www.surfacelogix.net

2. Product Description

Cobble Strip is an eco-friendly low odor paint stripper designed to remove various types of coatings. **Cobble Strip** performs by penetrating and softening the paint film. **Cobble Strip** will remove most sealers, paints, and concrete stains, both solvent and water based.

Cobble Strip is designed to be used on horizontal concrete and natural stones substrates and will not harm the substrate.

3. Applications

Horizontal Brick Pavers
Natural Stone
Concrete



Cleaners & Chemicals: COBBLE CLEAN, 125-1g, 125-5g

Technical Data Sheet

COBBLE STRIP

Paint Stripper

6. Packaging

| Size | Package | Per Case | Units / Pallet |
|----------|---------|----------|----------------|
| 1 gallon | Can | 4 | 180 |
| 5 gallon | Pail | N/A | 36 |

9 pounds per 1 gallon pail, 45 pounds per 5 gallon pail

7. Coverage

DO NOT DILUTE

General Application:

1 gallon covers 50 to 100 sq. feet

8. Curing Information

Cobble Strip should not be left to dry on the surface.

9. Storage & Shelf Life

Product must be kept in its original, unopened and tightly sealed container. Store in a dry and well ventilated place with controlled temperature (40°F to 90°F). Keep sheltered from weather and direct sunlight. In proper storage conditions, the product's shelf life is 12 months following production (see date on packaging). Store product in original container and close lid tightly after each use.

10. Maintenance

Cobble strip will remove most sealers, paints, and concrete stains, both solvent and water based. It is designed to be used on horizontal concrete and natural stones substrates and will not harm the environment or substrate.

11. Shipping

Land & Sea: Not Regulated

Packing Group: III

Flash Point: 135°F

12. Clean Up

Clean tools with soap and water.

13. Health Hazard Information

Health Hazards:

Eyes: Irritation

Skin: Prolonged or repeated exposure may cause irritation.

Inhalation: Irritation of the upper respiratory system.

Indigestion: May result in abdominal discomfort, nausea, and diarrhea.
distress.

Precautions:

Respiratory Protection: None required. Wear NIOSH approved respirator if occupational exposure level exceeds limits.

Clothing: Wash clothing after use.

Gloves: Wear protective gloves to avoid possible skin irritation.

Eye Protection: Wear safety goggles. Protect plastic lenses.

Other Precautions: Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Will harm aquatic life.

14. Technical Support

For friendly, knowledgeable and courteous technical support please call 954.971.9111.

You may also reach us by sending a query from our website at www.surfacelogix.net.

15. Disclaimer

All SurfaceLogix products are manufactured with the finest raw materials. It is the applicator's responsibility to determine the appropriate use of the product.

All recommendations and suggestions are made without guarantee, since conditions of use are beyond our control.