

## COBBLE COLORS

### Color Tints for Concrete and Pavers



#### Characteristics & Technical Data

% Solids by Weight (+/- 3%):	30%
Gardner Gloss @ 60	NA
Flash point:	>93°C
WT./Gal	8.34 lbs.
Coverage:	It depends on the sealer used @ 3mil DFT
pH:	6-9
Clean Up:	Water
VOCs:	0 G/L

#### 4. Properties & Special Features

- Eco friendly
- Exceptional miscibility in water and sealers
- Great stability in solution
- Available in 5 standard colors: BRICK RED, CAMEL TAN, CHARCOAL, TERRA COTTA, VALLEY BROWN
- Custom colors available in earth tones for an additional fee
- Easy clean up with water

#### 5. Directions

**Before you begin:** Surfaces must be clean and free of any contaminants before sealing. The Sealers' performance is directly related to how thoroughly the surfaced is prepared. All grease, oil and potential contaminants must be removed. Cobble Clean and Cobble Prep may be used for specific cleaning situations.

**Preparation:** When adding Cobble Color to the sealer, the sealer should be already diluted if that is required for the application. 3 oz of Cobble Colors will color 1 gal of ready to apply sealer.

**Applications:** For example, 6 oz of Cobble Colors will be required to be added to the entire two gal dilution of Cobble Loc kit when mixed with water and ready to use. See back for dilutions directions. Do not apply with rollers.

**Sprayer:** Airless sprayer is recommended. Always maintain a wet edge.

**On bare surface:** One and sometimes two thin coats (2 dry mils) provide the best results on uncoated surfaces.  
**Over previously sealed:** 1 coat is recommended.

**Cleaning Tools:** Use soap and water.

#### 1. Manufacturer

**SurfaceLogix – a Reliance Supply Company**  
 1880 NW 18th Street  
 Pompano Beach, FL 33069

Phone: 954.971.9111

Fax: 954.971.6623

Email: support@surfacelogix.net  
 surfacelogix.net

#### 2. Product Description

Cobble Colors is a semi-transparent color additive (Tint) designed for use in properly prepared water based sealers. All surface preparation should be done according to the SurfaceLogix surface cleaning and preparation instructions located on the Sealers' container and technical data sheet. Cobble Colors comes in 5 colors to suit most colored surfaces.

#### 3. Applications

- Use blended in Clear Sealers like Cobble Coat H2O and Cobble Coat H2O Wet, Roof Clear, or our Cobble Loc.
- Use on driveways, walkways, parking decks, patios and pool decks or roofs, where you want to improve or enhance the color of the surface.
- Can be used diluted in water to check desired color intensity before applying sealer.

Decorative: COBBLE COLORS, 30 oz bottle

## Technical Data Sheet

# COBBLE COLORS

## Color Tints for Concrete and Pavers



### 6. Packaging

SIZE	PACKAGE
1 x 30 OZ	Plastic Bottle with dispensing -measuring attachment

### 7. Coverage

Coverage will depend on method of application, and will depend on the sealer used. Second coat will usually take slightly less product. 1 x 30 oz bottle could tint up to 100 gallon sealer at around 10% strength; see chart on label.

### 8. Curing Information

See the label or TDS for the sealer used, to determine curing times; Cobble Colors will not have a noticeable effect in the length of cure time.

### 9. Storage & Shelf Life

Product must be kept in its original, unopened and tightly sealed container, and stored in a dry and well ventilated place with controlled temperature (50°F to 90°F). Keep sheltered from weather and direct sunlight. In proper storage conditions, the product's shelf life is 24 months following production (see date on packaging or Invoice). Store product in original container and close lid tightly after each use.

### 10. Maintenance

Use water to clean or dilute Cobble Colors. In case of stains, Cobble Clean is recommended for cleaning or cleaning of tools. Follow Cobble Clean instructions for dilution ratios.

### 11. Shipping

Land and Sea: NOT REGULATED  
Packing Group: N/A  
Flash Point: NA

### 12. Clean Up

Clean sprayer and application tools with water. Use Cobble Clean is necessary.

### 13. Health Hazard Information

Follow the sealers' use precautions.

**Eye Contact:** Wear Eye Protection. Avoid contact with eyes. May irritate eyes. If in eyes, flush with water for at least 15 minutes.

**Inhalation:** Use a NIOSH approved respirator. Use with adequate ventilation.

**Ingestion:** If swallowed, DO NOT induce vomiting. Seek medical attention.

**Skin:** Avoid prolonged contact with skin.

### 14. Technical Support

For friendly, knowledgeable and courteous technical support please call 954.971.9111.

You may also reach us by sending a query from our website at [www.surfaceLogix.net](http://www.surfaceLogix.net).

### 15. Disclaimer

All SurfaceLogix products are manufactured with the finest raw materials. It is the applicator's responsibility to determine the appropriate use of the product. Do not use in any way not recommended by SurfaceLogix.

All recommendations and suggestions are made without guarantee, since conditions of use are beyond our control.

### 16. Dilution Chart

<b>CLEAR SEALER</b>	<b>10-GAL RTU ADDITIONS:</b>
<b>COLOR STRENGTH</b>	<b>Cobble Colors</b>
100%	30 oz.
50%	15 oz.
10%	3 oz.
<b>CLEAR SEALER</b>	<b>5-GAL RTU ADDITIONS:</b>
<b>COLOR STRENGTH</b>	<b>Cobble Colors</b>
100%	15 oz.
50%	7.5 oz.
10%	1.5 oz.
<b>CLEAR SEALER</b>	<b>2-GAL RTU ADDITIONS:</b>
<b>COLOR STRENGTH</b>	<b>Cobble Colors</b>
100%	6 oz.
50%	3 oz.
≈10%	0.5 oz.