

## Product Application Guidelines

Note: The table below should be used as a guide for application purposes. SurfaceLogix always recommends the application of a test area to determine product compatibility, adhesion, and desired result for end user. **Prep surfaces before sealing.**

	Cobble Coat & High Solids	Cobble Loc & Matte	Same Day Sealer	Cobble Coat H2O Wet	Cobble Coat H2O	Cobble Grip	Cobble Impregnator (NS)	Cobble Impregnator (CP)	Cobble Enhancer	Coloron	Colorcrete	TD One Step	Texture Deck	Roof Clear	Roof Loc
<i>Pavers over concrete</i>							•	•	•						
<i>Pavers over sand</i>	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
<b>SUBSTRATE</b>															
Concrete Pavers	•	•	•	•	•	•		•	•	•	•				
Clay Pavers/Chicago Brick							•								
Natural Stone	•	•	•	•	•	•	•	•	•	•					
Travertine	●	●	•	●	•	•	•	•		•					
Concrete Roof Tiles		•		•	•	•	•	•						•	•
Clay Roof Tiles							•	•							
Asphalt Shingles														•	•
Porous Concrete	•	•			•	•	•			•	•		•	•	
Asphalt											•		•		
Mexican Tiles															
Flagstone							•	•							
Artistic Pavers/Shellrock	●	●	•	●	●	•	•	•	•						
<b>FEATURES</b>															
Film Forming	•	•	•	•	•	•				•	•		•	•	•
Breathable							•	•	•						
Damp Apply		•	•												•
Water Based		•	•	•	•	•	•	•			•		•	•	•
Solvent Based	•									•	•				

● Can only be applied with Non-Skid