

COLORCRETE

Solid Color Stain for Concrete



Characteristics & Technical Data

% Solids by Weight (+/- 3%):	48%
Gardner Gloss @ 60	75
WT./Gal	10 lbs.
Coverage:	250-300 SqFt/Gal @ 3mil DFT
Clean Up:	Water
VOCs:	115 G/L

4. Properties & Special Features

- Eco friendly
- Exceptional durability
- Abrasion resistance
- Water resistance
- Available in 30 standard colors
- Custom colors available in earth tones for an additional fee
- Easy clean up with water

5. Directions

Before you begin: Surfaces must be clean and free of any contaminants before sealing. Colorcrete's performance is directly related to how thoroughly the surface is prepared. All grease, oil and potential contaminants must be removed. Cobble Clean and Cobble Prep may be used for specific cleaning situations.

Preparation: Stir product. Concrete should cure a minimum of 28 days before sealing. Read label instructions carefully. Smooth concrete must be etched.

Two thin coats(2 dry mils) provide the best results. Do not apply when the temperature of the air or the surface to be coated is below 50F. Testing the product on your surface is always recommended to ensure desired results.

Applications

Roller: Smaller surfaces can be applied with a 3/8" to 3/4" nap roller cover. Apply in slow passes. Avoid over rolling and maintain a wet edge.

Sprayer: Airless sprayer is recommended. Always maintain a wet edge.

On bare surface: One and sometimes two thin coats (2 dry mils) provide the best results on uncoated surfaces.

Over previously sealed: 1 coat is recommended.

Cleaning Tools: Use soap and water.

1. Manufacturer

SurfaceLogix – a Reliance Supply Company

1880 NW 18th Street
Pompano Beach, FL 33069

Phone: 954.971.9111

Fax: 954.971.6623

Email: support@surfacelogix.net
surfacelogix.net

2. Product Description

Colorcrete Sealer is a unique blend of 100% waterborne acrylic resins that provide exceptional durability, abrasion resistance, and water resistance.

Colorcrete Sealer will leave a hard, satin film, protecting interior and exterior concrete surfaces, SurfaceLogix Texture Deck Systems and aged asphalt. Easy clean up with water.

3. Applications

- Concrete driveways, walkways, parking decks, patios and pool decks
- Top coat for Texture Deck Systems
- Top coat for aged asphalt

Colorcrete is not recommended for pavers installed over a solid surface or on surfaces where moisture is unable to dissipate.

surfaceLogix

CHEMISTRY THAT PROTECTS YOUR WORLD

Decorative : **Colorcrete**, 110-1g, 110-5g

Technical Data Sheet

COLORCRETE

Solid Color Stain for Concrete



6. Packaging

Size	Package	Per Case	Units / Pallet
1 gallon	Pail	4	148
5 gallon	Pail	N/A	36

9 pounds per 1 gallon pail, 50 pounds per 5 gallon pail

7. Coverage

1 gal. covers 250 to 300 square feet per coat. Coverage will depend on method of application. Second coat will take slightly less product.

8. Curing Information

Dry to touch: 30 minutes
Recoat: 3 to 4 hours
Full cure: 48 hours

9. Storage & Shelf Life

Product must be kept in its original, unopened and tightly sealed container, and stored in a dry and well ventilated place with controlled temperature (50°F to 90°F). Keep sheltered from weather and direct sunlight. In proper storage conditions, the product's shelf life is 12 months following production (see date on packaging). Store product in original container and close lid tightly after each use.

10. Maintenance

Cobble Clean is recommended for routine cleaning. Follow Cobble Clean instructions for dilution ratios.

11. Shipping

Land and sea: NOT REGULATED
Packing Group: III
Flash Point: NA

12. Clean Up

Clean sprayer and application tools with water.

13. Health Hazard Information

Eye Contact: Wear Eye Protection. May irritate eyes. If in eyes, flush with water for at least 15 minutes.

Inhalation: Use a NIOSH approved respirator.

Ingestion: If swallowed, DO NOT induce vomiting. Seek medical attention.

Skin: Avoid prolonged contact with skin.

Use with adequate ventilation.

14. Technical Support

For friendly, knowledgeable and courteous technical support please call 954.971.9111.

You may also reach us by sending a query from our website at www.surfaceLogix.net.

15. Disclaimer

All SurfaceLogix products are manufactured with the finest raw materials. It is the applicator's responsibility to determine the appropriate use of the product.

All recommendations and suggestions are made without guarantee, since conditions of use are beyond our control.