

COBBLE ENHANCER

Enhanced Appearance, No Sheen



Characteristics & Technical Data

% Solids by Weight:	30%
WT./Gal:	6.6
Coverage:	200 to 2000 SqFt/Gal
VOCs:	>600 G/L

4. Properties & Special Features

- Easy to apply
- Breathable
- Enhanced appearance
- Stain & oil repellant
- Revitalizes color

5. Directions

Before You Begin: Surfaces must be clean, dry and free of any contaminants before sealing. Cobble Enhancer's performance is directly related to how thoroughly the surface is prepared. All grease, oil and potential contaminants must be removed. Do not apply when the temperature of the air or the surface to be coated is below 50°F. Testing on your surface is always recommended to ensure desired results.

Surface Preparation: Concrete should cure a minimum of 28 days before sealing. Read label instructions carefully. Cobble Clean, Cobble Prep and Cobble Oxhide may be used for specific cleaning situations.

Mixing Instructions: Stir product.

Application

Roller: Apply with a lambs wool or microfiber cloth, working the material into the surface.

Airless Sprayer: Spray by overlapping each pass. Always apply in an even film deposit and maintain a working wet line. Remove any excess material after 3-5 minutes.

On Bare Surface: Apply to the surface and allow to penetrate for 3-5 minutes, remove any excess. Do not allow any excess or pooling to dry on the surface.

Over Previously Sealed: Film forming sealers will need to be stripped prior to application. Cobble Enhancer may be applied over non film forming sealers provided the prior application is sufficiently worn away.

1. Manufacturer

SurfaceLogix – a Reliance Supply Company
1880 NW 18th Street
Pompano Beach, FL 33069

Phone: 954.971.9111

Fax: 954.971.6623

Email: support@surfacelogix.net

www.surfacelogix.net

2. Product Description

Cobble Enhancer is an odorless mineral spirits, penetrating breathable sealer. Cobble Enhancer is designed to protect and beautify natural stone, travertine, interlocking concrete pavers & concrete floors. Cobble Enhancer forms a wet look breathable barrier that is resistant to moisture retention, stains & oil.

3. Applications

Use Cobble Enhancer on driveways, patios, pool decks, parking lots, walkways, etc. constructed of:

Natural Stone • Concrete Pavers • Concrete

surfacelogix

CHEMISTRY THAT PROTECTS YOUR WORLD

Clear Sealers: **COBBLE ENHANCER**, 133-1g, 133-5g

Technical Data Sheet

COBBLE ENHANCER

Enhanced Appearance, No Sheen



5. Directions (Continued)

Note: Excess or puddled sealer must be removed from the surface before it dries. This timing will depend on temperature and exposure.

6. Packaging

Size	Package	Per Case	Units / Pallet
1 gallon	Pail	4	148
5 gallon	Pail	N/A	36

8 pounds per 1 gallon pail, 45 pounds per 5 gallon pail

7. Coverage

1 gallon covers 200 to 2000 square feet per coat. Coverage will depend on surface porosity, joint width, and method of application.

8. Curing Information

Dry To Touch: After excess is removed, surface should feel dry.

Recoat: 2 Hours

Full Cure: 48 —72 Hours

9. Storage & Shelf Life

Product must be kept in its original and tightly sealed container. Store in a dry and well ventilated place with controlled temperature (50°F to 90°F). Keep sheltered from weather and direct sunlight. In proper storage conditions, the product's shelf life is 24 months following production (see date on packaging). Store product in original container and close lid tightly after each use.

10. Maintenance

Cobble Clean is recommended for routine cleaning. Follow Cobble Clean instructions for dilution ratios.

11. Shipping

Land and sea: Not Regulated

Packing Group: III

Flash Point: >114F

12. Clean Up

Clean sprayer and tools with Odorless Mineral Spirits immediately after use.

13. Health Hazard Information

Eye Contact: Wear Eye Protection. May irritate eyes. If in eyes, flush with water for at least 15 minutes.

Inhalation: Use a NIOSH approved respirator.

Ingestion: If swallowed, DO NOT induce vomiting. Seek medical attention.

Skin: Avoid prolonged contact with skin.

Use with adequate ventilation. May be used interior or exterior application.

Any surface may become more slippery when a coating is applied. In testing, Cobble Enhancer increased the coefficient of friction on many substrates IE did not make the surface more slippery.

14. Technical Support

For friendly, knowledgeable and courteous technical support please call 954.971.9111.

You may also reach us by sending a query from our website at www.surfacelogix.net.

15. Disclaimer

All SurfaceLogix products are manufactured with the finest raw materials. It is the applicator's responsibility to determine the appropriate use of the product.

All recommendations and suggestions are made without guarantee, since conditions of use are beyond our control.