



COBBLE ENHANCER™

Breathable Solvent-Based Clear Sealer for Natural Stone, Interlocking Pavers, and Concrete Surfaces

- Enhanced appearance
- No sheen
- Penetrating oil-based sealer
- Moisture, stain, and oil repellent
- Non-yellowing

COBBLE ENHANCER™

Product Numbers: 133-1G (1 Gal.), 133-5G (5 Gal.)

Product Description

Surfacelogix® Cobble Enhancer is an odorless mineral spirits, penetrating, breathable sealer designed for the protection of all medium-to-dense porous surfaces. Cobble Enhancer is designed to protect and beautify natural stone, travertine, interlocking concrete pavers, and concrete floors. Cobble Enhancer forms a wet look breathable barrier that is resistant to moisture retention, stains, and oil.

Use Cobble Enhancer on driveways, patios, pool decks, parking lots, walkways, etc. constructed of natural stone, concrete pavers, or concrete.

How To Use

Before You Begin: Surfaces must be clean, dry and free of any contaminants before sealing. Cobble Enhancer's performance is directly related to how thoroughly the surface is prepared. All grease, oil, and potential contaminants must be removed. Do not apply when the temperature of the air or the surface to be coated is below 50°F. Testing on your surface is always recommended to ensure desired results. Concrete should cure a minimum of 28 days before sealing. Read label instructions carefully. Cobble Clean, Cobble Prep, and Cobble Oxhide may be used for specific cleaning situations.

Mixing: Stir product.

Applications:

Roller: Apply with a lambs wool or microfiber cloth, working the material into the surface.

Airless Sprayer: Spray by overlapping each pass. Always apply in an even film deposit and maintain a working wet line. Remove any excess material after 3-5 minutes.

On Bare Surface: Apply to the surface and allow to penetrate for 3-5 minutes, remove any excess. Do not allow any excess or pooling to dry on the surface.

Over Previously Sealed Surface: Film forming sealers will need to be stripped prior to application. Cobble Enhancer may be applied over non film forming sealers provided the prior application is sufficiently worn away.

Note: Excess or puddled sealer must be removed from the surface before it dries. This timing will depend on temperature and exposure.

Clean Up: Clean sprayer and tools with odorless mineral spirits immediately after use.

Maintenance: SurfaceLogix® Cobble Clean is recommended for routine cleaning. Follow Cobble Clean instructions for dilution ratios.

Additional Information

Coverage: 200 to 2,000 sq. ft. per gallon per coat. Coverage will depend on surface porosity, joint width, and method of application.

Packaging: Available in 1-gallon pails (8 lbs.) and 5-gallon pails (45 lbs.). 133-1G: 4 per case, 180 per pallet. 133-5G: 36 per pallet.

Storage & Shelf Life: Product must be kept in its original and tightly-sealed container. Store in a dry and well-ventilated place with controlled temperature (50°F to 90°F). Keep sheltered from weather and direct sunlight. In proper storage conditions, the product's shelf life is 24 months following production (see date on packaging). Store product in original container and close lid tightly after each use.

Technical Data Sheet: Additional product information can be found on this product's technical data sheet (TDS). Scan the QR code to view the TDS.

