

EK25G-212LI 4 Wheel Lithium Forklift

| Model | | EK25G-212LI |
|--|--------|----------------------|
| Lift | | Lithium |
| Drive | | Sit-Down |
| Load capacity | (lb.) | 5000 |
| Load center distance | (in) | 20 |
| Wheelbase | (in) | 65.35 |
| Lifting height | (in) | 212 |
| Free lifting height | (in) | 54.9 |
| Lowered mast height | (in) | 94.5 |
| Mast/Fork carriage tilt forward/backward | (°) | 6/6 |
| Side Shift | | 3-way valve |
| Overall length | (in) | 138 |
| Overall width | (in) | 46.45 |
| Fork Size, | (in) | 42 |
| Tire Material | | Solid Pneumatic |
| Turning radius | (in) | 84.2 |
| Max Gradient Performance, laden/unladen | (%) | 15/25 |
| Fork Adjust Width | (in) | 8.7-29 |
| ZAPI Controller | | ZAPI |
| Battery voltage | (V/Ah) | 80V/202AH Lithium |
| Service Weight | (lb.) | 9,915 |

The EKKO EK25G-212LI 4 Wheel Electric Forklift is designed for use for all your material handling demands. It is ideal for loading and unloading trucks, loading docks, stock rooms, manufacturing floors and warehousing.

Made from high quality steel and components with durable quality drives to withstand any terrain, usage, impact and directional changes for the use of any application with confidence and assurance.

- o Load Capacity 5000 lb.
- Raised Height 212"
- Side Shifting Forks
- o Free Lift 47.48"
- o Fork Length 42"
- o ZAPI Controller
- o Battery 80/202 Ah Lithium
- Solid Pneumatic Tires
- Ergonomic Handle and Controls

3-Phase 480V Charger (optional 220V & 110V)





