

according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. A

Revision date: 10.10.2023 Page 1 of 16

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

PASF - Polyester approved styrene free, Comp. A

UFI: GX20-D07N-Q00F-A659

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

Adhesive mortar for fastening elements A-component (resin)

### Uses advised against

no restriction

#### 1.3. Details of the supplier of the safety data sheet

Company name: Chemofast Anchoring GmbH Street: Hanns-Martin-Schleyer-Str. 23

Place: D-47877 Willich

Telephone: +49 2154 8123 0 Telefax: +49 2154 8123 333

Internet: www.chemofast.de Responsible Department: sdb@chemofast.de

**1.4. Emergency telephone** +49 (0)551-19240 (GIZ-Nord, German and English 24/7)

number:

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### **GB CLP Regulation**

Skin Sens. 1; H317 Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

# **GB CLP Regulation**

### Hazard components for labelling

Tetramethylene dimethacrylate;

Methacrylic acid, monoester with propane-1,2-diol;

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl]

(4-methylphenyl)amino]

Signal word: Warning

Pictograms:



### **Hazard statements**

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

#### **Precautionary statements**

P261 Avoid breathing vapours.

P273 Avoid release to the environment.

P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. A

Revision date: 10.10.2023 Page 2 of 16

P501

Dispose of contents/container to an approved waste disposal plant in accordance with local/national regulation.

### 2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. (--> UK REACH)

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

# **SECTION 3: Composition/information on ingredients**

### 3.2. Mixtures

## **Hazardous components**

EC No Classification (GB CLP Regulati Tetramethylene dimethacrylate	Index No ion)	REACH No		
<u> </u>	ion)			
Tetramethylene dimethacrylate				
,			5 - < 15 %	
218-218-1		01-2119967415-30		
Skin Sens. 1B; H317				
Vinyltoluene			1-<6 %	
246-562-2		01-2119622074-50		
Flam. Liq. 3, Skin Irrit. 2, Aquat	ic Acute 1, Aquatic Chroni	c 2; H226 H315 H400 H411		
Methacrylic acid, monoester wit	h propane-1,2-diol		< 2,5 %	
248-666-3		01-2119490226-37		
Eye Irrit. 2, Skin Sens. 1; H319 H317				
1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate				
229-934-9		01-2119451093-47		
Repr. 2, Aquatic Chronic 3; H361d H412				
Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]				
911-490-9		01-2119979579-10		
Acute Tox. 4, Skin Irrit. 2, Eye Γ H412	Dam. 1, Skin Sens. 1, Aqua	atic Chronic 3; H302 H315 H318 H317		
1,1'-(p-Tolylimino)dipropan-2-ol			< 0,5 %	
254-075-1		01-2119980937-17		
Acute Tox. 2, Eye Irrit. 2, Aquatic Chronic 3; H300 H319 H412				
1,4-naphthoquinone			< 0,05 %	
204-977-6		01-2120760462-57		
Acute Tox. 2, Acute Tox. 3, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 1; H330 H301 H314 H318 H317 H335 H400 H410				
	18-218-1 kin Sens. 1B; H317 (inyltoluene 46-562-2 lam. Liq. 3, Skin Irrit. 2, Aquat Methacrylic acid, monoester wit 48-666-3 kye Irrit. 2, Skin Sens. 1; H319 -Isopropyl-2,2-dimethyltrimethy 29-934-9 Repr. 2, Aquatic Chronic 3; H36 Reaction mass of 2,2'-[(4-methy 2-hydroxyethoxy)ethyl](4-methy 11-490-9 Repr. 2, Skin Irrit. 2, Eye E 1412 11-490-1 Repr. 2, Skin Irrit. 2, Eye E 1412 11-490-1 Repr. 3, Skin Irrit. 2, Eye E 1412 11-490-1 Repr. 4, Skin Irrit. 2, Eye E 1412 11-490-1 Repr. 54-075-1 Repr. 5	18-218-1 kin Sens. 1B; H317 finyltoluene 46-562-2 lam. Liq. 3, Skin Irrit. 2, Aquatic Acute 1, Aquatic Chronic Methacrylic acid, monoester with propane-1,2-diol 48-666-3 kye Irrit. 2, Skin Sens. 1; H319 H317 -Isopropyl-2,2-dimethyltrimethylene Diisobutyrate 29-934-9 Repr. 2, Aquatic Chronic 3; H361d H412 Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol at 2-hydroxyethoxy)ethyl](4-methylphenyl)amino] 11-490-9 Locute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Skin Sens. 1, Aquatic 1,1'-(p-Tolylimino)dipropan-2-ol 54-075-1 Locute Tox. 2, Eye Irrit. 2, Aquatic Chronic 3; H300 H319 F 4,4-naphthoquinone 04-977-6 Locute Tox. 2, Acute Tox. 3, Skin Corr. 1C, Eye Dam. 1, Skin Corr. 1, Skin Sens. 1, Skin Sens. 1, Aquatic Tox. 2, Acute Tox. 3, Skin Corr. 1, Eye Dam. 1, Skin Sens. 2, Acute Tox. 3, Skin Corr. 1, Eye Dam. 1, Skin Sens. 1, Skin Sens. 1, Skin Sens. 1, Skin Sens. 2, Acute Tox. 3, Skin Corr. 1, Eye Dam. 1, Skin Sens. 1, Skin Sens	18-218-1	

Full text of H and EUH statements: see section 16.



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. A

Revision date: 10.10.2023 Page 3 of 16

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Cond	c. Limits, M-factors and ATE			
2082-81-7	218-218-1	Tetramethylene dimethacrylate	5 - < 15 %		
	dermal: LD5	0 = > 3000 mg/kg; oral: LD50 = 10066 mg/kg			
25013-15-4	246-562-2	Vinyltoluene	1 - < 6 %		
	dermal: LD5	0 = 4585 mg/kg			
27813-02-1	248-666-3	Methacrylic acid, monoester with propane-1,2-diol	< 2,5 %		
	dermal: LD5	0 = > 5000 mg/kg; oral: LD50 = > 2000 mg/kg			
6846-50-0	229-934-9	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate	< 0,5 %		
	dermal: LD50 = 18900 mg/kg; oral: LD50 = 3200 mg/kg				
-	911-490-9	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]	< 0,5 %		
	dermal: LD5	0 = > 2000 mg/kg; oral: LD50 = 619 mg/kg			
38668-48-3	254-075-1	1,1'-(p-Tolylimino)dipropan-2-ol	< 0,5 %		
	dermal: LD5	0 = > 2000 mg/kg; oral: LD50 = > 25 - < 200 mg/kg			
130-15-4	204-977-6	1,4-naphthoquinone	< 0,05 %		
	LD50 = 124 r	TE = 0,5 mg/l (vapours); inhalation: LC50 = 0,046 mg/l (dusts or mists); oral: ng/kg  Aquatic Acute 1; H400: M=10 nic 1; H410: M=1			

#### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### **General information**

Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

#### After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

## After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

## After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

### After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.

### 4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

# 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Foam

Extinguishing powder

Water spray jet

Carbon dioxide (CO2)



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. A

Revision date: 10.10.2023 Page 4 of 16

### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic Carbon monoxide

#### 5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit. In case of fire and/or explosion do not breathe fumes.

#### **Additional information**

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Use personal protective equipment as required. Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

### 6.2. Environmental precautions

Avoid release to the environment. Do not allow to enter into surface water or drains.

### 6.3. Methods and material for containment and cleaning up

#### For cleaning up

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

## 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

### Advice on safe handling

Use only outdoors or in a well-ventilated area.

Wear personal protection equipment (refer to section 8).

Avoid contact with skin, eyes and clothes.

When using do not eat, drink or smoke.

Wash hands thoroughly after handling.

Take off contaminated clothing and wash it before reuse.

#### Advice on general occupational hygiene

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme. Wash hands thoroughly after handling. When using do not eat, drink or smoke.

### 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed. Store in a place accessible by authorized persons only. Keep only in the original container in a cool, well-ventilated place.

#### Hints on joint storage

Do not use for products which come into contact with the food stuffs.



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. A

Revision date: 10.10.2023 Page 5 of 16

## Further information on storage conditions

storage temperature: 5 - 25°C

# 7.3. Specific end use(s)

Adhesive mortar for fastening elements A-component (resin)

# **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. A

Revision date: 10.10.2023 Page 6 of 16

# **DNEL/DMEL values**

CAS No Substance			
DNEL type	Exposure route	Effect	Value
2082-81-7 Tetramethylene dimethacrylate			
Worker DNEL, long-term	inhalation	systemic	14,5 mg/m³
Worker DNEL, long-term	dermal	systemic	4,2 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	4,3 mg/m³
Consumer DNEL, long-term	dermal	systemic	2,5 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	2,5 mg/kg bw/day
25013-15-4 Vinyltoluene			
Worker DNEL, long-term	inhalation	systemic	37 mg/m³
Worker DNEL, acute	inhalation	systemic	37 mg/m³
Worker DNEL, long-term	inhalation	local	37 mg/m³
27813-02-1 Methacrylic acid, monoester with propane-1,2-d	iol		
Worker DNEL, long-term	inhalation	systemic	14,7 mg/m³
Worker DNEL, long-term	dermal	systemic	4,2 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	8,8 mg/m³
Consumer DNEL, long-term	dermal	systemic	2,5 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	2,5 mg/kg bw/day
6846-50-0 1-Isopropyl-2,2-dimethyltrimethylene Diisobutyra	ate		
Worker DNEL, long-term	dermal	systemic	5 mg/kg bw/day
Worker DNEL, long-term	inhalation	systemic	17,62 mg/m³
Consumer DNEL, long-term	inhalation	systemic	4,35 mg/m³
Consumer DNEL, long-term	oral	systemic	5 mg/kg bw/day
Consumer DNEL, long-term	dermal	systemic	5 mg/kg bw/day
- Reaction mass of 2,2'-[(4-methylphenyl)imino]bi (4-methylphenyl)amino]	sethanol and Ethanol	2-[[2-(2-hydroxyetl	noxy)ethyl]
Worker DNEL, long-term	inhalation	systemic	9,8 mg/m³
Worker DNEL, long-term	dermal	systemic	1,4 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	2,9 mg/m³
Consumer DNEL, long-term	oral	systemic	0,83 mg/kg bw/day
Consumer DNEL, long-term	dermal	systemic	0,83 mg/kg bw/day
38668-48-3 1,1'-(p-Tolylimino)dipropan-2-ol			
Worker DNEL, long-term	inhalation	systemic	2 mg/m³
Worker DNEL, long-term	dermal	systemic	0,6 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	0,3 mg/kg bw/day
Consumer DNEL, long-term	dermal	systemic	0,3 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	0,4 mg/m³
130-15-4 1,4-naphthoquinone			
Worker DNEL, long-term	inhalation	systemic	0,033 mg/m³



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. A

Revision date: 10.10.2023 Page 7 of 16

# **PNEC** values

CAS No Substance	
Environmental compartment	Value
2082-81-7 Tetramethylene dimethacrylate	
Freshwater	0,043 mg/l
Marine water	0,004 mg/l
Freshwater sediment	3,12 mg/kg
Marine sediment	0,312 mg/kg
Micro-organisms in sewage treatment plants (STP)	2 mg/l
Soil	0,573 mg/kg
25013-15-4 Vinyltoluene	
Freshwater	0,05 mg/l
Marine water	0,002 mg/l
Freshwater sediment	0,684 mg/kg
Marine sediment	0,684 mg/kg
Soil	0,133 mg/kg
27813-02-1 Methacrylic acid, monoester with propane-1,2-diol	
Freshwater	0,904 mg/l
Marine water	0,904 mg/l
Freshwater sediment	6,28 mg/kg
Marine sediment	6,28 mg/kg
Micro-organisms in sewage treatment plants (STP)	10 mg/l
Soil	0,727 mg/kg
6846-50-0 1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate	
Freshwater	0,014 mg/l
Marine water	0,001 mg/l
Freshwater sediment	5,29 mg/kg
Marine sediment	0,529 mg/kg
Soil	1,05 mg/kg
- Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Etha (4-methylphenyl)amino]	anol 2-[[2-(2-hydroxyethoxy)ethyl]
Freshwater	0,048 mg/l
Marine water	0,005 mg/l
Freshwater sediment	0,12 mg/kg
Marine sediment	0,12 mg/kg
38668-48-3 1,1'-(p-Tolylimino)dipropan-2-ol	
Freshwater	0,017 mg/l
Marine water	0,0017 mg/l
Freshwater sediment	0,0783 mg/kg
Marine sediment	0,0072 mg/kg
Soil	0,005 mg/kg
130-15-4 1,4-naphthoquinone	
Freshwater	26,1 mg/l
Marine water	2,61 mg/l



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. A

Revision date: 10.10.2023 Page 8 of 16

Freshwater sediment	321 mg/kg
Marine sediment	32,1 mg/kg
Micro-organisms in sewage treatment plants (STP)	0,172 mg/l
Soil	49 mg/kg

#### Additional advice on limit values

This mixture contains quartz (inorganic filler) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

#### 8.2. Exposure controls



## Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

### Individual protection measures, such as personal protective equipment

## Eye/face protection

Wear eye/face protection. Wear safety glasses.

#### Hand protection

Disposable gloves

Recommended material: NBR (Nitrile rubber)

Breakthrough time: > 480 min

Thickness of the glove material: > 0,2 mm

DIN-/EN-Norms EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

### Skin protection

Wear suitable protective clothing.

### Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

### **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state: solid (pasty)
Colour: light beige
Odour: characteristic
Odour threshold: No data available

Melting point/freezing point:

No data available
Boiling point or initial boiling point and

No data available

boiling range:

Flammability:
Lower explosion limits:
upper explosion limits:
not applicable
Flash point:
not applicable
Auto-ignition temperature:
not applicable



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. A

Revision date: 10.10.2023 Page 9 of 16

Decomposition temperature: No data available

pH-Value: The study does not need to be

conducted because the substance is

known to be insoluble in water.

Viscosity / kinematic: not applicable

The study does not need to be conducted because the substance is known to be

insoluble in water.

Solubility in other solvents

No data available

Water solubility:

Partition coefficient n-octanol/water:

Vapour pressure:

Density (at 20 °C):

Relative vapour density:

Particle characteristics:

not applicable

not applicable

No data available

No data available

#### 9.2. Other information

# Information with regard to physical hazard classes

Explosive properties not explosive

Self-ignition temperature

Solid: not applicable

Oxidizing properties Not oxidising.

Other safety characteristics

Evaporation rate:

Solid content:

No data available

No data available

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

## 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

Response: Oxidising agent, strong

#### 10.4. Conditions to avoid

Heat. Keep cool. Protect from sunlight.

### 10.5. Incompatible materials

No information available.

#### 10.6. Hazardous decomposition products

No known hazardous decomposition products.

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in GB CLP Regulation

### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### **ATEmix calculated**

ATE (oral) 11282,6 mg/kg; ATE (inhalation vapour) 265,95 mg/l; ATE (inhalation dust/mist) 36,266 mg/l



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. A

Revision date: 10.10.2023 Page 10 of 16

CAS No	No Chemical name								
	Exposure route	Dose		Species	Source	Method			
2082-81-7	Tetramethylene dimet	Tetramethylene dimethacrylate							
	oral	LD50 mg/kg	10066	Rat					
	dermal	LD50 mg/kg	> 3000	Rabbit					
25013-15-4	Vinyltoluene								
	dermal	LD50 mg/kg	4585	Rabbit					
27813-02-1	Methacrylic acid, mon	oester with	propane-1	,2-diol					
	oral	LD50 mg/kg	> 2000	Rat					
	dermal	LD50 mg/kg	> 5000	Rabbit					
6846-50-0	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate								
	oral	LD50 mg/kg	3200	Rat					
	dermal	LD50 mg/kg	18900	Guinea pig					
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] (4-methylphenyl)amino]								
	oral	LD50 mg/kg	619	Rat					
	dermal	LD50 mg/kg	> 2000	Rat					
38668-48-3	1,1'-(p-Tolylimino)dipr	opan-2-ol							
	oral	LD50 200 mg/kg	> 25 - <	Rat					
	dermal	LD50 mg/kg	> 2000	Rat					
130-15-4	1,4-naphthoquinone								
	oral	LD50 mg/kg	124	Rat					
	inhalation vapour	ATE	0,5 mg/l						
	inhalation (4 h) dust/mist	LC50 mg/l	0,046	Rat					

# Irritation and corrosivity

Based on available data, the classification criteria are not met.

## Sensitising effects

May cause an allergic skin reaction. (Tetramethylene dimethacrylate; Methacrylic acid, monoester with propane-1,2-diol; Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]; 1,4-naphthoquinone)

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. A

Revision date: 10.10.2023 Page 11 of 16

## **Aspiration hazard**

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

## **Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

# **SECTION 12: Ecological information**

## 12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. A

Revision date: 10.10.2023 Page 12 of 16

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
2082-81-7	Tetramethylene dimeth	nacrylate					
	Acute algae toxicity	ErC50 mg/l	9,79	72 h	Desmodesmus subspicatus		
	Crustacea toxicity	NOEC mg/l	5,09	21 d	Daphnia magna (Big water flea)		
25013-15-4	Vinyltoluene						
	Acute fish toxicity	LC50 mg/l	1 - 10	96 h			
	Acute algae toxicity	ErC50 mg/l	0,319	72 h			
	Acute crustacea toxicity	EC50	9,3 mg/l		Daphnia magna (Big water flea)		
27813-02-1	Methacrylic acid, mono		propane-1,2	2-diol			
	Acute algae toxicity	ErC50 mg/l	> 97,2	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 mg/l	> 143		Daphnia magna (Big water flea)		
6846-50-0	1-Isopropyl-2,2-dimeth	yltrimethyle	ene Diisobu	tyrate			
	Algae toxicity	NOEC mg/l	2,25	3 d			
	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] (4-methylphenyl)amino]						
	Acute fish toxicity	LC50 mg/l	> 100	96 h			
	Acute algae toxicity	ErC50 mg/l	> 100	72 h			
	Acute crustacea toxicity	EC50	48 mg/l	48 h			
38668-48-3	1,1'-(p-Tolylimino)dipro	opan-2-ol					
	Acute fish toxicity	LC50	17 mg/l		Danio rerio (zebrafish)		
	Acute algae toxicity	ErC50	245 mg/l	72 h	Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 mg/l	28,8		Daphnia magna (Big water flea)		
	Algae toxicity	NOEC mg/l	57,8	72 d	Desmodesmus subspicatus		OECD 201
130-15-4	1,4-naphthoquinone						
	Acute fish toxicity	LC50 mg/l	0,045	96 h	Oryzias latipes (Ricefish)		
	Acute algae toxicity	ErC50 mg/l	0,42	72 h			
	Acute crustacea toxicity	EC50 mg/l	0,026	48 h			
	Algae toxicity	NOEC mg/l	0,07	3 d			

# 12.2. Persistence and degradability

The product has not been tested.



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. A

Revision date: 10.10.2023 Page 13 of 16

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
2082-81-7	Tetramethylene dimethacrylate			
	OECD 310	84 %	28	
25013-15-4	Vinyltoluene			
	OECD 310	36,7 %	28	
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol			
	OECD 301C	81%	28	
130-15-4	1,4-naphthoquinone			
		39 %	5	

### 12.3. Bioaccumulative potential

The product has not been tested.

#### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
2082-81-7	Tetramethylene dimethacrylate	3,1
25013-15-4	Vinyltoluene	3,35
27813-02-1	Methacrylic acid, monoester with propane-1,2-diol	0,97
6846-50-0	1-Isopropyl-2,2-dimethyltrimethylene Diisobutyrate	4,91
-	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]	2,17
38668-48-3	1,1'-(p-Tolylimino)dipropan-2-ol	2,1
130-15-4	1,4-naphthoquinone	1,77

### **BCF**

CAS No	Chemical name	BCF	Species	Source
25013-15-4	VinyItoluene	100 - 320		

### 12.4. Mobility in soil

The product has not been tested.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

## 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

# 12.7. Other adverse effects

No information available.

#### **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### **SECTION 13: Disposal considerations**

# 13.1. Waste treatment methods

#### **Disposal recommendations**

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

#### List of Wastes Code - residues/unused products



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. A

Revision date: 10.10.2023 Page 14 of 16

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

# List of Wastes Code - used product

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

### List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

## **SECTION 14: Transport information**

#### Land transport (ADR/RID)

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.

**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.

**14.4. Packing group:** No dangerous good in sense of this transport regulation.

### Inland waterways transport (ADN)

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.

**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation.

14.4. Packing group:

#### Marine transport (IMDG)

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.

**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.

**14.4. Packing group:** No dangerous good in sense of this transport regulation.

#### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.

**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.

**14.4. Packing group:** No dangerous good in sense of this transport regulation.

# 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### 14.6. Special precautions for user

No information available.

## 14.7. Maritime transport in bulk according to IMO instruments

not applicable

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU** regulatory information



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. A

Revision date: 10.10.2023 Page 15 of 16

Restrictions on use (REACH, annex XVII):

Entry 40, Entry 75

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

**Additional information** 

VOC content: 2,8 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

**National regulatory information** 

Employment restrictions: Observe restrictions to employment for juveniles according to the

'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### **SECTION 16: Other information**

#### Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)

ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level DNEL: Derived No Effect Level EC50: Effective concentration, 50%

ErC50: EC50 in terms of reduction of growth rate

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Oragnisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic vPvB: very persistent and very bioaccumulative

PNEC: Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations

Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound

Acute Tox. 3: Acute toxicity, Category 3 Acute Tox. 2: Acute toxicity, Category 2 Acute Tox. 4: Acute toxicity, Category 4

Aquatic Acute 1: Acute aquatic hazard, Category 1

Aquatic Chronic 1: Long-term aquatic hazard, Category 1 Aquatic Chronic 3: Long-term aquatic hazard, Category 3

Asp. Tox. 1: Aspiration hazard, Category 1

Eye Dam. 1: Serious eye damage/eye irritation, Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. A

Revision date: 10.10.2023 Page 16 of 16

Flam. Liq. 3: Flammable liquid, Category 3 Repr. 2: Reproductive toxicity, Category 2

Skin Corr. 1C: Skin corrosion/irritation, Category 1C Skin Irrit. 2: Serious eye damage/eye irritation, Category 2

Skin Sens. 1A: Skin sensitilization, Category 1A Skin Sens. 1B: Skin sensitilization, Category 1B

STOT SE 3: Specific target organ toxicity (single exposure), Category 3

## Key literature references and sources for data

Website European Chemicals Agency: https://echa.europa.eu

Data sources: Supplier

### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 3; H412	Calculation method

### Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H300	Fatal if swallowed.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H361d	Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. B

Revision date: 10.10.2023 Page 1 of 11

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

PASF - Polyester approved styrene free, Comp. B
UFI: TPJ5-00TG-700U-336U

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

compound mortar B-component (hardener)

### Uses advised against

no restriction

#### 1.3. Details of the supplier of the safety data sheet

Company name: Chemofast Anchoring GmbH Street: Hanns-Martin-Schleyer-Str. 23

Place: D-47877 Willich

Telephone: +49 2154 8123 0 Telefax: +49 2154 8123 333

Internet: www.chemofast.de Responsible Department: sdb@chemofast.de

**1.4. Emergency telephone** +49 (0)551-19240 (GIZ-Nord, German and English 24/7)

number:

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### **GB CLP Regulation**

Eye Irrit. 2; H319 Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

#### 2.2. Label elements

# **GB CLP Regulation**

### Hazard components for labelling

Dibenzoyl peroxide

Signal word: Warning

**Pictograms:** 



#### **Hazard statements**

H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.

## **Precautionary statements**

P261 Avoid breathing vapours.

P280 Wear protective gloves and eye/face protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container to an approved waste disposal plant in accordance with

local/national regulation.



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. B

Revision date: 10.10.2023 Page 2 of 11

### 2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII. (--> UK REACH)

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

### **Hazardous components**

CAS No	Chemical name	Chemical name		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
94-36-0	Dibenzoyl peroxide			5 - < 15 %
	202-327-6	617-008-00-0	01-2119511472-50	
	Org. Perox. B, Eye Irrit. 2, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 1; H241 H319 H317 H400 H410			

Full text of H and EUH statements: see section 16.

#### Specific Conc. Limits. M-factors and ATE

	,		
CAS No	EC No	Chemical name	Quantity
	Specific Conc	. Limits, M-factors and ATE	
94-36-0	202-327-6	Dibenzoyl peroxide	5 - < 15 %
	oral: LD50 = > 5000 mg/kg		

#### **Further Information**

The product has been tested for aquatic toxicity. The tests show no need for classification of the product as toxic and harmful to aquatic life. Test reports are available.

### **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

#### **General information**

First aider: Pay attention to self-protection! Take off immediately all contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

#### After inhalation

Provide fresh air. When in doubt or if symptoms are observed, get medical advice.

# After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

#### After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing.

#### After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Medical treatment necessary.



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. B

Revision date: 10.10.2023 Page 3 of 11

#### 4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

Causes serious eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

#### Suitable extinguishing media

Foam

Extinguishing powder

Water spray jet

Carbon dioxide (CO2)

#### Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Pyrolysis products, toxic

Carbon monoxide

#### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit

#### Additional information

Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

#### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

#### General advice

Use personal protective equipment as required. Provide adequate ventilation. Avoid contact with skin, eyes and clothes.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

# 6.3. Methods and material for containment and cleaning up

# For cleaning up

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

#### Other information

Collect spillage. Take up mechanically, placing in appropriate containers for disposal. Suitable material for taking up: Sand

Treat the recovered material as prescribed in the section on waste disposal.

Retain contaminated washing water and dispose it.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

### **SECTION 7: Handling and storage**



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. B

Revision date: 10.10.2023 Page 4 of 11

#### 7.1. Precautions for safe handling

### Advice on safe handling

Use only outdoors or in a well-ventilated area.

Wear personal protection equipment (refer to section 8).

Avoid contact with skin, eyes and clothes.

When using do not eat, drink or smoke.

Wash hands thoroughly after handling.

Take off contaminated clothing and wash it before reuse.

## Advice on general occupational hygiene

Take off contaminated clothing and wash it before reuse. Draw up and observe skin protection programme.

Wash hands thoroughly after handling. When using do not eat or drink.

#### 7.2. Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Keep container tightly closed.

Store in a place accessible by authorized persons only.

Keep only in the original container in a cool, well-ventilated place.

# Hints on joint storage

Do not store together with: Oxidising agent, strong

Do not use for products which come into contact with the food stuffs.

# Further information on storage conditions

Keep container tightly closed in a cool place.

storage temperature: 5 - 25°C

### 7.3. Specific end use(s)

see section 1.2

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
94-36-0	Dibenzoyl peroxide	-	5		TWA (8 h)	WEL
56-81-5	Glycerol, mist	-	10		TWA (8 h)	WEL

### **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
94-36-0	Dibenzoyl peroxide			
Consumer D	Consumer DNEL, long-term		systemic	2 mg/kg bw/day
Worker DNEL, long-term		dermal		13,3 mg/kg bw/day
Worker DNE	EL, long-term	inhalation	systemic	39 mg/m³



according to UK REACH Regulation

### PASF - Polyester approved styrene free, Comp. B

Revision date: 10.10.2023 Page 5 of 11

#### **PNEC values**

CAS No	Substance		
Environmental compartment Value			
94-36-0	Dibenzoyl peroxide		
Freshwater 0,00002 m		0,00002 mg/l	
Marine water		0,000002 mg/l	
Freshwater sediment		0,013 mg/kg	
Marine sediment		0,001 mg/kg	

#### Additional advice on limit values

This mixture contains quartz (inorganic filler) which is firmly bound in the pasty component, and thus not freely available during use, so that a risk of dust inhalation is excluded. Exposure limit values for respirable dusts are not relevant for this product.

### 8.2. Exposure controls





### Appropriate engineering controls

Provide adequate ventilation. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

#### Individual protection measures, such as personal protective equipment

### **Eye/face protection**

Wear eye/face protection. Wear safety glasses.

### Hand protection

Disposable gloves

Recommended material: NBR (Nitrile rubber)

Breakthrough time: > 480 min

Thickness of the glove material: > 0,2 mm

DIN-/EN-Norms EN 374

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### Skin protection

Wear suitable protective clothing.

# Respiratory protection

In case of inadequate ventilation wear respiratory protection. Respiratory protection with combination filter A1P2 (organic gases/vapors and particles) recommended.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: solid (pasty)
Colour: black
Odour: characteristic
Odour threshold: No data available

Melting point/freezing point:

No data available



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. B

Revision date: 10.10.2023 Page 6 of 11

Boiling point or initial boiling point and No data available

boiling range:

Flammability: Combustible Lower explosion limits: not applicable Upper explosion limits: not applicable Flash point: not applicable not applicable Auto-ignition temperature: Decomposition temperature: Start of decomposition: >35 °C pH-Value: The study does not need to be

conducted because the substance is

known to be insoluble in water. not applicable

The study does not need to be conducted Water solubility:

because the substance is known to be

insoluble in water.

Solubility in other solvents

No data available

Viscosity / kinematic:

Partition coefficient n-octanol/water: not applicable Vapour pressure: No data available Density (at 20 °C): 1,59 g/cm<sup>3</sup> Relative vapour density: not applicable Particle characteristics: No data available

#### 9.2. Other information

# Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Self-ignition temperature

Solid: not applicable

Oxidizing properties Not oxidisina.

Available oxygen content: 0,74 %

Other safety characteristics

Evaporation rate: No data available Solid content: No data available

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

see section 10.3

#### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

Violent reaction with: Oxidising agent

# 10.4. Conditions to avoid

see section 7.2

### 10.5. Incompatible materials

Oxidising agent, strong

## 10.6. Hazardous decomposition products

Benzoic acid Benzene **Biphenyl** 



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. B

Revision date: 10.10.2023 Page 7 of 11

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in GB CLP Regulation

### **Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
94-36-0	Dibenzoyl peroxide				
	oral	LD50 > 5000 mg/kg	Rat		

#### Irritation and corrosivity

Causes serious eve irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

#### Sensitising effects

May cause an allergic skin reaction. (Dibenzoyl peroxide)

#### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### 11.2. Information on other hazards

# **Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

The product is not: Ecotoxic.

OECD 201 (Desmodesmus subspicatus )

IC10: (0 - 72 h) = 30 mg/l IC50: (0 - 72 h) = 150 mg/l

OECD 202 (Daphnia magna)

EC0/NOEC (48h) = 100 mg/l EC50 (48h) = >500 mg/l

EC100 (48h) = >>500 mg/l

OECD 203 (Danio rerio)

LC0/NOEC (96 h) : 250 mg/l LC50 (96 h) : > 500 mg/l LC100 (96 h) : >> 500 mg/l



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. B

Revision date: 10.10.2023 Page 8 of 11

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method
94-36-0	Dibenzoyl peroxide						
	Acute fish toxicity	LC50 mg/l	0,0602		Oncorhynchus mykiss (Rainbow trout)	OECD 203	
	Acute algae toxicity	ErC50 mg/l	0,0711		Pseudokirchneriella subcapitata	OECD 201	
	Acute crustacea toxicity	EC50 mg/l	0,11		Daphnia magna (Big water flea)	OECD 202	
	Algae toxicity	NOEC mg/l	0,02		Pseudokirchneriella subcapitata	OECD 201	
	Crustacea toxicity	NOEC mg/l	0,001		Daphnia magna (Big water flea)	OECD 211	
	Acute bacteria toxicity	(EC50	35 mg/l)	0,5 h		OECD 209	

### 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
94-36-0	Dibenzoyl peroxide			
	OECD 301D	71%	28	
	Readily biodegradable (according to OECD cr	riteria).		

#### 12.3. Bioaccumulative potential

The product has not been tested.

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
94-36-0	Dibenzoyl peroxide	3,2

# 12.4. Mobility in soil

The product has not been tested.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

## 12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

### 12.7. Other adverse effects

No information available.

#### **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### **Disposal recommendations**

Subsequent waste code numbers of the European Waste Catalogue are considered as recommendations. Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. B

Revision date: 10.10.2023 Page 9 of 11

#### List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products);

waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

# **List of Wastes Code - used product**

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances;

hazardous waste

# List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

### **SECTION 14: Transport information**

### Land transport (ADR/RID)

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.

**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.

**14.4. Packing group:** No dangerous good in sense of this transport regulation.

# Inland waterways transport (ADN)

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.

**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation.

**14.4. Packing group:** No dangerous good in sense of this transport regulation.

### Marine transport (IMDG)

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.

**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.

**14.4. Packing group:** No dangerous good in sense of this transport regulation.

## Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number or ID number:** No dangerous good in sense of this transport regulation.

**14.2. UN proper shipping name:** No dangerous good in sense of this transport regulation.

**14.3. Transport hazard class(es):** No dangerous good in sense of this transport regulation.

**14.4. Packing group:** No dangerous good in sense of this transport regulation.

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

# 14.6. Special precautions for user

No information available.

### 14.7. Maritime transport in bulk according to IMO instruments

not applicable

### **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. B

Page 10 of 11 Revision date: 10.10.2023

Restrictions on use (REACH, annex XVII):

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

**Additional information** 

VOC content: 4,3 % (DIN EN ISO 11890-2)

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

**National regulatory information** 

**Employment restrictions:** Observe restrictions to employment for juveniles according to the

'juvenile work protection guideline' (94/33/EC).

1 - slightly hazardous to water Water hazard class (D):

Skin resorption/Sensitization: Causes allergic hypersensitivity reactions.

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

### **SECTION 16: Other information**

### Abbreviations and acronyms

ADN: Accord européen relativ au transport international des marchandises Dangereuses par voie de Navigation

(European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)

ADR: Accord européen sur le transport des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service

CLP: Classification, Labeling and Packaging

DMEL: Derived Minimal Effect level DNEL: Derived No Effect Level EC50: Effective concentration, 50%

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations (DRG) for the air transport (IATA)

ICAO: International Civil Aviation Organization

IC50: Inhibitory concentration, 50%

IMDG: International Maritime Code for Dangerous Goods

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

NOEC: No Observed Effect Concentration

OECD: Oragnisation for Economic Co-operation and Development

PBT: persistent, bioaccumulative and toxic vPvB: very persistent and very bioaccumulative

PNEC: Predicted No Effect Concentration

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Règlement concernant le transport international ferroviaire de marchandises dangereuses (Regulations

Concerning the International Carriage of Dangerous Goods by Rail)

VOC: Volatile organic compound

Aquatic Acute 1: Acute aquatic hazard. Category 1

Aquatic Chronic 1: Long-term aquatic hazard, Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Category 2

Skin Sens. 1: Skin sensitilization, Category 1 Org. Perox. B: Organic Peroxides, Type B

## Key literature references and sources for data

Website European Chemicals Agency: https://echa.europa.eu

Data sources: Supplier



according to UK REACH Regulation

# PASF - Polyester approved styrene free, Comp. B

Revision date: 10.10.2023 Page 11 of 11

### Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method

### Relevant H and EUH statements (number and full text)

H241	Heating may cause a fire or explosion.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

## **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)