

## **Verification of Conformity**

Low Voltage Directive EC Council Directive: 2014/35/EU

Applicant: Shenzhen Growatt Power Technology Co., Ltd.

1001,10/F. Building A, Sino-German(Europe) Industrial Park,

Hangcheng Ave, Xixiang, Bao'an District, Shenzhen

Manufacturer: Shenzhen Growatt Power Technology Co., Ltd.

1001,10/F. Building A, Sino-German(Europe) Industrial Park,

Hangcheng Ave, Xixiang, Bao'an District, Shenzhen

**Product Description:** Portable Power Station

Trademark: GROWATT

Model/Type Reference: Infinity 1500

Ratings: See page 2 for detail

Standards: EN IEC 62368-1:2020+A11:2020

Certificate No.: KS2210S4470SC

Report No.: KS2210S4470S

The referred test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the essential requirements in the above listed Directive(s). Other relevant Directives have to be observed. After preparation of the necessary technical documentation as well as the conformity declaration, the CE marking as shown below can be affixed on the equipment.

CE

Approved by: Hardy Ding

Handly Ding

Issued Date: December 16, 2022

KSIGN(Guangdong) Testing Co., Ltd.

Rev. 2.0

Add.: West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China

Tel: +(86) 0755-2985 2678 Fax: +(86) 0755-2985 2397 E-mail: info@gdksign.cn Web: www.gdksign.com



## **Verification of Conformity**

Low Voltage Directive
EC Council Directive: 2014/35/EU

Ratings:

Input:

AC Input: 200-240V~, 50/60Hz, 1500W Max.

DC Input: 12-24V=== 12A Max.

Output:

AC Output (x4):230V~, 50/60Hz, 2000W Max. (Surge 4000W)

Car Outlet (x1): 12.6V===10A, 126W Max.

USB-A (x2): 5V===2.4A, 12W Max.

Fast Charge (x2): 5V===2.4A, 9V===2A, 12V===1.5A

Type-C (x2): 5V/9V/12V/15V/20V===3A, 60W Max.

wireless charger: 5W/7.5W/10W/15W

DC 5521 (x2): 12.6V===3A Max.

**Battery** 

Battery Type: lithium

Battery capacity: 1512Wh, 30Ah

Charging temperature: 0-45°C (32-113°F) Discharging temperature: -20-60°C (-4-140°F)

KSIGN(Guangdong) Testing Co., Ltd.

Rev. 2.0

Add.: West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park, Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, China