



RHINO

ANTI-FATIGUE MATS

RANCO INDUSTRIES, INC.

K-SERIES DRAIN THRU

<u>Thickness:</u>	3/4"	3/4"
<u>Color:</u>	BLACK	TERRA COTTA
<u>Size:</u>	2' X 3'	2' X 3'
	3' X 3'	3' X 3'
	3' X 4'	3' X 4'
	3' X 5'	3' X 5'

Hardiness DIN 53505-A	56+5	61+5
Density ISO 2781 (g/cm3)	1.14	1.52
Density DIN 53479 (g/sm3)	±0.02	±0.02
Oil Resistance	Y	Y+
Tensile Strength ISO 37 (PSI)	1278	994
Tensile Strength ASTM D412 (PSI)	±426	±426
Elongation ISO 37 (%)	300	250
Elongation ASTM D412	±50	±50
Abrasion DIN 53504 (mm3)	<200	<300

	BLACK	TERRA COTTA
ANIMAL FATS, GREASES, OILS	P	G
BRAKE FLUID	F	G
BUTYL ALCOHOL	P	F
CARBON TETRACHLORIDE	F	F
CHROMIC ACID	F	P
COOKING OILS	P	F
DIESEL OIL	P	F
ETHYL ALCOHOL	P	F
GASOLINE	P	F
HYDRAULIC FLUID	P	G
HYDROGEN PEROXIDE	P	F
MINERAL OIL	P	G
MOTOR OIL	P	F
NITRIC ACID	F	P
SODIUM HYDROXIDE	G	G
SULFURIC ACID	F	P

P= POOR | F= FAIR | G= GOOD