



# RHINO

ANTI-FATIGUE MATS

## RANCO INDUSTRIES, INC.

### K-SERIES COMFORT TRACT

<u>Thickness:</u>	1/2"	1/2"
<u>Width:</u>	36"	36"
<u>Color:</u>	BLACK	TERRA COTTA
<u>Size:</u>	2' x 4'	3' x 5'
	3' x 5'	3' x 10'
	3' x 10'	3' x 15'
	3' x 15'	3' x 20'
	3' x 20'	

Hardness DIN 53505-A	56+5	61+5
Density ISO 2781 (g/cm <sup>3</sup> )	1.14	1.52
Density DIN 53479 (g/sm <sup>3</sup> )	±0.02	±0.02
Oil Resistance	Y	Y
Tensile Strength ISO 37 (PSI)	1278	994
Tensile Strength ASTM D412 (PSI)	±426	±426
Elongation ISO 37 (%)	300	250
Elongation ASTM D412	±50	±50
Abrasion DIN 53504 (mm <sup>3</sup> )	<200	<300

	BLACK	T/C
ANIMAL FATS, GREASES, OILS	P	G
BRAKE FLUID	F	G
BUTYL ALCOHOL	P	F
CARBON TETRACHLORIDE	F	F
CHROMIC ACID	F	P
COOKING OILS	P	F
DIESEL OIL	P	F
ETHYL ALCOHOL	P	F
GASOLINE	P	F
HYDRAULIC FLUID	P	G
HYDROGEN PEROXIDE	P	F
MINERAL OIL	P	G
MOTOR OIL	P	F
NITRIC ACID	F	P
SODIUM HYDROXIDE	G	G
SULFURIC ACID	F	P

P= POOR | F= FAIR | G= GOOD