

STOCK NO.	SIZE	WEIGHT	LIST PRICE	CLASS, COLOR & THICKNESS
CUT LENGTHS LIN. FT.				CORRUGATED SWITCHBOARD
SB336C	3' X LF'	4.2	\$20.00	
FULL ROLLS				
SB336C	3' X 75'	315	\$1,295.00	CLASS 1 BLACK 3/16" THICK
				DIELECTRIC TEST VOLTAGE: 20,000 VAC PROOF TESTED OVER ENTIRE SURFACE AT: 10,000 VAC RECOMMENDED MAXIMUM USE VOLTAGE: 7,500 VAC
CUT LENGTHS LIN. FT.				CORRUGATED SWITCHBOARD
SB424C	2' X LF'	3.9	\$20.00	
SB436C	3' X LF'	5.8	\$27.50	
SB448C	4' X LF'	7.75	\$32.50	
FULL ROLLS				
SB424C	2' X 75'	292	\$1,305.00	
SB436C	3' X 75'	435	\$1,710.00	
SB448C	4' X 75'	580	\$2,025.00	BLACK CLASS 2 1/4" THICK
				DIELECTRIC TEST VOLTAGE: 30,000 VAC PROOF TESTED OVER ENTIRE SURFACE AT: 20,000 VAC RECOMMENDED MAXIMUM USE VOLTAGE: 17,000 VAC
CUT LENGTHS LIN. FT.				CORRUGATED SWITCHBOARD
SB536	3' X LF'	8.7	\$42.50	
FULL ROLLS				
SB536	3' X 75'	653	\$2,627.50	BLACK CLASS 3 3/8" THICK
				DIELECTRIC TEST VOLTAGE: 40,000 VAC PROOF TESTED OVER ENTIRE SURFACE AT: 30,000 VAC RECOMMENDED MAXIMUM USE VOLTAGE: 26,000 VAC
CUT LENGTHS LIN. FT.				CORRUGATED SWITCHBOARD
SB636	3' X LF'	11.6	\$82.50	
FULL ROLLS				
SB636	3' X 30'	348	\$2,042.50	BLACK CLASS 4 1/2" THICK
				DIELECTRIC TEST VOLTAGE: 50,000 VAC PROOF TESTED OVER ENTIRE SURFACE AT: 40,000 VAC RECOMMENDED MAXIMUM USE VOLTAGE: 36,000 VAC