

STOCK NO.	SIZE	WEIGHT	LIST PRICE	CLASS, COLOR & THICKNESS
CUT LENGTHS LIN. FT.				CORRUGATED SWITCHBOARD CLASS 1 BLACK 3/16" THICK
SB336C	3' X LF'	3.9	\$20.00	
FULL ROLLS				
SB336C	3' X 75'	293	\$1,295.00	
				DIELECTRIC TEST VOLTAGE: 20,000 VAC PROOF TESTED OVER ENTIRE SURFACE AT: 10,000 VAC RECOMMENDED MAXIMUM USE VOLTAGE: 7,500 VAC
CUT LENGTHS LIN. FT.				CORRUGATED SWITCHBOARD BLACK CLASS 2 1/4" THICK
SB424C	2' X LF'	3.5	\$20.00	
SB436C	3' X LF'	5.2	\$27.50	
SB448C	4' X LF'	6.8	\$32.50	
FULL ROLLS				
SB424C	2' X 75'	263	\$1,305.00	
SB436C	3' X 75'	390	\$1,710.00	
SB448C	4' X 75'	510	\$2,025.00	
				DIELECTRIC TEST VOLTAGE: 30,000 VAC PROOF TESTED OVER ENTIRE SURFACE AT: 20,000 VAC RECOMMENDED MAXIMUM USE VOLTAGE: 17,000 VAC
CUT LENGTHS LIN. FT.				CORRUGATED SWITCHBOARD BLACK CLASS 3 3/8" THICK
SB536	3' X LF'	7.7	\$42.50	
FULL ROLLS				
SB536	3' X 75'	577	\$2,627.50	
				DIELECTRIC TEST VOLTAGE: 40,000 VAC PROOF TESTED OVER ENTIRE SURFACE AT: 30,000 VAC RECOMMENDED MAXIMUM USE VOLTAGE: 26,000 VAC
CUT LENGTHS LIN. FT.				CORRUGATED SWITCHBOARD BLACK CLASS 4 1/2" THICK
SB636	3' X LF'	10.7	\$82.50	
FULL ROLLS				
SB636	3' X 30'	321	\$2,042.50	
				DIELECTRIC TEST VOLTAGE: 50,000 VAC PROOF TESTED OVER ENTIRE SURFACE AT: 40,000 VAC RECOMMENDED MAXIMUM USE VOLTAGE: 36,000 VAC