



# RHINO

ANTI-FATIGUE MATS

## BRUSH RIB DATA & SPECS

**Commercial quality rib indoor entrance matting**

### Physical Description:

18 oz/yd<sup>2</sup> polypropylene based needle bond carpet top with high quality PVC based backing

	<b>Target</b>	<b>Tolerance</b>	<b>Method</b>
<b>Thickness</b>	0.065"	0.060" minimum	ASTM D-1667
Tufted Carpet Weight	18.0 oz/yd <sup>2</sup> (0.610 Kg/m <sup>2</sup> )	+/-5%	ASTM V-025
PVC Weight (Oz/Yd <sup>2</sup> )	70 Oz/yd <sup>2</sup> (2.374 Kg/m <sup>2</sup> )	+/- 5 oz/yd <sup>2</sup>	ASTM V-025
Flammability (OPSC FF-170)	Pass	Pass	Vendor Certification
Total Weight	88oz/yd <sup>2</sup> (2.984 Kg/m <sup>2</sup> )	+/-10%	ASTM-V025
Length Tolerance	+/- 3%		ASTM-V013
Width Tolerance	+/- 3%		ASTM-V013
Vinyl Borders	3/4" (19mm) wide		
Shipping Weight	0,80 lbs sq ft (3.906 Kg/sq m)		